# **ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18 12CT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18

12CT

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

**Emergency telephone numbers** 

For SDS Information : Compliance Services - 877-428-9937
For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

## **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	characteristic

#### **GHS Classification**

Flammable aerosols : Category 2
Gases under pressure : Liquefied gas
Eye irritation : Category 2A
Reproductive toxicity : Category 1B

**GHS** label elements

Signal word

Hazard pictograms :



: Danger

Gas cylinder





r

Hazard statements : H223 Flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

Precautionary statements : **Prevention:** 

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

#### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.
P337 + P313 If eye irritation persists: Get medical advice/

attention.

#### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

## Disposal:

P501 Dispose of contents/container in accordance with local regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
2-butoxyethanol	111-76-2	>= 5 - < 10
butane	106-97-8	>= 3 - < 5
acetone	67-64-1	>= 3 - < 5
propane	74-98-6	>= 1 - < 3
sodium borate, decahydrate	1303-96-4	>= 0.1 - < 1
sodium nitrite	7632-00-0	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

Consult a physician after significant exposure.

# **ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18 12CT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water for at least 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

contact time).

Symptoms may include irritation, redness, pain, and rash. Chronic effects are delayed and symptoms may not be

observed during an exposure. Causes serious eye irritation.

May damage fertility or the unborn child.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

•

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8. Do not breathe vapours or spray mist.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms.

Always replace cap after use.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force

or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Store and keep away from, oxidizing agents and acids.

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

# Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
		PEL	20 ppm 97 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
sodium borate, decahydrate	1303-96-4	TWA	5 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
		PEL	5 mg/m3	CAL PEL

## **Biological occupational exposure limits**

(	Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2	-BUTOXYETHANOL	111-76-2	Butoxyacetic	Urine	End of	200.mg/g	ACGIH BEI

## **ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18 12CT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

		acid (BAA)		shift (As soon as possible after exposure ceases)	Creatinine	
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water. Safety glasses

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : colourless
Odour : characteristic
Odour Threshold : No data available

pH : 9 - 10

Melting point/freezing point : No data available

Boiling point : 43.3 °C Flash point : 43.3 °C

## **ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18 12CT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

Method: TCC

Evaporation rate : 1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : not determined
Relative vapour density : No data available
Density : 0.9922 g/cm3

Solubility(ies)

Water solubility : soluble in hot water, soluble in cold water

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Acids

Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

Condition

: None known.

# **ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18 12CT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

Symptoms of Overexposure : Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

contact time).

Symptoms may include irritation, redness, pain, and rash. Chronic effects are delayed and symptoms may not be

observed during an exposure. Causes serious eye irritation.

May damage fertility or the unborn child.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC Group 2A: Probably carcinogenic to humans

sodium nitrite 7632-00-0

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

**Acute toxicity** 

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 15.02 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

**Components:** 

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l

Exposure time: 3 h

LC50 Rat: 50.1 mg/l

# **ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18 12CT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

#### Skin corrosion/irritation

#### **Product:**

Remarks: May cause skin irritation in susceptible persons.

## Serious eye damage/eye irritation

## **Product:**

Remarks: Severe eye irritation

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

## Carcinogenicity

No data available

## Reproductive toxicity

No data available

## STOT - single exposure

No data available

# STOT - repeated exposure

No data available

#### **Aspiration toxicity**

No data available

#### **Further information**

## **Product:**

Remarks: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

## **ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18 12CT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

: Remarks: No data available

## Persistence and degradability

No data available

Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water
Components:

butane :

Partition coefficient: n-

octanol/water

: Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

The product should not be allowed to enter drains, water

courses or the soil.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

## **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel):

# **ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18 12CT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export

notification requirements:

sodium nitrite 7632-00-0

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium nitrite	7632-00-0	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Gases under pressure

Serious eye damage or eye irritation

Reproductive toxicity

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-butoxyethanol 111-76-2 9.9865 %

#### California Prop. 65

# SAFETY DATA SHEET ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18 12CT

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **Further information**

#### NFPA:

HEALTH	2
FLAMMABILITY	3
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

#### HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	3

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms



e Gas cylinder







Signal word Hazard statements Danger:

Flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May damage fertility or the unborn child.

Precautionary statements

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. **Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °E

# SAFETY DATA SHEET ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18 12CT

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	2.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.