Version 1.0 Revision Date 02/01/2024 Print Date 04/27/2025

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP FOAMING CLEAR COAT PROTECTANT WITH PEACH

FRAGRANCE\_20 GAL

Material number : 00000000000821750

## Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street

Edmonton, Alberta T5S 1N6

Canada

Telephone : Compliance Services - 877-428-9937

# **Emergency telephone numbers**

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** 

Recommended use of the chemical and restrictions on use

# **SECTION 2. HAZARDS IDENTIFICATION**

# **Emergency Overview**

Appearance	viscous
Colour	clear, light yellow
Odour	mild

## **GHS Classification**

Flammable liquids : Category 4
Skin irritation : Category 2
Serious eye damage : Category 1
Skin sensitisation : Category 1
Aspiration hazard : Category 1

**GHS** label elements

Print Date 04/27/2025 Version 1.0 Revision Date 02/01/2024

Hazard pictograms







Health hazard

Corrosion

Signal word : Danger

H227 Combustible liquid. Hazard statements

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
2-butoxyethanol	111-76-2	>= 10 - < 30
Fatty acids, coco, reaction products with	68604-75-1	>= 10 - < 30
diethylenetriamine and soya fatty acids,		
ethoxylated, chloromethane-quaternized		

Version 1.0 Revision Date 02/01/2024 Print Date 04/27/2025

Distillates (petroleum), straight-run middle	64741-44-2	>= 10 - < 30
dodecyldimethylamine oxide	1643-20-5	>= 5 - < 10
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	61789-40-0	>= 1 - < 5
propan-2-ol	67-63-0	>= 1 - < 5
N,N-dimethyltetradecylamine N-oxide	3332-27-2	>= 1 - < 5

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

Consult a physician after significant exposure.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Rinse immediately with plenty of water for at least 15 minutes.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a

physician or poison control center. If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Aspiration may cause pulmonary oedema and pneumonitis. Symptoms may include blistering, irritation, burns, and pain.

Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

contact time).

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye damage. May cause an allergic skin reaction.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Carbon dioxide (CO2)

Water spray jet

Version 1.0 Revision Date 02/01/2024 Print Date 04/27/2025

Alcohol-resistant foam

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Nitrogen oxides (NOx)

Smoke

Chlorine compounds

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment.

Ensure adequate ventilation.

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms.

Version 1.0 Revision Date 02/01/2024 Print Date 04/27/2025

Do not breathe vapours or spray mist.

Take precautionary measures against static discharges. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm 97 mg/m3	CA QC OEL
		TWA	20 ppm	ACGIH
propan-2-ol	67-63-0	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm 983 mg/m3	CA QC OEL
		STEV	500 ppm 1,230 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

## **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio	Basis
		parameters	эресппеп	g time	n	
2-BUTOXYETHANOL	111-76-2	Butoxyaceti c acid (BAA)	Urine	End of shift (As soon as possible after exposure	200 mg/g Creatinine	ACGIH BEI

Version 1.0 Revision Date 02/01/2024 Print Date 04/27/2025

					ceases)		
Р	ROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workwee	40 mg/l	ACGIH BEI
					k		

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water. Safety glasses

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work

place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : viscous

Colour : clear, light yellow

Odour : mild

Odour Threshold : No data available

pH : 7 - 7.5

Melting point/freezing point : No data available

Boiling point :  $100 \,^{\circ}\text{C}$ Flash point :  $79.4 \,^{\circ}\text{C}$ 

Method: TCC

Evaporation rate : 1

Version 1.0 Revision Date 02/01/2024 Print Date 04/27/2025

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : not determined
Relative vapour density : No data available

Density : 0.95 g/cm3

Solubility(ies)

Water solubility : soluble in cold water, soluble in hot water

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : 23.2 mm2/s (20 °C)

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Organic Substances Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

**Potential Health Effects** 

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Aspiration may cause pulmonary oedema and pneumonitis.

Symptoms may include blistering, irritation, burns, and pain.

Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

Version 1.0 Revision Date 02/01/2024 Print Date 04/27/2025

contact time).

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye damage. May cause an allergic skin reaction.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2

hydrogen peroxide 7722-84-1

**Acute toxicity** 

Product:

Acute oral toxicity : Acute toxicity estimate : 2,510 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 38.31 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 4,413 mg/kg

Method: Calculation method

**Components:** 

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg

Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Version 1.0 Revision Date 02/01/2024 Print Date 04/27/2025

## **Components:**

## N,N-dimethyltetradecylamine N-oxide:

Remarks: No data available

## Serious eye damage/eye irritation

#### **Product:**

Remarks: May cause irreversible eye damage.

#### **Components:**

#### N,N-dimethyltetradecylamine N-oxide:

Remarks: No data available

## Respiratory or skin sensitisation

#### **Product:**

Remarks: Causes sensitisation.

#### **Components:**

#### Distillates (petroleum), straight-run middle:

Classification: May cause sensitisation by skin contact.

#### Germ cell mutagenicity

No data available

# Carcinogenicity

No data available

#### Reproductive toxicity

No data available

# STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

## **Aspiration toxicity**

No data available

#### **Further information**

#### **Product:**

Remarks: Solvents may degrease the skin.

Revision Date 02/01/2024 Print Date 04/27/2025 Version 1.0

: Remarks: No data available

: Remarks: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

**Components:** 

N,N-dimethyltetradecylamine N-oxide:

: Remarks: No data available Toxicity to fish

Toxicity to daphnia and

other aquatic invertebrates

Persistence and degradability

No data available

Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water Components: propan-2-ol:

Partition coefficient: n-

octanol/water

: log Pow: 0.05

Mobility in soil

No data available

Other adverse effects

No data available **Product:** 

Additional ecological

information

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

: Empty remaining contents. Contaminated packaging

> Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

### **SECTION 14. TRANSPORT INFORMATION**

Revision Date 02/01/2024 Print Date 04/27/2025 Version 1.0

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL **TSCA** 

On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

#### **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

Version 1.0 Revision Date 02/01/2024 Print Date 04/27/2025

#### WHMIS - GHS Label Information:

Hazard pictograms







mark

Health hazard

hazard Corrosion

Health naza

Signal word : **Danger:** Hazard statements : Combust

: Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage.

Precautionary statements

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the

workplace. Wear protective gloves/ eye protection/ face protection.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.0
Revision Date:	02/01/2024
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.