according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 06/04/2024

SECTION 1: IDENTIFICATION

Product Identifier Product Form: Mixture **Product Name: Viceroy** Product Code: AFCO 6010 **Intended Use of the Product**

Use of the Substance/Mixture: Acid cleaner for soak, manual, and foam cleaning of food processing equipment. Effective for the

removal of hardness scale and rust. For professional use only. Name, Address, and Telephone of the Responsible Party

Company **AFCO**

550 Development Avenue Chambersburg, PA 17201

T: 800-345-1329 www. afcocare.com

Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Met. Corr. 1 H290 Skin Corr. 1B H314 Eve Dam. 1 H318

Label Elements GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H290 - May be corrosive to metals

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

Precautionary Statements (GHS-US): P234 - Keep only in original container.

P260 - Do not breathe mist, spray, vapors, fumes.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P280 - Wear eye protection, face protection, protective clothing, protective gloves.

P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/physician.

P321 - Specific treatment (see Section 4).

P363 - Wash contaminated clothing before reuse. P390 - Absorb spillage to prevent material damage.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

EN (English US) 06/04/2024 1/9

Version: 1.2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards: May cause respiratory tract irritation. When heated to decomposition, emits toxic fumes. Contact with active metals may evolve flammable hydrogen gas.

Unknown Acute Toxicity (GHS-US) Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

| Name | Product identifier | % (w/w) | Classification (GHS-US) |
|--|---------------------|---------|--------------------------------------|
| Water | (CAS No) 7732-18-5 | 70 - 90 | Not classified |
| Hydrogen chloride | (CAS No) 7647-01-0 | 1 - 5 | Met. Corr. 1, H290 |
| | | | Acute Tox. 3 (Inhalation: gas), H331 |
| | | | Skin Corr. 1B, H314 |
| | | | Eye Dam. 1, H318 |
| | | | STOT SE 3, H335 |
| Phosphoric acid | (CAS No) 7664-38-2 | 5 - 10 | Met. Corr. 1, H290 |
| | | | Acute Tox. 4 (Oral), H302 |
| | | | Skin Corr. 1B, H314 |
| | | | Eye Dam. 1, H318 |
| Sodium xylene sulfonate | (CAS No) 1300-72-7 | 1 - 5 | Acute Tox. 4 (Oral), H302 |
| | | | Skin Irrit. 2, H315 |
| | | | Eye Irrit. 2A, H319 |
| | | | STOT SE 3, H335 |
| Benzenesulfonic acid, 4-C10-13-sec-alkyl | (CAS No) 85536-14-7 | 1 - 5 | Acute Tox. 4 (Oral), H302 |
| derivatives | | | Skin Corr. 1C, H314 |
| | | | Eye Dam. 1, H318 |
| | | | Aquatic Acute 2, H401 |
| | | | Aquatic Chronic 3, H412 |
| Decyl phenoxybenzenedisulfonic acid, | (CAS No) 36445-71-3 | .1 - 1 | Skin Irrit. 2, H315 |
| disodium salt | | | Eye Dam. 1, H318 |
| Nonylphenol ethoxylates | (CAS No) 9016-45-9 | 0.1 - 1 | Skin Irrit. 2, H315 |
| | | | Eye Irrit. 2A, H319 |
| | | | Aquatic Chronic 2, H411 |

Full text of H-phrases: see section 16.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Skin Contact: Remove contaminated clothing. Rinse cautiously with water for at least 30 minutes. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and eye damage. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

Inhalation: May cause respiratory tract irritation.

Skin Contact: Causes severe skin burns and eye damage.

Eye Contact: Causes serious eye damage.

06/04/2024 EN (English US) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ingestion: Ingestion is likely to be harmful or have adverse effects. **Chronic Symptoms:** None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive, however contact with metals may release explosive hydrogen gas. **Reactivity:** Thermal decomposition generates: Corrosive vapors and toxic fumes. Reacts violently with strong bases.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not breath fumes from fires or vapors from decompostion. Stop leak if safe to do so. Do not allow runoff from fire fighting to enter drains or water sources.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Sulfur oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Do not breathe mist or spray. Avoid contact with metal.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Eliminate ignition sources. Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Cautiously neutralize spill. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Ventilate area. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Store in original container. Store locked up. Keep container closed when not in use. Keep away from heat, extremely high temperatures and incompatible materials.

Incompatible Materials: Strong bases. Strong oxidizers.

Specific End Use(s)

For professional use only. Acid cleaner for soak, manual, and foam cleaning of food processing equipment. Effective for the removal of hardness scale and rust.

06/04/2024 EN (English US) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

| Phosphoric acid (7664-38-2) | | |
|-----------------------------|-----------------------------|------------------------|
| Mexico | OEL TWA (mg/m³) | 1 mg/m³ |
| Mexico | OEL STEL (mg/m³) | 3 mg/m³ |
| USA ACGIH | ACGIH TWA (mg/m³) | 1 mg/m³ |
| USA ACGIH | ACGIH STEL (mg/m³) | 3 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 1 mg/m³ |
| USA NIOSH | NIOSH REL (TWA) (mg/m³) | 1 mg/m³ |
| USA NIOSH | NIOSH REL (STEL) (mg/m³) | 3 mg/m³ |
| USA IDLH | US IDLH (mg/m³) | 1000 mg/m ³ |
| Ontario | OEL STEL (mg/m³) | 3 mg/m³ |
| Ontario | OEL TWA (mg/m³) | 1 mg/m³ |
| Québec | VECD (mg/m³) | 3 mg/m³ |
| Québec | VEMP (mg/m³) | 1 mg/m³ |
| Hydrogen chloride (7647-01 | -0) | |
| Mexico | OEL Ceiling (mg/m³) | 7 mg/m³ |
| Mexico | OEL Ceiling (ppm) | 5 ppm |
| USA ACGIH | ACGIH Ceiling (ppm) | 2 ppm |
| USA OSHA | OSHA PEL (Ceiling) (mg/m³) | 7 mg/m³ |
| USA OSHA | OSHA PEL (Ceiling) (ppm) | 5 ppm |
| USA NIOSH | NIOSH REL (ceiling) (mg/m³) | 7 mg/m³ |
| USA NIOSH | NIOSH REL (ceiling) (ppm) | 5 ppm |
| USA IDLH | US IDLH (ppm) | 50 ppm |
| Ontario | OEL Ceiling (ppm) | 2 ppm |
| Québec | PLAFOND (mg/m³) | 7.5 mg/m ³ |

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use with adequate ventilation. Use effective ventilation system to maintain air concentrations below occupational exposure limits. Ensure all national/local regulations are observed.

5 ppm

Personal Protective Equipment: Safety glasses. Face shield. Corrosionproof clothing. Gloves. Protective goggles.



Québec







Materials for Protective Clothing: Chemically resistant materials and fabrics.

PLAFOND (ppm)

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses. Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If workers are exposed to airborne concentrations above the exposure limits, they must use NIOSH certified

respirators.

Consumer Exposure Controls: Do not eat, drink, or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Liquid

Appearance : Clear, colorless to pale yellow

Odor: Moderate acidicOdor Threshold: Not available

pH : <1

06/04/2024 EN (English US) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative Evaporation Rate (butylacetate=1) Not available **Melting Point** Not available **Freezing Point** Not available **Boiling Point** 97.8°C (208.04°F) Not flammable **Flash Point** Not available **Auto-ignition Temperature** Not available **Decomposition Temperature** Flammability (solid, gas) Not flammable **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available **Vapor Pressure** Not available Relative Vapor Density at 20°C Not available

Specific Gravity : 1.08

Solubility : Complete in water
Partition coefficient: n-octanol/water : Not available
Viscosity : Not available

Explosion Data – Sensitivity to Mechanical Impact : Not expected to present an explosion hazard due to mechanical impact. Explosion Data – Sensitivity to Static Discharge : Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates: Corrosive vapors, toxic fumes. Reacts violently with strong bases.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous reactions will not occur under normal conditions.

Conditions to Avoid: Extremely high temperatures. Incompatible materials.

Incompatible Materials: Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Thermal decomposition generates: Corrosive vapors. Carbon oxides (CO, CO2). Hydrogen

chloride. Sodium oxides. Sulfur oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burns and eye damage. pH: <1

Serious Eye Damage/Irritation: Causes serious eye damage. pH: <1

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available. **Carcinogenicity:** Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: May cause respiratory tract irritation. **Symptoms/Injuries After Skin Contact:** Causes severe skin burns and eye damage.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

| Decyl phenoxybenzenedisulfonic acid, disodium salt (36445-71-3) | |
|---|-------------|
| LD50 Oral Rat | >2000 mg/kg |

06/04/2024 EN (English US) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| LD50 Dermal Rabbit | >2000 mg/kg | |
|---|---------------------------------------|--|
| Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7) | | |
| LD50 Oral Rat | 1219 mg/kg | |
| Phosphoric acid (7664-38-2) | | |
| LD50 Oral Rat | 1530 mg/kg | |
| LD50 Dermal Rabbit | 2730 mg/kg | |
| LC50 Inhalation Rat | >850 mg/m³ (Exposure time: 1 h) | |
| Hydrogen chloride (7647-01-0) | | |
| LD50 Oral Rat | 700 mg/kg | |
| LD50 Dermal Rabbit | >5010 mg/kg | |
| LC50 Inhalation Rat | 781 ppm/4h (reported as 3124 ppm/1 h) | |
| IARC Group | 3 | |
| Sodium xylene sulfonate (1300-72-7) | | |
| LD50 Oral Rat | 1000 mg/kg | |
| LD50 Dermal Rabbit | >2000 mg/kg | |
| Nonylphenol ethoxylates (9016-45-9) | | |
| LD50 Oral Rat | 2590 mg/kg | |
| LD50 Dermal Rabbit | 1780 μl/kg | |

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Not classified.

| Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7) | | |
|---|--|--|
| LC50 Fish 1 | 5.6 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [flow-through]) | |
| EC50 Daphnia 1 | 5.2 mg/l (Exposure time: 48 h - Species: Daphnia magna) | |
| LC50 Fish 2 | 1.67 mg/l (Exposure time: 96h - Species:Lepomis macrochirus) | |

Persistence and Degradability

| Viceroy (AFCO 6010) | |
|-------------------------------|------------------|
| Persistence and Degradability | Not established. |

Bioaccumulative Potential

| Viceroy (AFCO 6010) | |
|---|------------------|
| Bioaccumulative Potential | Not established. |
| Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7) | |
| Log Pow | 2 (at 23°C) |

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way. **Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations. RCRA Waste Code: D002 (Corrosive Material).

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Phosphoric acid, hydrochloric acid)

Hazard Class : 8
Identification Number : UN3264
Label Codes : 8

Packing Group : II
Marine Pollutant : Yes
ERG Number : 154

06/04/2024 EN (English US) 6/9

Safety Data Sheet

MFAG Number

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: 154

14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Phosphoric acid, hydrochloric acid)

Hazard Class : 8

Identification Number : UN3264

Packing Group : II
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B
Marine pollutant : Yes



14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Phosphoric acid, hydrochloric acid)

Packing Group : II

Identification Number : UN3264

Hazard Class: 8Label Codes: 8ERG Code (IATA): 8L



14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Phosphoric acid, hydrochloric acid)

Packing Group : II
Hazard Class : 8
Identification Number : UN3264
Label Codes : 8
Marine Pollutant (TDG) : Yes



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

| Viceroy (AFCO 6010) | | |
|--|--|--|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard. | |
| Decyl phenoxybenzenedisulfonic acid, disodium salt (36445-71-3) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory. | | |
| Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory. | | |
| Phosphoric acid (7664-38-2) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory. | | |
| Hydrogen chloride (7647-01-0) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory. | | |
| Listed on SARA Section 302 (Specific toxic chemical listings). | | |
| Listed on SARA Section 313 (Specific toxic chemical listings). | | |
| SARA Section 302 Threshold Planning Quantity (TPQ) | 500 (gas only) | |
| SARA Section 313 - Emission Reporting | 1.0% (acid aerosols including mists, vapors, gas, fog, and other | |
| | airborne forms of any particle size) | |
| Water (7732-18-5) | | |
| Listed on the United States TSCA (Toxic Substances Control A | ct) inventory. | |

| Listed on the United States TSCA (Toxic Substances Control Act) inventory |
|---|
|---|

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

US State Regulations

Sodium xylene sulfonate (1300-72-7)

Nonylphenol ethoxylates (9016-45-9)

| Phosphoric acid (7664-38-2) |
|---|
| U.S California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic |

06/04/2024 EN (English US) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Hydrogen chloride (7647-01-0)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New Jersey TCPA Extraordinarily Hazardous Substances (EHS)
- U.S. New York Occupational Exposure Limits Ceilings
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Sodium xylene sulfonate (1300-72-7)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Nonylphenol ethoxylates (9016-45-9)

- U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Canadian Regulations

Decyl phenoxybenzenedisulfonic acid, disodium salt (36445-71-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Phosphoric acid (7664-38-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Hydrogen chloride (7647-01-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Sodium xylene sulfonate (1300-72-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Nonylphenol ethoxylates (9016-45-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 06/04/2024

06/04/2024 EN (English US) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

| Acute Tox. 3 (Inhalation:gas) | Acute toxicity (inhalation:gas) Category 3 |
|-------------------------------|--|
| Acute Tox. 4 (Oral) | Acute toxicity (oral) Category 4 |
| Aquatic Acute 2 | Hazardous to the aquatic environment - Acute Hazard Category 2 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Eye Dam. 1 | Serious eye damage/eye irritation Category 1 |
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Met. Corr. 1 | Corrosive to metals Category 1 |
| Skin Corr. 1A | Skin corrosion/irritation Category 1A |
| Skin Corr. 1B | Skin corrosion/irritation Category 1B |
| Skin Corr. 1C | Skin corrosion/irritation Category 1C |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H290 | May be corrosive to metals |
| H302 | Harmful if swallowed |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H331 | Toxic if inhaled |
| H335 | May cause respiratory irritation |
| H401 | Toxic to aquatic life |
| H411 | Toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |
| | |

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was

given.

NFPA Fire Hazard : 0 - Materials that will not burn.

NFPA Reactivity : 1 - Normally stable, but can become unstable at elevated

temperatures and pressures or may react with water with

some release of energy, but not violently.



Health : 3 Serious Hazard - Major injury likely unless prompt action is taken, and medical treatment is

given.

Flammability : 0 - Minimal Hazard.

Physical : 1 - Slight Hazard.

Party Responsible for the Preparation of This Document

AFCO

550 Development Avenue Chambersburg, PA 17201

T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as quaranteeing any specific property of the product.

North America GHS SDS 2015 (U.S., Can., Mex.)

06/04/2024 EN (English US) 9/9