# **ZEP TILE & GROUT CLEANER**

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

## **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP TILE & GROUT CLEANER

Material number : 0000000000104600

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

**Emergency telephone numbers** 

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

## **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	liquid
Colour	reddish-violet
Odour	pleasant

# **GHS Classification**

Skin corrosion : Category 1
Serious eye damage : Category 1
Specific target organ toxicity - : Category 2

repeated exposure

(Inhalation)

**GHS** label elements

Hazard pictograms :



Corrosion

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or

repeated exposure if inhaled.

Precautionary statements : **Prevention**:

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P314 Get medical advice/ attention if you feel unwell. P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
tetrasodium ethylenediaminetetraacetate	64-02-8	>= 5 - < 10
1-(1-methyl-2-propoxyethoxy)propan-2-ol	29911-27-1	>= 3 - < 5
sodium xylenesulphonate	1300-72-7	>= 3 - < 5
potassium dodecylbenzenesulphonate	27177-77-1	>= 1 - < 3
Sodium polyacrylate	9003-04-7	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

Move to fresh air.

In case of skin contact : Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with

difficulty.

Take off contaminated clothing and shoes immediately.

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

Wash contaminated clothing before re-use.

Wash off immediately with plenty of water for at least 15

minutes.

If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

Rinse thoroughly with plenty of water for at least 15 minutes

and consult a physician. Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

Continue rinsing eyes during transport to hospital.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a

physician or poison control center. If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Chronic effects are delayed and symptoms may not be

observed during an exposure.

Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling,

respiratory issues, and general pain.

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Nitrogen oxides (NOx)

Smoke

Sulphur oxides

Specific extinguishing : Use extinguishing measures that are appropriate to local

# **ZEP TILE & GROUT CLEANER**

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

methods circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment.

Ensure adequate ventilation.

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

# **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. To avoid spills during handling keep bottle on a metal tray.

Do not breathe vapours or spray mist.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Components with workplace control parameters

Contains no substances with occupational exposure limit values.

**Engineering measures** : effective ventilation in all processing areas

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

# Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : reddish-violet
Odour : pleasant

Odour Threshold : No data available

pH : 12.5 - 13.5

Melting point/freezing point : No data available

Boiling point :  $104.44 \,^{\circ}\text{C}$ Flash point :  $> 93.3 \,^{\circ}\text{C}$ 

Method: closed cup

Evaporation rate : 1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 1,002 g/cm²

Density : 1.092 g/cm3

Solubility(ies)

# **ZEP TILE & GROUT CLEANER**

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

Water solubility : soluble

Solubility in other solvents : Not applicable

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : 25.1 mm2/s (20 °C)

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Acids

Hazardous decomposition

products

: Carbon oxides

Nitrogen oxides (NOx)

Sulphur oxides

## **SECTION 11. TOXICOLOGICAL INFORMATION**

# **Potential Health Effects**

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure

: Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Chronic effects are delayed and symptoms may not be

observed during an exposure.

Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling,

respiratory issues, and general pain.

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards.

May cause damage to organs through prolonged or repeated

# **ZEP TILE & GROUT CLEANER**

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

exposure.

Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

## **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

## Skin corrosion/irritation

# **Product:**

Remarks: Extremely corrosive and destructive to tissue.

## Serious eye damage/eye irritation

#### **Product:**

Remarks: May cause irreversible eye damage.

# Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

## Carcinogenicity

No data available

# Reproductive toxicity

No data available

## STOT - single exposure

No data available

## STOT - repeated exposure

# Components:

## tetrasodium ethylenediaminetetraacetate:

# **ZEP TILE & GROUT CLEANER**

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

Exposure routes: Inhalation

Assessment: May cause damage to organs through prolonged or repeated exposure.

## **Aspiration toxicity**

No data available

## **Further information**

## **Product:**

Remarks: No data available

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

# Persistence and degradability

No data available

# **Bioaccumulative potential**

## **Product:**

Partition coefficient: n- : Remarks: No data available

octanol/water **Components**:

**1-(1-methyl-2-propoxyethoxy)propan-2-ol :** Partition coefficient: n- : Pow: 7.7

octanol/water

# Mobility in soil

No data available

## Other adverse effects

No data available

# Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

# **ZEP TILE & GROUT CLEANER**

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

# **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

# **EPCRA - Emergency Planning and Community Right-to-Know Act**

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

## **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethylbenzene	100-41-4	1000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to

www.P65Warnings.ca.gov.

## The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

## **SECTION 16. OTHER INFORMATION**

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

## **Further information**

#### NFPA:

HEALTH	3
FLAMMABILITY	1
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

## HMIS III:

HEALTH	3*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

## **OSHA - GHS Label Information:**

Hazard pictograms





Health hazard

Signal word Hazard statements Danger:

Causes severe skin burns and eye damage. May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

**Prevention:** Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Get medical advice/ attention if you feel unwell. Wash contaminated clothing before reuse.

**Disposal:** Dispose of contents/container in accordance with local regulation.

# SAFETY DATA SHEET ZEP TILE & GROUT CLEANER

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

Version:	5.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.