



To Our Customers:

The attached Safety Data Sheet (SDS) was prepared by the vendor of the product you purchased through one of our divisions. We used the manufacturer's electronic document directly or scanned a paper copy and generated a file for our automated SDS delivery system.

All statements, technical information, and recommendations contained therein are solely that of the manufacturer of the product. We at Zep Inc. did not verify the accuracy and completeness of the statements and do not warrant or guarantee the information. We provide vendor SDSs to assist our customers in their compliance efforts. The attached document is in compliance with one of the respective country regulatory requirements noted below:

The OSHA Hazard Communication Standard (in the United States)
The Hazardous Products Regulations (in Canada)

We made every effort to deliver all of the information prepared by the manufacturer. We cannot anticipate all conditions under which this information will be used. If you have any questions about the statements on the SDS, please contact the company shown on the document.

Zep Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of this product, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the manufacturer's product label and Safety Data Sheet.

Sincerely,

Product Stewardship Team
Zep Inc.



SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: Tesla Dot 3 Brake Fluid
Part #: 1060099-00-A

Issue Date: 02/25/2015
Print Date: 04/08/2015

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: Dow Brake Fluid 372LB

Recommended use of the chemical and restrictions on use

Identified uses: A brake fluid - For use in automotive applications.

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY
2030 WILLARD H DOW CENTER
MIDLAND MI 48674-0000
UNITED STATES

Customer Information Number:

800-258-2436

SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 800-424-9300

Local Emergency Contact: 989-636-4400

2. HAZARDS IDENTIFICATION

Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Reproductive toxicity - Category 2

Label elements

Hazard pictograms



Signal word: **WARNING!**

Hazards

Suspected of damaging fertility or the unborn child.

Precautionary statements**Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Response

IF exposed or concerned: Get medical advice/ attention.

Storage

Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

no data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component	CASRN	Concentration
Triethylene glycol monomethyl ether	112-35-6	> 45.0 - < 55.0 %
Polyethylene glycol monomethyl ether	9004-74-4	> 10.0 - < 20.0 %
Triethylene glycol monobutyl ether	143-22-6	> 10.0 - < 20.0 %
Polyalkylene glycol monobutyl ether	9038-95-3	> 5.0 - < 15.0 %
Diethylene glycol monobutyl ether	112-34-5	< 10.0 %
Polyethylene glycol monobutyl ether	9004-77-7	< 5.0 %
Tetraethylene glycol monomethyl ether	23783-42-8	< 5.0 %
2-Piperazinoethanol	103-76-4	< 1.0 %

4. FIRST AID MEASURES

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: Do not use direct water stream. May spread fire.

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Combustion products may include trace amounts of: Nitrogen oxides.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Move container from fire area if

this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Small spills: Absorb with materials such as: Sand. Vermiculite. Collect in suitable and properly labeled containers. Large spills: Contain spilled material if possible. Pump into suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

Conditions for safe storage: Store in the following material(s): Carbon steel. Stainless steel. Phenolic lined steel drums. Do not store in: Aluminum. Copper. Galvanized iron. Galvanized steel.

Storage stability

Storage temperature:

10 - 35 °C (50 - 95 °F)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
Diethylene glycol monobutyl ether	Dow IHG	TWA	35 ppm
	ACGIH	TWA Inhalable fraction and vapor	10 ppm

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl").
NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	Liquid.
Color	Colorless to yellow
Odor	Ether
Odor Threshold	No test data available
pH	9.3 <i>FMVSS 116</i>
Melting point/range	No test data available
Freezing point	No test data available
Boiling point (760 mmHg)	253 °C (487 °F) <i>FMVSS 116</i> Equilibrium Reflux Boiling Point, dry 150 °C (302 °F) <i>FMVSS 116</i> Equilibrium Reflux Boiling Point, wet No test data available
Flash point	closed cup 146 °C (295 °F) <i>ASTM D92</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	No
Lower explosion limit	No test data available
Upper explosion limit	No test data available

Vapor Pressure	No test data available
Relative Vapor Density (air = 1)	No test data available
Relative Density (water = 1)	No test data available
Water solubility	No test data available
Partition coefficient: n-octanol/water	no data available
Auto-ignition temperature	No test data available
Decomposition temperature	No test data available
Dynamic Viscosity	No test data available
Kinematic Viscosity	2.2 mm ² /s <i>Literature</i>
Explosive properties	No test data available
Oxidizing properties	No test data available
Molecular weight	no data available
Volatile Organic Compounds	No test data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: no data available

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Do not distill to dryness. Product can oxidize at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems.

Incompatible materials: Avoid contact with: Strong acids. Strong oxidizers.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Ketones. Organic acids.

11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

For the component(s) tested:
LD50, Rat, > 5,600 mg/kg

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

For component(s) tested.
LD50, Rat, > 3,480 mg/kg

Acute inhalation toxicity

Prolonged exposure is not expected to cause adverse effects.

Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.
Corneal injury is unlikely.

Sensitization

For the minor component(s):
Has caused allergic skin reactions in humans.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Available data are inadequate to determine single exposure specific target organ toxicity.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on information for component(s):
In animals, effects have been reported on the following organs:
Kidney.
Liver.
Blood.

Carcinogenicity

No relevant data found.

Teratogenicity

In animals, diethylene glycol methyl ether is slightly toxic to the fetus at doses nontoxic to the mother following skin contact; birth defects have been seen only following high oral doses which have little relevance to human exposure. Contains component(s) which did not cause birth defects in animals; other fetal effects occurred only at doses toxic to the mother.

Reproductive toxicity

For the minor component(s): In laboratory animals, excessive doses toxic to the parent animals caused decreased weight and survival of offspring.

Mutagenicity

For the component(s) tested: In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:**Triethylene glycol monomethyl ether****Acute inhalation toxicity**

Prolonged exposure is not expected to cause adverse effects. For respiratory irritation and narcotic effects: No relevant data found.

Rat, 8 Hour, vapour, No deaths occurred following exposure to a saturated atmosphere.

Polyethylene glycol monomethyl ether**Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. For respiratory irritation and narcotic effects: No relevant data found.

The LC50 has not been determined.

Triethylene glycol monobutyl ether**Acute inhalation toxicity**

As product: The LC50 has not been determined.

Polyalkylene glycol monobutyl ether**Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. For respiratory irritation and narcotic effects: No relevant data found.

LC50, Rat, 4 Hour, dust/mist, > 5.01 mg/l No deaths occurred at this concentration.

Diethylene glycol monobutyl ether**Acute inhalation toxicity**

No adverse effects are anticipated from single exposure to vapor. For respiratory irritation and narcotic effects: No relevant data found.

As product: The LC50 has not been determined.

Polyethylene glycol monobutyl ether**Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility. Mist may cause severe irritation of upper respiratory tract (nose and throat).

As product: The LC50 has not been determined.

Tetraethylene glycol monomethyl ether**Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous.

As product: The LC50 has not been determined.

2-Pipera zinoethanol**Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility. Vapor from heated material may cause respiratory irritation and other effects.

As product: The LC50 has not been determined.

12. ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

Toxicity**Triethylene glycol monomethyl ether****Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Danio rerio (zebra fish), static test, 96 Hour, > 5,000 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 500 mg/l, Directive 84/449/EEC, C.2

Acute toxicity to algae/aquatic plants

ErC50, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, > 500 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC0, activated sludge, static test, 0.5 Hour, Respiration rates., > 2,000 mg/l, activated sludge test (OECD 209)

Polyethylene glycol monomethyl ether**Acute toxicity to fish**

For this family of materials:

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

For this family of materials:

LC50, Pimephales promelas (fathead minnow), 96 Hour, > 10,000 mg/l

Acute toxicity to aquatic invertebrates

For this family of materials:

LC50, Daphnia magna (Water flea), 48 Hour, > 10,000 mg/l

Triethylene glycol monobutyl ether**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Leuciscus idus (Golden orfe), static test, 96 Hour, 2,200 - 4,600 mg/l, DIN 38412

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 500 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

EC50, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, 62.5 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

IC50, Bacteria, static test, 16 Hour, > 5,000 mg/l

Polyalkylene glycol monobutyl ether**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, 24,500 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 21,000 mg/l, OECD Test Guideline 202 or Equivalent

Toxicity to bacteria

IC50, Bacteria, static test, 16 Hour, Growth inhibition, 32,000 mg/l, OECD 209 Test

Diethylene glycol monobutyl ether**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Lepomis macrochirus (Bluegill sunfish), static test, 96 Hour, 1,300 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, alga Scenedesmus sp., static test, 96 Hour, Growth rate inhibition, > 100 mg/l, OECD Test Guideline 201 or Equivalent
ErC50, alga Scenedesmus sp., static test, 96 Hour, Biomass, > 100 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, Bacteria, static test, 255 mg/l

Polyethylene glycol monobutyl ether**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
Based on information for a similar material:
LC50, Fish., semi-static test, 96 Hour, > 1,800 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

Based on information for a similar material:
EC50, Daphnia magna (Water flea), static test, 48 Hour, > 3,200 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

Based on information for a similar material:
ErC50, Scenedesmus capricornutum (fresh water algae), static test, 72 Hour, Growth rate inhibition, 2,490 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

IC50, activated sludge, static test, 16 Hour, Growth inhibition, > 5,000 mg/l

Tetraethylene glycol monomethyl ether

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis
(LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Danio rerio (zebra fish), static test, 96 Hour, > 10,000 mg/l

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), static test, 48 Hour, > 10,000 mg/l

Acute toxicity to algae/aquatic plants

EC50, alga Scenedesmus sp., 72 Hour, Biomass, > 500 mg/l

Toxicity to bacteria

IC50, Bacteria, 16 Hour, > 5,000 mg/l
EC50, activated sludge, 3 Hour, > 12,500 mg/l, OECD 209 Test

2-Piperazinoethanol

Acute toxicity to fish

Material is practically non-toxic to fish on an acute basis (LC50 > 100 mg/L).
LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 6,410 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, 384 mg/l, OECD Test Guideline 202 or Equivalent

Toxicity to bacteria

EC50, Bacteria, 16 Hour, > 5,000 mg/l, hUCC

Persistence and degradability

Triethylene glycol monomethyl ether

Biodegradability: Biodegradation under aerobic static laboratory conditions is high (BOD20 or BOD28/ThOD > 40%). Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

10-day Window: Pass

Biodegradation: 100 %

Exposure time: 13 d

Method: OECD Test Guideline 301B or Equivalent

Theoretical Oxygen Demand: 1.75 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	29 %
10 d	33 %
20 d	71 %

Photodegradation**Atmospheric half-life:** 3.2 Hour**Method:** Estimated.**Polyethylene glycol monomethyl ether**

Biodegradability: For this family of materials: Biodegradation under aerobic static laboratory conditions is low (BOD20 or BOD28/ThOD between 2.5 and 10%).

Triethylene glycol monobutyl ether

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

10-day Window: Fail

Biodegradation: 85 %**Exposure time:** 28 d**Method:** OECD Test Guideline 301D or Equivalent**Theoretical Oxygen Demand:** 2.10 mg/mg**Polyalkylene glycol monobutyl ether**

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 45 %**Exposure time:** 28 d**Method:** OECD Test Guideline 301B or Equivalent

10-day Window: Fail

Biodegradation: 44 %**Exposure time:** 28 d**Method:** OECD Test Guideline 301F or Equivalent**Diethylene glycol monobutyl ether**

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

Biodegradation: 89 - 93 %**Exposure time:** 28 d**Method:** OECD Test Guideline 301C or Equivalent

10-day Window: Not applicable

Biodegradation: 100 %**Exposure time:** 28 d**Method:** OECD Test Guideline 302B or Equivalent**Theoretical Oxygen Demand:** 2.17 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	27 %
10 d	60 %
20 d	81 %

Photodegradation**Test Type:** Half-life (indirect photolysis)**Sensitizer:** OH radicals**Atmospheric half-life:** 11 Hour**Method:** Estimated.**Polyethylene glycol monobutyl ether****Biodegradability:** Based on information for a similar material: Material is expected to be readily biodegradable.

10-day Window: Pass

Biodegradation: 76 %**Exposure time:** 28 d**Method:** OECD Test Guideline 301D or Equivalent**Photodegradation****Sensitizer:** OH radicals**Atmospheric half-life:** 0.21 d**Method:** Estimated.**Tetraethylene glycol monomethyl ether****Biodegradability:** Material is inherently biodegradable (reaches > 20% biodegradation in OECD test(s) for inherent biodegradability).

10-day Window: Fail

Biodegradation: 63.9 %**Exposure time:** 28 d**Method:** OECD Test Guideline 301B or Equivalent

10-day Window: Not applicable

Biodegradation: 99 %**Exposure time:** 8 d**Method:** OECD Test Guideline 302B or Equivalent**2-Piperazinoethanol****Biodegradability:** Biodegradation under aerobic static laboratory conditions is moderate (BOD₂₀ or BOD₂₈/ThOD between 10 and 40%).**Theoretical Oxygen Demand:** 2.83 mg/mg Calculated.**Chemical Oxygen Demand:** 1.81 mg/mg Dichromate**Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	3 - 5 %
10 d	3 - 6 %
20 d	6 - 13 %

Photodegradation**Test Type:** Half-life (indirect photolysis)**Sensitizer:** OH radicals**Atmospheric half-life:** 0.057 d**Method:** Estimated.**Bioaccumulative potential****Triethylene glycol monomethyl ether****Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).**Partition coefficient: n-octanol/water(log Pow):** -1.12 at 20 °C Measured**Polyethylene glycol monomethyl ether****Bioaccumulation:** For this family of materials: No bioconcentration is expected because of the relatively high water solubility.**Triethylene glycol monobutyl ether****Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).**Partition coefficient: n-octanol/water(log Pow):** 0.51 at 20 °C Measured**Polyalkylene glycol monobutyl ether****Bioaccumulation:** For this family of materials: No bioconcentration is expected because of the relatively high water solubility.**Diethylene glycol monobutyl ether****Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).**Partition coefficient: n-octanol/water(log Pow):** 1 Measured**Polyethylene glycol monobutyl ether****Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).**Partition coefficient: n-octanol/water(log Pow):** 0.436 at 20 °C Measured**Tetraethylene glycol monomethyl ether****Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).**Partition coefficient: n-octanol/water(log Pow):** -1.73 Estimated.**2-Piperazineethanol****Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).**Partition coefficient: n-octanol/water(log Pow):** -1.56 Estimated.**Mobility in soil****Triethylene glycol monomethyl ether**

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient(Koc): 10 Estimated.**Polyethylene glycol monomethyl ether**

No data available.

Triethylene glycol monobutyl ether

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient(Koc): 10 Estimated.

Polyalkylene glycol monobutyl ether

No relevant data found.

Diethylene glycol monobutyl ether

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient(Koc): 2 Estimated.

Polyethylene glycol monobutyl ether

No data available.

Tetraethylene glycol monomethyl ether

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient(Koc): 10 Estimated.

2-Piperazinoethanol

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient(Koc): 7 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

**Transport in bulk
according to Annex I or II
of MARPOL 73/78 and the
IBC or IGC Code**

Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Acute Health Hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313**Components****CASRN**

Triethylene glycol monomethyl ether

112-35-6

Triethylene glycol monobutyl ether

143-22-6

Diethylene glycol monobutyl ether

112-34-5

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause birth defects or other reproductive harm.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Components**CASRN**

Triethylene glycol monomethyl ether

112-35-6

Triethylene glycol monobutyl ether

143-22-6

Diethylene glycol monobutyl ether

112-34-5

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

:

16. OTHER INFORMATION

Hazard Rating System

NFPA

Health	Fire	Reactivity
0	1	0

Revision

Identification Number: 101207199 / A001 / Issue Date: 02/25/2015 / Version: 4.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
Dow IHG	Dow Industrial Hygiene Guideline
TWA	8-hour, time-weighted average

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.