

To Our Customers:

The attached Safety Data Sheet (SDS) was prepared by the vendor of the product you purchased through one of our divisions. We used the manufacturer's electronic document directly or scanned a paper copy and generated a file for our automated SDS delivery system.

All statements, technical information, and recommendations contained therein are solely that of the manufacturer of the product. We at Zep Inc. did not verify the accuracy and completeness of the statements and do not warrantee or guarantee the information. We provide vendor SDSs to assist our customers in their compliance efforts. The attached document is in compliance with one of the respective country regulatory requirements noted below:

The OSHA Hazard Communication Standard (in the United States) The Hazardous Products Regulations (in Canada)

We made every effort to deliver all of the information prepared by the manufacturer. We cannot anticipate all conditions under which this information will be used. If you have any questions about the statements on the SDS, please contact the company shown on the document.

Zep Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of this product, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the manufacturer's product label and Safety Data Sheet.

Sincerely,

Product Stewardship Team Zep Inc.



Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

SECTION 1. IDENTIFICATION

Product name : Valvoline™ LOW SOLIDS DILUTED

HEAT TRANSFER FLUID

Product code : 906342

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Valvoline Canada Corp

Address : 905 Winston Churchill Blvd

Mississauga ON L5J 4P2

Canada

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone

number

: +1-800-VALVOLINE (+1-800-825-8654)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Acute toxicity (Oral) : Category 4

Reproductive toxicity : Category 2

Specific target organ toxicity

- repeated exposure (Oral)

: Category 2 (Kidney, Liver)

GHS label elements

Hazard pictograms





Signal word : Warning

Hazard statements : H302 Harmful if swallowed.

H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs (Kidney, Liver) through

prolonged or repeated exposure if swallowed.

Valvoline, Global

SAFETY DATA SHEET

Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/ doctor if you feel unwell. Rinse mouth.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
ethanediol	ethanediol	107-21-1	>= 30 - < 60 *
2-ethylhexanoic acid and its salts	2-ethylhexanoic acid and its salts	149-57-5	>= 1 - < 5 *

^{*} Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.



Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital. No symptoms known or expected.

Most important symptoms and effects, both acute and

delayed

Notes to physician : No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Hazardous combustion

products

No hazardous combustion products are known

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Refer to protective measures listed in sections 7 and 8.

Use personal protective equipment.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

SAFETY DATA SHEET

Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on

storage stability

: No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanediol	107-21-1	(c)	100 mg/m3	CA AB OEL
		C (Vapour)	50 ppm	CA BC OEL
		C (Vapour and mist)	50 ppm 127 mg/m3	CA QC OEL
		TWA (Total, aerosol only)	10 mg/m3	CA BC OEL
		STEL (Total, aerosol only)	20 mg/m3	CA BC OEL
		C (Total, aerosol only)	100 mg/m3	CA BC OEL
		TWA (Vapour)	25 ppm	ACGIH
		STEL (Vapour)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH



Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025 02/10/2025

2-ethylhexanoic acid and its salts	149-57-5	TWA	5 mg/m3	CA AB OEL
		TWA (Vapour and inhalable aerosols)	5 mg/m3	CA BC OEL
		TWA (Inhalable fraction and vapor)	5 mg/m3	ACGIH

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour : No data available

Odour Threshold : No data available

pH : 8.5

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 249 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

SAFETY DATA SHEET

Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 1.074 g/cm3

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Chemical stability
Possibility of hazardous

reactions

Conditions to avoid Incompatible materials

No decomposition if stored and applied as directed. No decomposition if stored and applied as directed.

No decomposition if stored and applied as directed.

excessive heat
Aldehydes

Alkali metals

Alkaline earth metals

Amines Ammonia Bases

chromium trioxide

Copper Copper alloys Reducing agents

SAFETY DATA SHEET

Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025

Print Date: 02/10/2025

Strong acids strong alkalis

Strong oxidizing agents Sulphur compounds

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

: Acute toxicity estimate: 993.79 mg/kg Acute oral toxicity

Method: Calculation method

Components:

ethanediol:

Acute oral toxicity : LD0 (Human): estimated 1.56 g/kg

Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute inhalation toxicity LC50 (Rat): 10.9 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

Acute toxicity (other routes of : LD50 (Rat): 5,010 mg/kg

administration)

Application Route: Intraperitoneal

LD50 (Rat): 3,260 mg/kg Application Route: Intravenous

2-ethylhexanoic acid and its salts:

Acute oral toxicity : LD50 (Rat, male): 3,000 mg/kg

LD50 (Rat, female): 2,043 mg/kg

Acute inhalation toxicity : LC0 (Rat): 0.11 mg/l

Exposure time: 8 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute

Valvoline_m Global

SAFETY DATA SHEET

Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Components:

ethanediol:

Species : Rabbit

Result : No skin irritation

2-ethylhexanoic acid and its salts:

Species : Rabbi

Result : Slight, transient irritation

Serious eye damage/eye irritation

Components:

ethanediol:

Result : Slight, transient irritation

2-ethylhexanoic acid and its salts:

Species : Rabbit

Result : Slight, transient irritation

Respiratory or skin sensitisation

Components:

ethanediol:

Test Type : Maximisation Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

2-ethylhexanoic acid and its salts:

Test Type : Maximisation Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Valvoline, Market Global

SAFETY DATA SHEET

Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

Germ cell mutagenicity

Components:

ethanediol:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

2-ethylhexanoic acid and its salts:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

STOT - repeated exposure

Components:

ethanediol:

Exposure routes : Ingestion Target Organs : Kidney

Assessment : May cause damage to organs through prolonged or repeated

exposure.

Experience with human exposure

Components:

ethanediol:

Ingestion : Target Organs: Kidney

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

SAFETY DATA SHEET

Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

: Not classified based on available information. Chronic aquatic toxicity

Components:

ethanediol:

LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l Toxicity to fish

> Exposure time: 96 h Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 -

13.000 ma/l

End point: Growth inhibition Exposure time: 7 Days

Toxicity to fish (Chronic

toxicity)

NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l

Exposure time: 7 d

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 24,000 mg/l

Exposure time: 7 d

Ecotoxicology Assessment

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

2-ethylhexanoic acid and its salts:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

> Exposure time: 96 h Test Type: static test

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 85.4 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 49.3 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test



Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Not classified based on available information.

Persistence and degradability

Components:

ethanediol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 90 - 100 %

Exposure time: 10 d

Method: OECD Test Guideline 301

2-ethylhexanoic acid and its salts:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 99 % Exposure time: 28 d

Bioaccumulative potential

Components:

ethanediol:

Bioaccumulation : Species: Crayfish (Procambarus)

Bioconcentration factor (BCF): 0.27

Exposure time: 61 d Concentration: 1000 mg/l Method: Flow through

Partition coefficient: n-

octanol/water

: log Pow: -1.36

2-ethylhexanoic acid and its salts:

Partition coefficient: n-

: log Pow: 2.64

octanol/water

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological

information

: No data available

SAFETY DATA SHEET

Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

NPRI Components : ethanediol

2-butoxyethanol

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : On the inventory, or in compliance with the inventory



Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

Canadian lists

No substances are subject to a Significant New Activity Notification.

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION


Further information

SAFETY DATA SHEET

Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and

safety, Schedule 1, Part 1: Permissible exposure values for

airborne contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / (c) : ceiling occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit

CA BC OEL / C : ceiling limit
CA QC OEL / C : Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory



Valvoline™ LOW SOLIDS DILUTED HEAT TRANSFER FLUID

Version: 0.0 Revision Date: 02/10/2025 Print Date: 02/10/2025

concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States): UN - United Nations: UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 02/10/2025 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN

Internal information: 000000281965