ZEP IRON CLAD 20N13 12CT

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP IRON CLAD 20N13 12CT

Material number : 00000000000015201

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	tan, opaque
Odour	hydrocarbon-like

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Eye irritation : Category 2A

Specific target organ toxicity -

single exposure

: Category 3 (Central nervous system)

GHS label elements

Hazard pictograms



Gas cylinder



-lame

Odo oyiii k

Exclamation

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Precautionary statements : **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 Store in a well-ventilated place.

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Solvent naphtha (petroleum), light aliph.	64742-89-8	>= 30 - < 50
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 10 - < 20
heptane	142-82-5	>= 1 - < 5
octane	111-65-9	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes. Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Causes skin irritation.

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as

hazardous waste.

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Keep in a cool, well-ventilated place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
propane	74-98-6	TWA	1,000 ppm	NIOSH REL
			1,800 mg/m3	
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		С	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
		PEL	400 ppm 1,600 mg/m3	CAL PEL
		STEL	500 ppm 2,000 mg/m3	CAL PEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
octane	111-65-9	TWA	75 ppm 350 mg/m3	NIOSH REL
		С	385 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,350 mg/m3	OSHA Z-1
		TWA	300 ppm 1,450 mg/m3	OSHA P0
		STEL	375 ppm 1,800 mg/m3	OSHA P0
		PEL	300 ppm 1,450 mg/m3	CAL PEL
		STEL	375 ppm 1,800 mg/m3	CAL PEL
		TWA	300 ppm	ACGIH

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates

ZEP IRON CLAD 20N13 12CT

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : tan, opaque

Odour : hydrocarbon-like
Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Flash point :

Not applicable

: Not applicable

Evaporation rate : No data available

Flammability (solid, gas,

liquid)

Boiling point

Extremely flammable aerosol.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : 0.75 g/cm3

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : not determined

Auto-ignition temperature : not determined

ZEP IRON CLAD 20N13 12CT

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 35.5 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Causes skin irritation.

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

ZEP IRON CLAD 20N13 12CT

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

Components:

heptane:

Acute inhalation toxicity : LC50 Rat: 103 mg/l

Exposure time: 4 h

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

ZEP IRON CLAD 20N13 12CT

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

butane:

Partition coefficient: n-

: Pow: 2.89

octanol/water heptane:

Partition coefficient: n-

: log Pow: 5

octanol/water

octane:

Partition coefficient: n-

octanol/water

: log Pow: 5.15

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Gases under pressure Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SAFETY DATA SHEET ZEP IRON CLAD 20N13 12CT

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Further information

NFPA:

HEALTH	3
FLAMMABILITY	4
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	3

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Gas cylinder



Signal word Hazard statements Danger:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness

Precautionary statements

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protection/ face protection.

Wear protective gloves/ eye protection/ face protection.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take

SAFETY DATA SHEET ZEP IRON CLAD 20N13 12CT

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

off contaminated clothing and wash before reuse.

Storage: Store in a well-ventilated place. Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.