ZEP HIGH PH PRESOAK (XT-1398) VEHICLE WASH_5 GAL

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP HIGH PH PRESOAK (XT-1398) VEHICLE WASH_5

GAL

Material number : 000000000000988535

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937
For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

| Appearance | liquid |
|------------|--------------|
| Colour | clear, amber |
| Odour | mild |

GHS Classification

Acute toxicity (Oral) : Category 4
Skin corrosion : Category 1
Serious eye damage : Category 1
Specific target organ toxicity - : Category 2

repeated exposure

(Inhalation)

GHS label elements

Of 10 label elements

Hazard pictograms



nazard Corrosion



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or

repeated exposure if inhaled.

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

Precautionary statements : **Prevention:**

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/doctor if you feel unwell. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P314 Get medical advice/ attention if you feel unwell. P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration [%] |
|---|------------|-------------------|
| sodium dodecylbenzenesulfonate | 25155-30-0 | >= 10 - < 20 |
| 2-aminoethanol | 141-43-5 | >= 5 - < 10 |
| tetrasodium ethylenediaminetetraacetate | 64-02-8 | >= 5 - < 10 |
| Alcohols, C9-11, ethoxylated | 68439-46-3 | >= 5 - < 10 |
| sodium xylenesulphonate | 1300-72-7 | >= 5 - < 10 |
| Sodium metasilicate (disodium salt) | 6834-92-0 | >= 1 - < 5 |

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

Consult a physician after significant exposure.

ZEP HIGH PH PRESOAK (XT-1398) VEHICLE WASH_5 GAL

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Rinse immediately with plenty of water for at least 15 minutes.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling,

respiratory issues, and general pain.

Effects are dependent on exposure (dose, concentration,

contact time).

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Review section 2 of SDS to see all potential hazards.

Causes severe skin burns and eye damage.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Nitrogen oxides (NOx)

Smoke

Sulphur oxides

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Do not breathe vapours or spray mist.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Store and keep away from, oxidizing agents and acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|----------------|----------|-------------------------------------|--|-----------|
| 2-aminoethanol | 141-43-5 | TWA | 3 ppm | ACGIH |
| | | STEL | 6 ppm | ACGIH |
| | | TWA | 3 ppm | NIOSH REL |

ZEP HIGH PH PRESOAK (XT-1398) VEHICLE WASH_5 GAL

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

| | 8 mg/m3 | |
|------|-------------------|-----------|
| ST | 6 ppm 15 mg/m3 | NIOSH REL |
| TWA | 3 ppm 6 mg/m3 | OSHA Z-1 |
| STEL | 6 ppm 15 mg/m3 | OSHA P0 |
| TWA | 3 ppm 8 mg/m3 | OSHA P0 |
| PEL | 3 ppm 8 mg/m3 | CAL PEL |
| STEL | 6 ppm 15 mg/m3 | CAL PEL |

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location.

Safety glasses

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear, amber

Odour : mild

Odour Threshold : No data available

pH : 13 - 13.5

Melting point/freezing point : No data available

Boiling point : 100 °C

ZEP HIGH PH PRESOAK (XT-1398) VEHICLE WASH_5 GAL

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

Flash point

does not flash

Evaporation rate : 1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : not determined
Relative vapour density : No data available

Density : 1.1 g/cm3

Solubility(ies)

Water solubility : soluble in cold water, soluble in hot water

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : 28.7 mm2/s (20 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Acids

Oxidizing agents

Hazardous decomposition

products

: Nitrogen oxides (NOx)

Carbon oxides Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

ZEP HIGH PH PRESOAK (XT-1398) VEHICLE WASH_5 GAL

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling,

respiratory issues, and general pain.

Effects are dependent on exposure (dose, concentration,

contact time).

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Review section 2 of SDS to see all potential hazards.

Causes severe skin burns and eye damage.

Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 1,981 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 146.6 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

sodium dodecylbenzenesulfonate:

Acute oral toxicity : LD50 Oral Rat: 438 mg/kg

2-aminoethanol:

Acute oral toxicity : LD50 Oral Mouse: 700 mg/kg

LD50 Oral Rat: 1,515 mg/kg

Acute inhalation toxicity : LC50 Mouse: > 1.21 mg/l

ZEP HIGH PH PRESOAK (XT-1398) VEHICLE WASH_5 GAL

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

Alcohols, C9-11, ethoxylated:

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

Sodium metasilicate (disodium salt):

Acute oral toxicity : LD50 Rat: 1,153 mg/kg

Skin corrosion/irritation

Product:

Remarks: Causes skin burns.

Serious eye damage/eye irritation

Product:

Remarks: Risk of serious damage to eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Product:

Carcinogenicity - : Not classifiable as a human carcinogen.

Assessment

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

Components:

tetrasodium ethylenediaminetetraacetate:

Exposure routes: Inhalation

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

.

: Remarks: No data available

octanol/water
<u>Components:</u>
2-aminoethanol:

Partition coefficient: n-

: log Pow: -1.31

octanol/water

Mobility in soilNo data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

ZEP HIGH PH PRESOAK (XT-1398) VEHICLE WASH_5 GAL

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM METASILICATE), 8, II

Transportation Regulation: IMDG (Vessel):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM METASILICATE), 8, II

Transportation Regulation: IATA (Cargo Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM METASILICATE), 8, II

Transportation Regulation: IATA (Passenger Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM METASILICATE), 8, II

Transportation Regulation: TDG (Canada):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM METASILICATE), 8, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|--------------------------------|------------|--------------------|-----------------------------|
| sodium dodecylbenzenesulfonate | 25155-30-0 | 1000 | * |

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Acute toxicity (any route of exposure)

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

ZEP HIGH PH PRESOAK (XT-1398) VEHICLE WASH_5 GAL

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

Further information

NFPA:

| HEALTH | 3 |
|-----------------|---|
| FLAMMABILITY | 1 |
| INSTABILITY | 0 |
| SPECIAL HAZARD. | |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

| HEALTH | 3* |
|-----------------|----|
| FLAMMABILITY | 0 |
| PHYSICAL HAZARD | 0 |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Corrosion



Health hazard

Signal word Hazard statements : Danger:

Harmful if swallowed. Causes severe skin burns and eye damage. May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

Prevention: Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Get medical advice/ attention if you feel unwell. Wash

contaminated clothing before reuse.

SAFETY DATA SHEET ZEP HIGH PH PRESOAK (XT-1398) VEHICLE WASH_5 GAL

Version 5.0 Revision Date 01/31/2024 Print Date 04/27/2025

Disposal: Dispose of contents/container in accordance with local regulation.

| Version: | 5.0 |
|----------------|------------|
| Revision Date: | 01/31/2024 |
| Print Date: | 04/27/2025 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.