ZEP PROFESSIONAL Z-TREAD BLACK FLOOR POLISH

Version 4.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP PROFESSIONAL Z-TREAD BLACK FLOOR POLISH

Material number : 00000000001041583

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937
For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	black
Odour	characteristic

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
2-(2-ethoxyethoxy)ethanol	111-90-0	>= 1 - < 5
tris(2-butoxyethyl) phosphate	78-51-3	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

Version 4.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 4. FIRST AID MEASURES

General advice Do not leave the victim unattended.

Show this safety data sheet to the doctor in attendance.

Move out of dangerous area.

Get medical attention if symptoms occur.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water.

> Remove contaminated clothing and shoes. Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water, also under the eyelids.

If swallowed : Keep respiratory tract clear.

> Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a

physician or poison control center. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Alcohol-resistant foam

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Standard procedure for chemical fires.

ZEP PROFESSIONAL Z-TREAD BLACK FLOOR POLISH

Version 4.1 Revision Date 10/01/2023 Print Date 04/27/2025

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-(2-ethoxyethoxy)ethanol	111-90-0	TWA	25 ppm	US WEEL

Engineering measures : effective ventilation in all processing areas

Version 4.1 Revision Date 10/01/2023 Print Date 04/27/2025

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

> Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles

with pure water.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : black

Odour : characteristic Odour Threshold : No data available

: 7.5 - 8.5 Hq

Melting point/freezing point : No data available **Boiling point** : not determined

Flash point : > 93.3 °C

Method: closed cup

Evaporation rate

n-Butyl Acetate = 1.0

Upper explosion limit : No data available Lower explosion limit : No data available

: 23 hPa Vapour pressure : 1 g/cm3 Density

Solubility(ies)

Water solubility : slightly soluble Partition coefficient: n-: No data available

octanol/water

ZEP PROFESSIONAL Z-TREAD BLACK FLOOR POLISH

Version 4.1 Revision Date 10/01/2023 Print Date 04/27/2025

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : 6.4 mm2/s (20 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Acids

Oxidizing agents

Hazardous decomposition

products

: Carbon oxides Acrylic monomers

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ZEP PROFESSIONAL Z-TREAD BLACK FLOOR POLISH

Version 4.1 Revision Date 10/01/2023 Print Date 04/27/2025

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: May irritate skin.

Serious eye damage/eye irritation

Product:

Remarks: May irritate eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

Version 4.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

: Remarks: No data available

octanol/water Components:

2-(2-ethoxyethoxy)ethanol:

Partition coefficient: n-

: Pow: 0.54

octanol/water

Mobility in soilNo data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

ZEP PROFESSIONAL Z-TREAD BLACK FLOOR POLISH

Version 4.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

NOT REGULATED AS DANGEROUS GÓODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to TSCA 12(b) export notification

requirements.

No substances are subject to a Significant New Use Rule.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ammonia, aqueous solution	1336-21-6	1000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethylene oxide	75-21-8	10	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : No SARA Hazards

Version 4.1 Revision Date 10/01/2023 Print Date 04/27/2025

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-(2-ethoxyethoxy)ethanol 111-90-0 3.9667 %

California Prop. 65



WARNING: This product can expose you to chemicals including 2-phenylpropene, styrene, ethylene oxide, 1,4-dioxane, which is/are known to the State of California to cause

cancer, and 2-phenylpropene, ethylene oxide, 2-

ethoxyethanol, pentadecafluorooctanoic acid, which is/are known to the State of California to cause birth defects or other

reproductive harm. For more information go to

www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL This product contains one or several components that are not on the

Canadian DSL nor NDSL.

TSCA Not On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 4.1 Revision Date 10/01/2023 Print Date 04/27/2025

Further information

NFPA:

HEALTH	0
FLAMMABILITY	1
INSTABILITY	0
SPECIAL HAZARD.	

^{0 =} not significant, 1 = Slight,

HMIS III:

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

^{0 =} not significant, 1 = Slight,

OSHA - GHS Label Information:

Not a hazardous substance or mixture.

Version:	4.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

^{2 =} Moderate, 3 = High

^{4 =} Extreme

^{2 =} Moderate, 3 = High

^{4 =} Extreme, * = Chronic

SAFETY DATA SHEET ZEP PROFESSIONAL Z-TREAD BLACK FLOOR POLISH

Version 4.1 Revision Date 10/01/2023 Print Date 04/27/2025