Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP PRESERVE NC TOOL RENTAL_12CS

Material number : TR31501

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street

Edmonton, Alberta T5S 1N6

Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a compressed gas	
Colour	amber	
Odour	solvent-like	

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Compressed gas
Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitisation : Category 1
Carcinogenicity : Category 2

GHS label elements

Hazard pictograms









1 / 13

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H351 Suspected of causing cancer.

Precautionary statements : **Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 30 - < 60
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 10 - < 30
1,2,4-trimethylbenzene	95-63-6	>= 5 - < 10

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

2-ethylhexan-1-ol	104-76-7	>= 1 - < 5
Distillates (petroleum), straight-run middle	64741-44-2	>= 1 - < 5
Aromatic Hydrocarbons (C9 - C10)	Not Available	>= 1 - < 5
ethanol	64-17-5	>= 1 - < 5
2-(2-butoxyethoxy)ethanol	112-34-5	>= 1 - < 5
carbon dioxide	124-38-9	>= 1 - < 5
3-ethyltoluene	620-14-4	>= 1 - < 5
mesitylene	108-67-8	>= 1 - < 5
4-ethyltoluene	622-96-8	>= 1 - < 5
cumene	98-82-8	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on clothes, remove clothes.

Wash off immediately with plenty of water for at least 15

minutes.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

Immediately flush eyes for at least 15 minutes. Get medical

attention.

If swallowed : Keep respiratory tract clear.

Take victim immediately to hospital.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation;

dizziness; and confusion. May progress to unconsciousness,

paralysis, and convulsions.

Effects are dependent on exposure (dose, concentration,

contact time).

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Keep in a dry, cool and well-ventilated place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m3 (As total hydrocarbon vapour)	CA BC OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m3	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,880 mg/m3	CA QC OEL
		TWA	1,000 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m3	CA AB OEL
		STEL	30,000 ppm 54,000 mg/m3	CA AB OEL

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

		TWA	5,000 ppm	CA BC OEL
		STEL	15,000 ppm	CA BC OEL
		STEV	30,000 ppm	CA QC OEL
			54,000 mg/m3	
		TWAEV	5,000 ppm 9,000 mg/m3	CA QC OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
mesitylene	108-67-8	TWA	25 ppm	CA AB OEL
			123 mg/m3	
		TWA	25 ppm	CA BC OEL
		TWA	25 ppm	ACGIH
cumene	98-82-8	TWA	50 ppm	CA AB OEL
			246 mg/m3	
		TWA	25 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWAEV	50 ppm	CA QC OEL
			246 mg/m3	
		TWA	50 ppm	ACGIH

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work

place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a compressed gas

Colour : amber
Odour : solvent-like

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Odour Threshold : No data available pH : Not applicable Melting point/freezing point : Not applicable Boiling point : No data available

Flash point

No data available

Evaporation rate : < 1

Flammability (solid, gas,

liquid)

: Extremely flammable aerosol.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : 0.85 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : > 20 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Carbon oxides

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Symptoms

: Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness,

paralysis, and convulsions.

Effects are dependent on exposure (dose, concentration,

contact time).

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

cumene 98-82-8

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethanol 64-17-5

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

2-ethylhexan-1-ol:

Acute oral toxicity : LD50 Oral Rat: 3,730 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: > 3,000 mg/kg

ethanol:

Acute oral toxicity : LD50 Oral Rat: 7,060 mg/kg

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Components:

Distillates (petroleum), straight-run middle:

Classification: May cause sensitisation by skin contact.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n- : Remarks: No data available

octanol/water <u>Components:</u> 2-ethylhexan-1-ol :

Partition coefficient: n- : Pow: 2.9

octanol/water ethanol:

Partition coefficient: n- : Remarks: No data available

octanol/water

2-(2-butoxyethoxy)ethanol:

Partition coefficient: n- : Pow: 1

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

DSL This product contains one or more components that are listed on the

Canadian NDSL. All other components are on the Canadian DSL.

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms









.

: Danger:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Suspected of causing cancer.

Precautionary statements

Signal word

Hazard statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eve protection/ face protection.

protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with

water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 1 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.1
Revision Date:	10/01/2023
Print Date:	04/28/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

 Version 2.1
 Revision Date 10/01/2023
 Print Date 04/28/2025