

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP ELECTRONICS CLEANER

Material number : 000000000001047442

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview


Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	solvent-like

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration [%]
1,1-difluoroethane	75-37-6	>= 50 - < 70
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 30 - < 50
propan-2-ol	67-63-0	>= 3 - < 5
heptane	142-82-5	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: If skin irritation persists, call a physician. Wash off with soap and water. Wash off immediately with plenty of water for at least 15

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

	minutes. If on clothes, remove clothes.
In case of eye contact	: Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Most important symptoms and effects, both acute and delayed	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Effects are dependent on exposure (dose, concentration, contact time). Causes skin irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO ₂) Carbon monoxide Smoke Fluorine compounds
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
Keep in a dry, cool and well-ventilated place.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1,1-difluoroethane	75-37-6	TWA	1,000 ppm	US WEEL
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL
heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		C	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
		PEL	400 ppm 1,600 mg/m3	CAL PEL
		STEL	500 ppm 2,000 mg/m3	CAL PEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

Hand protection	
Material	: Protective gloves
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: clear
Odour	: solvent-like
pH	: No data available
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas, liquid)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 0.69 g/cm ³
Solubility(ies)	
Water solubility	: partly soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 22.99 kJ/g

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if used as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Effects are dependent on exposure (dose, concentration, contact time). Causes skin irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

1,1-difluoroethane:

Acute inhalation toxicity : LC50 Mouse: 977,000 mg/l
Exposure time: 2 h

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg
Method: Calculation method

heptane:

Acute inhalation toxicity : LC50 Rat: 103 mg/l
Exposure time: 4 h

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: May irritate eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

propan-2-ol :

Partition coefficient: n-octanol/water : log Pow: 0.05

heptane :

Partition coefficient: n-octanol/water : log Pow: 5

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life., Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of as hazardous waste in compliance with local and national regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel):
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

- TSCA list** : No substances are subject to a Significant New Use Rule.
- No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene	108-88-3	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Gases under pressure
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

Further information

NFPA:

HEALTH	2
FLAMMABILITY	4
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme


HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	3

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
Causes skin irritation. May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves.
Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.
Storage: Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

SAFETY DATA SHEET

ZEP ELECTRONICS CLEANER

Version 4.1

Revision Date 10/01/2023

Print Date 04/27/2025

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	4.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.