ZEP SELIG ON AND OFF LIQUID OVEN & GRILL CLEANER

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP SELIG ON AND OFF LIQUID OVEN & GRILL

CLEANER

Material number : J44600

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	colourless, clear
Odour	characteristic

GHS Classification

Skin corrosion : Category 1 Serious eye damage : Category 1

GHS label elements

Hazard pictograms :

Correction

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention**:

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

Revision Date 10/01/2023 Print Date 04/28/2025

> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
sodium hydroxide	1310-73-2	>= 5 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5	>= 1 - < 3
propane-1,2-diol	57-55-6	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with

difficulty.

Wash off immediately with plenty of water for at least 15

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.

Small amounts splashed into eyes can cause irreversible In case of eye contact

tissue damage and blindness.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain.

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment.

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

ZEP SELIG ON AND OFF LIQUID OVEN & GRILL CLEANER

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

respective authorities.

Methods and materials for containment and cleaning up

: Neutralise with acid.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

This product is formulated for use on hard metal surfaces. This product does contain a reducing agent(s) that may corrode soft metals. This product should be stored in its original packaging or containers of similar construction, and

not in metal vessels.

Materials to avoid : Do not store near acids.

Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
sodium hydroxide	1310-73-2	С	2 mg/m3	ACGIH
		С	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z-1
		С	2 mg/m3	OSHA P0
		С	2 mg/m3	CAL PEL
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
propane-1,2-diol	57-55-6	TWA	10 mg/m3	US WEEL

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location. Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless, clear
Odour : characteristic
Odour Threshold : No data available

pH : 13 - 14

Melting point/freezing point : No data available

Boiling point : $121.11 \,^{\circ}\text{C}$ Flash point : $> 93.3 \,^{\circ}\text{C}$

Method: closed cup

Evaporation rate : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 1.067 g/cm3

ZEP SELIG ON AND OFF LIQUID OVEN & GRILL CLEANER

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Bulk density : No data available

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : Not applicable

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 1116.2 mm2/s (20.0 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Incompatible materials : Reducing agents

Oxidizing agents

Acids

This product contains sodium hydroxide or potassium hydroxide that may corrode some soft metals and may react

with tin, zinc, aluminum to form hydrogen gas.

Hazardous decomposition

products

: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain.

ZEP SELIG ON AND OFF LIQUID OVEN & GRILL CLEANER

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l

Exposure time: 4 h

Test atmosphere: vapour Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

sodium hydroxide:

Acute dermal toxicity : Acute toxicity estimate Rabbit: 1,350 mg/kg

Skin corrosion/irritation

Product:

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

ZEP SELIG ON AND OFF LIQUID OVEN & GRILL CLEANER

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

sodium hydroxide:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l

Exposure time: 96 h
Test Method: static test

LC50 (Oncorhynchus tshawytscha (chinook salmon)):

152 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 40 mg/l

Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 34 - 47 mg/l

Exposure time: 48 h

EC50 (Crangon crangon (shrimp)): 33 - 100 mg/l

Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

ZEP SELIG ON AND OFF LIQUID OVEN & GRILL CLEANER

Revision Date 10/01/2023 Print Date 04/28/2025

Product:

Partition coefficient: n-

: Remarks: No data available

octanol/water Components:

2-(2-butoxyethoxy)ethanol:

Partition coefficient: n-: Pow: 1

octanol/water propane-1,2-diol:

Partition coefficient: n-: log Pow: -1.07

octanol/water

Mobility in soil No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

> with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

Components:

sodium hydroxide:

information

Additional ecological : Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYDROXIDE), 8, II - Limited quantity

ZEP SELIG ON AND OFF LIQUID OVEN & GRILL CLEANER

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Transportation Regulation: IMDG (Vessel):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYDROXIDE), 8, II - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYDROXIDE), 8, II

Transportation Regulation: IATA (Passenger Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYDROXIDE), 8, II

Transportation Regulation: TDG (Canada):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYDROXIDE), 8, II - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium hydroxide	1310-73-2	1000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-(2-butoxyethoxy)ethanol 112-34-5 2.9991 %

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

California Prop. 65



WARNING: This product can expose you to chemicals including methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Revision Date 10/01/2023 Print Date 04/28/2025

Further information

NFPA:

HEALTH	3
FLAMMABILITY	1
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Signal word Hazard statements Precautionary statements Danger:

Causes severe skin burns and eye damage.

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective

clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before

Disposal: Dispose of contents/container in accordance with local regulation.

ZEP SELIG ON AND OFF LIQUID OVEN & GRILL CLEANER

Version 2.1 Revision Date 10/01/2023 Print Date 04/28/2025

Version:	2.1
Revision Date:	10/01/2023
Print Date:	04/28/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.