G00726 MSTY RED GREASE_TUBE_48CS

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : G00726 MSTY RED GREASE_TUBE_48CS

Material number : 00000000001003057

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	gel
Colour	red
Odour	oily

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 30 - < 50
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 30 - < 50

G00726 MSTY RED GREASE TUBE 48CS

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025

acetone	67-64-1	>= 1 - < 5
quartz (SiO2)	14808-60-7	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Do not leave the victim unattended.

Get medical attention if symptoms occur.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Wash off immediately with plenty of water.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water, also under the eyelids.

Keep eye wide open while rinsing.

If swallowed : Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms

and effects, both acute and

delayed

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

G00726 MSTY RED GREASE TUBE 48CS

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent further leakage or spillage.

Clean contaminated floors and objects thoroughly while

observing environmental regulations.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Conditions for safe storage : Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable	5 mg/m3	ACGIH

G00726 MSTY RED GREASE_TUBE_48CS

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025

	[fraction)	1	
quartz (SiO2)	14808-60-7	TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m3	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
quartz (SiO2)	14808-60-7	TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWÁ (Respirable dust)	0.05 mg/m3	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI
				shift (As	_	
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Engineering measures : effective ventilation in all processing areas

G00726 MSTY RED GREASE_TUBE_48CS

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water.

Safety glasses

Skin and body protection : No special protection is required.

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : gel

Colour : red Odour : oily

Odour Threshold : No data available pH : Not applicable Boiling point : Not applicable

Flash point

Not applicable

Evaporation rate : No data available
Upper explosion limit : Not applicable
Lower explosion limit : Not applicable
Vapour pressure : No data available
Relative vapour density : No data available
Density : 0.988 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

G00726 MSTY RED GREASE TUBE 48CS

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025

Viscosity, kinematic : > 10000 mm2/s (40 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : None.

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

G00726 MSTY RED GREASE_TUBE_48CS

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 80.64 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l

Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

Skin corrosion/irritation

Product:

Remarks: May irritate skin.

Serious eye damage/eye irritation

Product:

Remarks: May irritate eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Product:

Carcinogenicity -

Assessment

: Not classifiable as a human carcinogen.

G00726 MSTY RED GREASE_TUBE_48CS

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological : No data available

G00726 MSTY RED GREASE TUBE 48CS

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025

information

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Do not burn, or use a cutting torch on, the empty drum.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

G00726 MSTY RED GREASE_TUBE_48CS

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
acetone	67-64-1	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025

Further information

NFPA:

HEALTH	0
FLAMMABILITY	1
INSTABILITY	0
SPECIAL HAZARD.	

^{0 =} not significant, 1 = Slight,

HMIS III:

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

^{0 =} not significant, 1 = Slight,

OSHA - GHS Label Information:

Not a hazardous substance or mixture.

Version:	2.1
Revision Date:	10/01/2023
Print Date:	04/25/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

^{2 =} Moderate, 3 = High

^{4 =} Extreme

^{2 =} Moderate, 3 = High

^{4 =} Extreme, * = Chronic

SAFETY DATA SHEET G00726 MSTY RED GREASE_TUBE_48CS

Version 2.1 Revision Date 10/01/2023 Print Date 04/25/2025