ZEP ZEPRESERVE

Revision Date 10/01/2023 Version 2.2 Print Date 04/25/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP ZEPRESERVE

Material number 00000000000143485

Manufacturer or supplier's details

Company Zep Inc.

Address 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Compliance Services - 877-428-9937 Telephone

Emergency telephone numbers

For SDS Information Compliance Services - 877-428-9937 For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded For a Transportation CHEMTREC: 800-424-9300 - All Calls Recorded. **Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	dark brown
Odour	sweet

GHS Classification

: Category 3 Flammable liquids Category 2A Eye irritation Aspiration hazard Category 1

GHS label elements

Hazard pictograms



Health hazard



mark

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

Precautionary statements : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

Version 2.2 Revision Date 10/01/2023 Print Date 04/25/2025

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 50 - < 70
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 20 - < 30
2-ethylhexan-1-ol	104-76-7	>= 5 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5	>= 5 - < 10

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

Version 2.2 Revision Date 10/01/2023 Print Date 04/25/2025

In case of skin contact : Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

contact time).

Symptoms may include irritation, redness, pain, and rash. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat.

Aspiration may cause pulmonary oedema and pneumonitis.

May be fatal if swallowed and enters airways.

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

Version 2.2 Revision Date 10/01/2023 Print Date 04/25/2025

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline

materials.

Version 2.2 Revision Date 10/01/2023 Print Date 04/25/2025

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

Version 2.2 Revision Date 10/01/2023 Print Date 04/25/2025

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : dark brown

Odour : sweet

Odour Threshold : No data available pH : No data available Melting point/freezing point : No data available

Boiling point : 151.7 °C Flash point : 39.4 °C

Method: closed cup

Evaporation rate : 0.1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 0.826 g/cm3

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble Solubility in other solvents : insoluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available Viscosity, kinematic : 7 mm2/s (20 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

ZEP ZEPRESERVE

Version 2.2 Revision Date 10/01/2023 Print Date 04/25/2025

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon oxides Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure

: Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

contact time).

Symptoms may include irritation, redness, pain, and rash. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat.

Aspiration may cause pulmonary oedema and pneumonitis.

May be fatal if swallowed and enters airways.

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

ZEP ZEPRESERVE

Version 2.2 Revision Date 10/01/2023 Print Date 04/25/2025

Method: Calculation method

Components:

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

2-ethylhexan-1-ol:

Acute oral toxicity : LD50 Oral Rat: 3,730 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: > 3,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Irritating to eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

ZEP ZEPRESERVE

Version 2.2 Revision Date 10/01/2023 Print Date 04/25/2025

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n- : Remarks: No data available

octanol/water
Components:
2-ethylhexan-1-ol:

Partition coefficient: n- : Pow: 2.9

octanol/water

2-(2-butoxyethoxy)ethanol:

Partition coefficient: n- : Pow: 1

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

Version 2.2 Revision Date 10/01/2023 Print Date 04/25/2025

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (PETROLEUM DISTILLATES), 3, III

Transportation Regulation: IATA (Cargo Air):

UN1993, Flammable liquid, n.o.s., (PETROLEUM DISTILLATES), 3, III

Transportation Regulation: IATA (Passenger Air):

UN1993, Flammable liquid, n.o.s., (PETROLEUM DISTILLATES), 3, III

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Version 2.2 Revision Date 10/01/2023 Print Date 04/25/2025

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation

Aspiration hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-(2-butoxyethoxy)ethanol 112-34-5 5.0642 % 2-butoxyethanol 111-76-2 0.0771 %

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Print Date 04/25/2025 Version 2.2 Revision Date 10/01/2023

Further information

NFPA:

HEALTH	2
FLAMMABILITY	2
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	3
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Health hazard



Signal word

Hazard statements

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes serious eye irritation.

Precautionary statements

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash skin thoroughly after

handling. Wear protective gloves/ eye protection/ face protection.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

SAFETY DATA SHEET ZEP ZEPRESERVE

Version 2.2 Revision Date 10/01/2023 Print Date 04/25/2025

Storage: Store in a well-ventilated place. Keep cool. **Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	2.2
Revision Date:	10/01/2023
Print Date:	04/25/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.