Version 1.2 Revision Date 10/01/2023 Print Date 04/27/2025

### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP FOAMING GLASS CLEANER 538G 12CT

Material number : CAFGC19

## Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street

Edmonton, Alberta T5S 1N6

Canada

Telephone : Compliance Services - 877-428-9937

## **Emergency telephone numbers**

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** 

Recommended use of the chemical and restrictions on use

## **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	Aerosol containing a liquefied gas		
Colour	colourless		
Odour	pleasant		

### **GHS Classification**

Gases under pressure : Liquefied gas

**GHS** label elements

Signal word

Hazard pictograms :



Gas cylinder : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Precautionary statements : Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

Version 1.2 Revision Date 10/01/2023 Print Date 04/27/2025

place.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
ethanol	64-17-5	>= 1 - < 5
butane	106-97-8	>= 1 - < 5
propan-2-ol	67-63-0	>= 1 - < 5
propane	74-98-6	>= 1 - < 5

#### **SECTION 4. FIRST AID MEASURES**

General advice : Do not leave the victim unattended.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical

Consult a physician after significant exposure.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water for at least 15 minutes.

Keep respiratory tract clear. If swallowed

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms and effects, both acute and : Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

delayed

contact time). Overexposure may cause mild eye or skin irritation.

Review section 2 of SDS to see all potential hazards.

: Treat symptomatically. Symptoms may be delayed. Notes to physician

Version 1.2 Revision Date 10/01/2023 Print Date 04/27/2025

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**Environmental precautions** 

: Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

## **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Version 1.2 Revision Date 10/01/2023 Print Date 04/27/2025

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the application area.

Do not breathe vapours or spray mist.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Keep in a dry, cool and well-ventilated place.

Materials to avoid : Oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m3	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,880 mg/m3	CA QC OEL
		TWA	1,000 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m3	CA QC OEL
		STEL	1,000 ppm	ACGIH
propan-2-ol	67-63-0	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm 983 mg/m3	CA QC OEL
		STEV	500 ppm 1,230 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

Version 1.2 Revision Date 10/01/2023 Print Date 04/27/2025

propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm	CA QC OEL
			1,800 mg/m3	
		TWA	1,000 ppm	CA ON OEL

## **Biological occupational exposure limits**

Components	CAS-No.	Control	Biological	Samplin	Permissible	Basis
		parameters	specimen	g time	concentratio	
					n	
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workwee k	40 mg/l	ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water. Safety glasses

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work

place.

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat, drink or smoke.

When using do not smoke.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : colourless
Odour : pleasant

Odour Threshold : No data available

pH : 10 - 11

Melting point/freezing point : No data available

Version 1.2 Revision Date 10/01/2023 Print Date 04/27/2025

Boiling point : No data available

Flash point

No data available

Evaporation rate : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : 0.986 g/cm3

Solubility(ies)

Water solubility : soluble in cold water, soluble in hot water

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

## **SECTION 11. TOXICOLOGICAL INFORMATION**

**Potential Health Effects** 

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

contact time).

Version 1.2 Revision Date 10/01/2023 Print Date 04/27/2025

Overexposure may cause mild eye or skin irritation. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethanol 64-17-5

2-butoxyethanol 111-76-2

**Acute toxicity** 

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

ethanol:

Acute oral toxicity : LD50 Oral Rat: 7,060 mg/kg

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg

Method: Calculation method

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Print Date 04/27/2025 Version 1.2 Revision Date 10/01/2023

STOT - single exposure

No data available

STOT - repeated exposure

No data available

**Aspiration toxicity** 

No data available

**Further information** 

**Product:** 

Remarks: No data available

### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water **Components:** ethanol:

Partition coefficient: n-

octanol/water

butane:

Partition coefficient: n-

octanol/water propan-2-ol:

Partition coefficient: n-

octanol/water

: Pow: 2.89

: log Pow: 0.05

: Remarks: No data available

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Additional ecological

information

: No data available

Version 1.2 Revision Date 10/01/2023 Print Date 04/27/2025

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

## **SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

Version 1.2 Revision Date 10/01/2023 Print Date 04/27/2025

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

### **SECTION 16. OTHER INFORMATION**

WHMIS - GHS Label Information:

Hazard pictograms

Gas cylinder

Signal word

Warning:

Hazard statements

Contains gas under pressure; may explode if heated. Precautionary statements

Storage: Protect from sunlight. Store in a well-ventilated place.

Version:	1.2
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.