

# SAFETY DATA SHEET

## ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Material number : B41801

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

#### Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation  
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview


Appearance	Aerosol containing a compressed gas
Colour	pink
Odour	characteristic

#### GHS Classification

Flammable aerosols : Category 1  
Gases under pressure : Compressed gas  
Skin irritation : Category 2

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames  
and other ignition sources. No smoking.

# SAFETY DATA SHEET

## ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Disposal:

P501 Dispose of contents/container in accordance with local regulation.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 70 - < 90
Propanol, 1(or 2)-(2-methoxymethylethoxy)-, acetate	88917-22-0	>= 5 - < 10
Fuel oil, no. 2	68476-30-2	>= 3 - < 5
carbon dioxide	124-38-9	>= 3 - < 5
kerosine (petroleum)	8008-20-6	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

## SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.  
Get medical attention.

If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.  
Wash off immediately with plenty of water for at least 15 minutes.

## SAFETY DATA SHEET

### ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

	Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.
In case of eye contact	: Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration, contact time). Review section 2 of SDS to see all potential hazards. Causes skin irritation. Causes serious eye irritation.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

---

## SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO2) Water spray jet Alcohol-resistant foam Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment	: Wear self-contained breathing apparatus for firefighting if

# SAFETY DATA SHEET

## ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

for firefighters

necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains, inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Always replace cap after use.  
Dispose of rinse water in accordance with local and national regulations.  
Do not breathe vapours or spray mist.
- Conditions for safe storage : No smoking.  
Observe label precautions.  
Keep in a dry, cool and well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.  
BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
- Materials to avoid : Oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible	Basis
------------	---------	----------------------------------	----------------------------------	-------

**SAFETY DATA SHEET****ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT**

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

			concentration	
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0
		PEL	5,000 ppm 9,000 mg/m3	CAL PEL
		STEL	30,000 ppm 54,000 mg/m3	CAL PEL
kerosine (petroleum)	8008-20-6	TWA	100 mg/m3	NIOSH REL

**Engineering measures** : effective ventilation in all processing areas

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Safety glasses

Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

# SAFETY DATA SHEET

## ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a compressed gas
Colour	: pink
Odour	: characteristic
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas, liquid)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 0.8425 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 43.62 kJ/g

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

## ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration, contact time). Review section 2 of SDS to see all potential hazards. Causes skin irritation. Causes serious eye irritation. Treat symptomatically. Symptoms may be delayed.

#### Carcinogenicity:

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### Acute toxicity

##### Product:

Acute inhalation toxicity	: Acute toxicity estimate : 41.98 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : 3,072 mg/kg Method: Calculation method

##### Components:

##### **Distillates (petroleum), hydrotreated light:**

Acute oral toxicity	: LD50 Rat: > 5,000 mg/kg
---------------------	---------------------------

## SAFETY DATA SHEET

### ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l  
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

#### Skin corrosion/irritation

**Product:**

Remarks: Irritating to skin.

#### Serious eye damage/eye irritation

**Product:**

Remarks: Irritating to eyes.

#### Respiratory or skin sensitisation

**Product:**

Remarks: Not applicable

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

#### Aspiration toxicity

No data available

#### Further information

**Product:**

Remarks: No data available

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity



# SAFETY DATA SHEET

## ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

No data available

### Persistence and degradability

No data available

### Bioaccumulative potential

#### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

### Mobility in soil

No data available

### Other adverse effects

No data available

#### Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

# SAFETY DATA SHEET

## ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### SECTION 15. REGULATORY INFORMATION

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
naphthalene	91-20-3	100	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Gases under pressure  
Skin corrosion or irritation

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

##### California Prop. 65



WARNING: This product can expose you to chemicals including naphthalene, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# SAFETY DATA SHEET

## ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>4</b>
<b>INSTABILITY</b>	<b>0</b>
<b>SPECIAL HAZARD.</b>	

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme

#### HMIS III:

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>4</b>
<b>PHYSICAL HAZARD</b>	<b>1</b>

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

# SAFETY DATA SHEET


## ZEP 45 SIDEWINDER SUPER PENETRANT 20N14 12CT

Version 3.1

Revision Date 10/01/2023

Print Date 04/27/2025

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.  
Causes skin irritation. Causes serious eye irritation.

Precautionary statements

:  
**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection.  
**Response:** IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.  
**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	3.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.