

## A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

: A00736 WIP ZEP MINI THROTTLE EA Material name

Material number U229 Manufacturer or supplier's details

Company : Zep Inc.

Address 1310 Seaboard Industrial Blvd., NW

Atlanta, GA 30318

Telephone 404-352-1680

For SDS Information Compliance Services 1-877-428-9937 For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded For a Transportation CHEMTREC: 800-424-9300 - All Calls Recorded. In the District of Columbia 202-483-7616 **Emergency** 

#### Recommended use of the chemical and restrictions on use

: Vehicle Maintenance Recommended use

### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	Aerosol containing a compressed gas
Colour	clear
Odour	solvent-like

#### **GHS Classification**

: Category 1 Flammable aerosols : Compressed gas Gases under pressure : Category 2 Skin irritation Eve irritation : Category 2A Reproductive toxicity : Category 2

Specific target organ toxicity - : Category 3 (Central nervous system)

single exposure

Specific target organ toxicity -

repeated exposure

(Inhalation)

: Category 2

### **GHS** label elements

Hazard pictograms









Signal word Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.



## A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or

repeated exposure if inhaled.

### Precautionary statements

#### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

P281 Use personal protective equipment as required.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

P362 Take off contaminated clothing and wash before reuse.

#### Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

#### Disposal:

Dispose of contents/container in accordance with local regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

## **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 50 - < 70
Distillates (petroleum), hydrotreated light	64742-47-8	>= 20 - < 30
toluene	108-88-3	>= 5 - < 10
carbon dioxide	124-38-9	>= 5 - < 10

The exact percentages of disclosed substances are withheld as trade secrets.



## A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

:

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.



## A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50  $^{\circ}$ C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

Strong oxidizing agents

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**



# A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

# Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
		PEL	10 ppm 37 mg/m3	CAL PEL
		С	500 ppm	CAL PEL
		STEL	150 ppm 560 mg/m3	CAL PEL
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0
		PEL	5,000 ppm 9,000 mg/m3	CAL PEL
		STEL	30,000 ppm 54,000 mg/m3	CAL PEL

**Biological occupational exposure limits** 



# A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
				ceases)		
METHYLBENZENE	108-88-3	Toluene	In blood	Prior to	0.02 mg/l	ACGIH BEI
				last shift		
				of		
				workwee		
				k		
METHYLBENZENE		Toluene	Urine	End of	0.03 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
METING BENJERNE				ceases)		400000
METHYLBENZENE		o-Cresol	Urine	End of	0.3.mg/g	ACGIH BEI
				shift (As	Creatinine	
				soon as		
				possible		
				after		
				exposure		
				ceases)		

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a compressed gas



## A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

Colour : clear

Odour : solvent-like

pH : Not applicable

Melting point/freezing point : No data available

Boiling point : No data available

Flash point

Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available

Density : 0.8 g/cm3

Solubility(ies)

Water solubility : partly soluble
Partition coefficient: n- : No data available

octanol/water

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 33.98 kJ/g

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Strong oxidizing agents

Hazardous decomposition

products

: Carbon oxides

### **SECTION 11. TOXICOLOGICAL INFORMATION**



## A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

#### **Potential Health Effects**

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

## **Acute toxicity**

#### **Components:**

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l

Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

#### Skin corrosion/irritation

### Product:

Remarks: Irritating to skin.

## Serious eye damage/eye irritation

#### **Product:**

Remarks: Severe eye irritation

## Respiratory or skin sensitisation

No data available



# A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

# Reproductive toxicity

No data available

acetone:

Distillates (petroleum), hydrotreated light:

toluene:

carbon dioxide:

## STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### **Aspiration toxicity**

No data available

#### **Further information**

### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

## **Components:**

Distillates (petroleum), hydrotreated light:

Remarks: No data available

toluene:

Remarks: No data available

### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

No data available

### Persistence and degradability

No data available

## **Bioaccumulative potential**

## Product:

Partition coefficient: n-

octanol/water

: Remarks: No data available



# A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

**Components:** 

toluene :

Partition coefficient: n-

octanol/water

: Pow: 2.73

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to

aquatic life with long lasting effects.

Components:

Distillates (petroleum), hydrotreated light :

Additional ecological

information toluene:

: No data available

Additional ecological

information

: No data available

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION** 

Transportation Regulation: 49 CFR (USA):

ORM-D, CONSUMER COMMODITY



## A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, (LQ), - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

## **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Sudden Release of Pressure Hazard

Acute Health Hazard Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

toluene 108-88-3 9.975 %

**California Prop 65** WARNING: This product contains a chemical known to the

State of California to cause birth defects or other reproductive

harm.

toluene 108-88-3

## The components of this product are reported in the following inventories:



## A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

TSCA On TSCA Inventory

**DSL** All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


### **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA:



Special hazard.

#### HMIS III:

HEALTH	2*
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

## **OSHA - GHS Label Information:**

Hazard pictograms









Signal word Hazard statements Danger:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection. Wear protective gloves. Use personal protective equipment as required.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical

advice/ attention. Take off contaminated clothing and wash before reuse. **Storage:** Store locked up. Protect from sunlight. Do not expose to temperatures

exceeding 50 °C/ 122 °F.

**Disposal**: Dispose of contents/container in accordance with local regulation.



## A00736 WIP ZEP MINI THROTTLE EA

Version 1.1 Revision Date 10/06/2016 Print Date 07/05/2017

Version:	1.1
Revision Date:	10/06/2016
Print Date:	07/05/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.



## **BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ**

Version 2.1 Revision Date 03/02/2016 Print Date 07/05/2017

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ

Material number : R42900

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW

Atlanta, GA 30318

Telephone : 404-352-1680

For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

In the District of Columbia 202-483-7616

#### **SECTION 2. HAZARDS IDENTIFICATION**

### **Emergency Overview**

Appearance	liquid
Colour	blue
Odour	strong, solvent-like

#### **GHS Classification**

Flammable liquids : Category 3
Skin irritation : Category 2
Eye irritation : Category 2A
Carcinogenicity : Category 2
Aspiration hazard : Category 1

**GHS Label element** 

Hazard pictograms :







Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H351 Suspected of causing cancer.

Precautionary statements : **Prevention:** 

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.



## **BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ**

Version 2.1 Revision Date 03/02/2016 Print Date 07/05/2017

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

P281 Use personal protective equipment as required.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

## Storage:

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

#### Disposal:

Dispose of contents/container in accordance with local regulation.

## **Potential Health Effects**

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**



## **BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ**

Version 2.1 Revision Date 03/02/2016 Print Date 07/05/2017

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical Name	CAS-No.	Concentration [%]
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 90 - <= 100
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Immediately flush eyes for at least 15 minutes. Get medical

attention.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide



## **BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ**

Version 2.1 Revision Date 03/02/2016 Print Date 07/05/2017

Smoke

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: No smoking.

Keep container tightly closed in a dry and well-ventilated

place.



## **BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ**

Version 2.1 Revision Date 03/02/2016 Print Date 07/05/2017

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

Strong oxidizing agents

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL
xylenes	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : blue

Odour : strong, solvent-like



# **BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ**

Version 2.1 Revision Date 03/02/2016 Print Date 07/05/2017

Odour Threshold : No data available pH : No data available Melting point/freezing point : No data available

Boiling point : < 304 °C

Flash point : 41.11 °C

Method: TCC

Evaporation rate : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available

Relative vapour density : 1

Density : 0.78 g/cm3

Solubility(ies)

Water solubility : partly soluble Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Strong oxidizing agents

Hazardous decomposition

products

: Carbon oxides

Smoke



# **BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ**

Version 2.1 Revision Date 03/02/2016 Print Date 07/05/2017

### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

### **Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 40 mg/l

Exposure time: 4 h

Test atmosphere: vapour Method: Calculation method

#### Skin corrosion/irritation

### **Product:**

Remarks: Irritating to skin.

## Serious eye damage/eye irritation

### **Product:**

Remarks: Severe eye irritation

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

## Carcinogenicity

No data available

### Reproductive toxicity

No data available

### Naphtha (petroleum), hydrotreated light:

1,2,4-trimethylbenzene:

## STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

## **Aspiration toxicity**

No data available

#### **Further information**

## Product:

Remarks: Solvents may degrease the skin.



## **BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ**

Version 2.1 Revision Date 03/02/2016 Print Date 07/05/2017

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the

event of unprofessional handling or disposal., Harmful to

aquatic life with long lasting effects.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**



## **BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ**

Version 2.1 Revision Date 03/02/2016 Print Date 07/05/2017

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (PETROLEUM DISTILLATES), 3, III - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1993, Flammable liquid, n.o.s., (PETROLEUM DISTILLATES), 3, III - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1993, Flammable liquid, n.o.s., (PETROLEUM DISTILLATES), 3, III - Limited quantity

Transportation Regulation: TDG (Canada):

UN1993, FLAMMABLE LIQUID, N.O.S., (PETROLEUM DISTILLATES), 3, III - Limited quantity

### **SECTION 15. REGULATORY INFORMATION**

### **EPCRA - Emergency Planning and Community Right-to-Know Act**

## **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
naphthalene	91-20-3	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

 1,2,4-trimethylbenzene
 95-63-6
 4.9536 %

 naphthalene
 91-20-3
 0.2624 %

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.

ethylbenzene 100-41-4 benzene 71-43-2 naphthalene 91-20-3

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

harm.

toluene 108-88-3 benzene 71-43-2



## **BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ**

Version 2.1 Revision Date 03/02/2016 Print Date 07/05/2017

### The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

**DSL** All components of this product are on the Canadian DSL

AICS
Not in compliance with the inventory
NZIOC
Not in compliance with the inventory
Not in compliance with the inventory
IECSC
Not in compliance with the inventory


## **Inventory Acronym and Validity Area Legend:**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA:



Special hazard.

#### HMIS III:

HEALTH	2*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

#### **OSHA GHS Label Information:**

Hazard pictograms







Signal word

Hazard statements

: Danger:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer.

Precautionary statements

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face

Response: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire:

Use dry sand, dry chemical or alcohol-resistant toam for extinction.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container in accordance with local regulation.

protection. Use personal protective equipment as required.



## **BJ0075 WIP ZEP FUEL INJ CLNR 12 OZ**

Version 2.1 Revision Date 03/02/2016 Print Date 07/05/2017

Version:	2.1
Revision Date:	03/02/2016
Print Date:	07/05/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.



## **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : BJ0742 ZEP TOP ENGINE CLNR 12OZ

Material number : V33800

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW

Atlanta, GA 30318

Telephone : 404-352-1680

**Emergency telephone numbers** 

For SDS Information: Compliance Services 1-877-428-9937For a Medical Emergency: 877-541-2016 Toll Free - All Calls RecordedFor a Transportation: CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** In the District of Columbia 202-483-7616

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	liquid
Colour	colourless
Odour	ammoniacal

#### **GHS Classification**

Flammable liquids : Category 2
Skin corrosion : Category 1A
Serious eye damage : Category 1
Carcinogenicity : Category 2
Reproductive toxicity : Category 1B

Specific target organ toxicity -

single exposure

Specific target organ toxicity -

repeated exposure

(Inhalation)

Aspiration hazard : Category 1

**GHS Label element** 

Hazard pictograms :



: Category 2



: Category 3 (Central nervous system)





Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage.

H336 May cause drowsiness or dizziness.



## **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or

repeated exposure if inhaled.

#### Precautionary statements

#### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P281 Use personal protective equipment as required.

#### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

## Disposal:

Dispose of contents/container in accordance with local regulation.

#### **Potential Health Effects**

#### Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed



## **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## Hazardous components

Chemical Name	CAS-No.	Concentration [%]
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 30 - < 50
propan-2-ol	67-63-0	>= 10 - < 20
toluene	108-88-3	>= 10 - < 20
triethylamine	121-44-8	>= 10 - < 20
1-methyl-2-pyrrolidone	872-50-4	>= 5 - < 10
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 5
ammonia, anhydrous	7664-41-7	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

## **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water for at least 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.



## **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Nitrogen oxides (NOx)

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions :

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.



## **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Do not breathe vapours or spray mist.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Store and keep away from, oxidizing agents and acids.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm	OSHA P0



# **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

			560 mg/m3	
triethylamine	121-44-8	TWA	1 ppm	ACGIH
-		STEL	3 ppm	ACGIH
		TWA	25 ppm 100 mg/m3	OSHA Z-1
		STEL	15 ppm 60 mg/m3	OSHA P0
		TWA	10 ppm 40 mg/m3	OSHA P0
1-methyl-2-pyrrolidone	872-50-4	TWA	10 ppm	US WEEL
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL

## **Biological occupational exposure limits**

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workwee k	40 mg/l	ACGIH BEI
METHYLBENZENE	108-88-3	Toluene	In blood	Prior to last shift of workwee k	0.02 mg/l	ACGIH BEI
METHYLBENZENE		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
METHYLBENZENE		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g	ACGIH BEI
Remarks: Creatinine						
N-METHYL-2- PYRROLIDINONE	872-50-4	5-Hydroxy- N-methyl-2- pyrrolidone	Urine	End of shift (As soon as possible after exposure ceases)	100 mg/l	ACGIH BEI

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection



## **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location.

Safety glasses

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : colourless
Odour : ammoniacal

Odour Threshold : No data available pH : No data available Melting point/freezing point : No data available

Boiling point : 82 - 202 °C

Flash point : 8.89 °C

Method: PMCC

Evaporation rate : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : Not applicable
Relative vapour density : No data available

Density : 0.80 g/cm3

Solubility(ies)

Water solubility : partly soluble
Partition coefficient: n- : No data available

octanol/water

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available



## **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Strong oxidizing agents

Hazardous decomposition

products

: Smoke

Carbon monoxide Nitrogen oxides (NOx) Carbon dioxide (CO2)

Hydrocarbons

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate : 3,946 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 25.84 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 3,000 mg/kg

Method: Calculation method

**Components:** 

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg

Method: Calculation method

1-methyl-2-pyrrolidone:

Acute oral toxicity : LD50 Oral Rat: 3,914 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 8,000 mg/kg

## Skin corrosion/irritation

**Product:** 



# **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

Remarks: Extremely corrosive and destructive to tissue.

### Serious eye damage/eye irritation

## **Product:**

Remarks: May cause irreversible eye damage.

### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

## Carcinogenicity

No data available

## Reproductive toxicity

No data available

Naphtha (petroleum), hydrotreated light:

propan-2-ol:

toluene:

triethylamine:

1-methyl-2-pyrrolidone:

1,2,4-trimethylbenzene:

ammonia, anhydrous:

#### STOT - single exposure

No data available

## STOT - repeated exposure

No data available

### **Aspiration toxicity**

No data available

### **Further information**

#### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

No data available

## Persistence and degradability

No data available

Bioaccumulative potential



## **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

: Remarks: No data available

**Product:** 

Partition coefficient: n-

octanol/water <a href="Components:toluene">Components:toluene</a> :

Partition coefficient: n-

: Pow: 2.73

octanol/water

1-methyl-2-pyrrolidone:

Partition coefficient: n-

: log Pow: -0.46

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the

event of unprofessional handling or disposal., Harmful to

aquatic life with long lasting effects.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

## **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY



## **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

Transportation Regulation: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (ISOPROPANOL), 3, II - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1993, Flammable liquid, n.o.s., (ISOPROPANOL), 3, II - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1993, Flammable liquid, n.o.s., (ISOPROPANOL), 3, II - Limited quantity

Transportation Regulation: TDG (Canada):

UN1993, FLAMMABLE LIQUID, N.O.S., (ISOPROPANOL), 3, II - Limited quantity

#### **SECTION 15. REGULATORY INFORMATION**

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene	108-88-3	1000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
ammonia, anhydrous	7664-41-7	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

Fire Hazard

SARA 302 : The following components are subject to reporting levels

established by SARA Title III, Section 302:

ammonia, anhydrous 7664-41-7 0.9 %

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

11.4 % toluene 108-88-3 10 % triethylamine 121-44-8 1-methyl-2-pyrrolidone 872-50-4 5 % 1,2,4-trimethylbenzene 2.6034 % 95-63-6 0.195 % naphthalene 91-20-3 ethylbenzene 100-41-4 0.195 %

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.

 ethylbenzene
 100-41-4

 benzene
 71-43-2

 naphthalene
 91-20-3

WARNING: This product contains a chemical known to the



## **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

State of California to cause birth defects or other reproductive

harm.

toluene 108-88-3 1-methyl-2-pyrrolidone 872-50-4 benzene 71-43-2

#### The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

**DSL** All components of this product are on the Canadian DSL

AICS
Not in compliance with the inventory
NZIOC
Not in compliance with the inventory
PICCS
Not in compliance with the inventory
IECSC
Not in compliance with the inventory


### **Inventory Acronym and Validity Area Legend:**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA:



Special hazard.

#### HMIS III:

HEALTH	3*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

#### OSHA GHS Label Information:

Hazard pictograms :









Signal word : Danger:

Hazard statements : Highly flammable liquid and vapour. May be fatal if swallowed and enters airways.

Causes severe skin burns and eye damage. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility or the unborn child. May cause

damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements :

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective



## **BJ0742 ZEP TOP ENGINE CLNR 120Z**

Version 2.1 Revision Date 03/11/2016 Print Date 07/05/2017

clothing/ eye protection/ face protection. Use personal protective equipment as required.

Response: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/ attention. Wash contaminated clothing before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.1
Revision Date:	03/11/2016
Print Date:	07/05/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.