

# SAFETY DATA SHEET

## ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP POWER HOUSE 20N18 12CT

Material number : 000000000000028201

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

#### Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	characteristic

#### GHS Classification

Gases under pressure : Liquefied gas  
Skin irritation : Category 2  
Eye irritation : Category 2A

#### GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**  
P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**

# SAFETY DATA SHEET

## ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

### **Storage:**

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

P412 Do not expose to temperatures exceeding 50 °C/ 122 °F.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
ethanol	64-17-5	>= 10 - < 30
butane	106-97-8	>= 1 - < 5
2-butoxyethanol	111-76-2	>= 1 - < 5
2-aminoethanol	141-43-5	>= 1 - < 5
propan-2-ol	67-63-0	>= 1 - < 5
propane	74-98-6	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
Wash off immediately with plenty of water for at least 15 minutes.  
If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.  
If in eyes, rinse with water for 15 minutes.
- If swallowed : Keep respiratory tract clear.

# SAFETY DATA SHEET

## ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

Never give anything by mouth to an unconscious person.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Causes skin irritation.  
Causes serious eye irritation.  
Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

---

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray jet  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke  
Nitrogen oxides (NO<sub>x</sub>)

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Remove all sources of ignition.

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains, inform respective authorities.  
Prevent product from entering drains.

Methods and materials for : Wipe up with absorbent material (e.g. cloth, fleece).

# SAFETY DATA SHEET

## ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

containment and cleaning up

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Always replace cap after use.  
Dispose of rinse water in accordance with local and national regulations.  
Do not breathe vapours or spray mist.  
Avoid exposure - obtain special instructions before use.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.  
Keep in a dry, cool and well-ventilated place.
- Materials to avoid : Do not store near acids.  
Strong oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
		STEL	1,000 ppm	ACGIH
		PEL	1,000 ppm 1,900 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH

# SAFETY DATA SHEET

## ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
		PEL	20 ppm 97 mg/m3	CAL PEL
2-aminoethanol	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m3	NIOSH REL
		ST	6 ppm 15 mg/m3	NIOSH REL
		TWA	3 ppm 6 mg/m3	OSHA Z-1
		STEL	6 ppm 15 mg/m3	OSHA P0
		TWA	3 ppm 8 mg/m3	OSHA P0
		PEL	3 ppm 8 mg/m3	CAL PEL
		STEL	6 ppm 15 mg/m3	CAL PEL
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL

### Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as	200.mg/g Creatinine	ACGIH BEI

# SAFETY DATA SHEET

## ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

				possible after exposure ceases)		
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Tightly fitting safety goggles

Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : colourless

Odour : characteristic

Odour Threshold : No data available

pH : 10.5 - 11.5

Melting point/freezing point : No data available

Boiling point : Not applicable

Flash point

:

Not applicable

Evaporation rate

: < 1

n-Butyl Acetate = 1.0

## SAFETY DATA SHEET

### ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

Flammability (solid, gas, liquid) : The product is not flammable.

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.97 g/cm<sup>3</sup>

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : not determined

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : < 20 kJ/g

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.  
No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.  
Extremes of temperature and direct sunlight.

Incompatible materials : Acids  
Strong oxidizing agents

Hazardous decomposition products : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).  
Nitrogen oxides (NO<sub>x</sub>)

---

## SECTION 11. TOXICOLOGICAL INFORMATION

### Potential Health Effects

## SAFETY DATA SHEET

### ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Causes skin irritation.  
Causes serious eye irritation.  
Review section 2 of SDS to see all potential hazards.  
Treat symptomatically. Symptoms may be delayed.

#### Carcinogenicity:

##### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

##### ACGIH

Confirmed animal carcinogen with unknown relevance to humans

ethanol

64-17-5

2-butoxyethanol

111-76-2

##### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

##### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### Acute toxicity

##### Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 22.33 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

##### Components:

###### ethanol:

Acute oral toxicity : LD50 Oral Rat: 7,060 mg/kg

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

###### 2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg



# SAFETY DATA SHEET

## ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

### **2-aminoethanol:**

Acute oral toxicity : LD50 Oral Mouse: 700 mg/kg

LD50 Oral Rat: 1,515 mg/kg

Acute inhalation toxicity : LC50 Mouse: > 1.21 mg/l

### **propan-2-ol:**

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg  
Method: Calculation method

### **Skin corrosion/irritation**

#### **Product:**

Remarks: Irritating to skin.

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks: Severe eye irritation

### **Respiratory or skin sensitisation**

No data available

### **Germ cell mutagenicity**

No data available

### **Carcinogenicity**

No data available

### **Reproductive toxicity**

No data available

### **STOT - single exposure**

No data available

### **STOT - repeated exposure**

No data available

### **Aspiration toxicity**

No data available

### **Further information**

#### **Product:**

Remarks: No data available

# SAFETY DATA SHEET

## ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

##### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

##### Components:

##### **ethanol :**

Partition coefficient: n-octanol/water : Remarks: No data available

##### **butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

##### **2-aminoethanol :**

Partition coefficient: n-octanol/water : log Pow: -1.31

##### **propan-2-ol :**

Partition coefficient: n-octanol/water : log Pow: 0.05

#### Mobility in soil

No data available

#### Other adverse effects

No data available

##### Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.

# SAFETY DATA SHEET

## ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### SECTION 15. REGULATORY INFORMATION

**TSCA list** : No substances are subject to a Significant New Use Rule.  
  
No substances are subject to TSCA 12(b) export notification requirements.

#### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
2,2'-iminodiethanol	111-42-2	100	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Gases under pressure  
Skin corrosion or irritation

# SAFETY DATA SHEET

## ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

Serious eye damage or eye irritation

### SARA 302

: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

2-butoxyethanol	111-76-2	3.9604 %
-----------------	----------	----------

### California Prop. 65



WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The components of this product are reported in the following inventories:

#### DSL TSCA

All components of this product are on the Canadian DSL  
On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

## SECTION 16. OTHER INFORMATION

# SAFETY DATA SHEET

## ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

### Further information

#### NFPA:

HEALTH	2
FLAMMABILITY	1
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme

#### HMIS III:

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	3

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

Hazard pictograms



Signal word

Hazard statements

Precautionary statements

: **Warning:**  
: Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation.  
:  
: **Prevention:** Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection.  
: **Response:** IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.  
: **Storage:** Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F.

## SAFETY DATA SHEET

### ZEP POWER HOUSE 20N18 12CT

Version 3.2

Revision Date 10/01/2023

Print Date 04/27/2025

Version:	3.2
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.