

# SAFETY DATA SHEET

## PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Material number : V93600

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

#### Emergency telephone numbers

**For SDS Information** : Compliance Services - 877-428-9937

**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	liquid
Colour	clear, colourless
Odour	characteristic

#### GHS Classification

Flammable liquids : Category 3  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Carcinogenicity : Category 2  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)  
Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.

## SAFETY DATA SHEET

# PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.

### Precautionary statements

#### : **Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### **Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### **Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P235 Keep cool.

#### **Disposal:**

P501 Dispose of contents/container in accordance with local regulation.

---

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

# SAFETY DATA SHEET

## PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration [%]
Naphtha (petroleum), hydrotreated light	64742-49-0	$\geq 70$ - $< 90$
1,2,4-trimethylbenzene	95-63-6	$\geq 1$ - $< 5$
xylene	1330-20-7	$\geq 1$ - $< 5$
Paraffins (Petroleum), Normal C5-20	64771-72-8	$\geq 1$ - $< 5$
propan-2-ol	67-63-0	$\geq 1$ - $< 5$
ethylbenzene	100-41-4	$\geq 0.1$ - $< 1$

The exact percentages of disclosed substances are withheld as trade secrets.

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.  
Remove contaminated clothing and shoes.  
Wash contaminated clothing before re-use.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.  
Rinse immediately with plenty of water for at least 15 minutes.
- If swallowed : Keep respiratory tract clear.  
If swallowed, call a poison control centre or doctor immediately.  
If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.  
Effects are dependent on exposure (dose, concentration, contact time).  
Aspiration may cause pulmonary oedema and pneumonitis.  
Chronic effects are delayed and symptoms may not be observed during an exposure.

## SAFETY DATA SHEET

# PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

Causes skin irritation.  
May cause drowsiness or dizziness.  
Causes serious eye irritation.  
Suspected of causing cancer.  
May be fatal if swallowed and enters airways.  
Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

---

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains, inform respective authorities.
- Methods and materials for : Soak up with inert absorbent material (e.g. sand, silica gel,

## SAFETY DATA SHEET

# PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

containment and cleaning up

acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling

: Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Do not breathe vapours or spray mist.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage

: No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid

: Store and keep away from, oxidizing agents and acids.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL
xylenes	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	CAL PEL
		C	300 ppm	CAL PEL
		PEL	100 ppm 435 mg/m3	CAL PEL
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm	OSHA Z-1

**SAFETY DATA SHEET****PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL  
SYSTEM SUPREME**

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

			980 mg/m3	
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL
ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		STEL	125 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
		PEL	5 ppm 22 mg/m3	CAL PEL
		STEL	30 ppm 130 mg/m3	CAL PEL

**Biological occupational exposure limits**

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI
ETHYLBENZENE	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15.g/g creatinine	ACGIH BEI
ETHYLBENZENE		Ethylbenzene	In end-exhaled air	Not critical		ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection  
Material : Protective gloves

## SAFETY DATA SHEET

# PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: Wash hands before breaks and at the end of workday. When using do not eat, drink or smoke.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: clear, colourless
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point	: 160 - 304 °C
Flash point	: 38.89 °C Method: TCC
Evaporation rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: Not applicable
Relative vapour density	: No data available
Density	: 0.82 g/cm3
Solubility(ies)	
Water solubility	: negligible
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available

## SAFETY DATA SHEET

# PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Acids Strong oxidizing agents
Hazardous decomposition products	: Smoke Carbon monoxide Carbon dioxide (CO <sub>2</sub> ) Hydrocarbons

## SECTION 11. TOXICOLOGICAL INFORMATION

### Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Effects are dependent on exposure (dose, concentration, contact time). Aspiration may cause pulmonary oedema and pneumonitis. Chronic effects are delayed and symptoms may not be observed during an exposure. Causes skin irritation. May cause drowsiness or dizziness. Causes serious eye irritation. Suspected of causing cancer. May be fatal if swallowed and enters airways. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

### Carcinogenicity:

IARC	Group 2B: Possibly carcinogenic to humans	
ACGIH	ethylbenzene Confirmed animal carcinogen with unknown relevance to humans	100-41-4



## SAFETY DATA SHEET

# PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

<b>OSHA</b>	ethylbenzene	100-41-4
	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.	
<b>NTP</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.	

### Acute toxicity

#### Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 148.3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

#### Components:

**propan-2-ol:**  
Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg  
Method: Calculation method

### Skin corrosion/irritation

#### Product:

Remarks: Irritating to skin.

### Serious eye damage/eye irritation

#### Product:

Remarks: Severe eye irritation

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

No data available

## SAFETY DATA SHEET

# PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

#### Product:

Remarks: Solvents may degrease the skin.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

### Persistence and degradability

No data available

### Bioaccumulative potential

#### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

#### Components:

##### **xylenes :**

Partition coefficient: n-octanol/water : Pow: 3.12

##### **propan-2-ol :**

Partition coefficient: n-octanol/water : log Pow: 0.05

##### **ethylbenzene :**

Partition coefficient: n-octanol/water : Pow: 3.6

### Mobility in soil

No data available

### Other adverse effects

No data available

#### Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

## SAFETY DATA SHEET

# PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

Additional ecological information : No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN1993, Flammable liquids, n.o.s., (PETROLEUM DISTILLATES), 3, III - Limited quantity

Transportation Regulation: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (PETROLEUM DISTILLATES), 3, III - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1993, Flammable liquid, n.o.s., (PETROLEUM DISTILLATES), 3, III - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1993, Flammable liquid, n.o.s., (PETROLEUM DISTILLATES), 3, III - Limited quantity

Transportation Regulation: TDG (Canada):

UN1993, FLAMMABLE LIQUID, N.O.S., (PETROLEUM DISTILLATES), 3, III - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : No substances are subject to a Significant New Use Rule.

# SAFETY DATA SHEET

## PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

No substances are subject to TSCA 12(b) export notification requirements.

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	3199

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

1,2,4-trimethylbenzene	95-63-6	4.2919 %
ethylbenzene	100-41-4	0.8335 %

#### California Prop. 65



WARNING: This product can expose you to chemicals including ethylbenzene, benzene, naphthalene, which is/are known to the State of California to cause cancer, and toluene, benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### The components of this product are reported in the following inventories:

**TSCA** On TSCA Inventory  
**DSL** All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

#### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

# SAFETY DATA SHEET

## PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

### SECTION 16. OTHER INFORMATION

#### Further information

#### NFPA:

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>2</b>
<b>INSTABILITY</b>	<b>0</b>
<b>SPECIAL HAZARD.</b>	

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme

#### HMIS III:

<b>HEALTH</b>	<b>3*</b>
<b>FLAMMABILITY</b>	<b>2</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

Hazard pictograms

:



Flame



Health hazard



Exclamation  
mark

Signal word

: **Danger:**

Hazard statements

: Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary statements

:

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary

# SAFETY DATA SHEET

## PETRO CHEMICAL FX 2 PROFESSIONAL STRENGTH FUEL SYSTEM SUPREME

Version 4.1

Revision Date 10/01/2023

Print Date 04/28/2025

measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:** IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Keep cool.

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	4.1
Revision Date:	10/01/2023
Print Date:	04/28/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.