Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP INSTANT SPOT REMOVER 20N538G 12CT

Material number : CASPOT19

### Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street

Edmonton, Alberta T5S 1N6

Canada

Telephone : Compliance Services - 877-428-9937

### **Emergency telephone numbers**

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** 

Recommended use of the chemical and restrictions on use

### **SECTION 2. HAZARDS IDENTIFICATION**

### **Emergency Overview**

Appearance	Aerosol containing a liquefied gas		
Colour	clear		
Odour	characteristic		

### **GHS Classification**

Gases under pressure : Liquefied gas
Eye irritation : Category 2A
Reproductive toxicity : Category 1B

**GHS** label elements

Hazard pictograms :



odor Hoolth bazz



Gas cylinder

der Health hazard

Signal word : Danger

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

Precautionary statements : **Prevention:** 

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention. **Storage:** 

P410 + P403 Protect from sunlight. Store in a well-ventilated

place. **Disposal:** 

P501 Dispose of contents/container in accordance with local

regulation.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

### **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
2-butoxyethanol	111-76-2	>= 5 - < 10
butane	106-97-8	>= 1 - < 5
acetone	67-64-1	>= 1 - < 5
propane	74-98-6	>= 1 - < 5
sodium borate, decahydrate	1303-96-4	>= 0.1 - < 1

### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

and effects, both ac delayed

: Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Chronic effects are delayed and symptoms may not be

observed during an exposure. Causes serious eye irritation.

May damage fertility or the unborn child.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Evaporates.

Evacuate personnel to safe areas. Remove all sources of ignition.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Always replace cap after use.

Do not breathe vapours or spray mist.

Conditions for safe storage

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	CA AB OEL

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

			97 mg/m3	
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm 97 mg/m3	CA QC OEL
		TWA	20 ppm	ACGIH
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m3	CA QC OEL
		STEL	1,000 ppm	ACGIH
acetone	67-64-1	TWA	500 ppm 1,200 mg/m3	CA AB OEL
		STEL	750 ppm 1,800 mg/m3	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		STEV	1,000 ppm 2,380 mg/m3	CA QC OEL
		TWAEV	500 ppm 1,190 mg/m3	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
		TWA	1,000 ppm	CA ON OEL
sodium borate, decahydrate	1303-96-4	TWA	1 mg/m3	CA AB OEL
•		STEL	3 ppm	CA AB OEL
		TWAEV	5 mg/m3	CA QC OEL
		TWA (Inhalable)	2 mg/m3 (Borate)	CA BC OEL
		STEL (Inhalable)	6 mg/m3 (Borate)	CA BC OEL

### **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyaceti c acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g Creatinine	ACGIH BEI
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Eye wash bottle with pure water

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work

place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : clear

Odour : characteristic
Odour Threshold : No data available

pH : 9 - 10

Melting point/freezing point : No data available

Boiling point : 100 °C

Flash point :

No data available

Evaporation rate : No data available

Flammability (solid, gas,

liquid)

: The product is not flammable.

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Vapour pressure : No data available

Density : 0.9922 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: No data available

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 7.7 kJ/g

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

### **SECTION 11. TOXICOLOGICAL INFORMATION**

**Potential Health Effects** 

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Chronic effects are delayed and symptoms may not be

observed during an exposure. Causes serious eye irritation.

May damage fertility or the unborn child.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC Group 2A: Probably carcinogenic to humans

sodium nitrite 7632-00-0

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

2-butoxyethanol

111-76-2

**Acute toxicity** 

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

**Components:** 

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l

Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

Skin corrosion/irritation

**Product:** 

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

**Product:** 

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

**Aspiration toxicity** 

No data available

**Further information** 

**Product:** 

Remarks: No data available

### **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

No data available

Persistence and degradability

No data available

**Bioaccumulative potential** 

**Product:** 

Partition coefficient: n-

octanol/water Components:

butane:

Partition coefficient: n-

octanol/water

: Pow: 2.89

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Additional ecological

information

: No data available

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### **SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

### **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

### **SECTION 16. OTHER INFORMATION**

### WHMIS - GHS Label Information:

Hazard pictograms







Gas cylinde

Health hazard

Signal word : Danger:

Hazard statements : Contains gas under pressure; may explode if heated. Causes serious eye irritation. May

damage fertility or the unborn child.

Precautionary statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Storage: Protect from sunlight. Store in a well-ventilated place.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.