Version 1.3 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP CARB X AERO_EA

Material number : 21500C

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street

Edmonton, Alberta T5S 1N6

Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a compressed gas		
Colour	colourless		
Odour	strong, solvent-like		

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Compressed gas
Acute toxicity (Oral) : Category 4
Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 4
Skin irritation : Category 2
Serious eye damage : Category 1
Carcinogenicity : Category 2
Reproductive toxicity : Category 2
Specific target organ toxicity - : Category 1

single exposure

Specific target organ toxicity - : Category 3 (Central nervous system)

single exposure

Specific target organ toxicity - : Category 2

repeated exposure (Inhalation)

GHS label elements

Hazard pictograms











Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated. H302 + H312 + H332 Harmful if swallowed, in contact with skin

or if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or

repeated exposure if inhaled.

Precautionary statements

: Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/doctor if you feel unwell. Rinse mouth.

P302 + P352 + P312 IF ON SKIN: Wash with plenty of water.

Call a POISON CENTER/doctor if you feel unwell.

P304 + P340 + P312 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P308 + P311 IF exposed or concerned: Call a POISON CENTER/doctor.

P332 + P313 If skin irritation occurs: Get medical advice/

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 Store in a well-ventilated place.

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 30 - < 60
toluene	108-88-3	>= 10 - < 30
methanol	67-56-1	>= 10 - < 30
xylenes	1330-20-7	>= 5 - < 10
carbon dioxide	124-38-9	>= 5 - < 10
ethylbenzene	100-41-4	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended. Get medical attention immediately.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before re-use.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

If swallowed : Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Version 1.3 Revision Date 10/01/2023 Print Date 04/27/2025

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes skin irritation.

Causes serious eye damage.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

: Do not allow run-off from fire fighting to enter drains or water

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Dispose of rinse water in accordance with local and national

regulations.

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Keep in a dry, cool and well-ventilated place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm 1,200 mg/m3	CA AB OEL
		STEL	750 ppm 1,800 mg/m3	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		STEV	1,000 ppm 2,380 mg/m3	CA QC OEL
		TWAEV	500 ppm 1,190 mg/m3	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH

 Version 1.3
 Revision Date 10/01/2023
 Print Date 04/27/2025

108-88-3	TWA	50 ppm 188 mg/m3	CA AB OEL
	TWA	20 ppm	CA BC OEL
	TWAEV	50 ppm 188 mg/m3	CA QC OEL
	TWA	20 ppm	ACGIH
67-56-1	TWA 200 ppm 262 mg/m3		CA AB OEL
	STEL	250 ppm 328 mg/m3	CA AB OEL
	TWA	200 ppm	CA BC OEL
	STEL	250 ppm	CA BC OEL
	TWAEV	200 ppm 262 mg/m3	CA QC OEL
	STEV	250 ppm 328 mg/m3	CA QC OEL
	TWA	200 ppm	ACGIH
	STEL	250 ppm	ACGIH
1330-20-7	TWAEV	100 ppm 434 mg/m3	CA QC OEL
	STEV	150 ppm 651 mg/m3	CA QC OEL
	TWA	100 ppm	ACGIH
	STEL	150 ppm	ACGIH
124-38-9	TWA	5,000 ppm 9,000 mg/m3	CA AB OEL
	STEL	30,000 ppm 54,000 mg/m3	CA AB OEL
	TWA	5,000 ppm	CA BC OEL
	STEL	15,000 ppm	CA BC OEL
	STEV	30,000 ppm 54,000 mg/m3	CA QC OEL
	TWAEV	5,000 ppm 9,000 mg/m3	CA QC OEL
	TWA	5,000 ppm	ACGIH
	STEL	30,000 ppm	ACGIH
100-41-4	TWA	100 ppm 434 mg/m3	CA AB OEL
	STEL	125 ppm 543 mg/m3	CA AB OEL
	TWA	20 ppm	CA BC OEL
	STEV	125 ppm 543 mg/m3	CA QC OEL
	TWAEV	100 ppm 434 mg/m3	CA QC OEL
	TWA	20 ppm	ACGIH
	STEL	125 ppm	ACGIH
	1330-20-7	TWA TWAEV TWA TWAEV TWA 67-56-1 STEL TWA STEL TWAEV STEV TWA STEL 1330-20-7 TWAEV STEV TWA STEL 124-38-9 TWA STEL TWA STEL	TWA 20 ppm TWAEV 50 ppm 188 mg/m3 TWA 20 ppm 188 mg/m3 TWA 20 ppm 67-56-1 TWA 200 ppm 262 mg/m3 STEL 250 ppm 328 mg/m3 TWA 200 ppm 328 mg/m3 TWA 200 ppm STEL 250 ppm 328 mg/m3 TWAEV 200 ppm 262 mg/m3 STEV 250 ppm 328 mg/m3 TWAEV 200 ppm 328 mg/m3 TWAEV 250 ppm 328 mg/m3 TWA 200 ppm 328 mg/m3 TWA 200 ppm STEL 250 ppm 328 mg/m3 TWA 100 ppm 434 mg/m3 STEV 150 ppm 651 mg/m3 TWA 100 ppm STEL 150 ppm 124-38-9 TWA 5,000 ppm 9,000 mg/m3 STEL 30,000 ppm STEL 15,000 ppm STEL 15,000 ppm STEL 15,000 ppm STEL 15,000 ppm STEL 30,000 ppm STEL 15,000 ppm STEL 15,000 ppm STEL 30,000 ppm

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible	25 mg/l	ACGIH BEI

METHYLBENZENE	108-88-3	Toluene	In blood	after exposure ceases) Prior to last shift of workwee k	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI
ETHYLBENZENE	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. The use of skin protection is not normally required; however, good industrial

hygiene practice suggests the use of gloves or other

appropriate skin protection whenever working with chemicals, and especially if prolonged or frequent contact is possible or

likely.

Eye protection : Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

Version 1.3 Revision Date 10/01/2023 Print Date 04/27/2025

problems.

Skin and body protection : No special protection is required.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a compressed gas

Colour : colourless

Odour : strong, solvent-like
Odour Threshold : No data available
pH : Not applicable
Melting point/freezing point : Not applicable

Boiling point : 132 °C

Flash point

Not applicable

Evaporation rate : No data available

Flammability (solid, gas,

liquid)

: Extremely flammable aerosol.

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.814 g/cm3

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : > 30 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

Organic Substances

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes skin irritation.

Causes serious eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

ethylbenzene 100-41-4

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethylbenzene 100-41-4

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 801.2 mg/kg

Method: Calculation method

Version 1.3 Revision Date 10/01/2023 Print Date 04/27/2025

Acute inhalation toxicity : Acute toxicity estimate : 3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 1,995 mg/kg

Method: Calculation method

Components:

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l

Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

Version 1.3 Revision Date 10/01/2023 Print Date 04/27/2025

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

toluene:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

Components:

toluene:

Partition coefficient: n-

octanol/water methanol:

Partition coefficient: n-

octanol/water

xylenes:

Partition coefficient: n-

octanol/water ethylbenzene:

Partition coefficient: n-

octanol/water

: Pow: 2.73

: log Pow: -0.77

: Remarks: No data available

: Pow: 3.12

: Pow: 3.6

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to

aquatic life.

Version 1.3 Revision Date 10/01/2023 Print Date 04/27/2025

Components: toluene :

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms

Signal word











· Danger

Hazard statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
Harmful if swallowed, in contact with skin or if inhaled. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs.

May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection. **Response:** IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse

Response: IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. IF ON SKIN: Wash with plenty of water. Call a POISON CENTER/doctor if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. IF exposed or concerned: Call a POISON CENTER/doctor. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.

Storage: Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.3
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this

Version 1.3 Revision Date 10/01/2023 Print Date 04/27/2025

document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.