

# AJ0405 WIP SUBARU FOAM EVAP CLNR 20N18

Version 3.0 Revision Date 04/12/2018 Print Date 12/23/2019

# **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : AJ0405 WIP SUBARU FOAM EVAP CLNR 20N18

Material number : T467

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : 404-352-1680

# **Emergency telephone numbers**

For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	alcohol-like, ammoniacal

#### **GHS Classification**

Gases under pressure : Liquefied gas
Skin corrosion : Category 1
Serious eye damage : Category 1

**GHS** label elements

Hazard pictograms :





Signal word : Danger

Hazard statements : H280 Contains gas under pressure; may explode if heated.

H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention:** 

P260 Do not breathe dust or mist.

P264 Wash skin thoroughly after handling.



Version 3.0 Revision Date 04/12/2018 Print Date 12/23/2019

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P251 Pressurized container: Do not pierce or burn, even after

se.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place. **Disposal:** 

P501 Dispose of contents/container in accordance with local

regulation.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

# **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
butane	106-97-8	>= 5 - < 10
propan-2-ol	67-63-0	>= 1 - < 3
propane	74-98-6	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Get medical attention immediately if symptoms occur.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing and shoes.

Wash contaminated clothing before re-use.

Wash off immediately with plenty of water for at least 15

minutes.

If skin irritation persists, call a physician.



Version 3.0 Revision Date 04/12/2018 Print Date 12/23/2019

In case of eye contact Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

Rinse immediately with plenty of water for at least 15 minutes.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain.

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards.

Treat symptomatically. Symptoms may be delayed. Notes to physician

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media Water spray

Dry chemical

Carbon dioxide (CO2) Alcohol-resistant foam

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

: Collect contaminated fire extinguishing water separately. This Further information

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, : Use personal protective equipment.



Version 3.0 Revision Date 04/12/2018 Print Date 12/23/2019

protective equipment and emergency procedures

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50  $^{\circ}$ C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Store and keep away from, oxidizing agents and acids.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH



# AJ0405 WIP SUBARU FOAM EVAP CLNR 20N18

Version 3.0 Revision Date 04/12/2018 Print Date 12/23/2019

		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL

# **Biological occupational exposure limits**

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
PROPAN-2-OL	67-63-0	Acetone	Urine	End of	40 mg/l	ACGIH BEI
				shift at		
				end of		
				workwee		
				k		
PROPAN-2-OL		Acetone	Urine	End of	40 mg/l	ACGIH BEI
				shift at		
				end of		
				workwee		
				k		

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water. Safety glasses



# AJ0405 WIP SUBARU FOAM EVAP CLNR 20N18

Version 3.0 Revision Date 04/12/2018 Print Date 12/23/2019

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : colourless

Odour : alcohol-like, ammoniacal

Odour Threshold : No data available

pH : 12.5

Melting point/freezing point : No data available Boiling point : 82.2 - 100 °C

Flash point

No data available

Evaporation rate : No data available

Flammability (solid, gas) : The product is not flammable.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : No data available

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 4.58 kJ/g



Version 3.0 Revision Date 04/12/2018 Print Date 12/23/2019

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Acids

Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

# **Potential Health Effects**

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens. No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen



# **AJ0405 WIP SUBARU FOAM EVAP CLNR 20N18**

Revision Date 04/12/2018 Version 3.0 Print Date 12/23/2019

by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

**Acute toxicity** 

Product:

: Acute toxicity estimate : > 5,000 mg/kg Acute oral toxicity

Method: Calculation method

Components:

propan-2-ol:

: LD50 Oral Rat: 4,396 mg/kg Acute oral toxicity

Method: Calculation method

Skin corrosion/irritation

**Product:** 

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

**Product:** 

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

**Aspiration toxicity** 

No data available

**Further information** 

**Product:** 

Remarks: No data available



Version 3.0 Revision Date 04/12/2018 Print Date 12/23/2019

#### **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

No data available

Persistence and degradability

No data available

Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water Components:

butane:

Partition coefficient: n-

octanol/water

: Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

: Remarks: No data available

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Dispose of in accordance with local regulations.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

The product should not be allowed to enter drains, water

courses or the soil.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.



# AJ0405 WIP SUBARU FOAM EVAP CLNR 20N18

Version 3.0 Revision Date 04/12/2018 Print Date 12/23/2019

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

### **EPCRA - Emergency Planning and Community Right-to-Know Act**

### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ammonia, aqueous solution	1336-21-6	1000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Gases under pressure

Skin corrosion or irritation

Serious eye damage or eye irritation



Version 3.0 Revision Date 04/12/2018 Print Date 12/23/2019

**SARA 302** : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with

> known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

### The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


### **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

### **Further information**

NFPA:



# HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	1

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**



# AJ0405 WIP SUBARU FOAM EVAP CLNR 20N18

Version 3.0 Revision Date 04/12/2018 Print Date 12/23/2019

Hazard pictograms

Signal word



: Danger:

Hazard statements : Contains gas under pressure; may explode if heated. Causes severe skin burns and

eye damage.

Precautionary statements

**Prevention:** Do not breathe dust or mist. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection. Pressurized

container: Do not pierce or burn, even after use.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before

reuse.

Storage: Protect from sunlight. Store in a well-ventilated place.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.0
Revision Date:	04/12/2018
Print Date:	12/23/2019

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.



# **AJ2404 SUBARU INTAKE REFRESHER 6N4**

Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019

### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : AJ2404 SUBARU INTAKE REFRESHER 6N4

Material number : V467

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : 404-352-1680

# **Emergency telephone numbers**

For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Specialty Cleaner and Remover

### **SECTION 2. HAZARDS IDENTIFICATION**

# **Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	characteristic

#### **GHS Classification**

Gases under pressure : Liquefied gas

Eye irritation : Category 2A

**GHS** label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

Precautionary statements : **Prevention:** 

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P264 Wash skin thoroughly after handling.

P251 Pressurized container: Do not pierce or burn, even after

use.



Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019

P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention. Storage:

P410 Protect from sunlight.

P412 Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
propan-2-ol	67-63-0	>= 10 - < 20
1,1-difluoroethane	75-37-6	>= 5 - < 10
sodium nitrite	7632-00-0	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

# **SECTION 4. FIRST AID MEASURES**

General advice : Do not leave the victim unattended.

Get medical attention.

Show this safety data sheet to the doctor in attendance.

Move out of dangerous area.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing and shoes.

If symptoms persist, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

Wash contaminated clothing before reuse.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a



# AJ2404 SUBARU INTAKE REFRESHER 6N4

Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019

physician or poison control center.

Most important symptoms and effects, both acute and

contact time).

delayed

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Effects are dependent on exposure (dose, concentration,

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Carbon dioxide (CO2)

Carbon monoxide

Smoke

Fluorine compounds

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Evacuate personnel to safe areas.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).



Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019

Sweep up or vacuum up spillage and collect in suitable container for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms.

Always replace cap after use.

Dispose of rinse water in accordance with local and national

regulations.

Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

Strong oxidizing agents

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL



# **AJ2404 SUBARU INTAKE REFRESHER 6N4**

Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019

1,1-difluoroethane 75-37-6 TWA 1,000 ppm US WEEL

### **Biological occupational exposure limits**

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
PROPAN-2-OL	67-63-0	Acetone	Urine	End of	40 mg/l	ACGIH BEI
				shift at		
				end of		
				workwee		
				k		

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety goggles

Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles

with pure water.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat, drink or smoke.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : colourless
Odour : characteristic
Odour Threshold : No data available

pH : 11

Melting point/freezing point : No data available Boiling point : 82.2 - 100 °C

Flash point :

Not applicable



# **AJ2404 SUBARU INTAKE REFRESHER 6N4**

Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019

Evaporation rate : No data available

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available

Density : 0.95 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 7.2 kJ/g

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Acids

Strong oxidizing agents

Hazardous decomposition

products

: Carbon oxides

Nitrogen oxides (NOx)

Hydrocarbons

Smoke

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration,



# **AJ2404 SUBARU INTAKE REFRESHER 6N4**

Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019

contact time).

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Carcinogenicity:

IARC Group 2A: Probably carcinogenic to humans

sodium nitrite 7632-00-0

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethanol 64-17-5

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

**Acute toxicity** 

**NTP** 

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

**Components:** 

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg

Method: Calculation method

1,1-difluoroethane:

Acute inhalation toxicity : LC50 Mouse: 977,000 mg/l

Exposure time: 2 h

Skin corrosion/irritation

**Product:** 

Remarks: May irritate skin.

Serious eye damage/eye irritation

**Product:** 

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity



# **AJ2404 SUBARU INTAKE REFRESHER 6N4**

Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

**Aspiration toxicity** 

No data available

**Further information** 

**Product:** 

Remarks: No data available

### **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

No data available

Persistence and degradability

No data available

Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the

event of unprofessional handling or disposal.



Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, NON-FLAMMABLÉ, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export

notification requirements:

sodium nitrite 7632-00-0

# **EPCRA - Emergency Planning and Community Right-to-Know Act**



Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
sodium nitrite	7632-00-0	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Gases under pressure

Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including biphenyl-2-ol, which is/are known to the State of California to cause cancer. For more information go to

www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

### **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)


#### **SECTION 16. OTHER INFORMATION**



Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019

#### **Further information**

#### NFPA:



Special hazard.

#### HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	1

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms





Signal word Hazard statements Precautionary statements Warning:

Contains gas under pressure; may explode if heated. Causes serious eye irritation.

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wash skin thoroughly after handling. Pressurized container: Do not pierce or burn, even after use. Wear eye protection/ face protection.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.1
Revision Date:	04/06/2018
Print Date:	12/23/2019

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.



# AJ2404 SUBARU INTAKE REFRESHER 6N4

Version 3.1 Revision Date 04/06/2018 Print Date 12/23/2019