ZEP BMF ASPHALT RELEASE AGENT_275GL

Version 4.0 Revision Date 03/06/2024 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP BMF ASPHALT RELEASE AGENT_275GL

Material number : 00000000000436989

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	amber, brown
Odour	characteristic

GHS Classification

Eye irritation : Category 2B

GHS label elements

Signal word : Warning

Hazard statements : H320 Causes eye irritation.

Precautionary statements : **Prevention:**

P264 Wash skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

ZEP BMF ASPHALT RELEASE AGENT_275GL

Version 4.0 Revision Date 03/06/2024 Print Date 04/27/2025

Substance / Mixture : Mixture

Hazardous components

No hazardous ingredients

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water.

Remove contaminated clothing and shoes. If symptoms persist, call a physician. Wash contaminated clothing before re-use.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration,

contact time).

Causes eye irritation.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Dry chemical

Alcohol-resistant foam

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

ZEP BMF ASPHALT RELEASE AGENT_275GL

Version 4.0 Revision Date 03/06/2024 Print Date 04/27/2025

Hazardous combustion

products

: Carbon monoxide Carbon dioxide (CO2) Nitrogen oxides (NOx)

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Standard procedure for chemical fires.

Cool containers/tanks with water spray.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Material can create slippery conditions.

Use non-slip safety shoes in areas where spills or leaks can

occur.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prever

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Use only in area provided with appropriate exhaust ventilation.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Materials to avoid : Oxidizing agents

Store and keep away from, oxidizing agents and acids.

Packaging material : Suitable material: Mild steel

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ZEP BMF ASPHALT RELEASE AGENT_275GL

Version 4.0 Revision Date 03/06/2024 Print Date 04/27/2025

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
urea	57-13-6	TWA	10 mg/m3	US WEEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses with side-shields

Face-shield

Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles

with pure water.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

Do not enter confined spaces unless adequately ventilated.

Do not enter confined spaces without a safety observer

monitoring activities from outside the vessel.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : amber, brown
Odour : characteristic
Odour Threshold : No data available

pH : 8 - 9Melting point/freezing point : $-20 \,^{\circ}\text{C}$ Boiling point : $> 100 \,^{\circ}\text{C}$ Flash point : $> 205 \,^{\circ}\text{C}$

Evaporation rate : 1

ZEP BMF ASPHALT RELEASE AGENT_275GL

Version 4.0 Revision Date 03/06/2024 Print Date 04/27/2025

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Vapour pressure : < 22.6 hPa (20 °C)

Relative vapour density : Not applicable

Density : 1.1 - 1.2 g/cm3 (19.6 °C)

Solubility(ies)

octanol/water

Water solubility : completely soluble Partition coefficient: n- : No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : 200 mm2/s (40 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Contact with incompatible materials.

Heat, flames and sparks.

Incompatible materials : Strong acids

Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

Carbon dioxide (CO2) Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure : Effects are immediate and delayed.

ZEP BMF ASPHALT RELEASE AGENT_275GL

Version 4.0 Revision Date 03/06/2024 Print Date 04/27/2025

Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration,

contact time).

Causes eye irritation.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Result: Mild eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

ZEP BMF ASPHALT RELEASE AGENT_275GL

Version 4.0 Revision Date 03/06/2024 Print Date 04/27/2025

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable

No data available

Bioaccumulative potential

Product:

octanol/water

Partition coefficient: n- : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

> with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

ZEP BMF ASPHALT RELEASE AGENT_275GL

Version 4.0 Revision Date 03/06/2024 Print Date 04/27/2025

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

ZEP BMF ASPHALT RELEASE AGENT 275GL

Version 4.0 Revision Date 03/06/2024 Print Date 04/27/2025

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
pentasodium triphosphate	7758-29-4	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

ZEP BMF ASPHALT RELEASE AGENT_275GL

Version 4.0 Revision Date 03/06/2024 Print Date 04/27/2025

Further information

NFPA:

HEALTH	0
FLAMMABILITY	0
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Signal word : Warning:

Hazard statements : Causes eye irritation.

Precautionary statements :

Prevention: Wash skin thoroughly after handling.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/ attention.

Version:	4.0
Revision Date:	03/06/2024
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations

SAFETY DATA SHEET ZEP BMF ASPHALT RELEASE AGENT_275GL

Version 4.0 Revision Date 03/06/2024 Print Date 04/27/2025

to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.