TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53 GAL

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-

1ULBC-D_53 GAL

Material number : 00000000500273055

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937
For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

| Appearance | liquid | |
|------------|--------------|--|
| Colour | clear | |
| Odour | solvent-like | |

GHS Classification

Flammable liquids : Category 2 Eye irritation : Category 2A

Specific target organ toxicity -

single exposure

Category 3 (Central nervous system)

GHS label elements

Hazard pictograms



Exclamation mark

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention**:

TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53 GAL

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P233 Keep container tightly closed.

P235 Keep cool.

P403 Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration [%] |
|---|------------|-------------------|
| acetone | 67-64-1 | >= 90 - <= 100 |
| Naphtha (petroleum), hydrotreated light | 64742-49-0 | >= 5 - < 10 |

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D 53 **GAL**

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on clothes, remove clothes.

Wash off immediately with plenty of water for at least 15

minutes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water for at least 15 minutes.

If swallowed Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration,

contact time).

Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness,

paralysis, and convulsions.

Causes serious eye irritation. May cause drowsiness or dizziness.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

: Alcohol-resistant foam Suitable extinguishing media

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing : Use extinguishing measures that are appropriate to local

SAFETY DATA SHEET TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53 GAL

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

methods circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

No smoking.

Keep container tightly closed in a dry and well-ventilated

nlace

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53 GAL

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|---------|-------------------------------------|--|-----------|
| acetone | 67-64-1 | TWA | 250 ppm | ACGIH |
| | | STEL | 500 ppm | ACGIH |
| | | TWA | 250 ppm 590 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 2,400 mg/m3 | OSHA Z-1 |
| | | TWA | 750 ppm 1,800 mg/m3 | OSHA P0 |
| | | STEL | 1,000 ppm 2,400 mg/m3 | OSHA P0 |
| | | STEL | 750 ppm 1,780 mg/m3 | CAL PEL |
| | | С | 3,000 ppm | CAL PEL |
| | | PEL | 500 ppm 1,200 mg/m3 | CAL PEL |

Biological occupational exposure limits

| Component | CAS-No. | Control | Biological | Sampling | Permissible | Basis |
|-------------|---------|------------|------------|-----------|---------------|-----------|
| | | parameters | specimen | time | concentration | |
| 2-PROPANONE | 67-64-1 | Acetone | Urine | End of | 25 mg/l | ACGIH BEI |
| | | | | shift (As | _ | |
| | | | | soon as | | |
| | | | | possible | | |
| | | | | after | | |
| | | | | exposure | | |
| | | | | ceases) | | |

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

SAFETY DATA SHEET TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53 GAL

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

the workstation location. Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear

Odour : solvent-like

Odour Threshold : No data available pH : No data available Melting point/freezing point : Not applicable

Boiling point : 56.5 °C Flash point : -20 °C

Method: Tag closed cup

Evaporation rate : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : 0.76 g/cm3

Solubility(ies)

Water solubility : Not applicable Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : < 1 mm2/s

TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53 GAL

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Carbon dioxide (CO2) Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

Symptoms of Overexposure

: None known.

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration,

contact time).

Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness,

paralysis, and convulsions.

Causes serious eye irritation. May cause drowsiness or dizziness.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53 GAL

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Components:

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l

Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53 GAL

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53 GAL

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN1993, Flammable liquids, n.o.s., (ACETONE), 3, II

Transportation Regulation: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (ACETONE), 3, II

Transportation Regulation: IATA (Cargo Air):

UN1993, Flammable liquid, n.o.s., (ACETONE), 3, II

Transportation Regulation: IATA (Passenger Air): UN1993, Flammable liquid, n.o.s., (ACETONE), 3, II

Transportation Regulation: TDG (Canada):

UN1993, FLAMMABLE LIQUID, N.O.S., (ACETONE), 3, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ | Calculated product RQ |
|------------|---------|--------------|-----------------------|
| | | (lbs) | (lbs) |
| acetone | 67-64-1 | 5000 | * |

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation

TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

DSL All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53 GAL

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

Further information

NFPA:

| HEALTH | 2 |
|-----------------|---|
| FLAMMABILITY | 3 |
| INSTABILITY | 0 |
| SPECIAL HAZARD. | |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

| HEALTH | 2 |
|-----------------|---|
| FLAMMABILITY | 3 |
| PHYSICAL HAZARD | 0 |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms





Signal word :

Hazard statements

Danger:

Highly flammable liquid and vapour. Causes serious eye irritation. May cause

drowsiness or dizzines

Precautionary statements :

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse

SAFETY DATA SHEET TOYOTA ULTRA LOW VOC BRAKE CLEANER 00289-1ULBC-D_53 GAL

Version 4.2 Revision Date 10/01/2023 Print Date 04/27/2025

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Keep container tightly closed. Keep cool. Store in a well-ventilated place.

Disposal: Dispose of contents/container in accordance with local regulation.

| Version: | 4.2 |
|----------------|------------|
| Revision Date: | 10/01/2023 |
| Print Date: | 04/27/2025 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.