

# TCCS - Data Model\_11\_MAP

---

## 1 Table of Contents

1	Table of Contents	1
2	Package "Map"	1
2.1	Package Header	1
2.2	Map	2

## 2 Package "Map"

### 2.1 Package Header

#### SPT2TS-124910 - Package header

```
{
  "$schema": "ERJU meta-model.json",
  "isDefinedBy": "http://ERJU/datamodel/0.4/map",
  "name": "Map",
  "containerStruct": "MapSet",
  "prefix": "map",
  "intId": 7,
  "version": "1.0",
  "info": "Data model to build map",
  "enums": [],   "structs": []
}
```

## 2.2 Map

**SPT2TS-124911** - A map is considered a kind of projection of real-world elements in 2D/3D space. As there are many possible projections, adding special coordinates as part of the specification of real-world objects is not reasonable. Contrary, the maps are constructed by the specification of coordinates in a special coordinate system. Most geo-coordinate systems are specified by the European Petroleum Survey Group Geodesy (EPSG), which assigned unique 4-5 digits-key-numbers to all possible geo-coordinate systems. Several MapArea objects having the same epsg-code represent one map. As the EPSG-code starts at 1024, the value '1' can be assigned to monitor coordinates.

Different functional elements like Marker boards, Points, Balises, etc. can have projections on the map.




Figure 1 Class Diagram for Map definition

[  Open ]

### SPT2TS-63836 - Map

```

{
  "structs": [
    {
      "name": "Map",
      "info": "Defines Map for an area",
      "attrs": [
        { "intId": 1, "name": "id", "dataType": "string", "key": "global", "info": "Identity of the object;
used for referencing"},

```

```
    {"intId": 2, "name": "name", "dataType": "string", "info": "User-friendly name, only if different from id", "multiplicity": "0..1"},
```

```
    {"intId": 3, "name": "versionTimestamp", "dataType": "timestamp", "info": "Defines the version information which is valid since timestamp"},
```

```
    {"intId": 4, "name": "areald", "dataType": "string", "info": "Defines the arealds for a Map. There could be several maps representing one area"},
```

```
    {"intId": 5, "name": "epsg", "dataType": "uint32", "info": "Defines the applicable EPSG code for the map area. Use 1 for monitor coordinates"},
```

```
    {"intId": 6, "name": "linearElementProjections", "composition": "LinearElementProjection", "ordered": "byKey", "multiplicity": "*", "info": "Defines container for projections of linearElements on same mapping system"},
```

```
    {"intId": 7, "name": "functionalElements", "composition": "FunctionalElementProjection", "multiplicity": "*", "info": "Defines a container for a reference to a functional element of the infrastructure"}
  ]
}
```

### SPT2TS-125485 - LinearElementProjection (TrackEdgeProjection)

```
{
  "structs": [
    {
      "name": "LinearElementProjection",
      "attrs": [
        {"intId": 1, "name": "linearElement", "reference": "infra.LinearElement"},
        {"intId": 2, "name": "coordinates", "composition": "LinearElementCoordinate", "multiplicity": "2..*", "ordered": "byIndex", "info": "Defines a sequence of coordinates representing a mapping of a linear element"}
      ]
    },
    {
      "name": "LinearElementCoordinate",
      "attrs": [
        {"intId": 1, "name": "pos", "dataType": "uint32", "unit": "m", "exp": -3, "info": "Defines position"}
      ]
    }
  ]
}
```

on the associated LinearElement"},

```
{ "intId": 2, "name": "x", "dataType": "double", "info": "Defines the x coordiante value, mappin
g to each EPSG-code"},
```

```
{ "intId": 3, "name": "y", "dataType": "double", "info": "Defines the y coordiante value, mappin
g to each EPSG-code"},
```

```
{ "intId": 4, "name": "z", "dataType": "double", "info": "Defines the z coordiante value, mappin
g to each EPSG-code"},
```

```
{ "intId": 5, "name": "accPos", "dataType": "uint32", "unit": "m", "exp": -3, "info": "absolute
accuracy as 1sigma. Use 0 if not defined"},
```

```
{ "intId": 6, "name": "accX", "dataType": "double", "info": "absolute accuracy as 1sigma. Use
0.0 if not defined"},
```

```
{ "intId": 7, "name": "accY", "dataType": "double", "info": "absolute accuracy as 1sigma. Use
0.0 if not defined"},
```

```
{ "intId": 8, "name": "accZ", "dataType": "double", "info": "absolute accuracy as 1sigma. Use
0.0 if not defined"}
]
```

```
}
```

```
}
```

```
}
```

### SPT2TS-125486 - FunctionalElementProjection

```
{
```

```
"structs": [
```

```
{
```

```
"name": "FunctionalElementProjection",
```

```
"attrs": [
```

```
{ "intId": 1, "name": "elementRef", "composition": "FunctionalElementRef", "info": "Defines
reference container for which the coodinate is defined"},
```

```
{ "intId": 2, "name": "x", "dataType": "double", "info": "todo: mapping to each EPSG-code"},
```

```
{ "intId": 3, "name": "y", "dataType": "double", "info": "todo: mapping to each EPSG-code"},
```

```
{ "intId": 4, "name": "z", "dataType": "double", "info": "todo: mapping to each EPSG-code"},
```

```
{ "intId": 5, "name": "accX", "dataType": "double", "info": "absolute accuracy as 1sigma. Use
0.0 if not defined"},
```

```
{ "intId": 6, "name": "accY", "dataType": "double", "info": "absolute accuracy as 1sigma. Use
0.0 if not defined"},
```

```

    {"intId": 7, "name": "accZ", "dataType": "double", "info": "absolute accuracy as 1sigma. Use
0.0 if not defined"}
  ],
  {
    "name": "FunctionalElementRef",
    "union": true,
    "attrs": [
      {"intId": 1, "name": "switch", "reference": "infra.Switch", "info": "refers to switch/simple point"},
      {"intId": 2, "name": "etcsMarker", "reference": "infra.ETCSMarker", "info": "refers to ETCS
marker"},
      {"intId": 3, "name": "stopLocation", "reference": "infra.StopLocation", "info": "refers to stop
location"},
      {"intId": 4, "name": "timingPoint", "reference": "infra.TimingPoint", "info": "Defines a reference
to a timing point"},
      {"intId": 5, "name": "operationalPoint", "reference": "infra.OperationalPoint", "info": "Defines a
reference to an operational point (station, siding etc)."},
      {"intId": 6, "name": "balise", "reference": "infra.Balise", "info": "Defines a reference to a
functional balise"}
    ]
  }
]
}

```

#### **SPT2TS-125484 - MapSet**

```

{
  "structs": [
    {
      "name": "MapSet",
      "attrs": [
        {"intId": 1, "name": "maps", "composition": "Map", "multiplicity": "*", "ordered": "byKey", "info":
"Defines container for all Maps in a system"}
      ]
    }
  ]
}

```



}