

Customizing your document configuration and styling

There are three categories of document configuration

1. The document template
2. Text styles
3. Table styles

These three categories are set at three different levels of priority

1. The internal defaults (lowest priority)
2. Project config
3. Document internal config (highest priority)

Each level of priority in the configuration hierarchy effectively inherits the configuration of the level of priority above it.

Using a combination of configuration levels, you can customize the style of your documents with a minimum amount of configuration text.

The document template (`_doc`)

The `_doc` configuration controls the document-wide page size and orientation, along with one or more named `page templates`. Each page template controls settings such as

Margins

PDF background file path

The first page template listed is the one your document starts on. Within your report you can switch between page templates using the `_pagebreak` block (pass it the name or index of the template to use for the following pages) or the `_nextpagetemplate` block (which arms the template to switch to at the next page break).

Currently, the document template is internally configured to only use a single content frame. This limitation would only affect you if you wanted to do something like a two-column layout (where text flows into the second column on the same page once the first one is full).

Text styles (`_style`)

With text styles, you can control the body text

Text styling attributes

- Font family
- Text color
- Size
- Line spacing ratio
- Bullet style:
 - Bullet color
 - Bullet symbol heirarchy
 - Bullet indentation

You can also control the text heading styles separately from the body text by adjusting their

- Font family
- Text color
- Typographic ratio (in musical intervals, e.g. "minor second" or "major third")
- Alignment (left, center, right, justify) and underline

Beyond the default `body` and `headings`, you can define named `styles` — alternate text families you switch between within the document using the `_textstyle` block. Each named style is a sparse override that inherits everything you don't change from the defaults.

Table styles (`_tablestyle`)

You can control how your tables are displayed by modifying the table style. With the `_tablestyle` key, you can control

- Table header:
 - background (color)
 - gridlines (above, below, between)
 - text: font, size, color
- Table rows:
 - even (rows, background color)
 - odd (rows, background color)
 - gridlines (above, below, between)
 - text: font, size, color