ecommerce
catalog
reports
ReportVisitor
+visit(ProductSalesReport): String
Report
+accept(ReportVisitor): String
ProductSalesReportGenerator
+generate(List): ProductSalesReport
creates
uses
PlainTextExporter
+visit(ProductSalesReport): String
HtmlExporter
+visit(ProductSalesReport): String
CsvExporter
+visit(ProductSalesReport): String
ProductSalesReport
-entries: List
+ProductSalesReport(List)
+accept(ReportVisitor): String
+getEntries(): List
1
entries
0..*
SalesEntry
-item: CatalogItem
-unitsSold: int
-averagePricePaid: double
+SalesEntry(CatalogItem, int, double)
+getItem(): CatalogItem
+getUnitsSold(): int
+getAveragePricePaid(): double
lifecycle
Order
-state: State
-items: List
-creditNotes: List
-shippingType: ShippingType
-address: String
-paymentMethod: PaymentMethod
-receipt: PaymentReceipt
-observers: List
-email: String
+Order(String, ShippingType, PaymentMethod, String)
+getItems(): List
+getPaymentMethod(): PaymentMethod
+getCreditNote(): List
+getAddress(): String
+getState(): State
+getEmail(): String
+getShippingCost(): double
+getPaymentReceipt(): PaymentReceipt
+setState(State): void
+setPaymentMethod(PaymentMethod): void
+setPaymentReceipt(PaymentReceipt): void
+add(CatalogItem, int): void
+addNewItem(OrderItem): void
+delete(OrderItem): void
+confirm(): void
+start(): void
+send(): void
+deliver(): void
+cancel(): void
+registerCreditNote(CreditNote): void
+totalCost(): double
+totalWeight(): double
+getTotalToPay(): double
+isEverythingInStock(): boolean
+subscribe(OrderObserver): void
+unsubscribe(OrderObserver): void
+notifySuccessfulProgress(): void
+notifyFinal(): void
+notifyCanceled(): void
-validate(): void
-totalDemandPerSku(): Map
1
1
1
1
1
1
1
items
0..*
creditNotes
0..*
state
1
shippingType
1
paymentMethod
1
receipt
0..1
observers
0..*
OrderItem
-item: CatalogItem
-quantity: int
-priceAtConfirmation: double
+OrderItem(CatalogItem, int)
+getQuantity(): int
+getItem(): CatalogItem
+captureSalesSnapshot(): void
+getPriceAtConfirmation(): double
-validate(): void
1
item
CreditNote
-amount: double
-description: String
+CreditNote(double, String)
+getProductCost(): double
+getDescription(): String
State
+getName(): String
+addItem(Order, CatalogItem, int): void
+deleteItem(Order, OrderItem): void
+confirm(Order): void
+cancel(Order): void
+start(Order): void
+deliver(Order): void
+send(Order): void
Confirmed
+getName(): String
+start(Order): void
+cancel(Order): void
InPreparation
+getName(): String
+cancel(Order): void
+send(Order): void
Sent
+getName(): String
+cancel(Order): void
+deliver(Order): void
Delivered
+getName(): String
Canceled
+getName(): String
Draft
+getName(): String
+addItem(Order, CatalogItem, int): void
+deleteItem(Order, OrderItem): void
+confirm(Order): void
+cancel(Order): void
shippingmethods
ShippingType
+cost(Order): double
+waitingDays(Order): String
ExpressShipping
-apiConnection: ExpressShippingAPI
+ExpressShipping(ExpressShippingAPI)
+cost(Order): double
+waitingDays(Order): String
LocalPickUp
+cost(Order): double
+waitingDays(Order): String
StandardShipping
-apiConnection: StandarShippingAPI
+StandardShipping(StandarShippingAPI)
+cost(Order): double
+waitingDays(Order): String
1
apiConnection
1
ExpressShippingAPI
+calculateCost(double): double
1
apiConnection
1
StandarShippingAPI
+estimateCost(double, String): double
paymentmethods
PaymentMethod
-receipt: PaymentReceipt
-operationNumber: String
+process(Order): void
+validateData(Order): void
+setAsideFunds(Order): void
+executeTransaction(Order): void
+notifyResult(Order): void
+getReceipt(): PaymentReceipt
#getOperationNumber(): String
#setOperationNumber(String): void
1
creates
0..1
BankTransferPayment
-apiConnection: BankTransferAPI
-alias: String
-cbu: String
+BankTransferPayment(BankTransferAPI, String, String)
+validateData(Order): void
+setAsideFunds(Order): void
+executeTransaction(Order): void
-tranferAndGetOperationNumber(Order): String
CreditCardPayment
-cardNumber: String
-cvv: String
-expirationCode: String
-apiConnection: CreditCardAPI
+CreditCardPayment(CreditCardAPI, String, String, String)
+validateData(Order): void
+setAsideFunds(Order): void
+executeTransaction(Order): void
-preAuthorizeAndGetOperationNumber(Order): String
VirtualWalletPayment
-accountId: String
-sellerAccountId: String
-apiConnection: VirtualWalletAPI
+VirtualWalletPayment(VirtualWalletAPI, String, String)
+validateData(Order): void
+setAsideFunds(Order): void
+executeTransaction(Order): void
+notifyResult(Order): void
-accreditAndGetOperationNumber(Order): String
PaymentReceipt
-operationNumber: String
-amount: double
+PaymentReceipt(Order, String)
+getAmount(): double
+getOperationNumber(): String
1
apiConnection
1
BankTransferAPI
+validateCBU(String, String): void
+transfer(double, String): String
1
apiConnection
1
CreditCardAPI
+validateCard(String, String, String): void
+preAuthorize(double): String
+charge(double, String): void
1
apiConnection
1
VirtualWalletAPI
+validateBalance(String, double): void
+blockFunds(String, double): void
+realTimeAccreditation(String, double): String
notifications
OrderObserver
+notifySuccessfulProgress(Order): void
+notifyFinal(Order): void
+notifyCanceled(Order): void
EmailNotifier
-mailSender: MailSender
+EmailNotifier(MailSender)
+notifySuccessfulProgress(Order): void
LoyaltyProgram
-mailSender: MailSender
+LoyaltyProgram(MailSender)
+notifyCanceled(Order): void
InvoiceGenerator
-invoices: List
+InvoiceGenerator()
+notifyFinal(Order): void
+getInvoices(): List
1
mailSender
1
1
mailSender
1
1
invoices
0..*
MailSender
+enviarMail(String, String, String, String): void
Invoice
-amount: double
-address: String
+Invoice(double, String)
+getAmount(): double
+getAddress(): String
search
Catalog
-items: List
+Catalog()
+addItem(CatalogItem): void
+search(SearchCriteria): List
uses
1
items
0..*
SearchCriteria
+isSatisfiedBy(CatalogItem): boolean
0..*
criteria
1
0..*
criteria
1
1
criteria
1
AvailabilityCriteria
+isSatisfiedBy(CatalogItem): boolean
AndCriteria
-criteria: List
+AndCriteria(List)
+isSatisfiedBy(CatalogItem): boolean
-validate(): void
CategoryCriteria
-category: String
+CategoryCriteria(String)
+isSatisfiedBy(CatalogItem): boolean
OrCriteria
-criteria: List
+OrCriteria(List)
+isSatisfiedBy(CatalogItem): boolean
-validate(): void
MaxPriceCriteria
-maxPrice: double
+MaxPriceCriteria(double)
+isSatisfiedBy(CatalogItem): boolean
NotCriteria
-criteria: SearchCriteria
+NotCriteria(SearchCriteria)
+isSatisfiedBy(CatalogItem): boolean
-validate(): void
NameContainsCriteria
-text: String
+NameContainsCriteria(String)
+isSatisfiedBy(CatalogItem): boolean
CatalogItem
+getBasePrice(): double
+getName(): String
+getDescription(): String
+decreaseStock(int): void
+increaseStock(int): void
+hasStock(int): boolean
+getStock(): int
+getWeight(): double
+accumulateProductDemand(int, Map): void
+hasEnoughStockFor(Map): boolean
+getCategory(): String
1
0..*
items
1
Bundle
-name: String
-description: String
-discountRate: double
-items: List
-category: String
+Bundle(String, String, double, String)
+getName(): String
+getDescription(): String
+getCategory(): String
+getDiscountRate(): double
+getBasePrice(): double
+getWeight(): double
+getStock(): int
+addItem(CatalogItem): void
+decreaseStock(int): void
+increaseStock(int): void
+hasStock(int): boolean
+accumulateProductDemand(int, Map): void
+hasEnoughStockFor(Map): boolean
-validate(): void
Product
-sku: String
-name: String
-brand: String
-category: String
-description: String
-weight: double
-price: double
-discountRate: double
-stock: int
-extraAttributes: List
+Product(String, String, String, String, String, double, double, int)
+Product(String, String, String, String, String, double, double, int, List)
+getSku(): String
+getBrand(): String
+getDiscountRate(): double
+setDiscountRate(double): void
+addExtraAttribute(Attribute): void
+getExtraAttributes(): List
+getBasePrice(): double
+getName(): String
+getDescription(): String
+getCategory(): String
+getStock(): int
+getWeight(): double
+decreaseStock(int): void
+increaseStock(int): void
+hasStock(int): boolean
+accumulateProductDemand(int, Map): void
+hasEnoughStockFor(Map): boolean
-validate(): void
1
extraAttributes
0..*
Attribute
T
-name: String
-value: T
+Attribute(String, T)
+getName(): String
+getValue(): T
-validate(): void