

Catapult HLS User View Scheduling Rules

Stuart Swan, Platform Architect, Siemens EDA

22 June 2026

Introduction

In a high-level synthesis (HLS) design methodology, much of the benefit is lost if design verification and debug must still be performed at the RTL level. In manual RTL design flows, RTL verification is typically one of the most costly and time-consuming phases of the overall flow. In HLS flows, RTL-level verification is even more challenging, because the RTL is machine-generated rather than hand-crafted.

This document presents a user-visible scheduling contract, modeling methodology, and collection of formal proofs that together support a flow in which full-system design verification and debug can be performed primarily on the pre-HLS SystemC model. The practical purpose of the contract is to give HLS users and verification engineers “no surprises”: interface scheduling is reduced to a small set of uniform rules for message-passing operations, signal I/O, and explicit synchronization, so that a common verification intent can be reused across pre-HLS and post-HLS models, while still allowing aggressive implementation optimizations such as loop pipelining, added FSM states, memory-access scheduling and reordering where permitted, direct-input late sampling, and bounded or elaborated channel buffering. The same bounded-capacity modeling also lets the pre-HLS SystemC model be made capacity-accurate and throughput-accurate with respect to the post-HLS RTL — for example, when modeled with a library such as Matchlib — so that throughput behavior and capacity effects can be assessed at the pre-HLS level rather than deferred to RTL simulation.

The formal guarantees are subject to the explicitly stated assumptions, observation-boundary choices, witness-selection conditions, and liveness/progress premises described in the formal appendices. The formal safety guarantee is an observable trace-compatibility result: every compliant RTL_B behavior has a matching Sys_ref behavior under the fixed stimulus, while transfer of a particular source-side simulation execution to RTL_B applies only to RTL-consistent source prefixes or to source executions selected by the Appendix L snooping / witness-selection mechanism. The liveness/deadlock guarantee is a separate conditional preservation result: under the additional fairness, progress, and structural assumptions stated in the appendices, an RTL-matched internal message-passing deadlock is connected back to a corresponding source-side deadlock, so that the source-level deadlock-freedom premise can rule it out.

The methodology and proofs are organized around a latency-insensitive design style, while still fully supporting real-world techniques such as:

- both sequential and combinational logic
- pipelined designs
- shared memories between sequential processes
- reordering of RAM accesses to optimize hardware pipelines
- removal of pipeline registers for stable signal inputs to hardware pipelines
- latency-sensitive signal-level protocols and localized latency-sensitive islands, including cycle-accurate transactors, non-blocking arbiters, and one-way handshake protocols

These techniques capture the requirements gathered from hundreds of Catapult HLS customer tape-outs and are needed to meet the demanding quality-of-results (QOR) targets traditionally achieved with manual RTL design.

The methodology presented here builds on established verification practices such as SystemVerilog UVM, constrained-random stimulus generation, and functional and code coverage. The system under test is modeled and verified in SystemC, while RTL verification is focused on establishing that the synthesized or otherwise implemented RTL falls within the scope of the formal theorem instances. The proofs do not, by themselves, prove that any particular HLS tool invocation or generated RTL instance satisfies the required obligations. In particular, the RTL-side scheduling obligations, the per-channel E4 realization obligations, B-faithfulness — the faithfulness of each back-annotated capacity $B(c)$ to the chosen explicit abstract boundary and to the RTL storage/credit represented at that boundary — and the other named side conditions must be established by the tool, by tool documentation, by generated certificates, by static checks, by RTL/interface checks, or by another validation method appropriate to the flow.

Although the focus of this document is HLS, the underlying modeling methodology and formal proof framework are not limited to HLS-generated RTL. The safety/liveness distinction introduced above is central to that generality: safety decomposes primarily into local process and channel-boundary obligations, while liveness has a more global dependency structure. The following paragraphs summarize these two decompositions.

For safety, the key benefit is compositionality in a strong local sense. Each process is verified independently against the scheduling and endpoint obligations at its own observable boundaries. The abstract channels connecting processes have fixed, methodology-defined semantics, such as rendezvous or bounded-FIFO capacity, and each channel's specification is fixed at the methodology/proof boundary. The producer and consumer processes need only satisfy their local endpoint scheduling and handshake obligations; the channel realization supplies the corresponding ChannelEnabled/ChannelDisabled behavior required by E4. When each process satisfies its R-rule conformance locally, and when the chosen Sys_ref / RTL_B comparison satisfies the applicable E4 channel semantics at the agreed abstract channel boundaries, the system-level trace-compatibility results follow from the formal composition theorems.

This safety decomposition is what makes the approach applicable beyond HLS. Because the trace-compatibility obligations are local to processes and to explicitly specified channel boundaries, the same proof structure applies to any RTL implementation whose individual processes and channel realizations satisfy the required implementation-side obligations. Those processes may be HLS-generated, hand-written, or produced by other generation methods. RTL verification is then focused on showing that each process and channel realization satisfies the same formal side conditions required of HLS-generated RTL, rather than constructing an ad hoc full-system safety proof over all process interactions.

The single most important deadlock-avoidance property is worth stating in plain terms, because a designer experiences it directly: HLS cannot by default reverse the order of the message-passing calls written in the source, so it cannot introduce new deadlocks via call-order reversal. This is the intuitive benefit underlying the formal liveness result described below. That result additionally covers deadlock behavior that depends on timing rather than call order — most notably the overlapped execution of pipelined loops and finite-capacity (bounded-FIFO) effects — which is handled by the pipelined-loop discipline (automatic flush) and the machinery summarized below, not by the no-reverse rule alone.

Liveness and deadlock preservation decompose differently. The liveness-preservation result is a conditional global preservation theorem, not a per-process liveness theorem. In particular, Appendix K assumes that the prescribed Sys_ref is internally message-passing-deadlock-free under A5's conservative serial-blocking source semantics. It then relies on the serial-source dominance lemma, Lemma K.2b, to connect any RTL-matched overlapped witness deadlock back to a serial-source deadlock. The result also requires the RTL_B scheduler/environment and channel realization to satisfy the applicable progress, fairness, and structural assumptions, including B2/B3/B5, Kε, J.AbsConf, and the A6–A11 side conditions.

Thus, the methodology provides two related but distinct forms of scalability. Safety scales largely by local process and channel-boundary checking. Liveness/deadlock preservation scales by separating the proof into a source-level internal deadlock-freedom premise, an overlapped-to-serial dominance argument, and explicit RTL/environment/channel progress assumptions.

Together, these results support a verification flow in which much of the design reasoning can be performed at the pre-HLS SystemC level. For RTL produced by a compliant HLS flow, the required implementation-side obligations are expected to be discharged primarily by the tool and its associated flow evidence, such as tool documentation, generated certificates, static checks, or targeted RTL/interface checks. For hand-written RTL, modified generated RTL, or RTL produced by other generation methods, RTL verification or equivalent implementation checks must establish the same obligations to bring the implementation within the scope of the formal guarantees.

Because these rules are expressed as a user-visible, tool-neutral scheduling contract rather than as the internals of any particular HLS tool, a further goal of this document is to serve as a starting point for a standardization proposal — for example, within the Accellera Synthesis Working Group (SWG). A standardized scheduling contract would let design and verification teams write models and testbenches against a single, vendor-independent set of interface scheduling rules, rather than against the specifics of any one tool's implementation.

A document abstract is provided in Appendix M.

Document Goals

This document presents HLS tool scheduling rules and a modeling methodology. The goals are:

1. To provide easy-to-understand rules to HLS users.
2. To ensure precise and consistent rules in both SystemC and C++.
3. To offer rules that are effectively compatible with how Catapult currently operates.
4. To enable the best possible *quality of results* (QOR) in Catapult synthesis.
5. To cover all known user requirements and scenarios.
6. To serve as a suitable starting point for a standardization proposal (e.g., in Accellera SWG).

To illustrate the goals of this document more specifically, consider what an engineer writing a testbench for an HLS model needs to understand about how HLS tools operate. This engineer may be using SystemVerilog UVM or may be writing a testbench in C++/SystemC.

They likely are not an expert in any specific HLS tool (and may not want to be), but their testbench should be usable across both the pre-HLS model and the post-HLS model, subject to the latency-insensitivity, observation-boundary, and witness-selection conditions stated in this document. Thus, it is crucial for the DV engineer to have a precise understanding of how the HLS tool will transform the design while still enabling the resulting RTL behavior to be checked against the prescribed source reference model. This document describes what transformations the HLS tool is allowed to perform so that the pre-HLS and post-HLS models can be effectively verified with a common verification intent, and in the deterministic or RTL-consistent cases with the same directly corresponding testbench execution. The overarching philosophy of the scheduling rules is to present “no surprises” to such a DV engineer, while still giving the HLS tool ample freedom to optimize the design.

The main body of this document is intended to be sufficiently precise and complete to support the Accellera standardization effort while still being understandable to HW architects. The formal appendices are intended to have a very high degree of precision and completeness sufficient to support AI-driven Lean mechanization of the formal theorems.

Background

HLS tools generate RTL from C++ models. Broadly speaking, this conversion takes a sequential C++ model and turns it into concurrent hardware that maintains the same behavior. HLS tools identify concurrent processes within the C++/SystemC model and then independently synthesize each process. Briefly, some of the techniques that HLS tools use to achieve good HW QOR when synthesizing each process include:

- Optimized scheduling based on the selected silicon target technology.
- Automatic HW pipeline construction according to the user’s specifications.
- Automatic HW resource sharing.
- Automatic scheduling of memory accesses.

The internal behavior of each process is specified by the control and dataflow behavior of the C++ code within the process. However, the external communication that each process has with other processes and HW blocks is specified via IO operations that are coded within the model. To enable a reliable, scalable, and verifiable HLS flow that generates high quality hardware, the scheduling behavior of these IO operations needs to be precisely handled at all steps of the flow. This document specifies the rules that govern the scheduling behavior for these IO operations within HLS models.

These rules are specified with respect to an individual process, but the intent of the rules is to enable reliable and verifiable behavior of large sets of interacting processes operating as a system in real-world designs. (Appendix G provides the formal trace-compatibility guarantees between the prescribed source reference model and the post-HLS system, including the unrestricted Post → Ref direction and the restricted RTL-consistent / witness-selected reverse use.)

By default, HLS tools can insert additional clock cycles (or latency) anywhere within a process -- for example, when pipelining a loop or to enable HW resource sharing. The overall approach used in this document is to make the entire design and testbench system *latency insensitive* to the maximum extent possible, while still fully enabling key HW optimizations. In addition, the overall approach enables the

pre-HLS system simulation to be capacity-accurate and throughput-accurate with respect to the post-HLS RTL system.

In some cases, designs or testbenches may use protocols which are latency-sensitive. These situations can be handled by isolating the latency-sensitive portions to small, self-contained parts of the design or testbench, and then keeping the rest of the design and testbench latency insensitive. See Appendix D for more information.

In many cases the overall design will need to satisfy end-to-end latency requirements. For these designs it is still highly advantageous to use a latency-insensitive modeling approach and verify in the post-HLS model that the overall design latency requirements have been satisfied, since this is typically easy to do.

This document focuses on sequential HW processes. Combinational HW processes are supported but mostly not discussed since their synthesis is straightforward. All the examples and discussion in this document are for SystemC processes that are sensitive only to a single rising clock edge. (Appendix O discusses support for multiple clock domains.)

This document distinguishes between the following:

1. The *conceptual model* for the scheduling rules.
2. The simulation behavior of a model using the rules in C++ or SystemC.
3. The synthesis of a C++/SystemC model using the rules in an HLS tool such as Catapult.

The goal is to align each of these three cases as closely as possible, so that the user has easy-to-understand rules, while simulation and synthesis work without surprises. However, as we will see, there are practical considerations which may in certain cases cause small deviations from the conceptual model in either simulation or HLS.

A simple real-world example that illustrates the motivation for the scheduling rules is provided in Appendix A of this document.

The examples referred to in this document are available here:

<https://github.com/Stuart-Swan/Matchlib-Examples-Kit-For-Accellera-Synthesis-WG/tree/master>

The most up-to-date version of this document is available here:

https://github.com/Stuart-Swan/Matchlib-Examples-Kit-For-Accellera-Synthesis-WG/blob/master/matchlib_examples/doc/catapult_user_view_scheduling_rules.pdf

A summary of the scheduling rules is available here:

https://github.com/Stuart-Swan/Matchlib-Examples-Kit-For-Accellera-Synthesis-WG/blob/master/matchlib_examples/doc/brief_scheduling_rules.txt

An Analogy from RTL Synthesis

To better understand the specific purpose of this document, let's consider how RTL synthesis works. Say you have a sequential block that you are modeling in Verilog RTL, and it has an output port coded like:

```
Out1 <= #some_delay new_val;
```

In Verilog simulation, if `some_delay` is less than the clock period of the block, then it will probably not affect the overall cycle-level behavior of the system during simulation. However, if `some_delay` is more than the clock period, it probably will.

During RTL synthesis, all RTL synthesis tools will ignore all delays in the input model, in this case even if `some_delay` is greater than the clock period. Some RTL synthesis tools might give a warning or error for code like the above such as "Simulation and synthesis results are likely to mismatch because the delay in model is greater than clock period." Some RTL synthesis tools might outright reject a model containing such delays.

One might argue that RTL synthesis tools should always match the Verilog simulation behavior of the input model. But the overall approach works well because RTL is a good and simple *conceptual model* that users and tool vendors can align around. The slight differences between the *simulation model* and the *conceptual model* used by RTL synthesis tools can be easily managed.

We'll return to this example later in this document.

Next, let's clarify some terminology related to signal IO. Say you have a Verilog model like:

```
forever begin
  @(posedge clk); // wait for 1st rising clock edge
  output1 <= input1 + 10;
  @(posedge clk); // wait for 2nd rising clock edge
end
```

In this example, `input1` is sampled when the process wakes on the first `@(posedge clk)` and evaluates the RHS. For the purposes of the scheduling rules, we anchor that `Read(input1,.)` to the most recent synchronization point. The resulting `Write(output1,.)` is anchored to the next synchronization point (the cycle in which the written value is treated as stable for others to observe).

Cycle-level anchoring convention (used throughout this document). For cycle-level reasoning, each signal IO is assigned an anchor cycle relative to surrounding synchronization calls (e.g., `wait()` / `SyncChannel` / `@(posedge clk)`):

- `Read(sig, val)` is anchored to the closest preceding synchronization call, i.e. `pred_S(Read)`.
- `Write(sig, val)` is anchored to the closest succeeding synchronization call, i.e. `succ_S(Write)`.

This convention is only for cycle-level reasoning and does not depend on simulator update regions or delta-cycle ordering.

Catapult HLS Status Concerning Rules in this Document

A separate document provides a list of clarifications related to support within Catapult HLS for the rules described in this document. The items in the list are named *Cat#*, so that each item has a unique number.

This document annotates certain rules with *Cat#* to refer to the items in the separate document.

These *Cat#* annotations are not part of the formal proof itself. They identify tool-support and tool-conformance points that must be satisfied for a Catapult-generated RTL instance to fall within the scope of the formal guarantees. Where the appendices assume an RTL-side property such as E3 issue-order conformance, E4 channel-realization conformance, automatic-flush behavior, or faithful back-annotation of B(c), the corresponding *Cat#* item or other tool-flow evidence is the mechanism by which that compliance obligation is expected to be discharged.

Terms Used in this Document

Latency-Insensitive: In digital hardware design, *latency-insensitive* refers to a system that operates correctly despite variable communication delays between components. This is achieved by using mechanisms to decouple computation from communication timing. Such designs improve scalability and reliability in complex systems with unpredictable or variable latencies. ARM's AXI4 and APB are examples of latency-insensitive protocols. ARM's AMBA 5 CHI credit-based NOC protocol is also an example of a latency-insensitive protocol.

Process: In Verilog, a process is an *always block* and its equivalent constructs. In SystemC, a process is an instance of an SC_THREAD or SC_METHOD.

Message-passing Interface: A *message-passing interface* reliably delivers messages (or transactions) from one process to another. This document uses this term to denote the type of communication found in Kahn Process Networks. See https://en.wikipedia.org/wiki/Kahn_process_networks
Message-passing read interfaces are always separate from message-passing write interfaces – there are no bidirectional message-passing interfaces. In this document, message-passing channels are assumed to be point-to-point: for each channel *c*, exactly one producer performs all Push_*c* operations and exactly one consumer performs all Pop_*c* operations.

Synchronization Interface: A *synchronization interface* synchronizes one process with another and/or with a global clock. For an example of a synchronization interface, see [https://en.wikipedia.org/wiki/Barrier_\(computer_science\)](https://en.wikipedia.org/wiki/Barrier_(computer_science))

Signal IO: In digital HW design, signals are the fundamental communication mechanism. Signals enable communication between two HW blocks/processes, but communication with signals in real HW always incurs at least some delay because communication cannot be faster than the speed of light. In HDLs and in SystemC, signal delays are modeled with the *delayed update* semantics.

blocking / non-blocking: In this document, a blocking message-passing operation is modeled as issuing a persistent request that remains asserted (and with stable payload, if applicable) until the operation commits (the message is sent or received). A non-blocking message-passing operation returns immediately with a status indicating whether the operation committed in that cycle.

One-way / two-way handshake protocols: A one-way handshake protocol only has one signal between a sender and receiver to synchronize communication. A two-way handshake protocol has two signals (one in each direction) between a sender and receiver to synchronize communication.

shall: This term indicates that a compliant tool or flow is required to follow the indicated rule.

may: This term indicates that a compliant tool or flow is allowed to follow the indicated rule but is not required to do so.

Classes of Operations Involved in Scheduling Rules

There are three classes of operations involved in the scheduling rules:

1. Calls to message-passing interfaces (which are all `ac_channel` methods, all SystemC Push/PushNB/Pop/PopNB calls except calls to `SyncChannel`)
2. Calls to synchronization interfaces (which are calls to `ac_sync` and Matchlib `SyncChannel`, also `ac_wait` and SystemC `wait`)
3. Signal IO (which are SystemC signal reads and writes, also C++ model *direct inputs*)

All the operations above are referred to as *IO operations*.

Basic Conceptual Model

The basic conceptual model encompasses processes that have no loop pipelining but may have preserved loops. If a process has a preserved loop, then the user may place a wait statement in the loop. Wait statements explicitly placed in the model are called *explicit wait statements* in this document and are classified as calls to a *synchronization interface*.

The basic conceptual model rules are:

1. Synchronization interface calls within a process always remain in the source code order.
2. Signal read operations occur at the closest preceding call to a synchronization interface. (Cat1)
3. Signal write operations occur at the closest succeeding call to a synchronization interface.
4. Message-passing operations are free to be reordered subject to the following constraints:
 - All message-passing operations before a call to a synchronization interface shall be issued before or in the same cycle in which the synchronization interface commits. (Here “the synchronization interface commits” refers to the commit of that synchronization call in the calling process’s trace. For blocking message-passing operations (Push/Pop), the process cannot complete the synchronization call until any earlier issued blocking message requests in that interval have committed.)
 - All message-passing operations after a call to a synchronization interface shall be issued after the cycle in which the synchronization interface call commits.

- Two message-passing operations on separate interfaces which appear in sequence in the model may be issued either in the same sequence or in parallel in simulation and in synthesis, but they shall not be issued in the reverse sequence. (Cat2)

Some explanation for the very last point: While pure message-passing systems with unbounded FIFOs are immune to reordering concerns, real-world hardware implementations have finite buffer sizes. Reversing the order of message-passing calls in a system with bounded FIFOs can introduce deadlocks that were not present in the original model. The last rule prevents HLS from introducing deadlocks *via this specific mechanism* (reversing the program order of message-passing calls that appear in sequence in the source). However, deadlock behavior can still be affected by other transformations that change the *timing* of request/commit—most notably overlapped execution in pipelined loops and finite-capacity effects.

Pipelined Loops

When a loop is pipelined in HLS, the body of the loop is split into pipeline stages. HLS may start the next iteration of the loop before the current iteration has completed, thus increasing throughput as compared to a non-pipelined implementation.

The user may place wait statements in the body of a pipelined loop to manually separate operations into their respective pipeline stages but is not required to (and in most cases will not do so). We call these wait statements *explicit pipeline stage wait statements*. The scheduling rules for pipelined loops are the same as the rules given in the basic conceptual model, with the addition of these pipeline stage wait statements into the set of calls to synchronization interfaces.

To guarantee equivalent behavior between the pre-HLS and post-HLS systems, pipelined loops must be implemented with automatic flush to prevent deadlocks. See Appendix B for a formal presentation of pipelined loops.

When HLS pipelines a loop, multiple iterations of the loop are overlapped and execute at the same time. During loop pipelining, for all IO operations, HLS shall ensure that an access to a specific message-passing interface, signal, or synchronization interface shall not be reordered relative to same-interface accesses from other iterations.

During pipelining any signal reads and writes and associated synchronization interface calls become embedded in specific pipeline stages. Considering the entire set of signals read or written by the process, if HLS pipelining would cause the order of signal IO to differ between the pre-HLS and post-HLS models, or if any two signal IO operations that occur on the same clock edge in the pre-HLS model would not occur on the same clock edge in the post-HLS model, then the HLS tool shall detect such a situation and require the user to explicitly indicate in the model source (e.g., via a pragma) that HLS pipelining can still be used. (Cat7) In other words, if a process communicates with other processes using only latency-insensitive protocols, then HLS pipelining by default shall not break any of the protocols.

Synchronization boundary for pipelined loops

If a pipelined loop is separated from later work by an explicit synchronization interface call, then while the process is pending at that synchronization call, any back-annotated message-passing capacity B(c) whose accepted data could otherwise be consumed only by work after that

synchronization call shall be treated as unavailable to upstream producers until the synchronization call commits. Equivalently, the producer-facing availability corresponding to such capacity is temporarily withdrawn at the synchronization boundary. Work already accepted before the boundary may drain under the automatic-flush rules, but no new transfer may be accepted across that boundary into the next post-sync interval before the sync commits.

Formal modeling requirement

This withdrawal is not a hidden exception to E4 at an otherwise ordinary bounded-FIFO boundary. The prescribed source reference model shall represent this behavior in $\text{Sys_B}^{\text{elab}}$, using explicit sync-boundary / epoch-gate abstract channels, or equivalent explicit staged realization structure, so that the refusal to accept new post-sync work appears as ordinary ChannelDisabled behavior at an explicit abstract boundary. Thus the pre-HLS back-annotated model ramps down in the same sense as the RTL: already accepted work may drain, but capacity belonging only to $\text{suff_S}(s)$ is not producer-facing available until s commits.

Direct Inputs

Ordinary SystemC signal reads occur at the closest preceding synchronization interface call (e.g., wait statement) in both the pre-HLS and post-HLS models. (Cat1). If the HLS tool adds states to the process, or if it pipelines the process, then this implies that the HLS tool must add registers for each such read operation such that the read occurs where specified in the pre-HLS model, and the value is stored until the point where it is consumed in the post-HLS model. The area cost of such registers may be high if there are a lot of signals, and in some cases, it may be unneeded area since the value of the signals may not actually need to be stored internally to the process.

The simplest case is if such external signals are held stable after the process comes out of reset. In this case, HLS may assume that it is free to physically sample the signal values as late as possible, with no need for register storage, while the logical Σ -visible Read event remains anchored as specified by E2. This case is handled with the following pragma on SystemC signals and ports (Cat6):

```
#pragma hls_direct_input
```

To ensure that there are no pre-HLS versus post-HLS simulation mismatches, the environment that drives the signal shall hold it stable within each relevant reset epoch: after all receiving processes that use this signal with this pragma have come out of a reset boundary, the signal value shall remain stable until the next reset boundary that affects those receiving processes, unless the signal is instead governed by an explicit `hls_direct_input_sync` update contract as described below. A *dynamic reset* starts a new stability epoch for the affected receiving logic and its associated direct-input signals. Thus it remains allowable to have *dynamic resets*, i.e. activation of block resets and associated resetting of direct input signals as part of the normal operation of the HW.

A related but somewhat more complex case is where input signals to the HW block may only be changed at “agreed upon” times, typically while the portion of the HW block that relies on them is temporarily idle. For example, a block may process 2D images. At the start of each new image, it may be desirable for the TB or external environment to update the control signals for how the block will process the next image. Typically HLS designs are pipelined, and the HW pipeline for the current iteration must be fully *ramped down* before the input signals can be updated to affect the next iteration. In the pipelined-loop

case, this relies on the general synchronization-boundary rule for pipelined loops: while the process is pending at the designated sync, any back-annotated message-passing capacity whose accepted data would belong to the next post-sync interval is temporarily unavailable to upstream producers until the sync commits. In this case we can use the SystemC *SyncChannel* or C++ *ac_sync* primitives to precisely synchronize the DUT with the TB/environment to enable the input signals to be updated at the correct time. The `#pragma hls_direct_input_sync` directive shown below associates the sync operation with the direct inputs that it controls. The precise synchronization scheme shown here ensures that there are no pre-HLS versus post-HLS simulation mismatches even though we are using direct inputs and also changing their values while the design is executing.

When a signal or port covered by `#pragma hls_direct_input` is also included in the scope of a later `#pragma hls_direct_input_sync` directive, the sync directive selects the effective update contract for that controlled signal set. Such signals remain direct inputs for purposes of late physical sampling, but they are not required to remain stable for the entire reset epoch; instead, they must satisfy the sync-controlled discipline described here: updates may occur only at the designated synchronization handshake, and the values must remain stable between permitted sync-controlled updates and reset boundaries.

```
// This is example 61 in Catapult Matchlib examples
sc_in<bool> SC_NAMED(clk);
sc_in<bool> SC_NAMED(rst_bar);

Connections::Out<uint32_t> SC_NAMED(out1);
Connections::In<uint32_t> sample_in[num_samples];
Connections::SyncIn SC_NAMED(sync_in);
#pragma hls_direct_input
sc_in<uint32_t> direct_inputs[num_direct_inputs];

void main() {
    out1.Reset();
    sync_in.Reset();

#pragma hls_unroll yes
    for (int i=0; i < num_samples; i++) {
        sample_in[i].Reset();
    }

    wait(); // reset state

    while (1) {
#pragma hls_direct_input_sync all
        sync_in.sync_in();

#pragma hls_pipeline_init_interval 1
#pragma hls_stall_mode flush
        for (uint32_t x=0; x < direct_inputs[0]; x++) {
            for (uint32_t y=0; y < direct_inputs[1]; y++) {
                uint32_t sum = 0;
#pragma hls_unroll yes
                for (uint32_t s=0; s < num_samples; s++) {
                    sum += sample_in[s].Pop() * direct_inputs[2 + s];
                }
                ac_int<32, false> ac_sum = sum;
                ac_int<32, false> sqrt = 0;
            }
        }
    }
}
```

```

        ac_math::ac_sqrt(ac_sum, sqrt); // internal loop unrolled in cat .tcl
file
    if (sqrt > direct_inputs[7])
        out1.Push(sqrt);
    }
}
}
};

```

From the perspective of the testbench or the environment, the updating of the signals controlled by the `hls_direct_input_sync` directive shall only occur at a precise point. The TB shall first wait for the `rdy` signal for the sync to be asserted by the DUT, and then the TB shall update all the input signals it wishes to change while simultaneously driving the `sync_vld` signal high for one cycle.

It is important to note that the only safe operation to use to synchronize the updating of direct inputs is the sync operation as shown above. Other operations such as Push/Pop or `ac_channel` operations should not be used for this. In terms of the Appendix G trace model, the Σ -visible Read(sig,val) events remain anchored to their synchronization points; any additional internal sampling made by the implementation between anchors is treated as an ϵ -step and must not change the recorded value label.

In the example above the DUT block that is being synthesized determines when to call sync, and thus it determines when the direct inputs will be updated. In some cases, it may be necessary for the environment around the DUT to determine when the direct inputs should be updated. In this case the same approach as shown above should be used; however a separate input from the environment to the DUT (either using a signal or a message-passing interface) should request that the DUT call sync as soon as feasible. This will ensure that the DUT has properly ramped down its pipeline and is ready to receive the newly updated direct inputs as per the overall synchronization scheme described above.

Additional Options for Scheduling Message-passing Interfaces

The following option may be added during HLS (Cat2):

```
STRICT_IO_SCHEDULING=relaxed
```

When this is specified, the HLS tool is allowed to reorder message-passing interface calls freely on distinct interfaces (still not moving calls across synchronization interface calls). This relaxed mode may violate the default no-reverse discipline and therefore may introduce deadlocks that are not present under the default rules. It is recommended that this relaxed option only be used when the user wants to see what order the HLS tool prefers to schedule message-passing interface calls (e.g., to achieve best QOR).

Once the user knows the preferred order, it is recommended that the user modify the pre-HLS source code to reflect the preferred order, and then return to the use of the default scheduling modes. This methodology ensures that HLS cannot introduce new deadlocks *via reversal of source order on distinct message interfaces* as described earlier. Deadlock behavior may still depend on bounded-capacity effects and on overlapped execution (e.g., loop pipelining); those cases are addressed separately in this document via the pipelined-loop discussion (automatic flush / WFG-inertness) and the later deadlock

reasoning. The formal equivalence and deadlock-preservation results in Appendices G–K assume `STRICT_IO_SCHEDULING` is not set to relaxed.

Scheduling of Array Accesses

Arrays may appear in HLS models, and they may be preserved through synthesis and mapped to RAMs. Pointers may also appear in HLS models, and pointer dereferences are resolved to array accesses during HLS.

There are two cases to consider for arrays for the purposes of the scheduling rules:

1. Array instantiation in the HW is internal to the process
 - The array accesses are not visible outside the process, and thus their scheduling is also not visible externally.
 - All the scheduling rules described elsewhere in this document remain unaffected in this case.
2. Array instantiation in the HW is external to the process
 - In this case the user model shall indicate how array accesses are mapped onto IO operations that are external to the process.
 - We call this the *array access mapping layer*. The *array access mapping layer* maps array accesses onto IO operations described above (signal IO, message-passing interface calls, and synchronization calls).
 - The user model may indicate that it is allowable for HLS to transform array accesses, for example, to cache, merge, split, or reorder array accesses (e.g., to improve QOR). These transformed operations, if allowed, are an outcome of using the *array access mapping layer*.
 - In all cases the scheduling rules described elsewhere in this document for the core IO operations (signal IO, message-passing calls, synchronization calls) remain unaffected.
 - In all cases array accesses shall remain constrained by any explicit synchronization interface calls present in the process in the source model. Precisely speaking, all array reads or writes before a synchronization call shall commit before or in the same cycle at which the synchronization call commits, and all array reads or writes after a synchronization call shall commit in a cycle after the synchronization call commits. This rule is stated in terms of commit cycles (the cycle the mapped memory storage is accessed); the scheduler enforces it by choosing issue cycles consistent with the fixed access latency defined by the array access mapping layer.
 - Note that if transformed operations occur and array accesses are visible externally in both the pre-HLS and post-HLS model, then comparison of pre-HLS and post-HLS behaviors may need to account for the transformed operations.

When a loop is pipelined, multiple iterations of the loop are overlapped and execute at the same time. During loop pipelining, an access to a memory interface (or array) may be moved over or in parallel with an access to the same memory if the HLS tool can prove the reordering is conflict-free. If the array/memory is external to the process, the *array access mapping layer* shall indicate that such reordering is allowable if such reordering is to occur during loop pipelining.

Definitions: Issue vs. Commit

Informally, we can define **commit** and **issue** as follows:

Definition: Commit (message channel) — as observed by an external clocked observer

Commit is the cycle in which an external clocked observer sees a transfer *complete*:

- A message commits in the cycle when the observer sees **both valid and ready high at the same time**.
- The committed payload is the data value seen in that same cycle.

Definition: Issue (message channel) — as observed by an external clocked observer

Issue is the cycle in which an external clocked observer sees a transfer *start*:

- A message action issues when a Push operation asserts vld, or a Pop operation asserts rdy.

See Appendix C for formal definitions of **issue** and **commit**.

For RAM reads/writes as presented above, **commit** denotes the precise cycle the memory storage is accessed; since the access latency is fixed and known to the HLS scheduler, it can schedule the operation's issue cycle so that the commit cycle satisfies the required ordering relative to Sync. The "Scheduling of Array Accesses" constraints above are therefore written in commit-time.

Additional States Added by HLS Synthesis

By default, HLS synthesis tools may add additional states to processes (e.g. add latency to enable resource sharing), which may introduce latency differences in the interface behavior between the pre-HLS and post-HLS models. These additional states are never included in the set of *synchronization interface calls* as described above.

When the directive `IMPLICIT_FSM=true` is set on a process, the HLS synthesis tool shall ensure that the cycle-level behavior of the interfaces of the pre-HLS and post-HLS models shall be identical. With this option, the internal state machines of the pre-HLS and post-HLS models will be the same.

When the directive `IO_MODE=FIXED` is set on a process, the HLS synthesis tool shall ensure that the cycle-level behavior of the interfaces of the pre-HLS and post-HLS models shall be identical. With this option, it is still possible that the state machine internal to the process is different between the pre-HLS and post-HLS models (e.g. the post-HLS model may choose to use a pipelined multiplier where the pre-HLS model did not.)

Avoiding Pre-HLS and Post-HLS Simulation Mismatches

The scheduling rules described in this document are designed to be easy to understand, while providing good QOR via HLS and generally avoiding any mismatches between the pre-HLS and post-HLS simulation behaviors.

Non-blocking message-passing operations (PushNB/PopNB in SystemC, C++ `ac_channel nb_read/nb_write`) are a potential source of mismatches between pre-HLS and post-HLS simulations since their behavior is inherently dependent on the latency within the model, which often changes during HLS. Because of this, non-blocking message-passing interfaces should only be used when no

alternative approach is possible. For example, non-blocking message-passing interfaces are required to model time-based arbitration of multiple message streams which access a shared resource. A full discussion of recommended guidelines on the use and verification of non-blocking message-passing interfaces is provided in Appendix L. Note that the scheduling rules described previously in this document fully specify how HLS tools are required to schedule such operations.

Unidirectional message-passing between two processes should not be relied on to achieve synchronization between the two processes, since in general the message latency and storage capacity between the processes may be variable. Also, depending on buffering/pipelining in the realization, the time between a producer's committed Push and the consumer's committed Pop (and the transient in-flight occupancy) may vary. Two unidirectional message-passing channels in opposite directions can be relied upon for synchronization between two processes. (An example of this is the AXI4 `ar` and `r`, and `aw` and `b`, channels). Note that such synchronization is weaker than explicit synchronization like `SyncChannel` or signal IO that uses a two-way handshake.

SystemC signal IO operations are a potential source of pre-HLS versus post-HLS simulation mismatches since timing behaviors may change between the two models. The following section provides guidance and rules to help avoid potential mismatches due to signal IO.

When signal IO operations are synchronized with a wait statement, there generally should be a proper two-way handshake associated with the wait statement so that the signal IO is latency insensitive. (Note that this statement does not apply to the signal synchronization approaches described in the Direct Inputs section.)

For example, here's a simple two-way handshake protocol when writing the signal `out_dat`:

```
out_dat = value;
out_vld = 1;
do {
    wait();
} while (out_rdy != 1);
out_vld = 0;
```

And here's a two-way handshake example when reading signal `in_dat`:

```
in_rdy = 1;
do {
    wait();
} while (in_vld != 1);
value = in_dat;
in_rdy = 0;
```

Some signal-level protocols have different two-way handshaking approaches (e.g. ARM APB), but they are still latency insensitive.

If signal IO operations are associated with a wait statement and that wait statement does not have a proper two-way handshake, then the signal IO is likely to be latency-sensitive and may result in pre-HLS versus post-HLS simulation mismatches. In some systems a one-way signal handshake is sufficient for reliable system operation. See Appendix E for further discussion.

The scheduling rules state that signal IO operations occur at either SystemC wait statements or SyncChannel calls (`sync_in` and `sync_out`). In the remainder of this section, we will use *wait* statements to refer to both.

RULE 1: It is always best coding style to group signal write operations just before their corresponding wait statement, and signal read operations just after their corresponding wait statement. (Cat3). An example is below:

```
sc_in<int> i1;
sc_in<bool> go;
sc_out<int> o1;
void my_thread() {
    int new_val=0;
    while (1) {
        o1.write(new_val);
        do {
            wait();
        } while (!go.read());
        new_val = i1.read();
        new_val = some_function(new_val); // function has no internal IO
    }
}
```

By placing the signal IO operations as close as possible to their corresponding wait statement, the HW intent is very clear. And there is no benefit either in terms of simulation performance or HLS QOR if they are placed further away from their corresponding wait statement.

Let's look at another similar example, which now also uses a Matchlib Connections blocking Pop operation:

```
sc_in<int> i1;
sc_in<bool> go;
sc_out<int> o1;
Connections::In<int> pop1;
void my_thread() {
    int new_val=0;
    while (1) {
        o1.write(new_val);
        do {
            wait();
        } while (!go.read());
        int pop_val = pop1.Pop();
        new_val = i1.read();
        new_val = some_function(new_val + pop_val); // function has no internal
IO
    }
}
```

Under the anchoring rules, `i1.read()` remains associated with the same synchronization point regardless of the intervening Pop. However, in raw pre-HLS simulation, a blocking Pop may stall for one or more cycles, so `i1` can change before the `i1.read()` executes—creating behavior that differs from the anchored interpretation (and potentially from post-HLS scheduling). The fix is simply to place `i1.read()` immediately after its intended `wait()` anchor; this removes the mismatch risk without affecting QOR or simulation performance.

For a proof-backed flow, RULE 1 conformance is a source well-formedness obligation, not merely a recommended diagnostic. If a blocking message-passing operation separates a signal read or write operation from its corresponding synchronization interface call, then the flow shall either reject the model for purposes of applying the formal guarantees, require the source to be rewritten so the signal IO is adjacent to its intended anchor, or discharge an explicit source-level well-formedness argument showing that the signal IO has a unique unconditional real synchronization anchor on every dynamic path and cannot observe a value inconsistent with that anchor. HLS tools may implement this requirement using errors, warnings, lint checks, or other diagnostics, but an unresolved warning is not sufficient to claim the RULE 1 / RULE 2-based guarantees.

Another scenario in which RULE 1 applies is shown below:

```
sc_in<bool> go;
sc_out<int> o1;
void my_thread() {

    while (1) {
        wait();                // WAIT 1
        o1.write(some_value);
        if (go.read()) {
            some_value = some_function();
        }
        else {
            wait();             // WAIT 2
        }
        some_other_function();
        wait();                 // WAIT 3
    }
}
```

The signal read of `go` is clearly and uniquely associated with WAIT 1. However, the signal write of `o1` associates with WAIT 2 if `go` is false and WAIT 3 if it is not. This is a violation of RULE 1 and should be flagged as an error during HLS. The fix, as before, is to move the signal IO operation as close as possible to its intended wait statement so that the association is unconditional.

Next, let's consider *rolled* (or *preserved*) loops that perform signal IO within the loop body. Consider the following example:

```
sc_in<int> i1;
sc_out<int> o1;
void my_thread() {
    wait(); // reset state
    while (1) {
        wait(); // start of while loop
        #pragma hls_unroll no
        for (int i=0; i < 10; i++) {
            o1.write(i1.read() * i);
        }
    }
}
```

Note that the `i1.read()` operation is located inside the `for` loop, so presumably the user's intent is that it should be read as the loop iterates. *If that is not the user's intent, they simply should move the `i1.read()` operation before the loop start.*

In the post-HLS simulation, each iteration of the loop will consume at least one clock cycle, and a new value for `i1` will be read (and a new value for `o1` written) on each iteration. Again, this is the user's intent as per the code. In the pre-HLS simulation, the `for` loop body will execute in zero time, and only the last write to `o1` will have any effect. The solution to avoid this mismatch is to manually place a `wait()` statement within the `for` loop body so that the signal IO synchronization is explicit in the pre-HLS simulation.

RULE 2: If you have signal IO operations within *rolled* (or *preserved*) loops, manually place a `wait` statement within the body of the loop to avoid pre-HLS versus post-HLS simulation mismatches, and while doing so also follow **RULE 1**.

For a proof-backed flow, a rolled loop with signal IO operations but no `wait` statement in the loop body shall be treated as a source well-formedness failure unless an explicit source-level argument shows that each observable signal Read/Write still has a unique real synchronization anchor on every dynamic path. HLS tools may implement this requirement using errors, warnings, lint checks, or other diagnostics. However, if a diagnostic is emitted as a warning rather than an error, the warning must be resolved, waived with an explicit well-formedness justification, or treated as excluding that model from the formal guarantees. (Cat4)

If a pre-HLS model has established RULE 1 and RULE 2 conformance, then all signal IO in the post-HLS model shall occur only at clock cycles that correspond to explicit `wait` statements or explicit synchronization statements. For direct-input signals/ports (e.g., `#pragma hls_direct_input` and `#pragma hls_direct_input_sync`), this requirement refers to the logical (Σ -visible) anchor cycle of the Read/Write: the event is still considered to occur at its synchronization point even if HLS physically samples a stable signal later; such late-sampling micro-steps are ϵ -steps and are not Σ -visible. User designs that do not adhere to both RULE 1 and RULE 2 are ill-formed and are outside the formal guarantees unless the nonconformance has been eliminated or explicitly discharged by a valid source-level well-formedness argument.

Returning to the Analogy from RTL Synthesis

At the beginning of this document, we presented the example of a Verilog sequential block with an output coded like:

```
Out1 <= #some_delay new_val;
```

Recall that in Verilog simulation, if `some_delay` is less than the clock period of the block, then it will probably not affect the overall cycle-level behavior of the system during simulation. However, if `some_delay` is more than the clock period, it probably will.

During RTL synthesis, all RTL synthesis tools will ignore all delays in the input model, in this case even if `some_delay` is greater than the clock period. Some RTL synthesis tools might give a warning for the code

above like “Simulation and synthesis results are likely to mismatch because delay in model is greater than clock period.”

HLS tools or associated lint/qualification flows that adhere closely to the conceptual model presented in this document should provide a concrete mechanism for detecting or discharging violations of RULE 1 and RULE 2 as described in the section above. This is analogous to the error or warning that the RTL synthesis tool would provide in the example directly above.

However, the formal guarantees in this document do not depend on any particular diagnostic mechanism. If an HLS synthesis tool does not report a RULE 1 / RULE 2 issue, the design is not thereby made well-formed. The proof-backed flow must still establish that the source model satisfies the RULE 1 / RULE 2 well-formedness obligation before applying the trace-compatibility guarantees.

Summary

At the beginning of this document, we said that the intent was to present “no surprises” to a DV engineer who wants a common verification methodology for the pre-HLS and post-HLS models. The key aspects of the document which support this are:

- Three groups of IO operations are defined (message-passing, signal IO, and synchronization calls) and each is treated uniformly. These IO operations are easy for verification engineers to understand because they are already using them in their testbenches.
- The document specifically avoids complex constructs such as *protocol regions* used in some HLS tools.
- The document preserves the ability of the pre-HLS SystemC model to be *throughput accurate* by using a library such as Matchlib.
- Synchronization calls can affect the scheduling (anchoring) of signal IO operations, and synchronization calls can affect the scheduling of message-passing calls. In the conceptual anchoring semantics of this document, message-passing calls do not affect the anchor cycle of signal IO operations (and signal IO does not affect the legality/order of committed message transfers) except through explicit synchronization. Practically, in raw pre-HLS SystemC simulation a blocking message operation may introduce additional cycles of waiting, so signal IO statements that are lexically separated from their intended anchor can observe different values; RULE 1 addresses this by recommending placement of signal IO adjacent to its anchor.
- HLS cannot by default reverse the order of message-passing calls, so it cannot introduce new deadlocks *via call-order reversal*. For pipelined loops (overlapped iterations) and other transformations that change the timing of request/commit under bounded capacities, deadlock preservation depends on the additional pipelined-loop discipline described in this document (automatic flush / WFG-inertness), not on the no-reverse rule alone.
- HLS pipelining is largely a *don’t care* from the perspective of the verification engineer. If the design and the testbench are insensitive to changes in latency, and if external array accesses are not reordered or rearranged during loop pipelining, then the possible use of HLS pipelining will not affect verification, provided the pipelines flush automatically. Even if the design or

testbench are sensitive to changes in latency, or if they are sensitive to reordering or rearranging of external memory accesses due to the use of HLS loop pipelining, then the behavior of the DUT will only change in expected (rather than unexpected) ways, provided the applicable observation-boundary and witness-selection conditions are satisfied. (Appendix G provides formal trace-compatibility guarantees rather than an unrestricted bidirectional equivalence theorem.)

- For sequential processes, signal IO operations in the post-HLS model always occur exactly at synchronization points (e.g., wait statements) that are explicit in the pre-HLS source. For direct-input signals/ports, “occur at synchronization points” is meant in the logical/anchoring sense: the Σ -visible Read/Write is timestamped at the synchronization point even if the implementation samples the stable signal later; those internal late samples are ϵ -steps. For combinational processes, observable signal Read/Write events are instead interpreted at the cycle’s ϵ -quiescent combinational fixed point, as specified by R2C.

Appendix A – Factory Analogy

The scheduling rules described in this document apply to pre-HLS and post-HLS HW models. Although the rules may seem abstract and perhaps even arbitrary, they are shaped by the need to model systems in the real world that are required to have predictable behavior.

To understand the motivation behind the rules, it might be helpful to draw a simple real-world analogy and its correspondence to the rules described earlier.

Consider a factory that produces various types of wooden furniture:

The factory consists of people (processes) stationed at workbenches with various tools.

Each person is given written instructions about the specific tasks they are to perform (C++ code within a process).

People are instructed to send or receive objects (messages) to or from other people in the factory.

Sending or receiving objects may be blocking or non-blocking from the perspective of a person.

There is a clock with a second hand on the factory wall that everyone can see. (HW clock).

People have colored flags they can raise or lower to communicate with other people (signals).

If someone raises or lowers a flag, this is only seen by others the next time the clock second hand is at the top of the clock. (propagation delay of signals between sequential processes)

A person can choose to pipeline the tasks that they were assigned by hiring subordinates (pipeline stages) and having each one do a subtask. In general, this will improve the throughput for the tasks that the person was assigned.

It is possible for two people to explicitly synchronize their work by communicating via a synchronization protocol such as a barrier (synchronization).

It is possible to restart the work of some or all the people by raising a reset flag (HW resets).

Assume:

1. That the time that people take to complete their various tasks is in general variable, and similarly that the time that objects (messages) take to pass between people is in general variable.
2. That each person in general wants to complete their tasks as quickly and efficiently as possible.
3. That the factory needs to be able to make multiple types of furniture at the same time. For example, it might make chairs that need to be different colors or have different styles.

To reliably produce output, each person in the factory will need to adhere to rules like those described in this document.

Here's a sketch of a specific way the above example relates to the scheduling rules:

Person 1 sends chair seats and chair backs to Person 2. This is done with blocking operations, and there is no storage capacity between the people when the objects are sent. (This means that a Push operation cannot complete until the corresponding Pop operation is performed.) Assume that the fastest an object can be sent between people is 1 minute.

The written instructions that person 1 is given are:

```
while (1) {  
    // internal processing code for seats and backs ...  
    seats.Push(seat_object);  
    backs.Push(back_object);  
}
```

The written instructions that person 2 is given are:

```
while (1) {  
    seat_object = seats.Pop();  
    back_object = backs.Pop();  
    // internal processing code for seats and backs ...  
}
```

If both person 1 and person 2 choose to perform their tasks sequentially as written, then objects will be passed over time as:

	Person 1	Person 2
Minute 1:	seats.Push(seat1);	
Minute 2:	backs.Push(back1);	seat1 = seats.Pop();
Minute 3:	seats.Push(seat2);	back1 = backs.Pop();
Minute 4:	backs.Push(back2);	seat2 = seats.Pop();
Minute 5:		back2 = backs.Pop();

If both person 1 and person 2 choose to perform their IO operations in parallel, then objects will be passed over time as:

	Person 1	Person 2
Minute 1:	seats.Push(seat1); backs.Push(back1);	
Minute 2:	seats.Push(seat2); backs.Push(back2);	seat1 = seats.Pop(); back1 = backs.Pop();
Minute 3:		seat2 = seats.Pop(); back2 = backs.Pop();

If person 1 chooses to perform their IO operations in parallel, and person 2 chooses to perform their IO operations sequentially as written, then objects will be passed over time as:

	Person 1	Person 2
Minute 1:	seats.Push(seat1); backs.Push(back1);	
Minute 2:		seat1 = seats.Pop();
Minute 3:	seats.Push(seat2); backs.Push(back2);	back1 = backs.Pop();
Minute 4:		seat2 = seats.Pop();
Minute 5:		back2 = backs.Pop();

If person 1 chooses to perform their IO operations sequentially as written, but person 2 chooses to perform their IO operations sequentially in the reverse order as it was written, then objects will be passed over time as:

	Person 1	Person 2
Minute 1:	seats.Push(seat1);	
Minute 2:	backs.Push(back1);	back1 = backs.Pop();
Minute 3:		seat1 = seats.Pop();

In this case the person 1 seats.Push(seat1) operation at minute 1 will not complete at the start of minute 2. This means that the person 1 backs.Push(back1) operation will never start, and thus the Person 2 back1 backs.Pop() operation will never complete. So, the system will be in deadlock.

This example directly corresponds to the ordering rules related to message-passing operations in the *basic conceptual model* within this document, and in particular the specific rule that disallows reversing the order of message-passing operations.

Appendix B – Formal Presentation of Pipelined Loops

Modeling convention for pipelined-loop overlap.

The post-HLS pipelined-loop implementation may overlap iterations and may internally accept/stage up to the finite bound $B(c_in)$ of input values for younger overlapped iterations before older iterations' outputs are produced. This internal accept/stage behavior is part of the back-annotated channel realization counted in $B(c_in)$ between the Σ -visible endpoints of c_in (producer $Push_c_in$ and consumer Pop_c_in). Here $B(c_in)$ is an effective abstract-boundary capacity/credit bound, not a claim that the RTL contains a single physical FIFO named c_in ; the proof obligation is that the chosen Sys_ref boundary exposes E4-consistent ChannelEnabled/ChannelDisabled behavior, with hidden physical storage represented as ϵ -state unless it is explicitly elaborated into Sys_B^{elab} channels. These internal accept/stage movements are modeled as ϵ -steps. **Σ records only the committed boundary transfers at the Σ -visible endpoints.** In particular, the consumer-side boundary Pop_c_in is the loop-body Pop_c_in operation from the pre-HLS source when that Pop is included in the chosen Σ / Σ_DUT projection. The externally relevant effect of pipelining is therefore captured entirely by $B(c_in)$ (via

boundary backpressure/acceptance behavior and overlap timing at the Σ -visible boundary), without introducing any new auxiliary or duplicate Σ -visible boundary Pops: the Σ -visible consumer-side $\text{Pop}_{\{c_in\}}$ commits are still the same loop-body $\text{Pop}_{\{c_in\}}$ operations from the pre-HLS source, though they may commit at different times (and thus at different prefixes) than in an unpipelined execution. Once the pipeline reaches a quiescent blocked state under the automatic flush discipline below, it does not initiate new blocking request assertions for younger overlapped iterations.

B-faithfulness obligation

The use of $B(c_in)$ in this modeling convention assumes that the selected abstract boundary and the reported capacity faithfully summarize the corresponding RTL realization: all storage/credit that can accept, hold, or backpressure messages between the chosen producer and consumer endpoints is either counted in $B(c_in)$ or represented as an explicit $\text{Sys_B}^{\text{elab}}$ boundary, and movements inside that realization are ϵ -steps that do not create, delete, duplicate, reorder, or relabel Σ -visible boundary transfers. This is a tool/RTL-flow compliance obligation, not a fact derived by Appendix B.

Multi-input Pop points and coupler policies.

When a pipelined loop consumes from multiple input channels (e.g., $c1, c2$), back-annotation still assigns a separate finite bound $B(c_i)$ and cycle-boundary occupancy $\text{occ}_{ci}(t)$ to each outer Σ -visible boundary channel c_i . However, in the multi-input / coupler cases of Appendix Q the formal source-side proof target is no longer merely the outer-boundary Sys_B ; it is the elaborated reference model $\text{Sys_B}^{\text{elab}}$ of Appendix J, Remark 2. In $\text{Sys_B}^{\text{elab}}$, $B(\cdot)$, $\text{occ}_{\cdot}(t)$, E4, BoundaryReq, ChannelEnabled/ChannelDisabled, and the Appendix K blocking/WFG machinery are interpreted per explicit abstract channel, including any introduced staged/bundle/join channels. Any conjunctive/join dependency (e.g., “join not met”) shall therefore be represented only via such explicit staged/bundle/join boundary channels in $\text{Sys_B}^{\text{elab}}$ (not as cross-channel disablement at the outer Σ -visible endpoints), so that for Appendix K the blocking point is that explicit boundary and the relevant $\text{Front_P}(\sigma)$ members there are jointly channel-disabled (“ALL disabled $\Rightarrow$ stall”). For the detailed elaboration patterns and examples, see Appendix Q.

Practical note (outer Σ_{DUT} projection and proof-internal Σ)

The loop-body $\text{Pop}_{\{c_in\}}$ in the pre-HLS source (i.e., the consumer-side $\text{Pop}_{\{c_in\}}$ operation, conceptually after the in-flight capacity $B(c_in)$) may be exposed in the outer DUT/testbench-visible alphabet Σ_{DUT} if desired, but is typically omitted since it is latency-insensitive, and it is often practically difficult to expose/collect in the post-HLS RTL. The liveness/deadlock reasoning still accounts for this blocking point without requiring it to be Σ_{DUT} -visible: Appendix K defines WFG edges using the ChannelEnabled/ChannelDisabled status of the corresponding pending boundary operation instance q with $\text{kind}(q)=\text{Pop}_{\{c_in\}}$ (via E4/ $\text{occ}_c/B(c)$). In ordinary non-elaborated Sys_B cases, this does not require introducing any additional proof-internal abstract channel. In elaborated cases $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$, however, any introduced staged/bundle/join channel needed to represent a blocking point is an explicit proof-internal Σ boundary for Appendix K, even if its committed Push/Pop events are projected away from the outer Σ_{DUT} trace by Π_{elab} .

Automatic flush (drain-only blocking discipline).

Potential deadlocks are avoided by having the pipeline automatically flush.

In this document, “automatic flush” does not mean a global pipeline clear or a mandatory drain-to-empty phase. It means the drain-only blocked-frontier discipline defined below: once the minimal pending blocking frontier is fully channel-disabled after ε -settling, the process is blocked at that frontier; no new later source work may issue past that frontier; already asserted blocking requests remain asserted until commit; and already-issued downstream work may continue to drain only insofar as it does not create new WFG-relevant blocking causes.

Terminology (pending blocking frontier / $\text{Front_P}(\sigma)$)

In an ε -quiescent cycle, consider the set of pending source-level blocking message-operation frontier items $x \in \Omega_{\text{msg},P}$ in the current interval between adjacent synchronization calls, where each such item has an owning dynamic message-call instance $q = \text{MsgOf_P}(x)$ whose $\text{Issue}(q)$ has occurred and whose $\text{Commit}(q)$ has not yet occurred. By the Issue/Commit linkage (Appendix C) together with BoundaryReq ’s definition at the Σ -visible boundary (as given in “Common Formal Definitions for Appendices I-K”), each such pending blocking frontier item x has its endpoint-owned boundary request asserted through q (Push: vld, Pop: rdy) until q commits; purely combinational channel-side structure (including couplers) may affect only the complementary mirror signal (Push: rdy, Pop: vld) and thus whether x commits in that cycle after ε -settling. Define $\text{Front_P}(\sigma)$ to be the set of such pending blocking message-operation frontier items that are minimal with respect to the source-induced order $\leq_P$ within that interval (if multiple minimal blocking frontier items are pending, they form a frontier). We refer to $\text{Front_P}(\sigma)$ as the pending blocking frontier (or “minimal pending blocking frontier”). This $\text{Front_P}(\sigma)$ notion is distinct from NextFront_P (Lemma S2 / Corollary J.1), which denotes the next source-level frontier-item set over Ω_P and may include synchronization-call items, signal-anchored action items, and message-operation items. A message-operation item in NextFront_P may be pending before it contributes any committed Σ -event.

A pipelined loop is said to automatically flush if, whenever the pending blocking frontier $\text{Front_P}(\sigma)$ is non-empty and every frontier item $x \in \text{Front_P}(\sigma)$ cannot make progress because it is not channel-enabled (evaluated after combinational ready/valid/backpressure has ε -settled for the cycle), then:

1. **Block point.** The process is blocked on message passing at that pending blocking frontier $\text{Front_P}(\sigma)$, as in the unpipelined source.
2. **No new later work.** While blocked at that frontier (i.e., while $\text{Front_P}(\sigma)$ remains non-empty and all of its members are channel-disabled), the implementation does not issue any new blocking Pop/Push message-operation frontier item $y \in \Omega_{\text{msg},P}$ that is later in source order than some $x \in \text{Front_P}(\sigma)$, including any younger overlapped iteration, and therefore does not begin asserting $\text{BoundaryReq}(y, \cdot)$ for such later work. Here issue is read through the owning message instance $q_y = \text{MsgOf_P}(y)$.
3. **No withdrawal.** While blocked, the implementation does not withdraw any already-asserted blocking Pop/Push request (no “try-and-withdraw”); outstanding blocking requests remain asserted until their owning message instances commit.
4. **Clarification (Frontier-minimality vs. other asserted requests).** The Wait-For Graph in Appendix K is intentionally defined from the minimal pending blocking frontier $\text{Front_P}(\sigma)$, i.e., the current blocking causes. Accordingly, an already-asserted blocking request whose frontier item is not in $\text{Front_P}(\sigma)$ (for example, a request from a younger overlapped iteration that was issued before the blocked condition, or a downstream request draining work already past the frontier) may persist as protocol state under the “no withdrawal” rule, but it is not treated as a wait-for source while an earlier pending blocking frontier item remains frontier-minimal. Such a request contributes WFG blocking only if/when its frontier item later becomes a member of $\text{Front_P}(\sigma)$.

5. **Drain-only downstream progress.** Work that has already passed the blocked frontier point(s) may continue to drain, and any already-asserted resulting output-Push requests may commit when channel-enabled, provided no work advances past the blocked frontier point(s). (Formally: “no work advances past” is meant in the $\leq_P$ / issue sense—while $\text{Front}_P(\sigma)$ is fully disabled, P does not issue any new blocking message-operation frontier item y , with owning instance $q_y = \text{MsgOf}_P(y)$, such that, for some $x \in \text{Front}_P(\sigma)$, $x \leq_P y$ and $x \neq y$; downstream drain may only complete/commit operations whose BoundaryReq was already asserted prior to reaching this blocked condition.) (Equivalently: this is the “ALL disabled $\Rightarrow$ stall” policy— P stalls only when none of the frontier items in $\text{Front}_P(\sigma)$ are channel-enabled; downstream work may drain while $\text{Front}_P(\sigma)$ is fully disabled.)
6. **Synchronization-boundary withdrawal of future-epoch acceptance.**
 Let s be an explicit synchronization interface call that separates the current source interval from later work. While the process is pending at s , the implementation shall not present producer-facing availability for any back-annotated capacity intended only for $\text{suff}_S(s)$; equivalently, any asserted upstream producer request targeting such capacity shall remain channel-disabled until s commits. This does not prevent drain of work already accepted before reaching s . **Formal elaboration requirement.** For purposes of Appendices J–K, this withdrawal shall be represented in Sys_ref by the elaborated source model $\text{Sys_B}^{\text{elab}}$, not by adding a hidden extra enablement predicate to an otherwise E4-enabled outer channel. $\text{Sys_B}^{\text{elab}}$ shall introduce explicit sync-boundary / epoch-gate abstract channels, or equivalent explicit staged realization structure, so that capacity usable only by $\text{suff}_S(s)$ is separated from capacity available to the current interval. While s is pending, the gate/boundary for future-epoch acceptance is channel-disabled in the ordinary E4 sense at that explicit abstract boundary. After s commits, the corresponding post-sync capacity may again become producer-facing available according to the ordinary ChannelEnabled rules for the elaborated channels.

Example (II=1, latency=4, automatic flush): a loop that performs one blocking $\text{Pop}_{\{c_in\}}$ and one blocking $\text{Push}_{\{c_out\}}$ per iteration in the pre-HLS source may, after pipelining in the post-HLS RTL, internally accept/stage up to four input values into pipeline staging (pipeline overlap) before the first output $\text{Push}_{\{c_out\}}$ commits, subject to the back-annotated bound $B(c_in)$ (E4). Values may then reside for several cycles in internal pipeline storage; such internal staging/hand-off is ε -state within the back-annotated realization and does not create any new auxiliary or duplicate Σ -visible $\text{Push}_c/\text{Pop}_c$ events beyond the boundary commits at the Σ -visible endpoints (it may change only the timing of those boundary commits under overlapped execution). The drain-only blocking behavior is as defined above under “automatic flush”; in particular, if the blocked operation is in a late pipeline stage (e.g., the final Push), there may be little or no downstream work to drain.

Appendix C – Formal Definitions of Issue and Commit

Scope / shared definitions

The definitions below are with respect to the Σ -visible endpoints of the chosen source reference model Sys_ref (Appendix J, Remark 2)—i.e., the ready/valid interfaces at which Σ records message-transfer events in the raw rendezvous case Sys , the ordinary bounded-FIFO case Sys_B , or the elaborated back-annotated case $\text{Sys}_B^{\text{elab}}$. All shared notions about (i) Σ vs. ε steps, (ii) BoundaryReq / ChannelEnabled / ChannelDisabled , (iii) non-blocking polls as ε on failure, and (iv) the $B(c)$ / $\text{occ}_c(t)$ (cycle-boundary, non-fall-through) interpretation of E4 are as defined in “Common Formal Definitions for Appendices I–K”

and are to be interpreted over the explicit abstract channels of Sys_ref . Appendix C defines only Commit, Issue, and the Issue/Commit linkage conditions that make $\text{Issue}(q)$ well-defined.

Definition: Commit (message channel) — as observed by an external clocked observer

Commit is the cycle in which an external clocked observer sees a transfer complete at a Σ -visible boundary endpoint: A message commits in the cycle when the observer sees both valid and ready high at the same time. The committed payload is the data value seen in that same cycle.

Definition: Issue (message channel) — as an auxiliary (scheduler/witness) timestamp

Issue(q) is an auxiliary timestamp used to state scheduling constraints (R4/E3/E5). Intuitively, it is the first cycle in which the calling process begins requesting the transfer corresponding to the source-level message operation instance q at the chosen Σ -visible boundary endpoint.

Issue/Commit linkage (well-formedness conditions)

Fix a Σ -visible endpoint direction, and let $\text{req}(t)$ denote the endpoint-owned boundary request signal in cycle t (valid for Push, ready for Pop), i.e., the process-driven request level captured by BoundaryReq at that boundary (per “Common Formal Definitions for Appendices I-K”). For each source-level message operation instance q on that endpoint direction:

- Boundary-request soundness (blocking requests are non-withdrawable). $\text{req}(\text{Issue}(q)) = 1$. If q is a blocking Push/Pop, then once issued it remains the unique outstanding request on that endpoint direction until it commits: $\text{req}(t)=1$ in every cycle t from $\text{Issue}(q)$ through the commit cycle of q (inclusive), with stable payload while asserted for Push. (This is the “no deassert-before-commit” discipline used throughout the document.)
- Stable attribution for a single outstanding source-level request. If $\text{req}(t)=1$ and no transfer commits on that endpoint direction in cycle t , then any continued assertion $\text{req}(t+1)=1$ is attributed to the same outstanding source-level message-operation instance q only so long as the requesting source-level operation remains that same outstanding instance. For blocking Push/Pop, this is the mandatory non-withdrawable case above, so attribution cannot change before commit. For non-blocking PushNB/PopNB, continuous assertion of the endpoint request signal, by itself, does not identify later executed non-blocking call instances as the same q ; a new executed source-level non-blocking call creates a new dynamic instance $q' \in Q_{\text{exec},P}$ for the owning process P , even if req does not deassert between cycles.
- Back-to-back issuance under continuously asserted req . If q_0 commits in cycle t and the next source-level operation q_1 on the same endpoint direction is issued back-to-back, then $\text{Issue}(q_1)=t+1$ (even if the request signal does not deassert between commits), provided q_0 and q_1 lie within the same source interval between adjacent synchronization calls.
- Sync-boundary discipline. If $q_0 \in \text{pref}_S(s)$ and $q_1 \in \text{suff}_S(s)$ for a synchronization call s , then $\text{Issue}(q_1)$ is strictly after s ’s commit in the same trace (i.e., $\text{Issue}(q_1) > \text{clk_pre}(s)$ in τ_{pre} and $\text{Issue}(q_1) > \text{clk_post}(s)$ in τ_{post}). Any boundary request assertion that persists while the process is still pending at s is attributed to the outstanding operation(s) in $\text{pref}_S(s)$ and does not constitute issuance of any operation in $\text{suff}_S(s)$.

For non-blocking message passing (PushNB/PopNB), a failed poll produces no Σ -event and is modeled as an ϵ -step, while a successful poll contributes the corresponding committed $\text{Push_c}(v)$ / $\text{Pop_c}(v)$ event; see “Non-blocking message-passing” in “Common Formal Definitions for Appendices I-K” and Appendix I.2. Each executed non-blocking call is a distinct dynamic source-level message-call instance $q \in Q_{\text{exec},P}$ for the owning process P . Thus, if repeated PopNB/PushNB polls occur in later loop iterations or at later source-level call instances, they are distinct q ’s even if the endpoint request remains

continuously asserted and no intervening commit occurs. Stable attribution therefore applies to a single outstanding source-level request instance; it does not collapse distinct non-blocking dynamic call instances across iterations into one q . Successful non-blocking calls that commit induce message-operation frontier items $x \in \Omega_{\text{msg},P}$ when their committed transfer is relevant to Ω_P , with owning message instances $q = \text{MsgOf}_P(x)$ in $Q_{\Omega,P}$. Failed non-blocking polls remain only in $Q_{\text{exec},P}$ and contribute no Ω_P or $\Omega_{\text{msg},P}$ item.

Appendix D – Modeling Latency-Sensitive Protocols

In some cases, designs or testbenches may use protocols or local control policies which are latency-sensitive. These situations are handled by isolating the latency-sensitive portions into small, self-contained parts, and then keeping the rest of the design and testbench latency insensitive. A latency-sensitive portion is any local block of logic whose functional or externally visible behavior depends on cycle-level timing that is not represented by the ordinary latency-insensitive Σ interface. This includes ordinary signal-level protocols with fixed cycle timing, global interrupt/request ordering logic, non-blocking arbitration whose winner depends on request arrival timing, and non-blocking retry/timeout logic whose later behavior depends on the number or cadence of failed PushNB/PopNB polls before success.

For such logic, the intended methodology is not to treat the hidden timing dependence as part of the ordinary latency-insensitive source-core proof. Instead, the latency-sensitive portion should be isolated behind an explicit boundary. On one side of the boundary, the transactor or local protocol block may be modeled cycle-accurately, snooped, or otherwise verified with its detailed timing behavior. On the other side of the boundary, the rest of the system should see a latency-insensitive interface, such as message-passing transactions, synchronization events, or a properly handshaken signal protocol.

Consider a case where a signal-level protocol is latency-sensitive. The protocol will have specific timing behavior that it must meet. To handle this, we create a transactor that has two sides: the first side interacts with the signals and handles the detailed timing requirements, and the second side sends and receives messages with the rest of the system. The message-passing side is latency insensitive. The same pattern applies to cadence-sensitive non-blocking polling logic: if retry counters, timeout counters, or arbitration decisions depend on the number or cadence of failed non-blocking polls, that polling loop is part of the latency-sensitive local protocol block. Its detailed failed-poll cadence should be contained inside the isolated block or aligned by the Appendix L snooping mechanism; it should not leak as an unmodeled hidden timing dependence into the ordinary Appendix I/J latency-insensitive proof. To properly model the detailed timing behavior, the latency-sensitive transactor or local protocol block is modeled at the cycle-accurate level in SystemC, or is otherwise covered by an explicit snooping/alignment argument. There is an example of such a transactor model in the following document and example:

https://github.com/StuartSwan/Matchlib-Examples-Kit-For-Accellera-Synthesis-WG/blob/master/matchlib_examples/examples/53_transactor_modeling/transactor_modeling.pdf

For purposes of the formal appendices, once the latency-sensitive portion has been isolated, the ordinary Appendix I/J proof is applied at the chosen observable boundary of that isolated block. The failed-poll cadence internal to the isolated block remains local timing behavior; the rest of the system observes only the latency-insensitive or explicitly modeled boundary behavior.

Appendix E – One-Way Handshake Protocols

In some systems a one-way signal handshake is sufficient for reliable system operation. When using a one-way handshake, the implicit assumption is that the “missing” handshake isn’t required since it is always true.

For example, in time-domain signal processing hardware designs, signal processing HW blocks may input new samples at a fixed rate. The HW blocks are always ready to receive new samples on each clock, but they need to know if the samples are valid. These types of designs can be modeled with the one-way handshake dat/vld protocol demonstrated in this example:

https://github.com/Stuart-Swan/Matchlib-Examples-Kit-For-Accellera-Synthesis-WG/tree/master/matchlib_examples/examples/32_dat_vld

Appendix F – Scheduling Rules: Modeling Guidelines Summary

- 1) Prefer to use `Connections::In/Out + SyncChannel` over signal IO and `wait()`.
- 2) Prefer to use `Pop()/Push()` over `PopNB()/PushNB()`.
- 3) When pipelining a loop, prefer to use `hls_stall_mode flush`.

When using signal IO:

- 4) If modeling a cycle-accurate process, use `disable_spawn` and follow the example `53_transactor_modeling` style and do not use `Push/Pop` in the process.
- 5) If modeling a *direct input*, use `hls_direct_input` and possibly `hls_direct_input_sync`, and only change the signal at allowed times.
- 6) If combining signal IO with `Connections::In/Out` in the same process, use proper signal IO handshake that does not rely on `In/Out` ports for process synchronization. Place signal IO operations very close to their `wait()` statements.
- 7) Unless you are modeling a cycle-accurate process, you should expect that latency will change between the pre-HLS and post-HLS models.

Appendix G – Trace Compatibility Rules

This document informally states that a primary goal is to present “no surprises” to a DV engineer using the same testbench to verify the pre-HLS and post-HLS models.

Somewhat more formally, we can show how the scheduling rules within this document establish a set of trace-compatibility rules between the pre-HLS and post-HLS models that provide strong guarantees about their behaviors.

The *basic conceptual model* establishes the base behavior for a single process:

- 1) Synchronization interface calls always remain in source code order.
- 2) Signal reads occur at closest preceding synchronization interface call.
- 3) Signal writes occur at closest succeeding synchronization interface call.
- 4) All message-passing operations before a call to a synchronization interface shall be issued before or in the same cycle in which the synchronization interface commits.
(For blocking message-passing operations (Push/Pop), this implies the corresponding commits occur no later than the synchronization call's commit cycle.)
- 5) All message-passing operations after a call to a synchronization interface shall be issued after the cycle in which the synchronization interface call commits.
- 6) Two message-passing operations on separate interfaces which appear in sequence in the model may be issued either in the same sequence or in parallel in simulation and in synthesis, but they shall not be issued in the reverse sequence. Operations on the same message-passing interface are issued in source order (they are never reversed).
- 7) Synchronization calls can affect the scheduling of signal IO operations, and synchronization calls can affect the scheduling of message-passing calls, but message-passing calls cannot affect the scheduling of signal IO operations and vice-versa.
- 8) The STRICT_IO_SCHEDULING=relaxed option is not used.
- 9) We distinguish the rendezvous source model Sys (B(c)=0 for all channels) from the buffered source interpretation Sys_B, which uses bounded-FIFO channel capacities B(c) matching the post-HLS RTL (Appendices I–K).

Conceptually, systems are composed of many such processes which follow the basic conceptual model, and which communicate using only synchronization interface calls, latency-insensitive signal-level protocols, and committed message-passing transfers. If a design uses non-blocking message-passing calls (PushNB/PopNB), then unsuccessful polls are treated as internal ϵ -steps (no Σ -event), and each successful completion is represented in Σ as the corresponding committed Push_c/Pop_c transfer (Σ records transfers, not failed polls). If the resulting latency-sensitive behavior is externally visible at the DUT boundary, the snooping wrapper of Appendix L may be used to align the selected admissible pre-HLS execution with the RTL. Here we call this system of processes the *conceptual system*.

Practically, the modeling approach described above is too restrictive for real-world systems with optimized HW, so the scheduling rules in this document allow for key HW optimizations. But this is done in a carefully controlled manner, such that the HW optimizations do not break equivalent behavior with the *conceptual system*.

Here is a summary of the HW optimizations that the scheduling rules allow, and a brief description of how we maintain equivalent behavior with the *conceptual system*:

1. Pipelined loops: In the post-HLS RTL, the pipeline may overlap iterations to improve throughput. See Appendix B for a formal presentation of pipelined loops.
2. Pipelined loops: HLS by default will not break any latency-insensitive signal IO protocols when pipelining loops.

3. Direct inputs: Signals that do not change after a process comes out of reset can be read as late as possible using *hls_direct_input*, saving register area.
4. Direct inputs: When *hls_direct_input_sync* is used, signals read by a process are updated at the precise point at which the HW pipeline is guaranteed to be ramped down, so the signal values do not need to be saved within pipeline registers, saving register area.
5. Memory accesses: HLS can reorder memory accesses within a process only if it can prove that the reordering is conflict-free.
6. Shared memories: Memories shared between processes are modeled as simple C arrays but always include explicit synchronization between processes in both the pre-HLS and post-HLS models.
7. Non-blocking message-passing interfaces: They are modeled at the level of committed transfers (successful completion), with unsuccessful polls treated as ϵ -steps and thus not part of Σ . If latency differences in these committed-transfer events are externally visible at the DUT boundary and must be aligned for verification, equivalent behavior between pre-HLS and post-HLS systems can be maintained by snooping the post-HLS system and using this to delay pre-HLS message arrival (Appendix L).
8. Latency-sensitive global signal IO: If latency differences are externally visible to the DUT, equivalent behavior between pre-HLS and post-HLS systems can be maintained by snooping the post-HLS system and using this to delay pre-HLS signals.
9. Latency-sensitive local signal IO: Isolate local latency-sensitive protocols to small, dedicated transactors, and use latency-insensitive signal IO or message-passing to communicate with the rest of the system.
10. One-way signal handshake protocols: Only use in cases where backpressure is not possible and embed assertions into the model to check that this is always true.
11. Combinational processes: If the pre-HLS model contains combinational processes, their observable signal Read/Write behavior is interpreted at each cycle's ϵ -quiescent combinational fixed point. Under the well-formedness requirement that the combinational network is deterministic and reaches a unique fixed point, the RTL/tool-flow conformance obligation is to preserve the fixed-point signal relation, so combinational signal IO can be included in Σ without using synchronization anchors.

Taken as a whole, these rules support a verification methodology in which full-system verification is performed primarily on the pre-HLS system model, and post-HLS RTL verification can be reduced to targeted checks that the formal side conditions are met. The precise guarantee is the execution-level guarantee of Appendix J: every RTL_B observable behavior under the fixed stimulus has a matching Sys_ref behavior (Post $\rightarrow$ Ref), while the reverse direction applies only to RTL-consistent source-side prefixes or to source-side executions selected by the Appendix L snooping / witness-selection mechanism. Thus a source-side pass justifies the corresponding RTL_B behavior only within that RTL-consistent / witness-selected subset. For liveness/deadlock guarantees (Appendices I–K), the results additionally assume weak fairness and channel-progress obligations for the scheduler/environment (Appendix N); the cycle-by-cycle R/E rules alone do not imply those progress properties.

Formalization of the Trace Compatibility Rules in Appendix G

The following notation is used in this section.

Symbol Meaning

P	A process (thread or method) in the design
Σ	The alphabet of observable IO actions
τ_P	A (finite or infinite) per-cycle trace of observable actions executed by process P: for each global clock cycle t , $\tau_P[t]$ is the (possibly empty) set of Σ -actions committed by P at t . Actions committed in the same cycle are treated as simultaneous (unordered); only cross-cycle order (and the explicit E1–E5 constraints) is semantically significant.
S	The subset of Σ that are synchronization calls (explicit wait, SyncChannel, START_P/FINISH_P indicating process start/finish)
R	The subset of Σ that are signal reads
W	The subset of Σ that are signal writes
M	The subset of Σ that are committed message-passing transfers (i.e., committed Push_c / Pop_c events on message-passing channels, including successful non-blocking transfers). Unsuccessful non-blocking polls contribute no Σ -event and are modeled as ϵ -steps, and therefore are not members of M .
Q_{exec}	The execution-level set of dynamic source-level message-call instances executed by a process at the Σ -visible endpoints (blocking Push/Pop, and non-blocking PushNB/PopNB calls). Elements of Q_{exec} may or may not commit. In particular, failed non-blocking polls are elements of Q_{exec} , have no committed Σ -event, and are modeled as ϵ -steps. The frontier-item universe Ω_P , defined below, is separate from Q_{exec} .

A *system trace* is the tuple

$\tau = (\tau_P)_P$, one component per process.

For any action $a \in \Sigma$, let $\text{clk_pre}(a) / \text{clk_post}(a)$ be the clock cycle at which a is committed.

For any issued message-call instance $q \in Q_{\text{exec}}$, $\text{issue_pre}(q) / \text{issue_post}(q)$ denotes the auxiliary Issue timestamp for q in the pre-HLS / post-HLS trace, respectively, as defined in Appendix C and required to satisfy the associated Issue/Commit linkage (well-formedness) conditions with respect to the Σ -visible boundary request signal on q 's endpoint direction.

If q commits, it contributes a unique committed transfer $m(q) \in M$ with commit cycle $\text{clk_pre}(m(q)) / \text{clk_post}(m(q))$. If q does not commit (e.g., an unsuccessful non-blocking call), then $m(q)$ is undefined / absent and no Σ -event is added to M .

(Q_{exec} -matching / witness convention.) Because unsuccessful non-blocking polls are ϵ -steps and produce no Σ -event, Q_{exec} is not in general reconstructible from the Σ -projection alone. Whenever E3, E5, or any later proof compares executed message-call instances across Sys_ref and RTL_B , the comparison is made relative to the chosen execution witness. That witness supplies a partial matching μ_Q between dynamic source-level message-call instances in the compared traces, preserving process identity, endpoint/interface identity, dynamic source-order position, and source-level call-instance

identity where applicable. If q commits, then $\mu_Q(q)$ commits the corresponding matched transfer $m(\mu_Q(q))$ with the same Σ -label/value under the event-matching convention. If q is an unsuccessful non-blocking poll, then q has no $m(q)$ and no Σ -label; its presence and its match are supplied only by the witness-compatibility condition WC, by the sufficient NB-CF condition when applicable, or by the Appendix L snooping / witness-selection construction. Thus E3/E5 quantify over Q_{exec} only relative to this chosen witness; they do not require failed non-blocking polls to be inferable from Σ alone.

(No deassert-before-commit assumption.) For blocking message requests $q \in Q_{\text{exec}}$, once q is issued, its Σ -visible boundary request is not withdrawable: it remains asserted in every cycle from $\text{issue_pre}(q)$ (resp. $\text{issue_post}(q)$) through q 's commit cycle (if it commits), and for Push the payload remains stable while the request is outstanding.

Dynamic source-order convention

The order relation used below is over dynamic source-level operation/frontier items in the compared execution / witness, not over all syntactic call sites in the source text.

For a process P , let $Q_{\text{exec},P}$ denote the execution-level set of dynamic source-level message-call instances of P at the chosen abstract boundary. $Q_{\text{exec},P}$ includes blocking Push/Pop calls, successful non-blocking PushNB/PopNB calls, and failed non-blocking PushNB/PopNB polls.

Separately, let Ω_P denote the witness-specific dynamic universe of source-level frontier items that are actually reached under the fixed stimulus / selected witness and that are relevant to observable/frontier/deadlock reasoning. Items in Ω_P include synchronization-call instances, anchored signal Read/Write action instances, and message-operation frontier items at the chosen abstract boundaries. A message-operation frontier item is either (i) a blocking Push/Pop item that has been reached, whether pending or committed, or (ii) a successful non-blocking PushNB/PopNB item that contributes a committed $\text{Push}_c(v)$ / $\text{Pop}_c(v)$ event. A failed non-blocking poll q is an element of $Q_{\text{exec},P}$, has no committed Σ -event $m(q)$, and is not an element of Ω_P merely because it executed.

Because $Q_{\text{exec},P}$ is a universe of dynamic message-call instances while Ω_P is a universe of source-level frontier items, their message-operation overlap is not a literal set intersection. Let $\text{MsgOf}_P(x)$ be the partial projection from a frontier item $x \in \Omega_P$ to its owning dynamic message-call instance, defined exactly for message-operation frontier items and undefined for pure synchronization or signal-anchor items. Define the message-frontier slice

$$\Omega_{\text{msg},P} := \{ x \in \Omega_P \mid \exists q \in Q_{\text{exec},P} : \text{MsgOf}_P(x) = q \}.$$

Define the corresponding message-instance slice induced by Ω_P as

$$Q_{\Omega,P} := \{ q \in Q_{\text{exec},P} \mid \exists x \in \Omega_{\text{msg},P} : \text{MsgOf}_P(x) = q \}.$$

Let Σ_P denote the corresponding observable labels/events contributed by items of Ω_P when they are Σ -visible. For a message-call instance $q \in Q_{\text{exec},P}$, the committed Σ -event $m(q) \in M$ exists only if q commits; if q is a failed non-blocking poll, $m(q)$ is absent and q contributes no Σ -event. For a message-operation frontier item $x \in \Omega_{\text{msg},P}$ with $\text{MsgOf}_P(x)=q$, item x contributes the committed Σ -event $m(q)$ only if q commits. A pending blocking message-operation frontier item x may therefore be in Ω_P and $\Omega_{\text{msg},P}$, and its owning message instance q may be in $Q_{\Omega,P}$, even though $m(q)$ is not yet present.

Operations on untaken branches and unexecuted loop iterations are not members of Ω_P , $\Omega_{msg,P}$, $Q_{\Omega,P}$, or $Q_{exec,P}$. Distinct loop iterations, unrolled instances, and repeated calls are represented by distinct dynamic instances.

For dynamic items x and y of process P , write $x <_{src} y$, or equivalently $x <_P y$ when the process must be explicit, to mean that P 's source control flow and the R-rules force x to precede y in that dynamic execution / witness. The relation $<_{src}$ is used both on Ω_P for frontier reasoning and on $Q_{exec,P}$ for E3/E5 issue-order reasoning. Same-cycle issue or commit is still allowed where the R/E rules allow equality of issue timestamps or same-cycle buckets; $<_{src}$ identifies the source-induced precedence constraint, not a total simulator schedule over all syntactic statements. The relation $\leq_P$ used for frontier reasoning is the reflexive closure of the restriction of this source-induced order to Ω_P .

For sequential-process signal IO, $<_{src} / <_P$ is interpreted through the R2 anchor semantics rather than through the raw lexical statement location of the signal read or write. Thus a signal Read is ordered, for formal frontier and trace-compatibility purposes, at its $pred_S$ anchor, and a signal Write is ordered, for formal frontier and trace-compatibility purposes, at its $succ_S$ anchor. A lexically earlier signal Write whose $succ_S$ anchor is a later synchronization call does not, merely by lexical placement, precede or block intervening message-operation instances in the same source interval; conversely, a lexically later signal Read whose $pred_S$ anchor is an earlier synchronization call does not, merely by lexical placement, wait behind intervening message-operation instances. Signal IO may constrain message IO only through the explicit synchronization anchors and the stated R/E rules, not by raw lexical adjacency inside an interval.

Conceptual Model for a Single Process

For every process P the pre-HLS trace τ_P must satisfy the following *partial-order constraints* over these dynamic operation instances:

R1 (Program order of S).

$$\forall s1, s2 \in S : s1 <_{src} s2 \Rightarrow clk_pre(s1) < clk_pre(s2)$$

R2 (Location of R/W for sequential processes).

For a sequential process P , ordinary signal Read/Write events are anchored to synchronization events as follows:

$$\begin{aligned} \forall r \in R_P : clk_pre(r) &= clk_pre(pred_S(r)) \\ \forall w \in W_P : clk_pre(w) &= clk_pre(succ_S(w)) \end{aligned}$$

where $pred_S(r)$ (resp. $succ_S(w)$) is the closest dynamic synchronization-call instance that precedes (resp. follows) the signal Read/Write on the dynamic source path of the current execution / witness, after applying the anchoring convention above. This anchoring determines the signal event's formal position for $\leq_P / <_P$, $Done_P$, $Remain_P$, and $NextFront_P$ reasoning. In particular, for a sequential-process signal Write w , the fact that the write statement appears lexically before a message operation q in the same synchronization interval does not imply $w <_P q$ when w is anchored to the succeeding synchronization call; the write's formal observable event is placed at $succ_S(w)$. Likewise, a signal Read

anchored to $\text{pred_S}(r)$ is not delayed by intervening message operations merely because the read statement appears lexically after them.

Every observable signal Read/Write of a sequential process must have a real bounding synchronization anchor on the dynamic path on which it occurs. A process-start synchronization event START_P may serve as the initial predecessor anchor when the modeling convention explicitly includes START_P in S . A terminating process event FINISH_P may serve as the terminal successor anchor when the process actually terminates and FINISH_P occurs. If no real predecessor anchor exists for a Read, or no real successor anchor exists for a Write on the dynamic path being modeled, the sequential-process signal IO is ill-formed for this formal model or lies outside the finite observable prefix being compared. No observable Read/Write event is assigned clock time ∞ .

R2C (Combinational signal IO at the ϵ -fixed point).

A combinational process P has no process-owned synchronization events and no message-passing events in this formal clause; it may, however, contribute observable signal Read(sig, val) and Write(sig, val) events to Σ through explicitly selected R2C observation components. These events are not anchored by $\text{pred_S}/\text{succ_S}$. In every clock cycle t , the global state first reaches the cycle's ϵ -quiescent combinational fixed point after all sequential clock-boundary updates and all internal combinational propagation for that cycle have settled. Let μ_t denote this unique fixed-point valuation of the signal network.

R2C unit-generation convention

Fix an explicitly modeled combinational process or combinational network component C_comb and its selected observable slice $\text{Obs}(C_comb)$, consisting of the process/signal/direction labels whose fixed-point values are included in that component's R2C observation. The fixed-point valuation μ_t exists every cycle, but a Σ -visible R2C fixed-point signal-observation unit for C_comb is emitted only at canonical observation occurrences:

- (i) the first cycle in the compared execution in which C_comb 's observable slice is defined and observed; and
- (ii) any later cycle in which the vector of fixed-point values on $\text{Obs}(C_comb)$ differs from the vector in the most recent emitted R2C unit for C_comb , or in which an explicitly modeled observer/sampler requires a fresh observation unit.

Cycles in which C_comb 's observable fixed-point slice is identical to the most recent emitted R2C unit, and in which no explicit observer/sampler requires a fresh unit, are R2C stutter cycles for C_comb . They do not emit a new Σ -visible R2C unit. Delta-cycle re-evaluation, intermediate combinational values, redundant re-drive before the fixed point, and such R2C stutter cycles are $\epsilon/\text{stutter}$ for this component and are not separately Σ -visible.

If a combinational process P reads sig in an emitted R2C unit of C_comb , the corresponding label is $\text{Read}(\text{sig}, \mu_t(\text{sig}))$ for the cycle t at which that unit is emitted. If P drives sig in an emitted R2C unit of C_comb , the corresponding label is $\text{Write}(\text{sig}, \mu_t(\text{sig}))$, where $\mu_t(\text{sig})$ is the final resolved fixed-point value of sig at the chosen observation boundary. All Read/Write labels inside one emitted R2C unit are interpreted at the same ϵ -quiescent fixed point and may not be split.

Combinational-process signal IO is well formed only when the relevant combinational network is deterministic and reaches a unique ϵ -fixed point in each cycle being compared, and when each observable R2C component has a well-defined selected observable slice $\text{Obs}(C_comb)$. For a multi-input combinational component whose inputs may be updated by independent latency-insensitive sources, the component is Σ -observable under the stutter-canonicalized R2C rule only if the chosen observation boundary provides a single explicit anchoring domain for the slice, or if an additional component-specific

well-formedness proof shows that all admissible interleavings induce the same emitted R2C unit sequence. Otherwise the component's internal combinational propagation must remain ϵ -hidden, or the design must expose the relevant behavior through explicit synchronization, message passing, a cycle-accurate transactor, or a cycle-locked R2C observation boundary. Pure combinational oscillations, ambiguous multiple-driver resolution, hidden stateful behavior, or intentional combinational-loop behavior outside a unique fixed-point interpretation are outside this R2C model unless represented by explicit state or synchronization elsewhere in the formal model.

R3 (Isolation around S).

Let s be a dynamic synchronization-call instance of process P . Let $\text{pref}_S(s)$ be the set of executed dynamic message-call instances $q \in Q_{\text{exec},P}$ in the immediately preceding source interval of P whose source-induced order places q before or at the boundary controlled by s . Let $\text{suff}_S(s)$ be the set of executed dynamic message-call instances $q \in Q_{\text{exec},P}$ in the immediately following source interval of P whose source-induced order places q after s . Then

$\forall q \in \text{pref}_S(s) : \text{issue_pre}(q) \leq \text{clk_pre}(s) \quad \text{and} \quad \forall q \in \text{suff}_S(s) : \text{issue_pre}(q) > \text{clk_pre}(s).$

(For blocking message requests, if the synchronization call commits in the process trace, then any earlier blocking message requests in that dynamic source interval must have committed in some cycle $\leq$ that sync-commit cycle, by blocking-call control-flow semantics. Failed non-blocking polls in $Q_{\text{exec},P}$ satisfy the same issue-side synchronization-boundary rule, but they contribute no Σ -event and do not become Ω_P frontier items merely because they executed.)

R4 (Safe message issue ordering).

For every pair $q_1, q_2 \in Q_{\text{exec},P}$ within the same process and within the compared dynamic execution / witness,

$q_1 <_{\text{src}} q_2 \Rightarrow \text{issue_pre}(q_1) \leq \text{issue_pre}(q_2).$

(For same-channel operations, this states that dynamic calls on a single interface are issued in source-induced program order. For distinct channels, it forbids issuing dynamic message-call instances in the reverse of their source-induced order. This rule does not impose ordering between syntactic operations on untaken branches or between dynamic instances that are not ordered by the source-induced partial order of the selected witness. Failed non-blocking polls are included in this issue-order universe when they are executed, but remain ϵ -steps with no Σ -event.)

R5 (Channel capacity semantics; Sys vs. Sys_B).

Appendix G defines the raw rendezvous source model Sys , in which every channel has effective capacity 0. Concretely: for every channel c and any clock cycle t , the number of unmatched committed Push_c actions is zero and the number of unmatched committed Pop_c actions is zero; equivalently, no Push_c shall commit unless a matching Pop_c also commits at t , and no Pop_c shall commit unless a matching Push_c also commits at t .

In Appendices I–K we additionally use the back-annotated source interpretation Sys_B : the same source processes as Sys , but interpreted under the case-split channel semantics of E4 with capacities $B(c)$ matching RTL_B . Thus:

- $B(c)=0$ is interpreted as the rendezvous case of E4: matching $\text{Push}_c(v)$ and $\text{Pop}_c(v)$ endpoint events commit in the same cycle, and no unmatched committed endpoint event may remain after any cycle boundary.
- $B(c)>0$ is interpreted as the cycle-boundary, non-fall-through bounded-FIFO case of E4, using the

occupancy predicate $\text{occ}_c(t)$ and the FIFO availability predicates $\text{occ}_c(t) < B(c)$ for Push_c and $\text{occ}_c(t) > 0$ for Pop_c .

The source conceptual semantics for a process is thus a labeled partial order $(\Sigma, \leq_P)$ generated by R1–R4 plus the applicable E4 channel semantics: raw rendezvous for Sys, or the case-split back-annotated channel semantics of Sys_B / Sys_ref.

Trace Compatibility Relation

Let τ_{pre} and τ_{post} be the Σ -traces (finite or infinite) of the same process before and after HLS, where each Σ -event is labeled exactly as in “Common Formal Definitions for Appendices I–K” (e.g., $\text{Push}_c(v)$, $\text{Pop}_c(v)$, $\text{Read}(\text{sig}, \text{val})$, $\text{Write}(\text{sig}, \text{val})$, and synchronization events).

Notation note. We write $\tau_{\text{pre}} \approx \tau_{\text{post}}$ as a named, ordered trace-compatibility predicate. The symbol $\approx$ is local to this document and is not used here to assert a mathematical equivalence relation; in particular, reflexivity, symmetry, and transitivity are not being claimed. Its arguments are ordered: the left trace supplies the pre-HLS/source reference witness, and the right trace supplies the post-HLS implementation trace constrained by E1–E5. In later appendices the same convention applies to $\tau_{\text{ref}} \approx \tau_{\text{post}}$, with τ_{ref} as the prescribed Sys_ref witness.

Convention (S): all references to S , $\text{pred}_S/\text{succ}_S$, $\text{pref}_S/\text{suff}_S$, and $<_{\text{src}}$ in E1–E5 use the dynamic source-induced order defined in R1–R4 for the compared execution / witness. Thus τ_{pre} denotes the Σ -trace of the pre-HLS source over the dynamic operation instances reached under the fixed stimulus / selected witness.

Σ -event matching convention. We use a canonical per-endpoint occurrence matching to make “the same Σ -events” precise. For each channel c , match committed Push_c and Pop_c events by their ordinal occurrence on that channel (e.g., the k -th committed Push on c in τ_{pre} matches the k -th committed Push on c in τ_{post} ; likewise for Pop_c). For each such matched pair, the endpoint (c) and the payload/value label must agree. For the ordinal index k to be well-defined under the per-cycle “set/bucket” trace representation used in these appendices, we assume that for any fixed channel endpoint c , at most one committed Push_c and at most one committed Pop_c may occur in any single clock cycle.

For each observable signal sig of a sequential process, match $\text{Read}(\text{sig}, \cdot)$ and $\text{Write}(\text{sig}, \cdot)$ by their ordinal occurrence on that signal within the process trace, again requiring the value labels to agree.

For sequential processes, we apply the following canonicalization for observable signals: within each anchor interval between consecutive synchronization events in the order S , we record at most one Σ -visible $\text{Read}(\text{sig}, \text{val})$ and at most one Σ -visible $\text{Write}(\text{sig}, \text{val})$ for each (process, sig), with the anchor cycle given by E2. Any additional physical sampling of sig by the implementation, or redundant re-driving of sig within the same anchor interval, is treated as an internal ϵ -step and must not change the recorded value label. If a design intentionally relies on intra-interval changes of sig , or on distinguishing multiple reads/writes of sig within the same anchor interval, then sig must be modeled using an explicit synchronized interface rather than as an ordinary sequential-process observable signal.

For combinational processes, the canonical observable unit is the emitted R2C fixed-point

signal-observation unit for the relevant combinational process/network component C_comb : the set of $Read(sig, val)$ and $Write(sig, val)$ labels for the selected observable slice $Obs(C_comb)$, recorded at one ϵ -quiescent combinational fixed point under the R2C unit-generation convention. Intermediate delta-cycle reads/writes, repeated re-evaluations before the fixed point, and stutter cycles in which $Obs(C_comb)$ is unchanged and no explicit observer/sampler requires a fresh unit are $\epsilon/stutter$ and are not separately Σ -visible.

R2C unit matching/index convention

For each combinational process or explicitly modeled combinational network component C_comb , project each trace to the subsequence of emitted R2C fixed-point signal-observation units for C_comb . The k -th emitted such unit in Sys_ref is matched with the k -th emitted such unit in RTL_B . This local emitted-occurrence ordinal, together with the component identity C_comb , is the correspondence rule for R2C fixed-point units; it is not the global observable-cycle bucket number of the whole-system trace. Thus repeated identical fixed-point observations across stutter cycles do not create additional units, while repeated equal-valued units created by explicit observer/sampler occurrences are distinguished by their local emitted-occurrence ordinal for C_comb .

Matched pre-HLS and post-HLS fixed-point units must agree on the included process/signal/direction labels and fixed-point values. The same-cycle agreement required here is local to the matched emitted R2C fixed-point unit: all $Read/Write$ labels inside that unit are interpreted at one ϵ -quiescent fixed point and may not be split. This local atomicity requirement is one of the explicit same-cycle semantic constraints and does not require unrelated Sys_ref and RTL_B events to share the same global bucket decomposition. If a design requires every cycle's combinational fixed point to be externally observable even when the fixed-point slice is unchanged, then that component must be declared cycle-locked; a cycle-locked R2C component is matched by its per-cycle emitted occurrences and therefore falls outside the bucket-stutter freedom claimed for ordinary latency-insensitive R2C components.

For synchronization events, match by their per-process occurrence index in the source order (R1; preserved on the post-HLS side by E1 below). Independent Σ -events on different endpoints (including distinct message-passing interfaces) may commute and/or be grouped differently within a clock cycle as permitted by the R-rules and E3. Here “independent” is meant in the Σ -equivalence sense: the pair is not additionally ordered by any explicit Σ -visible ordering/timestamp constraint in E1–E5 (notably E3/E5); it is not a statement about (in)comparability under the Appendix G causal-dependency relation ($\rightarrow$). Accordingly, τ_pre and τ_post are not required to be identical as a single total order, nor to agree on same-cycle “grouping” of distinct-interface Push/Pop operations, beyond the explicit ordering/timestamp constraints in E1–E5 below.

We say $\tau_pre \approx \tau_post$ iff the two traces match on Σ in this sense, and all the following hold:

E1 (Per-process synchronization-order preservation).

For every process P ,

$$\forall s_1, s_2 \in S_P : s_1 <_P s_2 \Rightarrow clk_post(s_1) < clk_post(s_2).$$

Equivalently, synchronization events are matched and ordered by their per-process source occurrence index. E1 does not preserve incidental global clock ordering between synchronization events of different processes unless that ordering is induced by an explicit inter-process synchronization relation already represented in Σ .

E2 (Signal-visibility preservation).

Partition signal Read/Write events by process kind:

- R_seq and W_seq are the ordinary signal Read/Write events of sequential processes.
- R_comb and W_comb are the signal Read/Write events of combinational processes, interpreted by R2C.

For sequential-process signal IO:

$\forall r \in R_seq : clk_post(r) = clk_post(pred_S(r))$

$\forall w \in W_seq : clk_post(w) = clk_post(succ_S(w))$

Equivalently, ordinary signal Reads/Writes of sequential processes are logically timestamped at their synchronization anchors, as in R2. The same anchoring convention is used on the pre-HLS side when forming the matched trace.

For combinational-process signal IO, $pred_S/succ_S$ anchoring does not apply. Instead, each R2C fixed-point signal-observation unit is matched by the component-local occurrence ordinal defined above: for each combinational process or explicitly modeled combinational network component C_comb , the k -th R2C fixed-point unit of C_comb in Sys_ref matches the k -th R2C fixed-point unit of C_comb in RTL_B . The matched units must contain the same corresponding combinational Read/Write events and fixed-point values at their respective ϵ -quiescent combinational fixed points, as defined by R2C. Any delta-cycle re-evaluation, intermediate combinational value, or redundant re-drive before the fixed point is an ϵ -step and is not separately Σ -visible. This condition does not require the matched R2C units to occur in the same global observable-cycle bucket number, nor to be grouped with the same unrelated events, in the two executions.

E3 (Safe message issue ordering). (Post-HLS preservation of R4).

For every pair of executed message-call instances $q1, q2 \in Q_exec, P$ of the same process P :

(i) Same-interface source order: if $q1$ and $q2$ access the same message-passing interface and $q1 <_{src} q2$, then $issue_post(q1) \leq issue_post(q2)$. This preserves source order at cycle granularity; any stricter serialization required by the concrete interface is supplied by the channel/interface semantics, not by E3 itself.

(ii) Distinct-interface no-reverse: if $q1$ and $q2$ access distinct message-passing interfaces and appear in sequence in the source ($q1 <_{src} q2$), then $issue_post(q1) \leq issue_post(q2)$ (i.e., they shall not be issued in the reverse sequence).

(Note: any pipelined-loop internal staging/dequeue discussed in “Pipelined Loops” is ϵ -microstate within the back-annotated channel realization and is not a Σ -visible boundary issue event in Q_exec, P nor a committed-transfer event in M ; therefore it does not constitute a counterexample to (ii).)

E4 (Per-channel channel semantics: rendezvous and bounded FIFO).

For every observable channel c with capacity $B(c)$, the projection of τ_post to events on c is legal for that channel’s capacity model. The channel model splits into two cases.

- Rendezvous case, $B(c)=0$. Channel c is a capacity-zero rendezvous channel. A committed transfer on c consists of a matching same-cycle pair $Push_c(v)$ and $Pop_c(v)$ with the same payload value v . No unmatched committed $Push_c$ or Pop_c may exist after any cycle boundary. Equivalently, the k -th committed $Push_c(v)$ and the k -th committed $Pop_c(v)$ occur in the same clock cycle and carry the same value. A $Push_c$ endpoint can commit in cycle t only when the matching Pop_c endpoint boundary request is also asserted in cycle t , and symmetrically a Pop_c endpoint can commit in cycle t only when

the matching Push_c endpoint boundary request is also asserted in cycle t.

- Buffered case, $B(c) > 0$. Channel c is a bounded FIFO with cycle-boundary, non-fall-through semantics. The committed Pop_c(v) events return exactly the FIFO-ordered sequence of values v previously committed by Push_c(v), with no drops, duplications, or reordering. For every cycle-aligned prefix π_t of the c-projection—i.e., π_t contains exactly the events on c committed in cycles $< t$ —letting $\text{push}(\pi_t)$ and $\text{pop}(\pi_t)$ be the number of Push_c and Pop_c events in π_t , we have

$$0 \leq \text{push}(\pi_t) - \text{pop}(\pi_t) \leq B(c).$$

Equivalently, the abstract occupancy after cycle $t-1$ is $\text{occ}_c(t) = \text{push}(\pi_t) - \text{pop}(\pi_t)$. Availability for commits in cycle t is evaluated against $\text{occ}_c(t)$ at the start of cycle t: Pop_c may commit in cycle t only if $\text{occ}_c(t) > 0$, Push_c may commit in cycle t only if $\text{occ}_c(t) < B(c)$, and simultaneous Push_c and Pop_c commits in the same cycle are permitted iff $0 < \text{occ}_c(t) < B(c)$.

Thus the inequality-based FIFO availability predicates are used only for $B(c) > 0$. The $B(c) = 0$ case is not interpreted by substituting $B(c) = 0$ into the bounded-FIFO inequalities; it is interpreted by the rendezvous rule above.

Note: $\text{occ}_c(t)$ is the logical occupancy of channel c at the chosen Σ boundary, induced solely by the Σ -visible boundary-commit history (Push_c/Pop_c) and the annotated capacity $B(c)$ in the buffered case $B(c) > 0$. For $B(c) = 0$, the corresponding channel fact is the same-cycle rendezvous request/commit predicate rather than a nonzero FIFO occupancy predicate.

E5 (Messages cannot cross their immediate synchronization boundary).

For every synchronization call s (in the source order used by R3 / pref_S / suff_S over Q_{exec}, P):

$\forall q \in \text{pref}_S(s) : \text{issue_post}(q) \leq \text{clk_post}(s)$

$\forall q \in \text{suff}_S(s) : \text{issue_post}(q) > \text{clk_post}(s)$

(For blocking message requests, if the synchronization call commits in the process trace, then any earlier blocking message requests in that source interval must have committed in some cycle $\leq$ that sync-commit cycle, by blocking-call control-flow semantics. Under the Issue/Commit linkage above, any boundary request assertion that persists while the process is still pending at s reflects only already-issued outstanding operation(s) in $\text{pref}_S(s)$; no operation $q \in \text{suff}_S(s)$ may have $\text{Issue}(q) \leq \text{clk_post}(s)$, and any back-to-back issuance on that endpoint direction may occur only in the first cycle strictly after $\text{clk_post}(s)$. For non-blocking calls, a later executed source-level PushNB/PopNB in $\text{suff}_S(s)$ is a distinct q and cannot be identified with an earlier $\text{pref}_S(s)$ call solely because the endpoint request signal remained asserted.)

See *Appendix I – Per Process Trace Compatibility Proof* for formal proof of the following one-way witness statement:

For any single source-level process P that obeys the conceptual R rules and B rules, when interpreted as part of the prescribed source reference model Sys_ref (see Appendix J, Remark 2), every finite observable trace/prefix of the post-HLS RTL_B process has a matching source-level trace/prefix in Sys_ref that satisfies E1–E5 (Post $\rightarrow$ Ref). Appendix I does not claim the unrestricted converse for all source-side traces. When a reverse correspondence is needed, it is restricted to RTL-consistent source-side prefixes as stated later in Appendix J / Theorem J.1. The raw rendezvous case is recovered when $\text{Sys_ref} = \text{Sys_B}$ and all effective capacities are zero.

Allowed Transformations and Why They Preserve $\approx$

Transformation permitted by the rules	Formal justification
Loop pipelining (overlaps iterations)	Introduces internal pipeline stages (modeled as ϵ -steps) and overlaps iterations. R1–R5 (and hence E1–E5) are applied to the explicit S set. Loop pipelining may commute independent Σ -actions across iterations (e.g., across distinct channels)—where “independent” here means “not additionally ordered by any explicit Σ -visible constraint in E1–E5 between the pair (notably E3/E5),” rather than “incomparable under Appendix G’s causal-dependency relation ($\rightarrow$)”—but it must still preserve: (i) per-channel FIFO legality (E4), (ii) the required issue discipline (E3) for source-ordered pairs, and (iii) the sync-boundary constraints (E1/E5) with respect to the (explicit + implicit) S-actions.
Overlap of internal dequeue/staging vs. later pipeline work (ϵ)	Permitted because the internal staging/acceptance activity is ϵ -internal within the back-annotated channel realization (as defined in “Appendix B - Pipelined Loops”) and does not constitute a Σ -visible boundary message-issue reorder. Σ -visible boundary message issues must still satisfy E3, and per-channel committed-transfer legality is ensured by E4; automatic flush / Appendix K addresses deadlock preservation for overlap timing.
#pragma hls_direct_input (late sampling of static signals)	This pragma imposes a designer/environment stability contract: the signal’s value must remain stable after reset (or after its last permitted update) while the receiving process may consume it. The logical signal Read actions r remain anchored exactly as in E2 ($\text{clk_post}(r) = \text{clk_post}(\text{pred_S}(r))$). HLS may implement this by sampling the signal later (instead of inserting internal storage), but because the signal is stable the sampled value equals the value at $\text{pred_S}(r)$; therefore E2 and $\approx$ are preserved.
#pragma hls_direct_input_sync (controlled updates)	This pragma imposes an explicit timing contract on the environment: the controlled direct-input signals may change only on the cycle of the designated synchronization call s^* (i.e., during the sync handshake). With that contract, the logical anchoring required by E2 is preserved: for the receiving process, the relevant Reads are anchored at the closest preceding synchronization call $\text{pred_S}(r) = s^*$, and any environment update Write w_update is aligned with synchronization ($\text{succ_S}(w_update) = s^*$). HLS may still implement late sampling internally, but the value observed is the same as the value at the E2 anchor point, so $\approx$ is preserved without modifying E2.

Transformation permitted by the rules	Formal justification
	Instrumentation note (logical signal timestamping). In the Σ-traces used for $\approx$ checking, sequential-process signal Read/Write events are timestamped at their E2 anchor points (e.g., $\text{clk_post}(\text{pred_S}(r))$ for Reads), not at any later physical RTL sample cycle that HLS may introduce. Any internal late-sampling micro-steps are treated as ϵ-steps. Combinational-process signal Read/Write labels are handled by R2C rather than by $\text{pred_S}/\text{succ_S}$ anchoring or by global observable-cycle bucket number. A monitor records a combinational fixed-point value only after the simulator/RTL has reached an ϵ-quiescent combinational fixed point, and that value contributes to Σ only when the relevant R2C observation component emits an R2C fixed-point signal-observation unit under the R2C unit-generation convention. Intermediate delta-cycle reads/writes, redundant re-evaluations, transient combinational values before the fixed point, and R2C stutter cycles whose selected observable slice is unchanged are $\epsilon/\text{stutter}$ and are not separately Σ-visible. Therefore, equivalence checking must instrument/record the appropriate logical Read/Write event: the anchored event for sequential-process signal IO, or the emitted R2C fixed-point signal-observation unit for combinational-process signal IO. A wrapper/transactor may be used when needed to expose only those logical events rather than naive physical sample, delta-cycle, or per-cycle stutter events.
Memory-access reordering proven conflict-free	Let $\text{addr}(a)$ be the symbolic address of access a. If the tool proves $\text{addr}(a_1) \neq \text{addr}(a_2)$ for the overlapped window, then the commutation of a_1 and a_2 is observationally silent; no external signal/message depends on the internal order.
Implicit FSM states / added latency	Extra states introduce <i>silent</i> ϵ-steps between observable actions; the partial order on Σ is unchanged, so E1–E5 are unaffected.
Shared-memory arrays with explicit synchronization	When a memory is accessed by multiple processes, the designer explicitly coordinates access with synchronization operations modeled as S-actions, and the externally relevant memory behavior is defined by the array access mapping layer. E1 preserves the order of the synchronization actions that bracket or authorize the shared-memory accesses. The array access mapping layer then defines the mapped memory operations, their commit cycles, and the required serialization/coherence rule for the shared storage, and the pre-HLS and post-HLS traces must agree under that declared memory semantics. E2 is not used here except for ordinary signal IO. E4 is relevant only if the mapping layer represents memory commands/responses as message-passing channels;

Transformation permitted by the rules	Formal justification
	otherwise memory legality is discharged by the mapping layer's memory semantics, not by FIFO channel semantics. Under these conditions, the shared-memory transformation preserves the observable behavior required by $\approx$.
Non-blocking message-passing (PushNB/PopNB) verified by post-HLS snooping	If the latency differences are externally visible to the DUT, a verification wrapper delays the pre-HLS side so that the committed transfer events (successful completions) occur in the same order/timing as observed on the post-HLS channel. This wrapper is itself purely synchronising (S), so it cannot violate R1–R5. Once the wrapper is assumed, τ_{pre} and τ_{post} coincide on the committed message-transfer history recorded in Σ (i.e., the Push_c/Pop_c commit events), so E3–E5 are preserved. Unsuccessful non-blocking polls remain ϵ -steps and are not required to match. This is not a transformation that inherently preserves $\approx$, but rather a verification technique to enforce equivalence for inherently latency-sensitive operations.
Latency-sensitive <i>global</i> signal IO matched by snooping	If the latency differences are externally visible to the DUT, the same “mirror-and-delay” wrapper used for NB channels is applied to any globally-visible signal whose timing matters. Because the wrapper inserts only S-actions, the partial-order constraints are unchanged. This is not a transformation that inherently preserves $\approx$, but rather a verification technique to enforce equivalence for inherently latency-sensitive operations.
Latency-sensitive <i>local</i> signal IO isolated in cycle-accurate transactors	Local timing-exact protocols are confined to dedicated transactor processes that expose only latency-insensitive M or S operations to the rest of the design. Since the transactor boundary is now the observable interface, R1–R5 apply <i>outside</i> the timing-sensitive region, so system-level $\approx$ still holds.
One-way signal-handshake protocols with run-time assertions	For single-direction vld or rdy signals, an assertion proves that back-pressure can <i>never</i> occur. That assertion establishes a refinement in which the missing handshake is equivalent to a permanent logical '1', so the protocol is observationally identical to a two-way handshake that trivially satisfies E2.
Combinational processes	Combinational processes have no process-owned S actions and no message-passing M actions in this formal clause, but they may have observable signal Read/Write events in Σ through explicitly selected R2C observation components. Their signal IO is interpreted at ϵ -quiescent combinational fixed points as specified by R2C: intermediate delta-cycle propagation is ϵ , and only emitted fixed-point Read/Write

Transformation permitted by the rules	Formal justification
	labels in the selected observable slice are Σ-visible. Repeated cycles in which the selected fixed-point slice is unchanged are R2C stutter for that component unless an explicitly modeled observer/sampler requires a fresh emitted unit. Under the well-formedness requirement that the combinational network is deterministic, reaches a unique fixed point in each compared cycle, and has a well-defined R2C unit-generation rule for the selected component, the RTL/tool-flow conformance obligation is to preserve the emitted fixed-point signal-observation unit sequence at the chosen observation boundary. Thus the required correspondence is not equality of simulator delta-cycle behavior, nor equality of global cycle-bucket numbers, nor an automatic consequence of ordinary combinational synthesis; it is equality of matched emitted R2C fixed-point units by component identity and local emitted-occurrence ordinal. Designs with oscillation, ambiguous multiple-driver resolution, hidden stateful behavior, intentional combinational-loop behavior outside a unique fixed-point interpretation, or multi-input observation slices whose interleavings can change the emitted unit sequence are outside R2C unless represented by explicit state, synchronization, a cycle-accurate transactor, a cycle-locked R2C observation boundary, or another formally modeled boundary.

For the purposes of the formal analysis, non-blocking message-passing is modeled at the level of committed transfers: a successful PushNB/PopNB contributes the same committed Push_c/Pop_c event to Σ as a blocking Push/Pop, while unsuccessful polls are ϵ -steps.

If a design contains latency-sensitive global signals or non-blocking transfers whose timing/ordering is externally visible at the DUT boundary and must be reproduced exactly in both simulations, we take as an axiom that a purely synchronizing snooping wrapper can be applied to supply the same latency choices to the pre-HLS simulation as those observed in the post-HLS RTL (Appendix L). Conceptually, this wrapper is a witness-selection device: it does not enlarge the set of admissible pre-HLS behaviors, but restricts the pre-HLS run to one admissible execution whose Σ -events align with the observed RTL execution. Under this wrapper, the committed Σ -traces of the two simulations agree, and the trace-compatibility rules E1–E5 apply to the wrapped runs.

Appendix L provides detailed guidance to enable this perfect alignment to be achieved in practice.

Proof Structure

The proofs proceed in three stages:

First, in Appendix I we establish the per-process witness correspondence needed by the later system-level proof: under the imported local execution/progress side conditions, every post-HLS RTL_B process trace (equivalently, every reachable finite observable prefix) has a matching source-level trace in the prescribed source reference model Sys_ref (Post $\rightarrow$ Ref), satisfying E1–E5. Here Sys_ref is the source-side proof target defined later in Appendix J, Remark 2: in the ordinary bounded-FIFO case, Sys_ref = Sys_B; in the elaborated back-annotated cases, Sys_ref = Sys_B^{elab}. The converse direction (Ref $\rightarrow$ Post) is not claimed for all Sys_ref traces in general; when it is needed, it is restricted to RTL-consistent prefixes or to source executions selected by Appendix L’s snooping / witness-selection mechanism. The side conditions used at this stage include the relevant weak-fairness, finite-pipeline-depth, local progress/channel-usage, and realization-correctness obligations needed to make the finite-prefix witness construction meaningful. They are not a claim that the entire system is deadlock-free, and they are not the liveness-preservation conclusion of Appendix K.

Second, in Appendix J we compose these per-process results into a system-level observable trace-compatibility theorem. This stage relies on channel-ordering, occupancy, cutpoint-abstraction, and required-order lemmas, but it remains a trace-compatibility argument. It does not assume or prove global source liveness, and it does not by itself prove that RTL_B is free of internal message-passing deadlock.

Finally, Appendix K addresses a separate liveness-preservation obligation for internal message-passing deadlock. Appendix K does not discharge the Appendix I/J weak-fairness, finite-depth, channel-progress, realization-correctness, K ϵ , J.AbsConf, or A6–A11 side conditions; those remain standing assumptions or tool/source/environment obligations, summarized in Appendix N. Nor does Appendix K derive the source-level liveness premise from the local R-rules. Instead, Appendix K proves a conditional preservation/contradiction result: if the prescribed Sys_ref is internally message-passing-deadlock-free under A5’s conservative serial-blocking source semantics, if the compared RTL_B execution satisfies the imported progress, fairness, structural, abstraction, and realization assumptions, and if the serial-source dominance lemma applies, then any RTL_B-internal message-passing deadlock matched by the witness construction would imply a corresponding serial-blocking Sys_ref deadlock, contradicting A5. In the ordinary case Sys_ref = Sys_B; in the elaborated back-annotated cases Sys_ref = Sys_B^{elab}. When Sys_ref = Sys_B and B(c)=0 for all channels, this specializes to the raw rendezvous model.

Thus the architecture is non-circular for a different reason than “discharging” the earlier side conditions: Appendices I and J use local execution/progress side conditions to establish conditional trace compatibility, while Appendix K separately preserves internal message-passing deadlock freedom under A5 and the standing Appendix N assumptions. The liveness-preservation theorem is therefore conditional on those assumptions; it is not a derivation of them.

Causal Dependency Between Processes

To prove system-level trace compatibility, we must distinguish between incidental timing and functionally significant ordering.

Formal Definition of Causal Dependency

To formalize the notion of functionally significant dependency and resolve ambiguity, we define a causal-dependency relation, denoted by $\rightarrow$, on the set of observable IO actions (Σ) across all processes in the system. The relation is causal/information-flow rather than purely temporal: events related by $\rightarrow$

may commit in the same clock cycle, and the direction of $\rightarrow$ indicates which event may be depended on by the other.

Important: $\rightarrow$ is a causal-dependency graph, not by itself the strict partial order used for the Appendix J induction. In particular, because the methodology permits distinct-interface message operations to be issued in source order or in parallel, and because rendezvous transfers are same-cycle atomic Push/Pop transactions, the unquotiented dependency graph $\rightarrow$ need not be acyclic in every legal execution. A cycle in $\rightarrow$ can represent a legal same-cycle mutually enabling dependency among atomic transactions; it is not, by itself, an observable mismatch.

When Appendix J needs a well-founded induction order, it uses the separate required-order relation $<_J$ over observable units. That relation is generated only by the explicit ordering, timestamp, FIFO, atomicity, and synchronization constraints that must be preserved by the trace-compatibility predicate, not by the full causal-dependency graph $\rightarrow$ and not by raw per-process source order on distinct-interface message commits.

Well-formedness use of causal-dependency. The well-formedness rule below uses $\rightarrow$ as a design-intent and source-admissibility relation: if correctness depends on the relative timing, value, availability, or cross-process observation of two events, that dependence must be represented by an explicit modeled causal mechanism such as message passing, synchronization, signal handshakes/anchors, declared memory serialization, or an Appendix L snooped/witness-selected boundary. This use of $\rightarrow$ does not add proof-preserved observable ordering beyond $<_J$, FIFO legality, rendezvous/synchronization atomicity, signal-anchor constraints, synchronization-boundary constraints, and declared memory-serialization constraints.

The causal-dependency relation $\rightarrow$ is the smallest directed relation satisfying the conditions below:

1. **Intra-Process Order:** If actions a and b occur within the same process P and a precedes b in the program's execution trace, then $a \rightarrow b$. This directly reflects the sequential nature of the code within a single thread. **Clarification (non-temporal).** Here “precedes” refers to the order of IO action *instances* in the process's trace/program order (i.e., the order induced by the process's execution), **not** the relative order of their **commit cycles**; distinct-interface message actions may be **issued** in order while **committing** in either order depending on backpressure.
2. **Inter-Process Communication:** The relation is established by the direct exchange of information or synchronization between processes.
 - **Message-passing (committed transfer):** If a is the commit of a send on channel c in process P_1 (a committed Push _{c} , including a successful PushNB), and b is the commit of the corresponding receive on c in process P_2 (a committed Pop _{c} , including a successful PopNB), for the same logical message instance, then $a \rightarrow b$. Here “corresponding receive” is defined by the channel's FIFO semantics: b is the Pop _{c} commit that consumes the element produced by a (matching is by FIFO position / transfer instance, not by payload-value equality; duplicate payload values do not introduce ambiguity). Equivalently, if we enumerate committed Pushes on c as Push _{c} ¹, Push _{c} ², ... in commit order and committed Pops as Pop _{c} ¹, Pop _{c} ², ... in commit order, then Push _{c} ^{k} $\rightarrow$ Pop _{c} ^{k} . For buffered channels with $B(c) > 0$, E4 also imposes the required FIFO legality used by Appendix J's required-order relation $<_J$. For rendezvous channels with $B(c) = 0$, the matching Push _{c} and Pop _{c} commits occur in the same clock cycle and are treated in Appendix J as one explicitly atomic observable unit. The directed

dependency $a \rightarrow b$ records unidirectional information flow — the Pop observes the value supplied by the Push — but it does not make the two rendezvous endpoints separately orderable for the Appendix J induction, and it does not imply an earlier commit cycle. No reverse edge $b \rightarrow a$ is implied unless there is an explicit reverse-direction communication, such as another channel or a signal handshake. Unsuccessful non-blocking polls are ϵ -steps and do not participate in $\rightarrow$.

- **Signal Handshake:** If a is a signal write action $w(\text{sig})$ in $P1$ and b is a signal read action $r(\text{sig})$ in $P2$ that reads the value written by a as part of an explicit handshake protocol, then $a \rightarrow b$. A complete two-way handshake (e.g., vld/rdy) creates a causal chain, such as $w(\text{vld})@P1 \rightarrow r(\text{vld})@P2 \rightarrow w(\text{rdy})@P2 \rightarrow r(\text{rdy})@P1$.
- **Explicit Synchronization (two-party SyncChannel / ac_sync):** Let sout be the commit of a SyncChannel sync_out (or equivalent ac_sync call) in process $P1$, and let sin be the commit of the matching sync_in in process $P2$ for the same synchronization instance. Then this synchronization acts as a two-process barrier:
 - Every observable action in $P1$ that occurs before sout (in $P1$'s trace/program order) satisfies $a \rightarrow b$ for every observable action b in $P2$ that occurs after sin .
 - Symmetrically, every observable action in $P2$ that occurs before sin satisfies $a \rightarrow b$ for every observable action b in $P1$ that occurs after sout .
 - (The two sync commits sout and sin are treated as simultaneous; we do not impose $\text{sout} \rightarrow \text{sin}$ or $\text{sin} \rightarrow \text{sout}$.)

3. **Transitivity:** The relation is transitive. If $a \rightarrow b$ and $b \rightarrow c$, then $a \rightarrow c$.

Using this relation, we now provide a formal definition for causal dependency between synchronization events, which are the fundamental ordering anchors in the scheduling model.

Definition: Causal Dependency

A synchronization event $s2$ in process $P2$ is **causally dependent** on a synchronization event $s1$ in process $P1$ if and only if $s1 \rightarrow s2$.

If neither $s1 \rightarrow s2$ nor $s2 \rightarrow s1$ holds true, the events $s1$ and $s2$ are considered **causally independent** (or concurrent). Any change in the observed temporal ordering of causally independent events between the pre-HLS and post-HLS simulations is considered an incidental, functionally insignificant variation in latency. A **well-formed design**, under this methodology, **shall not rely** on a specific ordering of causally independent events for functional correctness.

To be clear, the shall-not-rely requirement is a design rule. To adhere to this design rule, designs must express functionally significant cross-process dependencies through explicit modeled mechanisms such as message passing, SyncChannel/ac_sync operations, signal handshakes/anchors, declared memory-serialization constraints in the array-access mapping layer, or Appendix L snooping/witness-selection boundaries. Designs that violate this design rule are outside the formal guarantees. This rule concerns design well-formedness; it does not convert every causal-dependency edge into a strict proof-order edge.

System-Level Theorem (B1-Specialized Appendix G Statement)

Appendix G gives the high-level system theorem in the same standing-assumption regime used by Appendices J–K: B1 is assumed for RTL_B under the fixed stimulus, so the practical “unique RTL_B trace” reading is available throughout the main theorem stack. The authoritative execution-set theorem, including the exact execution-set quantification and the conditional use of B4/B5 when ϵ -normalization or uniqueness up to finite ϵ -stutter is invoked, is Theorem J.1. Therefore, if this Appendix G statement and Theorem J.1 are read together, Theorem J.1 controls; Appendix G is the high-level summary of the same B1-standing theorem regime.

Fix an initial state and a fixed external stimulus/environment behavior for both the prescribed source reference model Sys_ref and RTL_B , with Sys_ref as defined in Appendix J, Remark 2. (The raw rendezvous model Sys is the special case obtained when $\text{Sys_ref} = \text{Sys_B}$ and all effective capacities are zero.)

Interpret “fixed stimulus” per Appendix I.2, “Fixed-stimulus interpretation (reactive environments).” Let Exec_post denote the set of finite execution prefixes of RTL_B that are reachable under this stimulus and that are prefixes of at least one infinite execution under the same stimulus satisfying the stated fairness/progress premises; let Exec_ref denote the corresponding set of finite execution prefixes of Sys_ref .

Assume the Appendix I / Appendix L witness machinery is available as follows—namely: the per-process $\text{Post} \rightarrow \text{Ref}$ witness construction from Appendix I, including the witness-compatibility premise WC for ϵ -modeled non-blocking polls (and any other ϵ -only internal choices that can affect the next Σ -visible control flow/frontier) as stated in Appendix I.2 and enforceable via Appendix L’s snooping / witness-selection technique; with NB-CF as a sufficient condition that makes the witness trivial—together with the capacities/occupancies/enablement semantics of Sys_ref , finite capacities on every explicit abstract channel of Sys_ref , channel progress invariants $\text{P_push} / \text{P_pop}$ (B3), weak fairness (B2), and the standing RTL_B determinism assumption B1 under the fixed stimulus. Use B4/B5 additionally when ϵ -normalization or uniqueness up to finite ϵ -stutter is invoked.

Then the B1-specialized system-level result is:

($\text{Post} \rightarrow \text{Ref}$ existence) For every $\tau_{\text{post}} \in \text{Exec_post}$, there exists $\tau_{\text{ref}} \in \text{Exec_ref}$ such that $\tau_{\text{ref},\text{system}} \approx \tau_{\text{post},\text{system}}$ under E1–E5.

($\text{Ref} \rightarrow \text{Post}$ existence, RTL -consistent prefixes only) For every $\tau_{\text{ref}} \in \text{Exec_ref}$ whose Σ -projection matches a prefix of the unique RTL_B Σ -trace under the same fixed stimulus, there exists $\tau_{\text{post}} \in \text{Exec_post}$ such that $\tau_{\text{ref},\text{system}} \approx \tau_{\text{post},\text{system}}$.

Moreover, because B1 holds in this Appendix G specialization, the matching Σ -label sequence is unique (up to insertion/removal of finite ϵ -steps permitted by B4/B5), although the corresponding source-side witness prefix/state in Sys_ref need not be unique as a full micro-state.

Proof sketch. Appendix J first proves a pairwise composition lemma: any chosen compatible pair of system traces whose per-process projections satisfy $\approx$ lifts to system-level $\approx$. Appendix J then instantiates that lemma at the execution-set level using Appendix I’s witness construction together with

the Exec_post / Exec_ref scope conditions. Thus the main result is explicitly about sets of executions under fixed stimulus, not merely about a single pre-chosen trace pair. The Ref $\rightarrow$ Post direction is not a symmetric arbitrary-source construction; it applies only to RTL-consistent source prefixes, and under this Appendix G specialization B1 supplies the unique RTL_B Σ -trace against which that consistency is judged.

Practical Implication (“No Surprises” Guarantee)

If a verification environment exercises only the alphabet Σ (signals, message ports, synchronization calls) and does not test internal latency, then—under the assumptions of Theorem J.1 in Appendix J (fixed stimulus, the stated fairness/progress premises, and the Appendix I / Appendix L witness conditions where needed)—the prescribed source reference model Sys_ref and the post-HLS RTL agree at the chosen observable boundary in the following qualified execution-level sense:

- for every $\tau_{\text{post}} \in \text{Exec_post}$, there exists a matching $\tau_{\text{ref}} \in \text{Exec_ref}$; and
- in the reverse direction, only those source-side $\tau_{\text{ref}} \in \text{Exec_ref}$ that are RTL-consistent (i.e. whose Σ -projection matches a prefix/execution admitted by the unique RTL_B Σ -trace under the same fixed stimulus, using the standing B1 assumption for RTL_B) are guaranteed to have a matching $\tau_{\text{post}} \in \text{Exec_post}$.

Latency-sensitive testbench caveat

A testbench that branches on raw cycle counts, uses timeout watchdogs, checks performance/latency bounds, or otherwise changes its stimulus or pass/fail behavior based on timing not represented in Σ is not covered by the same-stimulus trace-compatibility guarantee unless that timing dependence is itself modeled through explicit Σ -visible causal mechanisms such as synchronization events, handshakes, or message-passing transactions. Such checks may still be useful, but they should be treated as latency-sensitive testbench logic, isolated as described in Appendix D, or performed as post-HLS / RTL-level performance checks rather than as properties transferred automatically from an arbitrary pre-HLS simulation run.

Accordingly, the precise “no surprises” reading is one-sided for arbitrary RTL behavior and restricted on the source side: no Σ -observable behavior can appear in RTL_B under the fixed stimulus without a matching behavior in Sys_ref; but a source-side pass claim transfers to RTL_B only for the RTL-consistent subset of source-side behaviors covered by Theorem J.1 (or after the Appendix L snooping / witness-selection restriction has been applied where needed).

Thus, for a Σ -only testbench under the same fixed stimulus, any mismatch found on RTL_B corresponds to a matching mismatch on Sys_ref; however, a source-side pass justifies RTL_B only through the theorem’s restricted reverse direction. Here Sys_ref means Sys_B in the ordinary bounded-FIFO case and Sys_B^{elab} in the elaborated back-annotated cases of Appendix B / Appendix Q. See Appendix J / Theorem J.1 for the full execution-level statement.

Appendix G states the trace-compatibility rules and a B1-specialized high-level implication. Appendix I provides the per-process Post $\rightarrow$ Ref witness construction, and Appendix J makes the main system theorem explicit at the execution-set level for the prescribed source reference model. Taken together, these appendices establish the stated witness-based execution-level correspondence at the chosen observable interfaces under fixed stimulus, the stated fairness/progress premises, and the Appendix I / Appendix L witness conditions where needed. In particular, the unrestricted guarantee is Post $\rightarrow$ Ref; the reverse direction ranges only over RTL-consistent source-side behaviors covered by Theorem J.1.

Appendix H – Possible Criticisms

This section highlights several potential challenges in the verification approach of Appendix G.

1. Designer-Managed Shared-Memory Synchronization

Appendix G requires that any memory shared between processes use explicit synchronization primitives inserted by the designer. The HLS tool does not perform static verification of those primitives. In practice, we mitigate this risk by encapsulating shared memories within parameterized library classes (for example, see examples 12_ping_pong_mem and 15_native_ram_fifo) that are pre-verified for correct memory access coordination in both the pre-HLS and post-HLS models. Typically such classes will be parameterized for aspects such as element type and memory size.

2. Latency-Sensitive Signal Alignment (“Snooping”)

See Appendix L for detailed discussion on snooping.

3. By Default, Matchlib Connections Model a Skidbuffer inside In<> Ports

(Note that this overall document and specifically Appendix G are not intended to be strictly tied to Matchlib. Instead, this document is intended to be applicable to any pre-HLS model written in SystemC using signals, message-passing channels, and synchronization calls.)

Matchlib Connections supports throughput accurate modeling in the pre-HLS simulation. Currently the throughput accurate modeling mechanism relies on the Pre() and the Post() methods using a 1-place buffer to store transactions that are in flight on Connections::In<> ports. This means that by default In<> ports function like a skidbuffer. Connections::Out<> ports do not introduce any additional storage capacity into the pre-HLS simulation.

By default, Catapult adds skidbuffers on input ports into the post-HLS design, so the formal trace-compatibility relationship described in this document still holds. In other words, the default pre-HLS and post-HLS designs both still model rendezvous semantics, since both explicitly include a structural instantiation of a skidbuffer on input ports. In effect, we define the rendezvous boundary *before* the skidbuffer.

It is possible to remove some or all the skidbuffers during Catapult HLS. Because the abstract rendezvous boundary is defined before the skidbuffer, this choice is orthogonal to the trace-compatibility rules (R1–R5/E1–E5) as long as skidbuffer-internal behavior is not included in Σ . However, to keep the pre-HLS simulation’s port micro-architecture aligned with the RTL configuration, the following compile flag must then be used in this case:

```
-DFORCE_AUTO_PORT=Connections::SYN_PORT
```

This will remove all the skidbuffers from the pre-HLS model. In this case, if some of the skidbuffers are still inserted during HLS, the capacity effects of those specific skidbuffers should be added into Sys_B so that the formal trace-compatibility relationship still holds.

In this case the recommended methodology is to use both approaches:

- Use the default throughput accurate mode in Matchlib for most analysis and debug, and for pre-HLS performance verification.
- To keep the pre-HLS simulation's *port micro-architecture* strictly aligned with the RTL configuration, then use -DFORCE_AUTO_PORT=Connections::SYN_PORT, and rerun final verification tests.

Common Formal Definitions for Appendices I-K

Throughout Appendices I–K, the formal comparison is between RTL_B and Sys_ref (Appendix J, Remark 2), i.e., the same source processes interpreted under the channel semantics of E4 with capacities $B(c)$ matching the RTL. The E4 channel semantics are case-split: $B(c)=0$ is interpreted as a capacity-zero rendezvous channel, and $B(c)>0$ is interpreted as a cycle-boundary, non-fall-through bounded FIFO. The rendezvous case is therefore recovered as the $B(c)=0$ case of the channel model, not by applying the $B(c)>0$ FIFO-availability inequalities with $B(c)=0$.

Symbol / Rule	Definition — concise but complete
BoundaryReq(q, σ)	For any dynamic source-level message-operation instance $q \in Q_{\text{exec},P}$ on an explicit abstract channel c of Sys_ref, with $\text{kind}(q) \in \{\text{Push}_c, \text{Pop}_c\}$, BoundaryReq($q, \sigma$) means: at the chosen abstract boundary and ϵ-quiescent cutpoint σ, q's endpoint-owned boundary request is asserted. Operationally (ready/valid): · for $\text{kind}(q)=\text{Push}_c$: the producer endpoint asserts vld_c, with stable payload as required; and · for $\text{kind}(q)=\text{Pop}_c$: the consumer endpoint asserts rdy_c. BoundaryReq is therefore a predicate about the endpoint's boundary-visible request assertion for a specific dynamic operation instance q, not about an already-committed Σ-event label. Purely combinational realization structure on the channel side may affect only the complementary mirror signal at that boundary (Push: rdy; Pop: vld) and thus the commit condition after ϵ-settling, but it does not change the endpoint request assertion captured by BoundaryReq(q, σ). When a cycle-index notation is needed, BoundaryReq(q, t) is shorthand for BoundaryReq(q, σ_t), where σ_t is the ϵ-quiescent cutpoint for cycle t.
ChannelEnabled(q, σ)	ChannelEnabled(q, σ) means: BoundaryReq(q, σ) holds, and in the ϵ-quiescent ready/valid fixed point at σ, the channel-side commit-enabling condition for q holds at the chosen boundary. Concretely, for bounded-FIFO channels $B(c)>0$, the channel-side condition is exactly the E4 availability predicate at that boundary: · for $\text{kind}(q)=\text{Push}_c$: $\text{occ}_c(\sigma) < B(c)$, i.e. space is available; and

Symbol / Rule	Definition — concise but complete
	· for $\text{kind}(q)=\text{Pop_c}$: $\text{occ_c}(\sigma) > 0$, i.e. data is available. For rendezvous channels $B(c)=0$, the channel-side condition is the matching complementary endpoint participation in the same ε-quiescent cycle. If q commits, it contributes the corresponding committed Σ-event $m(q) \in M$; before q commits, $m(q)$ is absent, but $\text{BoundaryReq}(q,\sigma)$ and $\text{ChannelEnabled}(q,\sigma)$ are still well-defined.
ChannelDisabled(q, σ)	$\text{ChannelDisabled}(q,\sigma)$ means: $\text{BoundaryReq}(q,\sigma)$ holds but $\text{ChannelEnabled}(q,\sigma)$ does not. Intuitively: the endpoint is requesting the transfer for dynamic operation instance q, but the transfer is blocked by channel-side conditions, such as empty/full status or the rendezvous partner not simultaneously requesting, as evaluated at the ε-quiescent handshake fixed point used throughout the document's enablement tests. Consequently, at the chosen boundary the channel-side enablement test remains exactly E4. Let $q \in Q_{\text{exec},P}$ be a dynamic source-level message-operation instance of its owning process P on an explicit abstract channel c of Sys_ref, and let $\text{kind}(q) \in \{\text{Push_c}, \text{Pop_c}\}$ denote its endpoint direction. $\text{BoundaryReq}(q,\sigma)$ means that q's endpoint-owned boundary request is asserted at the ε-quiescent cutpoint σ, with stable payload if q is a Push. For a message-operation frontier item $x \in \Omega_{\text{msg},P}$ on channel c with $\text{MsgOf_P}(x)=q$, $\text{ChannelEnabled}(x,\sigma)$ means that $\text{BoundaryReq}(x,\sigma)$ holds operation-attributively through q and c's E4 availability predicate holds at σ after combinational settling: space/data availability for $B(c)>0$, or complementary endpoint participation for $B(c)=0$. $\text{ChannelDisabled}(x,\sigma)$ means that $\text{BoundaryReq}(x,\sigma)$ holds but $\text{ChannelEnabled}(x,\sigma)$ does not. If q commits, x contributes the corresponding committed Σ-event $m(q) \in M$, labeled $\text{Push_c}(v)$ or $\text{Pop_c}(v)$; if q has not yet committed, $m(q)$ is absent, but $\text{BoundaryReq}(x,\sigma)$, $\text{ChannelEnabled}(x,\sigma)$, and $\text{ChannelDisabled}(x,\sigma)$ are still well-defined through the owning message instance q. Failed non-blocking polls $q \in Q_{\text{exec},P}$ that induce no frontier item in $\Omega_{\text{msg},P}$ do not have BoundaryReq, ChannelEnabled, or ChannelDisabled obligations merely because they executed. Any cross-channel dependency introduced by combinational couplers must be reflected only at explicit internal staged/bundle/join boundaries introduced by the elaboration (i.e., via $\text{BoundaryReq}/\text{ChannelEnabled}/\text{ChannelDisabled}$ on message-operation frontier items $x \in \Omega_{\text{msg},P}$, with $\text{MsgOf_P}(x)=q$, at those explicit staged/bundle channels). At the chosen Σ-visible channel endpoints, $\text{BoundaryReq}(x,\sigma)$ and $\text{ChannelEnabled}(x,\sigma)/\text{ChannelDisabled}(x,\sigma)$ for a message-operation frontier item $x \in \Omega_{\text{msg},P}$ on channel c may not depend on other channels' state beyond the per-channel E4 predicate for c, and no extra hidden predicate may block an otherwise E4-enabled boundary transfer.
Σ	Set of observable actions for the equivalence check (committed IO events) at the chosen observable boundary (often the DUT IO boundary for functional

Symbol / Rule	Definition — concise but complete
	equivalence, but optionally expanded—e.g., for Appendix K deadlock reasoning): • channel commit events Push_c(v) and Pop_c(v) on channels designated as observable, labeled with the transferred message value (or abstract message identity) v • synchronization events wait(), Sync, START_P, FINISH_P • single-cycle signal actions Write(sig, val) and Read(sig, val) on signals designated as observable, labeled with the value written/read. Internal-only channels/signals may be excluded from Σ (treated as ϵ-microstate) when they are not part of the chosen observable boundary. If such channels/signals are later brought into the observable boundary (e.g., by snooping for debug or analysis), then they become Σ-events and must match under $\approx$. Deadlock-analysis requirement (Appendix K): for Appendix K, Σ is instantiated to include every message-passing channel whose endpoint transfers at the chosen Sys_ref boundary can contribute a dependency edge in the Appendix K Wait-For Graph, either because the channel is on the declared observable boundary or because it is snooped. The WFG itself is defined over pending blocking message-operation frontier items $x \in \Omega_msg, P$ for the relevant owning process P, with owning dynamic message-call instance $q = \text{MsgOf_P}(x)$, not over already-committed Σ-event labels and not over failed non-blocking polls in Q_exec, P. Thus, when Appendix K refers to a blocked Push or Pop at a boundary, the relevant frontier object is x, and its owning pending source-level operation instance is q with $\text{kind}(q) \in \{\text{Push_c}, \text{Pop_c}\}$; the edge is determined by $\text{BoundaryReq}(x, \sigma)$ together with $\text{ChannelEnabled}(x, \sigma)/\text{ChannelDisabled}(x, \sigma)$ at the ϵ-quiescent cutpoint σ. Internal micro-interfaces that lie within the back-annotated realization counted in B(c) (e.g., post-HLS RTL pipeline stage implementation) are not treated as separate channels for this requirement: they may be exposed/snooped for debug, but Appendix K's WFG edges are defined using the $\text{ChannelEnabled}/\text{ChannelDisabled}$ status of the corresponding boundary operation instance q via $E4/occ_c/B(c)$, so such internal points can participate logically in the deadlock argument without being explicitly Σ-observable. Non-blocking message-passing (PushNB/PopNB): A non-blocking call that returns “not completed” produces no Σ-event and is modeled as an internal ϵ-step. When a non-blocking call succeeds (returns “completed”), that success is represented in Σ as the corresponding committed Push_c(v) or Pop_c(v) event on that channel, labeled with the same transferred value/message v (i.e., Σ records transfers and their payloads, not failed polls). A non-blocking call is considered issued in the cycle in which it executes (its Issue cycle). A call that returns “completed” commits in that same cycle and therefore yields a committed transfer $m(q) \in M$; a call that returns “not completed” produces no committed transfer event ($m(q)$ undefined / absent) and may be treated as an

Symbol / Rule	Definition — concise but complete
	ϵ-step with respect to Σ-visible message-transfer events. Each executed non-blocking call is still a distinct dynamic source-level message-call instance $q \in Q_{\text{exec},P}$ for the owning process P. Since failed non-blocking q's have no Σ-label, their cross-trace matching is witness-relative: it is supplied by the chosen μ_Q / WC witness, by NB-CF when failed polls cannot affect the next Σ-visible control flow or frontier, or by Appendix L's snooping / witness-selection mechanism. Continuous assertion of an endpoint request does not by itself identify multiple executed non-blocking calls as one q, and the Σ trace alone is not required to determine how failed non-blocking q's are matched. A successful non-blocking call may also be a member of $Q_{\Omega,P}$ when it contributes a committed $\text{Push}_c(v)$ / $\text{Pop}_c(v)$ event; a failed non-blocking poll remains in $Q_{\text{exec},P} \setminus \Omega_P$.
START_P	First observable action emitted by process P after reset. Marks the moment P begins executing user code. A new START_P is emitted each time P exits reset.
FINISH_P	Last observable action of process P in the current reset epoch. If P executes an unbounded loop within that reset epoch, FINISH_P never occurs for that epoch, and the epoch-local trace is treated as infinite until a later reset boundary, if any. If a later reset affecting P occurs and P exits reset again, a new dynamic START_P begins a fresh reset epoch; any later termination is represented by a distinct dynamic FINISH_P occurrence.
ϵ-step	An <i>internal</i> , unobservable RTL state transition (pipeline advance, FSM micro-state, etc.).
B(c)	Back-annotated effective capacity of channel c at the chosen explicit abstract Sys_ref boundary used by E4 and Appendix K. In the ordinary non-elaborated case this is the chosen Σ-observable Sys_B boundary; in elaborated cases it is the corresponding explicit abstract channel boundary of $\text{Sys_B}^{\text{elab}}$, which may be proof-internal and later projected away from the outer Σ_{DUT} trace. Finite, $B(c) \geq 0$. It reflects the total bounded “composite buffer” storage/credit in the RTL realization represented by that explicit abstract channel boundary, including FIFO storage, skid/elastic buffering, HLS-inserted pipeline staging that can hold in-flight messages, and any explicit staged/bundle/join channel capacity introduced by $\text{Sys_B}^{\text{elab}}$. • $B(c)=0 \Rightarrow$ rendezvous (capacity-zero) channel. • $B(c)>0 \Rightarrow$ bounded FIFO (of that effective capacity). B-faithfulness. For the formal results to apply to a concrete RTL_B instance, each back-annotated $B(c)$ must be faithful to the chosen explicit abstract boundary. This means: • Boundary completeness: every RTL storage element, credit, skid/elastic buffer, pipeline stage, or elaborated staged/bundle/join component that can accept, hold, release, or backpressure messages across the abstract boundary c is either included in the effective capacity $B(c)$ for that boundary or represented as a separate explicit $\text{Sys_B}^{\text{elab}}$ boundary with its own capacity and E4 semantics.

Symbol / Rule	Definition — concise but complete
	• No hidden capacity or hidden enablement: the RTL realization does not permit a producer-facing accept or consumer-facing delivery at boundary c except in cycles allowed by E4 using the corresponding $\text{occ}_c(t)$ and $B(c)$, and any additional enablement restriction that affects boundary behavior is represented by an explicit $\text{Sys_B}^{\text{elab}}$ boundary rather than by an unmodeled predicate. • ϵ-opacity of internal movement: movement of an already accepted message within the RTL realization counted by $B(c)$ is internal ϵ-state. Such movement does not create additional Σ-visible $\text{Push}_c/\text{Pop}_c$ events and does not create, delete, duplicate, reorder, or relabel the Σ-visible boundary transfers. • Evidence obligation: B-faithfulness is a tool/RTL-flow compliance obligation. It may be discharged by a trusted back-annotation algorithm, generated certificate, structural RTL check, interface monitor, formal equivalence/checking flow, or other validation method appropriate to the implementation flow. It is not derived by E4, Proposition J.0, or Theorem J.1. Point-to-point endpoint assumption (single-producer/single-consumer): For every message-passing channel c (including both buffered channels with $B(c)>0$ and rendezvous channels with $B(c)=0$), there is exactly one producer process that may execute Push_c on c, and exactly one consumer process that may execute Pop_c on c. Hence the complementary endpoint relevant to any blocked $\text{Push}_c/\text{Pop}_c$ on c is unique. Modeling note (shared resources / arbitration): If an implementation conceptually has multiple producers and/or multiple consumers for a logical resource, that sharing must be modeled explicitly (e.g., an arbiter process plus per-client point-to-point channels), rather than as a single multi-endpoint “channel.” This keeps WFG wait dependencies well-defined and unique per edge. Single-transfer-per-cycle endpoint constraint (scalar channel interface): For every message-passing channel c, in any clock cycle t, at most one Push_c may commit and at most one Pop_c may commit. Equivalently, the set of commits on a fixed channel in a single cycle contains ≤ 1 Push and ≤ 1 Pop (it may contain one of each in the same cycle). For rendezvous channels ($B(c)=0$), a committed transfer occurs only as a matching same-cycle $\text{Push}_c(v)$ and $\text{Pop}_c(v)$ pair. For buffered channels ($B(c)>0$), a same-cycle Push_c and Pop_c do not imply fall-through; the channel semantics are cycle-boundary, non-fall-through as stated in E4. Reset-empty FIFO convention: after each reset boundary at which the compared execution begins or restarts, every buffered message-passing channel with $B(c)>0$ has logical FIFO occupancy 0 at the chosen Σ boundary. Equivalently, the reset state contains no preloaded in-flight messages in the abstract channel realization used by Sys_ref / RTL_B. If a design requires preloaded channel contents, those contents must be modeled explicitly as post-reset producer actions or by a separate initialized-state extension outside the present empty-FIFO formal model. Modeling note (multi-lane / burst transfers): If an implementation can

Symbol / Rule	Definition — concise but complete
	transfer $k > 1$ messages per cycle on a logical resource, model it as k parallel point-to-point channels (or as a single widened message transferred by one Push_c/Pop_c per cycle) so that the Σ -level event model continues to satisfy the scalar constraint above.
occ_c(t)	Abstract FIFO occupancy at the chosen explicit abstract Sys_ref channel boundary: number of items committed by Push_c but not yet committed by Pop_c at that boundary, measured from the most recent reset boundary under the reset-empty FIFO convention. In the ordinary non-elaborated case this is the chosen Sys_B channel boundary; in elaborated cases Sys_ref = Sys_B^elab, this is the occupancy of the relevant explicit abstract staged/bundle/join channel boundary. Equivalently (E4), $\text{occ_c}(t) = \text{push}(\pi_t) - \text{pop}(\pi_t)$, where π_t is the Σ-visible boundary-commit prefix for that explicit abstract channel strictly before cycle t (i.e., excluding any Push_c/Pop_c commits that occur in cycle t), so $\text{occ_c}(t)$ is the abstract occupancy at the beginning of cycle t. For pure-FIFO channels with $B(c) > 0$, the FIFO availability predicates (not-full/not-empty) are evaluated against this begin-of-cycle occupancy; hence a Pop_c cannot commit in a cycle that begins empty solely because a Push_c also commits in that same cycle (no fall-through), and likewise a Push_c cannot commit in a cycle that begins full solely because a Pop_c also commits in that same cycle. Clarification (no “second Push/Pop”): movements of an item within the RTL channel realization (e.g., FIFO $\rightarrow$ staging/skid buffering, staging/skid buffering $\rightarrow$ pipeline-stage registers, pipeline-stage $\rightarrow$ pipeline-stage handoff) are internal ε-steps; they do not constitute additional Σ-visible committed Push_c/Pop_c events beyond the boundary events counted by $\text{push}(\pi_t)/\text{pop}(\pi_t)$. Derived cutpoint shorthand (used in Appendices K and R): if σ is an ε-quiescent cutpoint occurring in cycle t_σ, write $\text{occ_c}(\sigma) \triangleq \text{occ_c}(t_\sigma)$. Likewise, when channel enablement is evaluated at an ε-quiescent cutpoint, write $\text{ChannelEnabled}(q, \sigma) \triangleq \text{ChannelEnabled}(q, t_\sigma)$ and $\text{ChannelDisabled}(q, \sigma) \triangleq \text{ChannelDisabled}(q, t_\sigma)$. This is only notational shorthand for cutpoint reasoning; the primary semantic definition of occupancy remains the cycle-boundary quantity $\text{occ_c}(t)$. Note: $\text{occ_c}(t)$ is an abstract analysis quantity derived from Σ-visible boundary commits; in both Sys_B and RTL_B, processes do not directly read $\text{occ_c}(t)$ and instead proceed solely based on the per-channel ready/valid outcome of their own Push/Pop attempts.
P_push(c)	<i>Finite-progress invariant (producer)</i> : this is a persistent-request premise, not a ChannelEnabled premise. In this paragraph, “the producer’s request remains asserted continuously” means that the producer presents a persistent, non-withdrawable Push_c endpoint request from the starting cycle through the matching discharge event, with no deassert-before-commit and with stable

Symbol / Rule	Definition — concise but complete
	payload while asserted. • Buffered case ($B(c) > 0$): If the producer's Push_c request remains asserted continuously from some cycle t_0 onward while the channel is full ($occ_c = B(c)$) —with stable payload while asserted—and the complementary endpoint continuously requests the matching Pop_c (persistent request asserted; Pop_c boundary request remains true), then some cycle $t' \geq t_0$ commits a complementary Pop_c (i.e., the full condition is eventually discharged). • Rendezvous case ($B(c) = 0$): If the producer's Push_c request remains asserted continuously from some cycle t_0 onward (with stable payload while asserted) and the complementary endpoint continuously requests the matching Pop_c (persistent request asserted; Pop_c boundary request remains true), then some cycle $t' \geq t_0$ commits the rendezvous transfer—i.e., a matching Push_c(v) and Pop_c(v) commit in the same cycle.
P_pop(c)	<i>Finite-progress invariant (consumer)</i>: this is a persistent-request premise, not a ChannelEnabled premise. In this paragraph, “the consumer’s request remains asserted continuously” means that the consumer presents a persistent, non-withdrawable Pop_c endpoint request from the starting cycle through the matching discharge event, with no deassert-before-commit. • Buffered case ($B(c) > 0$): If the consumer's Pop_c request remains asserted continuously from some cycle t_0 onward while the channel is empty ($occ_c = 0$)—and the complementary endpoint continuously requests the matching Push_c (persistent request asserted with stable payload; Push_c boundary request remains true)—then some cycle $t' \geq t_0$ commits a complementary Push_c (i.e., the empty condition is eventually discharged). • Rendezvous case ($B(c) = 0$): If the consumer's Pop_c request remains asserted continuously from some cycle t_0 onward and the complementary endpoint continuously requests the matching Push_c (persistent request asserted with stable payload; Push_c boundary request remains true), then some cycle $t' \geq t_0$ commits the rendezvous transfer—i.e., a matching Push_c(v) and Pop_c(v) commit in the same cycle.
Trace-compatibility rules (E1–E5)	<i>E1 Synchronization-order preservation</i>: For each process P, the sequence of synchronization events executed by P (wait(), SyncChannel, START_P, FINISH_P) appears in the same source order in the pre-HLS and post-HLS traces. <i>E2 Signal visibility</i>: For each sequential process P, each signal Read in P occurs at the closest preceding synchronization event in P, and each signal Write in P occurs at the closest succeeding synchronization event in P, in both the pre-HLS and post-HLS traces (per R2/E2). For each combinational process or explicitly modeled combinational network component C_comb, observable combinational signal Read/Write labels appear only inside emitted R2C fixed-point signal-observation units for the selected R2C observation component, as defined by R2C. Each emitted R2C unit is evaluated at one ϵ-quiescent combinational fixed point, and all

Symbol / Rule	Definition — concise but complete
	Read/Write labels inside that unit are atomic with respect to that fixed point. Emitted R2C units are matched by component identity and local emitted-occurrence ordinal, not by global observable-cycle bucket number. R2C stutter cycles whose selected observable slice is unchanged do not create separate Σ-visible units unless an explicitly modeled observer/sampler requires a fresh emitted unit. Interpretation (logical timestamping). For sequential processes, the equations in E2 define the logical timestamps of Read/Write Σ-events: the anchor points at which compatibility is checked. An implementation may physically sample a Read later than $\text{pred}_S(r)$, or physically apply a Write earlier than $\text{succ}_S(w)$, provided the value is stable across the anchor interval and the trace emitted for compatibility records the Σ-event at the anchor point. For combinational processes, the logical observation point is the emitted R2C fixed-point signal-observation unit, not a global observable-cycle bucket number; internal delta-cycle propagation before the fixed point and R2C stutter cycles with unchanged selected observable slices are $\varepsilon/\text{stutter}$ and are not separately Σ-visible. Direct-input pragmas (e.g., <code>#pragma hls_direct_input</code> and <code>#pragma hls_direct_input_sync</code>) do not change E2 and are not exceptions to E2. For sequential processes, they impose stability/timing contracts that allow later physical sampling, or controlled updates at a synchronization boundary, while the logical Read/Write Σ-events used for $\approx$ checking remain timestamped at the E2 synchronization anchor points and retain the anchored value labels. For combinational processes, ordinary direct-input pragmas do not introduce a separate anchoring rule; any observable combinational signal Read/Write label remains part of an emitted R2C fixed-point signal-observation unit under the R2C unit-generation and matching conventions. Thus the pragma affects only implementation sampling freedom under its stated contract, not the logical Σ observation used for compatibility. <i>E3 (Safe message issue ordering). (Post-HLS preservation of R4).</i> For any two executed message-call instances $q_1, q_2 \in Q_{\text{exec}, P}$ of the same process P: (i) Same-interface order is always preserved: if q_1 and q_2 access the same message-passing interface/channel and $q_1 <_{\text{src}} q_2$, then $\text{issue_post}(q_1) \leq \text{issue_post}(q_2)$. (ii) Distinct-interface no-reverse: if q_1 and q_2 access distinct message-passing interfaces and appear in sequence in the source ($q_1 <_{\text{src}} q_2$), then $\text{issue_post}(q_1) \leq \text{issue_post}(q_2)$ (i.e., they shall not be issued in the reverse sequence). (Note: any pipelined-loop internal staging/dequeue discussed in “Pipelined Loops” is ε-microstate within the back-annotated channel realization and is not a Σ-visible boundary issue event associated with any $q \in Q_{\text{exec}, P}$ nor a committed-transfer event in M; therefore it does not constitute a counterexample to (ii).) <i>E4 FIFO legality:</i> for each channel c, the post-HLS committed ($\text{Push}_c(v)$,

Symbol / Rule	Definition — concise but complete
	Pop_c(v)) history is a legal bounded-capacity execution consistent with Sys_B for that channel (capacity B(c)), and reduces to rendezvous consistency when B(c)=0. In particular, on each channel, the committed Pop_c(v) events return exactly the FIFO-ordered sequence of values v previously committed by Push_c(v), with no drops, duplications, or reordering. <i>E5 (Messages cannot cross their immediate synchronization boundary).</i> For every synchronization call s (in the source order used by R3 / pref_S / suff_S): $\forall q \in \text{pref_S}(s) : \text{issue_post}(q) \leq \text{clk_post}(s)$ $\forall q \in \text{suff_S}(s) : \text{issue_post}(q) > \text{clk_post}(s)$

Additional Semantic Assumptions (B-rules)

The following B rules are process assumptions used within the formal proofs. These B rules are in addition to the R rules presented in Appendix G.

ID	Basic-process property (informal statement)	Why it is needed / how it is used
B1 Deterministic Trace Property	For any fixed test stimulus and initial state, the sequence of observable actions emitted by the post-HLS design is unique, including the channel identity and payload/value of each committed Push_c(v)/Pop_c(v) and the value of each Write(sig,val)/Read(sig,val). Internal ϵ-steps may differ between runs, but the externally visible Σ-trace (with labels) cannot. Clarification: B1 is assumed of RTL_B (post-HLS) only. The source-level models Sys/Sys_B may admit multiple ϵ-/latency-different executions with the same Σ-projection. When a single concrete witness execution of Sys_B is required for simulation/debug, Appendix L's snooping wrapper may be used to select one admissible witness whose latency-sensitive events align with the unique RTL Σ-trace. Derived per-process consequence. For every process P, the projection of the unique RTL_B Σ-trace onto the observable units owned by or attributed to P is also unique. This follows from the system-level B1 property; it does not assert that P is deterministic when considered in isolation under arbitrary peer,	Ensures the per-process and system-level trace-compatibility proofs (App. I & J) can match one post-HLS trace to one pre-HLS trace without branching on scheduler nondeterminism.

ID	Basic-process property (informal statement)	Why it is needed / how it is used
	channel, arbitration, or environment behavior.	
B2 Weak Fairness of the Scheduler (WF)	If an action's enabling predicate remains continuously true from cycle t onward, the scheduler/arbitrator must eventually select that action, and the selected action then commits in the selected cycle, within a finite but unspecified number of cycles. Applies to Push, Pop, and Sync operations. For message-passing operations, "enabled" means ChannelEnabled under E4 at the chosen abstract boundary. Enablement is eligibility for selection; it is not itself a same-cycle commit. Thus B2 is not vacuous: an enabled Push/Pop may be delayed by fair arbitration, but it may not be delayed forever while it remains continuously enabled.	Required for all progress arguments, especially the liveness lemmas in Appendix K and the channel-progress corollaries.
B3 Channel Progress Invariants	B3 is exactly the following family of per-channel progress obligations. For every explicit abstract channel c with capacity $B(c)$, B3 consists of both $P_push(c)$ and $P_pop(c)$, as defined below. Thus references such as "B3," "Appendix N's B3," and "the P_push/P_pop obligations" name the same channel-progress assumption; $P_push(c)$ and $P_pop(c)$ are not additional assumptions separate from B3. B3 is stated separately from B2 because the proofs often reason from the perspective of a currently stalled request. A blocked $Push_c$ at $occ_c = B(c)$, a blocked Pop_c at $occ_c = 0$, or a rendezvous endpoint waiting for its peer is not itself able to complete until the relevant complementary discharge occurs. B3 packages that discharge fact as a named per-channel progress obligation: under the persistent-request premises below, the full/empty/rendezvous-blocked condition is eventually discharged, after which ordinary E4 availability and B2 can be	Explicitly assumed in Appendix J to rule out permanent back-pressure loops in which both endpoints continuously request a transfer until the matching discharge event but that transfer never completes, which are logically independent of the cycle-by-cycle R-rules.

ID	Basic-process property (informal statement)	Why it is needed / how it is used
	used for any still-pending enabled transfer. For a single explicit abstract boundary with ordinary E4 buffered or rendezvous semantics, the corresponding B3 discharge is implied by B2 plus E4 once the complementary endpoint request in the B3 premise remains continuously asserted. In the buffered full case, $occ_c = B(c) > 0$ makes the complementary Pop_c continuously ChannelEnabled; B2 then forces eventual selection and commit of that Pop_c, freeing space. In the buffered empty case, $occ_c = 0 < B(c)$ makes the complementary Push_c continuously ChannelEnabled; B2 then forces eventual selection and commit of that Push_c, providing data. In the rendezvous case, the two persistent endpoint requests make the rendezvous pair continuously ChannelEnabled, so B2 similarly supplies eventual rendezvous selection and commit. B3 is nevertheless retained as an explicit named obligation because Lemma I.2, Appendix K, and the channel-validation methodology consume that modular form directly. It is also the form checked per explicit abstract channel in elaborated Sys_B^{elab} boundary chains. Thus B3 should be read as the modular channel-progress assumption used by the proof and checked against channel realizations, not as a claim that the ordinary single-boundary buffered clauses are logically independent of B2+E4. In the definitions below, “persistent,” “continuously requests,” and “remains true” are interval-scoped. The relevant endpoint request must remain asserted from the starting cycle t_0 through the first matching discharge event, if such a discharge occurs. If no matching	

ID	Basic-process property (informal statement)	Why it is needed / how it is used
	discharge occurs, the request must remain asserted for all later cycles. A Push request also keeps its payload stable throughout the outstanding interval. B3 does not require an endpoint request or Push payload to remain asserted forever after the matching transfer has already committed. • $P_push(c)$: If a process P is stalled at a blocking $Push(c)$ with its boundary request true and a persistent request asserted with stable payload while the channel is full ($occ(c) = B(c)$), and the complementary endpoint process continuously requests the matching $Pop(c)$ until the matching discharge event ($Pop(c)$ endpoint request asserted; $Pop(c)$ boundary request remains true), then the transfer on c must eventually complete. In particular, for $B(c) > 0$, some $Pop(c)$ eventually commits, freeing space; for $B(c) = 0$, the rendezvous completion eventually occurs. • $P_pop(c)$: If a process P is stalled at a blocking $Pop(c)$ with its boundary request true and a persistent request asserted while the channel is empty ($occ(c) = 0$), and the complementary endpoint process continuously requests the matching $Push(c)$ until the matching discharge event ($Push(c)$ endpoint request asserted with stable payload; $Push(c)$ boundary request remains true), then the transfer on c must eventually complete. In particular, for $B(c) > 0$, some $Push(c)$ eventually commits, providing data; for $B(c) = 0$, the rendezvous completion eventually occurs.	
B4 Finite Stutter Bound	Every process P has a finite constant depth D_P such that whenever P is not externally stalled (i.e., P is advancing internal micro-state toward its next observable Σ-action, or its next Σ-action is locally enabled), P can execute at most D_P consecutive ϵ-steps before either (i) executing a Σ-action, or (ii) reaching a stable waiting state in which P has no further ϵ-step available until some	This guarantees the ϵ-stutter closure needed to construct witness mappings in Appendix I and to bound internal micro-latency (pipeline/FSM bookkeeping) by $\leq D_P$. Unbounded waiting due to back-pressure or missing peer stimulus is governed by WF/B2 and the progress obligations B3, not by B4.

ID	Basic-process property (informal statement)	Why it is needed / how it is used
	external/peer/environment condition changes the enabling predicates.	
B5 System Quiescence Closure	If, at some cycle t_0 , no observable actions are enabled in any process, then within at most $\max_P D_P$ further cycles the system reaches a fixed point and executes no additional ϵ -steps.	Needed to finish the starvation-vs-deadlock analysis in Appendix K: ensures an all-disabled state cannot hide behind an infinite tail of unobservable activity.
B6 Time-Divergence / Idle-Stutter Convention	After the fixed point of B5 is reached — that is, after the system is ϵ -quiescent, no Σ -visible action is enabled, and no further internal ϵ micro-step is enabled under the same stimulus — the global clock continues to advance. We model each subsequent idle clock tick as a stutter step that produces no Σ -event, performs no ϵ -prefix or ϵ -suffix work, and leaves all non-clock state unchanged.	For prefix/trace matching in E1–E5 and for the Exec_post / Exec_ref conventions in Appendix J, these idle ticks are treated as ϵ-stutter. Thus B6 gives a time-divergent infinite extension for any reachable finite execution prefix/state that is already at a B5/global fixed point. B6 is not, by itself, an arbitrary deadlock-cutpoint extension principle. In particular, a partial internal message-passing deadlock cutpoint in Appendix K need not be a global fixed point, because outside-D activity, environment activity, or already-issued non-frontier drain work may still be possible. Such cutpoints are handled by the separate Appendix K fair drain-normalization argument: enabled drain-only transfers may commit as finite drain-only progress under the B2/B3 progress assumptions, while pure idle-stutter is used only once the relevant disabled frontier blockers and drain-closed closed component are preserved in the required execution-scoped continuation.

Side-condition discharge record

Before applying Theorem J.1 or the Appendix K liveness-preservation theorem to a concrete design, the verification flow shall maintain an explicit side-condition discharge record. The record need not have a prescribed format, but it shall state, for each side condition below, whether the condition is inapplicable, satisfied by a simple syntactic/design restriction, discharged by tool/RTL evidence, or discharged by a source/RTL witness construction.

- WC — witness-compatible ϵ choices / non-blocking outcomes.

Trigger: Required when failed non-blocking polls or other ϵ -modeled choices can affect later Σ -

visible control flow, frontier membership, request attribution, guard values, or payload values.
 Discharge: Show NB-CF, or provide a witness selector W satisfying the Appendix L snooping conditions, or otherwise prove the μ_Q / WC witness used in Appendix I/J.

Evidence examples: Source inspection showing failed polls are control-flow neutral; a generated witness/certificate; a co-simulation or snooping wrapper satisfying Lemma L.2.

- NB-CF — non-blocking control-flow neutrality.

Trigger: Used as the simple sufficient condition that avoids nontrivial witness selection for failed PushNB/PopNB polls.

Discharge: Show that failed non-blocking poll outcomes do not affect the next Σ -visible control flow, frontier membership, request attribution, guard values, payload values, or other later Σ -visible choices.

Evidence examples: Source-level coding restriction; static control/dataflow check; manual review of the affected non-blocking call sites.

- Appendix L snooping / witness selector W .

Trigger: Needed when NB-CF does not hold but a source execution must be selected to match the $RTL_B \varepsilon$ /latency choices.

Discharge: Show that the snooped outcomes cover every ε -modeled source choice that can affect later Σ -visible behavior, that the wrapper changes only ε -choice selection, and that it does not add, remove, reorder, or relabel Σ -visible events.

Evidence examples: A wrapper proof, monitor specification, generated instrumentation report, or simulation/cosimulation harness satisfying Lemma L.2.

- Sys_B^{elab} — elaborated source reference model.

Trigger: Required when ordinary Sys_B capacities at the outer abstract boundaries are not sufficient to represent the RTL realization as ordinary E4 bounded-FIFO/rendezvous behavior; examples include multi-input/join couplers, staged/bundle/join channels, and sync-boundary / epoch-gate capacity withdrawal.

Discharge: Provide a well-formed elaboration package E defining the explicit abstract channels, capacities, projection Π_{elab} , and E4 ChannelEnabled/ChannelDisabled behavior used by $Sys_B^{\text{elab}}(E)$.

Evidence examples: Tool-generated elaboration, structural back-annotation report, Appendix Q-style construction, or manual elaboration justified against the RTL channel structure.

- J.AbsConf — RTL_B cutpoint-abstraction conformance.

Trigger: Required whenever Corollary J.1 cutpoint correspondence is used, and therefore required for

Appendix K / Appendix R uses that transfer Pending_P, BoundaryReq, rendezvous endpoint-request,

ChannelEnabled/ChannelDisabled, Front_P, or WFG facts between RTL_B and Sys_ref .

Discharge: For each compared ε -quiescent RTL_B cutpoint p_{post} , identify the same selected Sys_ref

witness prefix, terminal cutpoint σ_{ref} , and witness w used by Theorem J.1 / Corollary J.1, and show

$p_{\text{post}} \Downarrow_{\{Abs, J, w\}} \sigma_{\text{ref}}$ at the chosen abstract boundaries. The discharge must cover the source-visible

value slice, abstract channel-state slice, rendezvous endpoint-request slice, blocking request

attribution/pending slice, and enablement slice required by J.Abs.

Evidence examples: Tool-generated cutpoint certificate; RTL/interface monitor report; structural back-annotation and attribution certificate; co-simulation witness log; bounded proof over the generated RTL; or manual proof that the chosen RTL boundary, capacities, request signals, and attribution metadata faithfully implement the J.Abs source slice.

- $K\varepsilon$ — WFG-inert ε / no hidden micro-timing control decisions.

Trigger: Required for Appendix K liveness/deadlock preservation when ε -steps occur between Σ -visible cutpoints.

Discharge: Show that ε -only steps do not create, remove, or redirect the relevant Appendix K WFG blocking causes except through the explicit Σ -visible or E4-modeled channel state already represented in Sys_ref.

Evidence examples: RTL structural argument, scheduler proof, bounded pipeline/drain argument, formal check over the WFG abstraction, or tool certificate.

This record is not an additional semantic assumption beyond the named premises already used in Appendices I–K. Its purpose is to make theorem application auditable: realistic complications are allowed, but each complication must be mapped to a named condition and discharged rather than left implicit.

Appendix I – Per Process Trace Compatibility Proof

I.1 Overview

This appendix establishes only the per-process witness property in the direction needed by Appendix J’s execution-level correspondence: under a fixed initial state and fixed external stimulus/environment behavior, every reachable finite observable prefix of the post-HLS model RTL_B has a matching finite observable prefix in the prescribed source reference model Sys_ref (Appendix J, Remark 2), satisfying E1–E5 (Post $\rightarrow$ Ref).

Downstream citation discipline. Later appendices may cite Appendix I for this Post $\rightarrow$ Ref witness construction over Sys_ref, and for the local per-process ordering / anchoring facts proved along the way, including Implementation assumption I.A0 and Lemmas I.1–I.3. Appendix I does not, by itself, justify an unrestricted statement that every Sys_ref trace/prefix has a matching RTL_B trace/prefix.

Importantly, the converse direction (“every Sys_ref trace has a matching RTL_B trace”) is NOT claimed in general when latency-sensitive / non-blocking effects are made Σ -visible (e.g., by observing non-blocking poll outcomes or other timing-sensitive events via an expanded observation boundary). In such cases, Sys_ref may admit additional Σ -traces (for example, extra unsuccessful poll observations, or in elaborated cases additional source-side micro-realizations with the same outer intent) that do not match the RTL_B Σ -trace under the same stimulus. When a reverse correspondence is required, Appendix L’s snooping / witness-selection technique is used to restrict attention to RTL-consistent Sys_ref executions (see Theorem J.1). The rendezvous specialization is recovered when Sys_ref = Sys_B and B(c)=0.

I.2 Formal Preconditions

- **Observable alphabet Σ** is as defined in *Common Formal Definitions for Appendices I–K*: it consists of the event schemas {Push_c, Pop_c, Sync, wait, START_P, FINISH_P, Write, Read} instantiated only for channels/signals designated observable at the chosen proof boundary. For Appendices I–K, Σ is the proof-internal observable alphabet of the prescribed Sys_ref / RTL_B comparison. Thus all message-passing channels that can participate in Appendix K deadlock reasoning are designated observable at that proof boundary and hence included in Σ . In elaborated cases Sys_ref = Sys_B^elab, this proof-internal Σ may include introduced staged/bundle/join channels even when the projection Π_{elab} hides those internal events from the outer DUT/testbench-visible alphabet Σ_{DUT} . Such events are therefore Σ -visible for the proof-internal comparison, but may be projected away from the outer observation boundary.
- **Non-blocking message-passing interpretation.** In both RTL_B and Sys_ref, a non-blocking call (PushNB / PopNB) is treated as a poll. A successful poll contributes the same observable event as the corresponding committed Push_c / Pop_c on that channel. An unsuccessful non-blocking call (returns “false” / “not completed”) contributes no Σ -event and is modeled as an ϵ -step. A non-blocking poll may still assert a Σ -visible endpoint request in the cycle of that call. However, each executed non-blocking call is a distinct dynamic source-level instance $q \in Q_{\text{exec},P}$ for its owning process P. Accordingly, continuous assertion of an endpoint request with no intervening commit does not by itself collapse later executed non-blocking call instances into an earlier q. Only a poll that succeeds contributes the corresponding committed transfer $m(q) \in M$ for that call instance. If a request assertion persists without a new executed source-level call instance being entered, its attribution remains with that same currently outstanding q; but repeated non-blocking polls in later loop iterations or later source-level call instances create additional $q \in Q_{\text{exec},P}$ even if req does not deassert.
- **Silent step** Any internal RTL microstate transition is written ϵ . In particular, unsuccessful non-blocking polls, arbitration bookkeeping, and pipeline advances are ϵ -steps.
- **Finite-pipeline-depth premise (FPD)** There exists a finite constant $\text{pipe_depth}(P) = D_P < \infty$ such that once P begins internal micro-progress toward its next observable Σ -action (or that next Σ -action is locally enabled), P executes at most D_P cycles of ϵ -steps before either committing a Σ -action or reaching a stable waiting state with no further ϵ -step available until external/peer conditions change. In particular, a process cannot perform an unbounded number of ϵ -only failed non-blocking polls while making no progress toward any Σ -action; designs that can spin indefinitely without reaching either a Σ -action or a stable wait state violate FPD/B4 and are outside the model.
- **Weak-fairness premise (WF)** If a micro-operation remains continuously enabled, the scheduler eventually selects it for progress. For an already-issued blocking message request whose BoundaryReq is asserted and whose ChannelEnabled predicate remains true, this means the enabled transfer is eventually allowed to commit; it does not mean that the same source-level operation is “issued” again. This is an assumption on the execution/scheduling environment (see Appendix N), not an automatic guarantee of “clock-synchronous RTL.” In practice it requires that any arbiters/back-pressure logic that can affect whether an enabled operation is selected or allowed to commit must be fair in the sense of B2/B3.
- **Finite-progress invariants (B3)** For every channel c, assume producer and consumer obligations $P_{\text{push}}(c)$ and $P_{\text{pop}}(c)$ hold, guaranteeing that data (or space) eventually becomes available. This is an assumption on the execution/scheduling environment (e.g., fairness of arbiters/back-pressure; see Appendix N), not a consequence of the cycle-by-cycle R-rules.

- **Channel enablement semantics.** Let $q \in Q_{\text{exec},P}$ be a dynamic source-level message-operation instance of its owning process P on message-passing channel c , and let $\text{kind}(q) \in \{\text{Push}_c, \text{Pop}_c\}$ denote its endpoint direction. If q has issued a persistent blocking request to transfer on c , then $\text{BoundaryReq}(q, \sigma)$ holds at the ε -quiescent cutpoint σ : the endpoint-owned boundary request remains asserted, and the payload is stable if q is a Push. The channel-side commit-enabling predicate for q is determined as follows.

Rendezvous case, $B(c)=0$. A Push_c operation instance q is channel-enabled exactly when $\text{BoundaryReq}(q, \sigma)$ holds and the matching Pop_c endpoint boundary request is asserted in the same ε -quiescent cycle. A Pop_c operation instance q is channel-enabled exactly when $\text{BoundaryReq}(q, \sigma)$ holds and the matching Push_c endpoint boundary request is asserted in the same ε -quiescent cycle. Thus, when both endpoint requests are asserted in that cycle, the matched $\text{Push}_c(v)$ and $\text{Pop}_c(v)$ operation instances are eligible for selection as a rendezvous pair. If the scheduler selects that enabled rendezvous pair in that cycle, the matched $\text{Push}_c(v)$ and $\text{Pop}_c(v)$ commit as a same-cycle rendezvous pair and contribute the corresponding Σ -events. If the pair remains continuously enabled, B2 supplies eventual selection.

Buffered case, $B(c)>0$. The channel-side eligibility predicate for q is exactly the FIFO availability predicate conjoined with $\text{BoundaryReq}(q, \sigma)$:

for $\text{kind}(q)=\text{Push}_c$: $\text{ChannelEnabled}(q, \sigma) \Leftrightarrow \text{BoundaryReq}(q, \sigma) \wedge \text{occ}_c(\sigma) < B(c)$ (“not full”), and

for $\text{kind}(q)=\text{Pop}_c$: $\text{ChannelEnabled}(q, \sigma) \Leftrightarrow \text{BoundaryReq}(q, \sigma) \wedge \text{occ}_c(\sigma) > 0$ (“not empty”).

Here ChannelEnabled means that the abstract channel boundary permits the transfer to be selected; it does not by itself assert that the transfer has already committed in the current cycle.

Modeling note (fall-through / simultaneous empty/full cases). The buffered abstraction for $B(c)>0$ is cycle-boundary, non-fall-through. A Push and a Pop may both be selected and commit in the same cycle when the FIFO begins the cycle neither empty nor full ($0 < \text{occ}_c(t) < B(c)$); in that case both commits are legal and the occupancy is unchanged. The abstraction does not permit a Pop to be selected in a cycle that begins empty solely because a Push is also selected in that same cycle, nor does it permit a Push to be selected in a cycle that begins full solely because a Pop is also selected in that same cycle. If an implementation uses a fall-through FIFO (allowing same-cycle pass-through when empty), model that behavior explicitly (e.g., as an explicit bypass/rendezvous path composed with the bounded FIFO), so that the Σ -level committed-transfer trace matches the intended cycle semantics.

Operational interpretation (availability, selection, and ready/valid): $\text{occ}_c(t)$ is an abstract quantity derived from Σ -visible boundary commits for $B(c)>0$ buffered channels; processes do not read $\text{occ}_c(t)$ directly. For $B(c)=0$ rendezvous channels, the corresponding channel-side availability fact is the matching endpoint request predicate in the same ε -quiescent cycle. In both Sys_ref and RTL_B , $\text{ChannelEnabled}/\text{ChannelDisabled}$ records the settled abstract boundary availability/eligibility predicate. A commit occurs only when an enabled operation, or enabled rendezvous pair, is selected by the scheduler/arbiter for that cycle.

Here Sys_ref denotes the prescribed source reference model at the chosen abstract boundary: Sys_B in the ordinary case, or $\text{Sys_B}^{\text{elab}}$ in the elaborated back-annotated cases. A concrete realization is correct only if its committed ready/valid transfers are legal with respect to the

corresponding rendezvous or buffered availability predicate at that chosen boundary, and if every transfer that remains continuously eligible is eventually selected as required by B2. Thus E4 is a safety/legality condition on which transfers may commit, while B2 is the progress/fairness condition that prevents continuously eligible transfers from starving.

No additional hidden availability predicate is part of the channel semantics. Any cross-channel coordination, arbitration, grant, or back-pressure policy in the realization must be represented either

- (1) as scheduler/arbitrator selection among already ChannelEnabled actions, governed by B2, or
- (2) as explicit abstract boundary structure in $\text{Sys_B}^{\text{elab}}$ with its own $B(\cdot)$, $\text{occ_}\cdot(t)$, BoundaryReq, ChannelEnabled/ChannelDisabled, and B3 obligations. Such coordination must not be encoded as an unmentioned extra conjunct that silently changes the E4 availability predicate at an otherwise ordinary channel boundary.

Therefore, when the boundary request is true and the relevant rendezvous or FIFO availability predicate holds continuously, the transfer is continuously enabled; by weak fairness (B2), the corresponding commit occurs after a finite, though not necessarily bounded, delay.

- **No ill-formed signal IO.** Every observable signal Read/Write has a unique real bounding synchronization operation on each dynamic path on which it occurs; otherwise, the design is ill-formed. START_P may be used as an initial anchor only when it is included as a real synchronization event in S, and FINISH_P may be used as a terminal anchor only when the process actually terminates. The formal model does not use a virtual synchronization event at ∞ . (From RULE 1 and RULE 2.)
- **Fixed-stimulus interpretation (reactive environments).** If the “same stimulus” includes a reactive testbench and/or peer processes, it is interpreted as the same global Σ -causal behavior (same externally supplied inputs, and the same peer/environment responses to the same prior Σ -visible history), not as a function of P-local history alone. In Appendix I this interpretation is used only as a witness-replay condition: when a next RTL_B event e is already fixed in the chosen post trace prefix, any peer/environment enabling needed for e is part of that same fixed global Σ -causal behavior and is therefore replayed consistently for the matching Sys_ref construction. This is not a standalone assumption that arbitrary Sys_ref continuations are globally live.
- **WC (Witness-compatible non-blocking outcomes).** Because failed polls are modeled as ϵ (unobservable), all correspondence results in Appendices I–K are stated for witness-compatible comparisons: any ϵ -modeled non-blocking poll outcome (and any other ϵ -modeled internal choice that can affect the next Σ -visible control flow / next Σ -visible blocking frontier) is fixed/selected to be consistent with the compared RTL_B execution prefix τ_{post} (e.g., via the Appendix L witness-selection/snooping wrapper). WC also supplies the μ_Q matching for ϵ -modeled failed non-blocking call instances when E3/E5 or the proof construction refers to $q \in Q_{\text{exec},P}$; those failed q ’s are not inferred from Σ alone.
- **Remark (NB-CF as a sufficient condition).** If a design satisfies the following non-blocking control-flow property—failed PopNB/PushNB polls do not influence the next Σ -visible control flow/frontier—then the witness is trivial and WC holds automatically. Equivalently: between two consecutive Σ -events of a process, inserting/removing any finite sequence of failed PopNB/PushNB polls may change only internal ϵ -behavior/timing, not which Σ -visible action (Push/Pop/synchronization anchor) is next in program order.

I.3 Auxiliary Lemmas

Implementation assumption I.A0 (RTL message-issue discipline).

The post-HLS RTL_B execution satisfies E3 as an implementation-side scheduling obligation: (i) per-interface issue order is preserved for all message operations; and (ii) for distinct interfaces, the no-reverse rule holds. This condition is not derived inside Appendix I; it is the RTL/tool-compliance obligation corresponding to the scheduling rules stated in the main text and Appendix G. For hand-written RTL or other non-HLS implementations, I.A0 is the corresponding proof/qualification obligation on that implementation.

Lemma I.1 (Bounded ϵ -chain to Σ -action or stable wait).

Assume the finite-pipeline-depth / finite-internal-stutter premise FPD/B4. From any reachable well-formed cycle-boundary state of P in the Appendix I construction, if P is not already stably waiting on an external/peer enabling condition, then within at most D_P clock cycles of P-local ϵ -progress, P either:

- (i) commits its next observable Σ -action, or
- (ii) reaches a stable waiting state in which no further P-local ϵ -step is available until some external, peer, channel, or stimulus condition changes the relevant enabling predicates.

Equivalently, P cannot produce an infinite P-local ϵ -only execution segment from a reachable well-formed state while remaining internally enabled. Any unbounded delay that remains after the stable-wait point is therefore attributable to external/channel/stimulus enabling and is governed by the WF/B2 and B3 progress premises, not by local ϵ -stutter.

Proof. Direct from FPD/B4, applied only to reachable well-formed states of P in the Appendix I construction. ■

Lemma I.2 (Eventual space / data). Assume P is blocked on either:

- Push_c with $\text{occ}_c = B(c)$, P's Push_c request remains asserted with stable payload for the outstanding transfer, and the complementary endpoint continuously requests the matching Pop_c until the matching discharge event (Pop_c endpoint request asserted; Pop_c boundary request remains true); or
 - Pop_c with $\text{occ}_c = 0$, P's Pop_c request remains asserted for the outstanding transfer, and the complementary endpoint continuously requests the matching Push_c until the matching discharge event (Push_c endpoint request asserted with stable payload; Push_c boundary request remains true).
- Then a complementary Pop_c (respectively Push_c) commits within finite time.

Proof. (By B3 / Appendix N.) In either case, P is stalled at a blocking channel call while its persistent request for that outstanding transfer remains asserted until commit, with stable payload if it is a Push. By the additional premise, the complementary endpoint also continuously requests the matching operation until the corresponding discharge event, with its boundary request remaining true. Therefore the interval-scoped premises of P_push/P_pop (Appendix N) hold, and the corresponding transfer must eventually complete: for Push_c at full, some complementary Pop_c eventually commits, freeing space; for Pop_c at empty, some complementary Push_c eventually commits, providing data. The premise does not require either endpoint request or Push payload to remain asserted after that matching transfer has committed.

■

Definition I.Obs (Σ -relevant source-state slice).

Fix a process P, a fixed external stimulus, and a fixed witness w satisfying WC for the chosen observable boundary. Define $\text{Obs}_{\{\Sigma, P, w\}}(\sigma)$ to be the tuple of P-local source-level facts evaluated at the ϵ -quiescent source state σ that are relevant to future Σ -visible behavior or to the Appendix I–K proof predicates owned by P. This tuple includes: the source control position; source variables and latched

values used to evaluate future control predicates Pred_x , payload/value expressions, anchored Write values, and anchored Read labels under the fixed-stimulus interpretation; witness-selected ϵ outcome information that can affect later Σ -visible control flow, frontier membership, or request attribution; $Q_{\text{exec},P} / Q_{\Omega,P}$ attribution facts needed for E3/E5 or WFG reasoning; Pending_P , NextFront_P , and Front_P membership; and BoundaryReq values for message-operation instances owned by P . Define $\sigma \sim \{\Sigma, P, w\} \sigma'$ iff $\text{Obs}\{\Sigma, P, w\}(\sigma) = \text{Obs}\{\Sigma, P, w\}(\sigma')$. The Σ -relevant source-state slice of σ is its equivalence class $[\sigma]_{\{\Sigma, P, w\}}$.

This quotient intentionally ignores purely internal diagnostic state and ϵ -only micro-timing state that cannot affect any future Σ -visible label, frontier predicate, pending/request-attribution fact, payload/value expression, BoundaryReq predicate, or Appendix K blocking/WFG-facing predicate. $\text{ChannelEnabled} / \text{ChannelDisabled}$ facts are not independently added to this P -local quotient; they are obtained by combining the P -local slice, including BoundaryReq and pending/frontier facts, with the corresponding channel-state facts in the chosen Sys_ref boundary model, such as $B(c)$, $\text{occ}_c(\sigma)$, rendezvous complementary endpoint requests, and any explicit $\text{Sys_B}^{\text{elab}}$ staged/bundle/join boundary state.

For cadence-sensitive non-blocking polling sites, such as retry/timeout counters whose externally visible behavior depends on the number or cadence of failed polls, this definition is applied only after the site has been handled as an isolated or snoop-aligned latency-sensitive local protocol block under Appendix D / Appendix L. The ordinary Appendix I source-core proof does not derive retry/timeout behavior from an unconstrained hidden failed-poll cadence.

Lemma I.Obs-Congruence (one-step closure of the Σ -relevant slice).

Fix P , the external stimulus, the chosen observable boundary, and a witness w satisfying WC. Let σ_1 and σ_2 be ϵ -quiescent source states of P such that $\text{Obs}_{\{\Sigma, P, w\}}(\sigma_1) = \text{Obs}_{\{\Sigma, P, w\}}(\sigma_2)$. Suppose that, from σ_1 and σ_2 , the same next P -local Σ label ℓ is produced under the same witness w and the same fixed-stimulus interpretation, where ℓ includes any committed Push/Pop value, successful non-blocking transfer value, synchronization/wait label, anchored Read value, anchored Write value, $\text{START}_P/\text{FINISH}_P$ event, or other Σ -visible boundary event. Let σ'_1 and σ'_2 be the resulting ϵ -quiescent cutpoint states after that same-label step and its following finite ϵ -closure. Then:

$$\text{Obs}_{\{\Sigma, P, w\}}(\sigma'_1) = \text{Obs}_{\{\Sigma, P, w\}}(\sigma'_2).$$

Proof. By case analysis on the next source construct and on the kind of label ℓ .

For deterministic local computation, equality of the control position and of all variables/latched values feeding future predicates, payloads, anchored writes/reads, guards, and proof predicates implies equality of the updated members of Obs . Updates to variables or diagnostic state not included in Obs cannot affect any later Σ -visible label or Appendix I–K proof predicate by the definition of Obs and the source well-formedness obligations.

For anchored signal reads and writes, the relevant read/write value is either fixed by the common stimulus and anchor or is the common label ℓ ; therefore all future-relevant latched values and anchored-label facts agree after the step.

For blocking Push/Pop and synchronization operations, the common label ℓ , together with equality of the current control position, relevant payload variables, Pending_P , NextFront_P , Front_P , $Q_{\text{exec},P} / Q_{\Omega,P}$ attribution facts, and BoundaryReq facts, determines the same update to all P -owned frontier, pending, request-attribution, and BoundaryReq components of Obs . $\text{ChannelEnabled} / \text{ChannelDisabled}$ is not an independent P -local component; any needed enablement fact is obtained from the common P -local request/frontier facts together with the chosen Sys_ref boundary state and E4.

For successful non-blocking PushNB/PopNB, the successful transfer is included in ℓ as the corresponding committed $\text{Push}_c(v) / \text{Pop}_c(v)$ event. The common label and equal current slice determine the same control, data, attribution, frontier, pending, and BoundaryReq updates.

For failed non-blocking PushNB/PopNB, the failed poll is an ϵ -step. If NB-CF holds, failed polls cannot affect the next Σ -visible control flow, frontier membership, request attribution, guard values, or payload values, so any difference is outside Obs. If NB-CF does not hold but WC is supplied by Appendix L, the failed-poll outcome is fixed by the witness as part of selecting an admissible source execution at the chosen boundary. If the process computes externally visible behavior from the number or cadence of failed polls, the site must already have been isolated or snoop-aligned as a latency-sensitive local protocol block under Appendix D / Appendix L; otherwise the ordinary Appendix I source-core theorem is not applicable to that process at that boundary.

For any other ϵ -only implementation choice, WC requires that every outcome capable of affecting later Σ -visible behavior or Appendix I–K proof predicates is selected by w and is causally consistent with the matched prefix. Thus equal current Obs and the same witness-selected outcome produce equal successor Obs. ϵ -only state not included in Obs is, by the preceding cases and by the construction of Obs, inert with respect to all future labels and proof predicates owned by P .

Therefore equality of Obs is preserved by one same-label cutpoint-to-cutpoint step. ■

Lemma I.DR (Deterministic replay / Σ -relevant source-state determinacy under fixed stimulus + witness). Fix a process P , a fixed external stimulus, and a fixed witness w satisfying WC for the chosen observable boundary. Consider two executions of the same P source code that start from the same initial source-level state and are run with that same witness. If their chosen P -local observable-unit replay projections are the same, then for every k , the Σ -relevant source-state slice of P at the ϵ -quiescent cutpoint after the first k P -local observable units is identical in the two executions. Here “ P -local observable-unit replay projection” means the sequence obtained from the document’s event-matching / Appendix J observable-unit convention: explicitly atomic same-cycle transactions are grouped as single units; independent same-cycle bucket members are not given an intrinsic order by the bucket itself; and any ordering used for deterministic replay is the selected witness/replay order, together with w and μ_Q for ϵ -modeled failed non-blocking $q \in Q_{\text{exec},P}$ when those instances are needed by E3/E5. Thus Lemma I.DR is not a determinacy theorem from a bare unordered Σ -bucket projection alone.

Proof. At $k = 0$ the executions start from the same initial source-level state, so their $\text{Obs}_{\{\Sigma, P, w\}}$ slices agree. For the induction step, assume the slices agree after k P -local Σ -events. The two executions have the same $(k+1)$ -st P -local Σ label and are run under the same fixed stimulus and witness. By Lemma I.Obs-Congruence, the ϵ -quiescent cutpoint states after that label have equal $\text{Obs}_{\{\Sigma, P, w\}}$ slices. Therefore, by induction on k , the Σ -relevant source-state slice agrees at every ϵ -quiescent cutpoint after the first k P -local Σ -events. ■

I.4 Inductive Construction for Finite Traces (Post $\rightarrow$ Ref)

Let

$\tau_{\text{post}} = \tau_{\text{post}}[0..n-1] \circ e$ (where $|\tau_{\text{post}}| = n + 1$)

be the next post-HLS prefix of RTL_B for process P (under the fixed initial state and fixed stimulus).

Assume by induction that we already have a matching Sys_ref prefix $\tau_{\text{ref}}[0..n-1]$ satisfying E1–E5 with $\tau_{\text{post}}[0..n-1]$. We extend τ_{ref} by a finite ϵ -chain (written ϵ^*) followed by an observable action e' so that

$\tau_{\text{ref}} \circ \epsilon^* \circ e'$ matches τ_{post} .

Here Sys_ref is the prescribed source reference model for this process/boundary, as fixed in Appendix J, Remark 2.

Non-blocking note. For a non-blocking PopNB/PushNB call, unsuccessful polls are treated as ϵ -steps. This is sound for Post $\rightarrow$ B construction under the witness-compatible (WC) premise (I.2): ϵ -modeled poll outcomes are either (a) irrelevant to the next Σ -visible control flow/frontier (NB-CF holds), or (b)

fixed/selected consistently with τ_{post} (e.g., via Appendix L), so they do not introduce an unmatched Σ -visible control-flow/frontier divergence. Each executed PopNB/PushNB call still constitutes its own dynamic source-level message-call instance $q \in Q_{\text{exec},P}$ for the owning process P ; WC/NB-CF fixes the ϵ -modeled outcomes of those calls, but it does not identify multiple executed non-blocking call instances as one q merely because the endpoint request stays asserted across cycles. The matching of failed non-blocking q instances, when needed by E3/E5 or by the witness construction, is part of the chosen μ_Q witness and is not reconstructed from Σ . A successful non-blocking call may also be represented in $Q_{\Omega,P}$ when its committed transfer contributes a frontier/observable item; a failed non-blocking poll remains in $Q_{\text{exec},P} \setminus \Omega_P$.

Lemma I.3 (Finite ϵ^* -extension step for I.4).

Let $\tau_{\text{post}} = \tau_{\text{post}}[0..n-1] \circ e$ (where $|\tau_{\text{post}}| = n + 1$) be the next post-HLS prefix of RTL_B for process P (under the fixed initial state and fixed stimulus). Assume by induction that we already have a matching Sys_ref prefix $\tau_{\text{ref}}[0..n-1]$ satisfying E1–E5 with $\tau_{\text{post}}[0..n-1]$. Also assume the global witness/channel-history invariant used by the Appendix I/J construction: the matched prefix fixes the same Σ -causal history, the same selected ϵ -only witness choices covered by WC, the same relevant channel histories/occupancies at the chosen Sys_ref abstract boundaries, and, for any message transfer whose matching RTL_B event is e , the necessary complementary endpoint request or channel-progress premise is supplied by the same matched global execution/witness. Then there exists a Sys_ref extension by a finite ϵ -chain ϵ^* followed by an observable action e' such that:

- (i) $\tau_{\text{ref}} \circ \epsilon^* \circ e'$ matches τ_{post} under the document's Σ -event matching convention; and
- (ii) the extended prefix continues to satisfy E1–E5 (in particular, E3's message-operation issue-order clause holds by Implementation assumption I.A0).

Proof. By cases on the kind of Σ -event e . Lemma I.1 bounds P -local internal progress to the relevant call site by $\leq D_P$ ϵ -steps (or reaches a stable wait with no further ϵ -step available until external enabling changes). The remaining enablement needed for the matching observable action is not inferred from P -local state alone; it is supplied by the matched global witness/channel-history invariant. For Sync/wait and anchored signal I/O events, this means replaying the same environment/peer enabling and the same anchored values from the fixed-stimulus witness. For message-passing events, it means using the matched channel history and the corresponding complementary endpoint request / channel-progress premise at the chosen Sys_ref abstract boundary.

Once the matching operation is continuously ChannelEnabled under E4, weak fairness (B2) guarantees that the scheduler/arbitrator selects it after a further finite, though not necessarily bounded, delay; the selected operation then commits in the selected cycle. For blocking message transfers, if temporary disablement is due only to bounded-capacity/full-or-empty conditions ($\text{occ}_c = B(c)$ for Push_c , $\text{occ}_c = 0$ for Pop_c) or to rendezvous-style complementary-endpoint progress, Lemma I.2/B3 guarantees eventual space/data or rendezvous discharge when its stated persistent-complementary-request / channel-progress antecedents hold in the matched global witness. After that discharge creates ordinary E4 ChannelEnabled status for the pending transfer, the B2 argument applies. Hence ϵ^* is finite under the lemma's global witness/channel-history premises. ■

Case note (what differs across event kinds). For Sync/wait and anchored signal I/O events, the finite ϵ^* step is a witness-replay argument, not an independent global-liveness claim. The lemma conditions on the already chosen next RTL_B event e and, via the fixed-stimulus interpretation above, replays the same peer/environment enabling from the same global Σ -causal history in the Sys_ref witness construction. Thus Lemma I.3 does not assume that peer/environment progress follows from P -local history alone, and it does not preempt the system-level liveness/deadlock arguments of Appendices J

and K. For message-passing events, the corresponding channel availability is likewise read from the matched global channel history and the Appendix N / Lemma I.2 progress premises, including any persistent complementary request needed for a rendezvous or bounded-capacity transfer. Thus Lemma I.3 is a conditional finite-extension step inside the chosen Appendix I/J witness construction, not a standalone proof that P-local progress alone forces the next global message transfer.

I.5 Extension to Infinite Traces (Post $\rightarrow$ Ref)

Fix a process P and a fixed external stimulus/initial state. (For reactive environments, interpret “fixed stimulus” per Appendix I.2, “Fixed-stimulus interpretation (reactive environments).”)

Let p_{post} be any RTL_B execution under this stimulus that is within the intended Appendix J / Theorem J.1 scope (i.e., an execution whose finite prefixes lie in Exec_post; equivalently: an execution that is a fair/progress-satisfying infinite run, using the idle-stutter/time-divergence convention B6 when no further Σ -progress is enabled). Let $\tau_{\text{post},P}$ be the Σ -observable trace of P induced by p_{post} .

Finite- Σ -event case. If $\tau_{\text{post},P}$ contains only finitely many Σ -events $e_1 \dots e_n$ (i.e., after e_n no further Σ -event of P occurs), apply the finite-prefix construction in I.4 to obtain a Sys_ref prefix $\tau_{\text{ref},P[0..n]}$ whose Σ -projection matches $e_1 \dots e_n$ and whose correspondence satisfies E1–E5. Then, by B6, extend $\tau_{\text{ref},P[0..n]}$ to a countably infinite Sys_ref trace by appending idle clock ticks that produce no further Σ -events. This yields an infinite $\tau_{\text{ref},P}$ that remains Σ -equivalent to $\tau_{\text{post},P}$ (viewed under the same B6 idle-stutter extension), since both sides have exactly the same finite Σ -prefix and no further Σ -events thereafter.

Countably-infinite local- Σ -event case. Otherwise, $\tau_{\text{post},P}$ has countably many P-local Σ -events. We construct an infinite Sys_ref trace $\tau_{\text{ref},P}$ by an explicit inductive limit of the finite-prefix construction in I.4.

This paragraph is a per-process construction only. Its event index n ranges over the P-local Σ -events of a single process trace, after applying the document’s per-process Σ -event matching convention. It is not the system-level prefix index used by Theorem J.1, where prefixes advance by required-prefix observable units under $\prec_J$ rather than by requiring preservation of the RTL_B cycle-bucket decomposition.

Let $\tau_{\text{ref},P[0..0]}$ be the empty local prefix. For each $n \geq 0$, assume we have constructed a finite Sys_ref local prefix $\tau_{\text{ref},P[0..n]}$ such that its P-local Σ -projection matches the first n observable P-local Σ -events of $\tau_{\text{post},P}$ and the correspondence satisfies the applicable per-process parts of E1–E5. Let e_{n+1} be the $(n+1)$ -st P-local Σ -event of $\tau_{\text{post},P}$. Apply the I.4 construction step to extend $\tau_{\text{ref},P[0..n]}$ by a finite ϵ^* segment followed by a matching observable event e'_{n+1} , obtaining $\tau_{\text{ref},P[0..n+1]}$ while preserving the per-process E1–E5 obligations.

Because each extension step adds a finite segment, the increasing chain of local prefixes defines a countably infinite Sys_ref process trace $\tau_{\text{ref},P}$ whose every finite local event prefix matches the corresponding local event prefix of $\tau_{\text{post},P}$. Therefore, $\tau_{\text{ref},P} \approx \tau_{\text{post},P}$ at the per-process trace level. When these per-process witnesses are composed in Appendix J, the system-level proof schedules the matched local events into some legal Sys_ref execution satisfying E1–E5, the chosen channel/synchronization semantics, and the explicitly atomic same-cycle obligations. The resulting Sys_ref execution need not use the same observable cycle-bucket decomposition as the RTL_B execution: independent events may be placed in different cycles or grouped differently whenever no E1–E5 rule, channel rule, signal-anchor rule, or explicit synchronization transaction fixes their relative timing.

Scope clarification: this inductive-limit step establishes the per-process Σ -trace witness only (local prefix/trace matching under E1–E5); it does not by itself discharge global fairness/progress obligations (B2/B3) or prove that an arbitrary global Sys_ref continuation is fair/progress-satisfying. Those

execution-level existence/scope obligations are handled in Appendix J / Theorem J.1 via the Exec_post / Exec_ref definitions and qualifiers. ■

Appendix J – System-Level Trace Compatibility Proof

Synchronization-pair well-formedness for $\approx$.

For $\text{SyncChannel/ac_sync}$ operations with paired endpoints, the compared Sys_ref and RTL_B executions use the same dynamic synchronization-transaction pairing. That is, the two endpoint events of a matched sync_out/sync_in transaction are matched by dynamic sync-instance identity, commit as one two-party barrier transaction, and are treated as simultaneous events in the same observable cycle bucket. This synchronization transaction induces the same cross-process before/after ordering as described in the causal-dependency definition.

Equivalently, E1 preserves the per-process source order of synchronization endpoint events, but E1 does not weaken or replace the paired-barrier semantics of $\text{SyncChannel/ac_sync}$. The system-level trace-compatibility predicate $\tau_{\text{ref},\text{system}} \approx \tau_{\text{post},\text{system}}$ is defined only over synchronization-well-formed traces in this sense: if one endpoint of a dynamic $\text{SyncChannel/ac_sync}$ transaction appears in the trace, then the matching endpoint appears in the same observable synchronization transaction, with the same dynamic pairing, in both Sys_ref and RTL_B .

Theorem J.1 (Execution-Level / Trace-Set Compositional Compatibility)

Fix an initial state and a fixed external stimulus/environment behavior (e.g., the same testbench-driven inputs) for both the prescribed source reference model Sys_ref and RTL_B , with Sys_ref as defined in Remark 2. The raw rendezvous model Sys is the special case obtained when $\text{Sys_ref} = \text{Sys_B}$ and all effective capacities are zero.

Clarification (reactive environments). Interpret “fixed stimulus” per Appendix I.2, “Fixed-stimulus interpretation (reactive environments).”

Let Exec_post denote the set of finite execution prefixes of RTL_B that are reachable under this stimulus and that are prefixes of at least one (infinite) execution under the same stimulus that satisfies the Appendix J fairness/progress premises; and let Exec_ref denote the corresponding set of finite execution prefixes of Sys_ref (defined analogously).

Cycle-bucket and required-prefix convention for this theorem. A system execution may be represented as a sequence of observable cycle buckets $\beta_1 \beta_2 \dots$, where β_i is the finite set of Σ -events committed in one observable clock cycle of that particular execution. Same-cycle events inside a bucket are unordered except for the explicit constraints imposed by E1–E5, the channel semantics, signal-anchor semantics, and explicit synchronization constructs.

The bucket decomposition records the clock timing of one execution; it is not, by itself, part of the cross-model compatibility obligation. The relation $\tau_{\text{ref},\text{system}} \approx \tau_{\text{post},\text{system}}$ does not require Sys_ref and RTL_B to use the same observable cycle-bucket decomposition. Events that are not ordered by the explicit required constraints may be placed in different cycles or grouped into different buckets in the two executions, provided the matched executions preserve all ordering, timestamp, FIFO-legality, and

atomicity constraints required by E1–E5 and by the explicitly modeled channel, signal, and synchronization semantics.

The prefix order used by Theorem J.1 is required-prefix order over matched observable units, not RTL_B bucket-prefix order and not the full Appendix G causal-dependency graph $\rightarrow$. An observable unit is either:

- a singleton Σ -event; or
- an explicitly atomic same-cycle transaction that the semantics requires not to be split, including a rendezvous Push_c(v)/Pop_c(v) transfer, the two endpoints of a paired SyncChannel/ac_sync transaction, an R2C combinational fixed-point signal-observation unit, and any other same-cycle transaction explicitly identified by the signal/channel semantics.

Let $<_J$ be the strict required-order relation over observable units generated only by the explicit constraints that must be preserved by $\tau_{\text{ref,system}} \approx \tau_{\text{post,system}}$:

- E1 synchronization source-order constraints within each process;
- E2 signal-anchor timestamp constraints, interpreted as required alignment with the relevant synchronization or R2C fixed-point unit rather than as raw ordering among all source actions;
- E4 channel/FIFO legality for explicit abstract channels, including same-channel FIFO order for $B(c)>0$ and atomic rendezvous grouping for $B(c)=0$;
- E5 immediate synchronization-boundary constraints;
- paired SyncChannel/ac_sync barrier semantics; and
- any other explicitly stated signal/channel/synchronization atomicity constraint.

Per-process source order contributes to $<_J$ only where it is reflected in one of these explicit required constraints, such as synchronization order, same-endpoint/same-channel order, signal anchoring, or immediate synchronization-boundary legality. E3 contributes issue-order and request-attribution obligations, but it does not by itself create a strict predecessor edge between distinct-interface committed observable units merely because their source calls are lexically ordered. The Appendix G causal-dependency relation $\rightarrow$ is not a generator of $<_J$.

A theorem prefix is a finite ideal of observable units under $<_J$, i.e. a finite down-closed set H such that $\gamma \in H$ and $\gamma' <_J \gamma$ imply $\gamma' \in H$. The proof below proceeds by induction along a fixed RTL-time chain of such finite ideals, chosen from the RTL_B witness prefix as described below. Acyclicity of $<_J$ on the fixed execution prefix. For the chosen legal RTL_B execution prefix, assign each observable unit $\gamma \in U(\tau_{\text{post}})$ its RTL_B commit cycle $\text{clk}(\gamma)$. If γ is an explicitly atomic same-cycle unit, such as a rendezvous Push_c(v)/Pop_c(v) transfer or a paired SyncChannel/ac_sync transaction, $\text{clk}(\gamma)$ is the common commit cycle of the endpoints in that atomic unit.

Every strict generator edge $\gamma_1 <_J \gamma_2$ implies a strict cycle inequality $\text{clk}(\gamma_1) < \text{clk}(\gamma_2)$ in that same legal execution prefix:

- E1 synchronization source-order constraints impose strict ordering between the relevant synchronization commits.
- E4 buffered-channel FIFO/order/capacity constraints impose strict commit-cycle ordering through reset-empty FIFO order, bounded occupancy, and non-fall-through cycle-boundary availability. In particular, for $B(c)>0$, a Pop_c can consume only a value already present at the relevant cycle boundary, and a Push_c that depends on space becoming available after a full condition is enabled only in a later cycle after the required Pop_c effect has occurred.
- E5 immediate synchronization-boundary constraints impose strict separation between a synchronization commit and later suff_S work whose issue/commit is after that synchronization

boundary.

- Paired synchronization/barrier before/after constraints impose the corresponding strict before/after cycle relation between distinct observable units when such a relation is explicitly part of the synchronization semantics.
- E2 signal-anchor constraints contribute timestamp equality/alignment to the relevant synchronization or R2C fixed-point unit, or same-cycle atomicity when explicitly specified; they do not by themselves introduce an independent strict edge between distinct observable units.
- Rendezvous Push/Pop endpoints, paired same-cycle synchronization endpoints, and other explicitly atomic same-cycle transactions are represented as single observable units, not as strict internal edges.
- Non-strict issue simultaneity permitted by E3 does not create a strict $<_J$ edge.

Therefore any cycle $\gamma_0 <_J \gamma_1 <_J \dots <_J \gamma_0$ over $U(\tau_{\text{post}})$ would imply $\text{clk}(\gamma_0) < \text{clk}(\gamma_1) < \dots < \text{clk}(\gamma_0)$, an impossibility. Hence $<_J$ is acyclic on $U(\tau_{\text{post}})$, which is the only acyclicity needed for the finite-ideal induction. For the proof of Theorem J.1, we use a particular topological enumeration that refines the chosen RTL_B witness's commit-cycle / issue-attribution order. Its prefixes are ideals under $<_J$, but the enumeration itself has no semantic significance and must not be read as adding an observable order among independent events. There is no semantic cutpoint after only one endpoint of an explicitly atomic multi-endpoint unit has been taken; such units are split neither in Sys_ref nor in RTL_B.

Scope note (intentional). Appendix J is a correspondence result about fair/progress-satisfying infinite behaviors. We adopt the time-divergence / idle-stutter convention B6: from any reachable ϵ -quiescent state, the system can always be extended to an infinite execution under the same stimulus by appending idle clock ticks that produce no Σ -events. We also note the following stutter-closure/vacuity fact: the Appendix J fairness/progress premises (weak fairness B2 and channel progress invariants B3) constrain only intervals in which some relevant Σ -action/transfer is continuously enabled. Once the ϵ -quiescent fixed point of B5 is reached (no further internal ϵ micro-steps are possible and no observable action is enabled), appending idle-stutter ticks does not create any newly enabled observable actions or transfers; therefore B2/B3 remain satisfied (vacuously) on the idle suffix. Consequently, if an ϵ -quiescent cutpoint is a B5 fixed point, the idle-stutter extension is itself fair/progress-satisfying and the prefix lies in Exec_post / Exec_ref. For ϵ -quiescent cutpoints that are not B5 fixed points (i.e., some observable Σ -action/transfer is enabled), membership in Exec_post / Exec_ref depends on the existence of some infinite extension that satisfies B2/B3; idle-stutter alone need not suffice. The qualifier exists to exclude only prefixes that are inconsistent with the stated fairness/progress premises (i.e., prefixes that arise only under unfair scheduler/environment behavior).

Assume the Appendix I / Appendix L witness machinery is available as follows—namely: the per-process Post $\rightarrow$ Ref witness construction from Appendix I, including the witness-compatibility premise WC for ϵ -modeled non-blocking polls (and any other ϵ -only internal choices that can affect the next Σ -visible control flow/frontier) as stated in Appendix I.2 and enforceable via Appendix L's snooping / witness-selection technique; with NB-CF as a sufficient condition that makes the witness trivial—together with the capacities/occupancies/enablement semantics of Sys_ref, finite capacities on every explicit abstract channel of Sys_ref, channel progress invariants P_push / P_pop (B3), weak fairness (B2), and the standing RTL_B determinism assumption B1 under the fixed stimulus. Use B4/B5 additionally when ϵ -normalization or uniqueness up to finite ϵ -stutter is invoked. Then:

Compatibility-relation typing convention. The symbol $\approx$ is an ordered cross-model compatibility predicate, not a mathematical equivalence relation. It is intentionally directed from a Sys_ref

execution/projection to an RTL_B execution/projection, and no symmetry or transitivity property is implied. Its carrier is not a bare Σ -label trace alone.

For each process P , the per-process carrier is an annotated observable projection record. Such a record contains the P -local bucketed Σ projection, the relevant observable-unit projection, the dynamic source/witness universe Ω_P and Q_exec, P used for that comparison, the Issue/Commit annotation for dynamic message-call instances, the selected witness w , and the μ_Q matching supplied by WC / Appendix L when ε -modeled failed non-blocking calls or other witness-selected choices are relevant. Forgetting these annotations yields the ordinary P -local observable Σ projection, but E3, E5, BoundaryReq attribution, and the witness construction may depend on the annotations and are not reconstructed from the Σ projection alone.

Accordingly, write

$$\approx_P \subseteq \text{AnnTraces}_{\{\Sigma, P, w\}}(\text{Sys_ref}) \times \text{AnnTraces}_{\{\Sigma, P, w\}}(\text{RTL_B})$$

for the per-process annotated observable-compatibility predicate induced by the P -local R/E obligations: synchronization ordering, signal anchoring or R2C fixed-point agreement, message issue-order constraints, synchronization-boundary issue constraints, and the P -local witness/request-attribution facts needed for those obligations. Here $\text{AnnTraces}_{\{\Sigma, P, w\}}(\cdot)$ denotes the annotated projection records just described, not merely $\text{Traces}_{\{\Sigma, P\}}(\cdot)$.

Similarly, write

$$\approx_sys \subseteq \text{AnnTraces}_{\{\Sigma, w\}}(\text{Sys_ref}) \times \text{AnnTraces}_{\{\Sigma, w\}}(\text{RTL_B})$$

for system-level annotated observable compatibility. A system-level annotated record includes the per-process annotated projections plus the explicit abstract-channel histories and boundary-state facts needed to check E4 at the chosen Sys_ref / RTL_B boundaries.

For system executions $\tau_ref, system$ and $\tau_post, system$, the assertion $\tau_ref, system \approx_sys \tau_post, system$ is therefore an abbreviation: there exist compatible annotation/witness records for the two executions such that every process projection satisfies the corresponding $\tau_ref, P \approx_P \tau_post, P$ obligation and every explicit abstract channel in the chosen Sys_ref / RTL_B comparison satisfies the applicable E4 channel semantics at the agreed abstract boundary. When the annotations are clear from context, the same $\tau_ref \approx \tau_post$ notation may be used for readability; it should not be read as typing $\approx$ over bare Σ -traces alone.

Then:

(Post $\rightarrow$ Ref existence) For every $\tau_post \in \text{Exec_post}$ together with its selected RTL_B witness/annotation package, there exists $\tau_ref \in \text{Exec_ref}$ and a matching Sys_ref witness/annotation package such that the annotated system projections satisfy $\tau_ref, system \approx_sys \tau_post, system$ under E1–E5.

(Ref $\rightarrow$ Post existence, selected/RTL-consistent prefixes only) For every $\tau_ref \in \text{Exec_ref}$ whose annotated Σ projection is RTL-consistent under the same fixed stimulus—meaning that its observable-unit projection matches a required-prefix projection of some selected $\tau_post^{*} \in \text{Exec_post}$ admitted by RTL_B under that stimulus, equivalently, by the standing B1 assumption for RTL_B , a prefix of the unique RTL_B Σ trace—there exists $\tau_post \in \text{Exec_post}$ with a compatible witness/annotation package such that the annotated system projections satisfy $\tau_ref, system \approx_sys \tau_post, system$. In Appendix L snooping/witness-selection applications, the selected τ_post^{*} is the RTL_B execution prefix selected by the snooping wrapper/witness.

Moreover, when B1 holds (deterministic Σ -projected trace under fixed stimulus), the matching observable Σ projection is unique (up to insertion/removal of finite ε -steps permitted by B4/B5). This uniqueness is only a uniqueness statement about the observable projection; it does not by itself

determine μ_Q , failed-poll instances in Q_{exec} , issue annotations, request-attribution facts, or the full stateful Sys_ref witness. The corresponding execution prefix witness τ_{ref} need not be unique as a stateful prefix, since Sys_ref may admit multiple ε -different realizations with the same Σ projection. Sys_ref may also admit executions whose Σ projection does not match RTL_B 's Σ trace when latency-sensitive / non-blocking effects are Σ -visible; such executions are outside the scope of $(\text{Ref} \rightarrow \text{Post})$ unless constrained by the snooping/witness-selection technique (Appendix L).

Proof strategy. Theorem J.1 is not obtained from pairwise composition alone. Proposition J.0 below is only the conditional lifting step for a chosen compatible pair of system traces. The actual execution-level theorem is obtained by combining that conditional lifting step with the Appendix I / Appendix L witness machinery and the Exec_post / Exec_ref scope conditions, as proved later in this appendix under “Proof of Theorem J.1 (expanded execution-level witness construction).”

Proposition J.0 (Pairwise Composition Lemma)

Fix any test stimulus (environment inputs) and initial state. Let $\tau_{\text{ref},\text{system}} \in \text{Traces}_\Sigma(\text{Sys_ref})$ be an observable system trace of the prescribed source reference model Sys_ref under that stimulus, and let $\tau_{\text{post},\text{system}} \in \text{Traces}_\Sigma(\text{RTL_B})$ be an observable system trace of RTL_B under the same stimulus. For each process P , let $A_{\text{ref},P}$ and $A_{\text{post},P}$ be the annotated P -local projection records induced by $\tau_{\text{ref},\text{system}}$ and $\tau_{\text{post},\text{system}}$ under the chosen witness/annotation package. Their forgotten observable components are the ordinary projections $\tau_{\text{ref},P}$ and $\tau_{\text{post},P}$, but the records also carry the issue annotations, dynamic message-call universe, μ_Q matching, and request-attribution facts needed by E3/E5 and WC. Assume that for every process P , these annotated projections satisfy the per-process compatibility predicate $A_{\text{ref},P} \approx_P A_{\text{post},P}$. In readable prose below, this may be abbreviated as $\tau_{\text{ref},P} \approx_P \tau_{\text{post},P}$ when the annotation package is fixed by context.

Thus Proposition J.0 is only a conditional composition result for a chosen compatible trace pair. By itself it is not yet an execution-set theorem and does not provide unrestricted source $\leftrightarrow$ RTL correspondence. Theorem J.1 is the later execution-level result obtained by instantiating Proposition J.0 with the witness construction and scope restrictions stated in Appendix I / Appendix L and in the Exec_post / Exec_ref definitions.

Assume every explicit abstract channel c in the chosen Sys_ref / RTL_B comparison has finite capacity $B(c) \geq 0$. Also assume, as a per-channel Sys_ref / RTL_B well-formedness condition, that both chosen traces satisfy the applicable E4 channel semantics at the chosen abstract boundaries. Thus, for $B(c)=0$ channels, committed Push_c / Pop_c events obey the same-cycle rendezvous semantics; for $B(c)>0$ channels, the committed Push_c / Pop_c history obeys the reset-empty, cycle-boundary, non-fall-through bounded-FIFO semantics with capacity $B(c)$, including FIFO order, no underflow, no overflow, no duplication, and no loss. Proposition J.0 does not derive these per-channel E4 facts; it assumes them as part of the definition of the compared well-formed Sys_ref / RTL_B traces.

No weak-fairness or channel-progress premise is needed for this conditional pairwise lifting lemma: Proposition J.0 does not construct a matching trace, but only lifts already-compatible per-process trace projections and already well-formed per-channel communication histories to the aggregate system trace. The weak-fairness, progress, and witness-construction premises are used later in Theorem J.1 when proving the execution-level existence result. Then the aggregate traces are compatible: $\tau_{\text{ref},\text{system}} \approx_{\text{sys}} \tau_{\text{post},\text{system}}$ under rules E1–E5 (given the R rules and B rules).

Notation: The order relation $<_{\text{src}}$ used below is the dynamic source-induced order from Appendix G / R1–R4: it ranges over dynamic operation instances in the compared execution / witness, not over all syntactic call sites in the source text. Equivalently, when the process must be explicit, write $<_P$. Untaken branches and unexecuted loop iterations are not members of the witness-specific dynamic

universe.

Proof

We prove each compatibility property. The per-channel E4 facts are not derived inside this proposition; they are part of the per-channel Sys_ref / RTL_B well-formedness hypothesis for the chosen traces.

E1 (Synchronization-order preservation):

Fix any process P. By the proposition hypothesis, $\tau_{\text{ref},P} \approx_P \tau_{\text{post},P}$, so the synchronization events of P occur in the same source order in both traces. Since this holds for every P, E1 holds for the system traces $\tau_{\text{ref},\text{system}}$ and $\tau_{\text{post},\text{system}}$.

E2 (Signal-visibility preservation):

Fix any process P. If P is a sequential process, then by the proposition hypothesis (using the E2 anchoring relation embodied in $\tau_{\text{ref},P} \approx_P \tau_{\text{post},P}$), every signal Read in P is anchored to P's closest preceding synchronization event, and every signal Write in P is anchored to P's closest succeeding synchronization event, in both $\tau_{\text{ref},P}$ and $\tau_{\text{post},P}$.

If P is a combinational process, then R2C rather than pred_S/succ_S anchoring applies: P's observable signal Read/Write events are represented by the R2C fixed-point signal-observation unit for the relevant combinational process/network component, matched by that component's local R2C occurrence ordinal as specified in the R2C unit matching/index convention. By the combinational well-formedness condition and the compatibility hypothesis for the fixed stimulus / selected witness, the pre-HLS and post-HLS combinational networks reach corresponding unique ϵ -fixed-point valuations for the matched R2C occurrence unit, so the matched Read/Write labels agree within that fixed-point unit. This local R2C-unit agreement is an explicit atomicity constraint; it does not require Sys_ref and RTL_B to use the same global observable cycle-bucket decomposition for unrelated independent events.

Since the appropriate sequential or combinational signal-visibility condition holds for every process P, E2 holds for $\tau_{\text{ref},\text{system}}$ and $\tau_{\text{post},\text{system}}$.

E3 (Safe message issue ordering):

Fix any process P. E3 is the post-side issue-order conjunct of the per-process compatibility relation $\approx_P$, not an additional ordering property derived from the Sys_ref trace. Thus what must be checked here is that P's post-HLS execution satisfies E3 as stated in Appendix G: (i) for same-interface pairs $q_1, q_2 \in Q_{\text{exec},P}$ with $q_1 <_{\text{src}} q_2$, we have $\text{issue_post}(q_1) \leq \text{issue_post}(q_2)$; and (ii) for distinct interfaces that appear in sequence in the source ($q_1 <_{\text{src}} q_2$), the operations are not issued in reverse order. This post-side property is part of the local per-process hypothesis $\tau_{\text{ref},P} \approx_P \tau_{\text{post},P}$; in the execution-level use of Proposition J.0 / Theorem J.1, the needed post-side witness/order fact is supplied by Appendix I / Implementation assumption I.A0. Since the E3 post-side conjunct holds for every P, the aggregate system pair satisfies E3.

E4 (Per-channel channel semantics):

E4 holds by the per-channel Sys_ref / RTL_B well-formedness hypothesis of Proposition J.0. That hypothesis states that, for every explicit abstract channel c in the chosen comparison, the Sys_ref and RTL_B traces already satisfy the applicable E4 channel semantics at the chosen abstract boundary: same-cycle rendezvous semantics when $B(c)=0$, and reset-empty, cycle-boundary, non-fall-through bounded-FIFO semantics when $B(c)>0$. Thus Proposition J.0 uses E4 as an assumed channel-realization condition for the chosen traces; it does not attempt to derive E4 from the per-process compatibility relation. Accordingly, Proposition J.0 should be read as a composition theorem under already-established process and channel conformance hypotheses. It does not prove that the implementation realizes the chosen abstract channel boundaries, nor that the back-annotated capacities $B(c)$ satisfy B-faithfulness as defined in the Common Formal Definitions. Those facts are separate RTL/tool-flow compliance obligations required before the theorem is applied to a concrete generated design.

E5 (Messages cannot cross syncs):

For every synchronization call s (in the source order used by $R3$ / pref_S / suff_S over Q_{exec}, P):

$\forall q \in \text{pref_S}(s) : \text{issue_post}(q) \leq \text{clk_post}(s)$

$\forall q \in \text{suff_S}(s) : \text{issue_post}(q) > \text{clk_post}(s)$

(Note: For blocking message transfers, the “no-withdraw”/persistence semantics imply that if a blocking operation is issued in the pre-side interval before s , then it must also commit no later than s (and similarly on the post side), because the process cannot complete s until all earlier-issued blocking requests in that interval have committed. Failed non-blocking polls in Q_{exec}, P are constrained at the issue level by this rule but contribute no committed Σ -event when they fail.)

This property is guaranteed per-process by the proposition hypothesis on the chosen compatible pair (with Appendix I supplying the witnesses in the execution-level $\text{Post} \rightarrow \text{Ref}$ use case) and requires no inter-process reasoning, so it lifts directly to the system level.

Conclusion:

All five compatibility properties hold at the system level for this chosen compatible trace pair. The composition is valid because:

- Intra-process properties are preserved by the per-process compatibility hypothesis.
- Inter-process communication respects the applicable E4 channel semantics by the per-channel Sys_ref / RTL_B well-formedness hypothesis for the chosen traces.
- No additional progress or fairness argument is needed inside Proposition J.0, because this lemma does not construct or extend executions; it only composes already-given compatible projections and already well-formed per-channel communication histories. Progress, fairness, and witness existence are used later in Theorem J.1 when this pairwise lemma is instantiated at the execution-set level.

Therefore, $\tau_{\text{ref}, \text{system}} \approx \tau_{\text{post}, \text{system}}$. $\square$

Remark 1. When $\text{Sys_ref} = \text{Sys_B}$ and all $B(c)=0$, Sys_ref coincides with the rendezvous interpretation of Sys , so Proposition J.0 and Theorem J.1 both specialize to the rendezvous case. In the elaborated cases, the source-side proof target is $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$.

Remark 2 (Reference-model ladder: raw Sys , abstract Sys_B , and elaborated $\text{Sys_B}^{\text{elab}}$).

The Matchlib library provides a capacity back-annotation feature that extracts finite capacities $B(c)$ from the RTL realization of each message-passing channel and makes them available to the source-level model. To avoid ambiguity, this document distinguishes three source-side models:

- Sys : the raw source-level rendezvous interpretation of the user-written processes, i.e., the model obtained when every effective channel capacity is zero and no additional abstract realization structure is introduced.
- Sys_B : the abstract bounded-FIFO source-level interpretation of the same user-written processes under E4, with finite capacities $B(c)$ at the chosen abstract channel boundaries. When all $B(c)=0$ and no additional abstract realization structure is needed, Sys_B coincides with Sys .
- $\text{Sys_B}^{\text{elab}}$: the elaborated back-annotated source-level model used in the more complex cases discussed in Appendix B / Appendix Q, in which additional explicit abstract staged/bundle/join channels are introduced so that conjunctive/join dependencies, synchronization-boundary ramp-down / epoch-gating, occupancies, and enablement are represented at explicit abstract boundaries rather than as hidden predicates at the outer Σ -visible endpoints.

Formal proof target. Unless a statement explicitly says otherwise, the formal results of Appendices J–K target the prescribed source reference model Sys_ref , defined as follows:

- (i) $\text{Sys_ref} = \text{Sys_B}$ in the ordinary case where finite capacities $B(c)$ at the chosen abstract boundaries suffice to capture the RTL realization; and
- (ii) $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$ in the elaborated cases where additional explicit abstract staged/bundle/join channels or explicit sync-boundary / epoch-gate channels are required.

In particular, if an RTL pipeline with an explicit synchronization boundary ramps down by draining already accepted work and withholding producer-facing availability for capacity usable only after the synchronization call commits, then the prescribed source reference model is $\text{Sys_B}^{\text{elab}}$. That withholding shall be represented as ordinary `ChannelDisabled` behavior at an explicit abstract boundary of $\text{Sys_B}^{\text{elab}}$. It shall not be modeled as an extra hidden disablement predicate on an outer bounded channel whose E4 occupancy test would otherwise make the transfer enabled.

For a simple pipelined loop with a single message-passing input and output, Sys_ref is ordinarily just Sys_B : the RTL pipeline’s internal staging capacity is accounted for entirely by the back-annotated effective capacity $B(c)$ at the chosen Sys_B channel boundary. Concretely, Sys_B still has exactly one Σ -visible `Push_c(v)` at the producer endpoint and one Σ -visible `Pop_c(v)` at the consumer endpoint. With overlapped iterations, the post-HLS RTL may accept/read-ahead up to $B(c)$ values into internal pipeline staging before older iterations produce their corresponding outputs; these accept/read-ahead transfers are modeled as internal microstate (ϵ) within the concrete realization contributing to $B(c)$. The RTL may realize this staging on either side of a particular module-local “Pop interface” handshake point; that handshake point need not coincide with the chosen Σ -visible Pop endpoint. By construction, the chosen Sys_B boundary encloses all staging counted in $B(c)$ between the Σ -visible endpoints, so movements within that enclosed realization (including stage-to-stage handoff) do not create additional Σ -visible committed Push/Pop events beyond the single boundary Push/Pop events.

In more complex cases such as HW pipelines with multiple message-passing inputs, the back-annotation mechanism may elaborate the source-side simulation into $\text{Sys_B}^{\text{elab}}$ by introducing additional explicit abstract realization structure. In those cases the formal target is $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$, and $B(\cdot)$, $\text{occ_}\cdot(t)$, E4, `BoundaryReq`, `ChannelEnabled`/`ChannelDisabled`, and the Appendix K blocking/WFG machinery are interpreted over the explicit abstract channels of that elaborated model. See Appendix B and Appendix Q.

Note that in all cases the elaborated structure (staged/bundle/join channels, combinational couplers, and the projection map Π_{elab}) introduced for a particular pipelined realization is local to that process's side of the abstract channels at its boundaries. The complementary endpoint processes see only the abstract Σ -visible channels at the boundary and are unaffected by the elaboration choices.

For Lean-style formalization, the phrase “chosen Sys_ref ” should be read as an explicit theorem parameter: either Sys_B itself, or $\text{Sys_B}^{\text{elab}}(E)$ for a well-formed elaboration package E as defined in Appendix Q. Likewise, references to the Appendix I/L witness machinery assume either NB-CF or a witness selector W satisfying Lemma L.2.

Side-condition audit before theorem application. Applying Theorem J.1 to a concrete design requires instantiating the side-condition discharge record from the Common Formal Definitions. In particular, the proof/application must identify whether Sys_ref is ordinary Sys_B or elaborated $\text{Sys_B}^{\text{elab}}(E)$, whether failed non-blocking polls are covered by NB-CF or by a witness selector W satisfying Appendix L, whether the selected Theorem J.1 / Corollary J.1 cutpoints discharge `J.AbsConf` for the same selected $(\rho_{\text{post}}, \sigma_{\text{ref}}, w)$, and whether any liveness/deadlock use also discharges $K\epsilon$ and the Appendix K/N

progress assumptions. Thus Theorem J.1 should be read as a conditional theorem over an explicit assumption package, not as a claim that WC, NB-CF, Sys_B^{elab}, snooping, J.AbsConf, or K_ε are automatically satisfied by ordinary HLS synthesis.

Remark 3 (Practical rendezvous liveness screening under determinism).

When B1 holds and the design’s control flow does not branch on empty/full observations of non-blocking interfaces (i.e., it depends only on the ordered history of observable Push/Pop/synchronization actions, not on “probe” outcomes (NB-CF, Appendix I.2)), the rendezvous specialization B(c)=0 is often an effective practical screen for design-level deadlocks: it exercises the most constrained communication discipline and can expose true cyclic data-dependency deadlocks early. Because rendezvous is strictly more constrained than buffered/elaborated operation, it can also yield false positives: a deadlock observed under B(c)=0 may disappear once finite buffering or explicit elaborated staged/bundle/join structure is present. However, bounded buffering can still introduce capacity-induced deadlocks (FIFO-depth artifacts) when FIFO depths are underestimated; these deadlocks are real for that modeled capacity configuration but may disappear once capacities are increased to the intended design point. Increasing buffer capacity (or applying dynamic buffer-growth strategies) is a standard way to distinguish depth-limited deadlocks from true cyclic dependency deadlocks. Accordingly, the formal results of Appendices J–K deliberately target the prescribed source reference model Sys_ref of Remark 2, with the actual back-annotated capacities and explicit abstract boundaries required by the chosen realization, rather than relying on rendezvous alone.

Remark 4 (When raw Sys may be used instead of the prescribed source reference model for safety-only checks).

If verification is concerned only with safety properties over the chosen DUT-boundary projection Σ (denote it Σ_{DUT}) (and not with deadlock/liveness), the prescribed source reference model Sys_ref of Remark 2 remains the default reference model. This is because Σ_{DUT} includes committed channel-transfer events, and bounded buffering / explicit staged-bundle-join structure generally changes the set/timing of those committed Push_c/Pop_c events relative to the raw rendezvous case.

Practical note (early bring-up): Before accurate capacities B(c) are available (or before back-annotation/elaboration can be used), running the rendezvous specialization Sys against the intended testbench is still useful to validate functional intent and catch gross protocol/ordering bugs early; however, it remains a screening check, not a proof about the buffered/elaborated RTL-correspondent model.

Important (soundness): When any channel or explicit abstract staged/bundle/join boundary that can influence Σ_{DUT} -observable behavior has positive effective capacity or nontrivial enablement structure, the raw rendezvous model Sys is often a restriction of Sys_ref / RTL_B at Σ_{DUT} (it can admit fewer Σ_{DUT} behaviors). Therefore, using Sys in place of Sys_ref is generally suitable only as a debug/screening check: a failure can be useful diagnostically, but a pass does not by itself prove Σ_{DUT} -safety of the buffered/elaborated implementation.

Sys may be used as a proof-equivalent substitute for Sys_ref only when Sys and Sys_ref are Σ_{DUT} -equivalent for the chosen Σ_{DUT} (i.e., their Σ_{DUT} -projected trace sets coincide under the intended stimulus). A simple sufficient condition is that every Σ_{DUT} -visible explicit abstract channel/boundary in Sys_ref has effective capacity zero and that buffering/elaboration elsewhere is Σ_{DUT} -opaque (it cannot enable/disable/reorder Σ_{DUT} -events or change when Σ_{DUT} -events occur). In all other cases—i.e., if any Σ_{DUT} -visible explicit abstract boundary has positive effective capacity, or if buffered/elaborated internal channels can affect when Σ_{DUT} -events occur—use the prescribed Sys_ref of Remark 2.

Formal soundness condition. Let Traces_ Σ_{DUT} (M) denote the set of Σ_{DUT} -projected traces of model M under the intended fixed stimulus. Sys may replace Sys_ref for proving a universal Σ_{DUT} -safety

property ϕ only if $\text{Traces}_{\Sigma_DUT}(\text{Sys}) = \text{Traces}_{\Sigma_DUT}(\text{Sys_ref})$; under that condition, $\text{Sys} \models \phi$ iff $\text{Sys_ref} \models \phi$ (and otherwise Sys is only a diagnostic/screening check as stated above).

Proof of Theorem J.1 (expanded execution-level witness construction)

We now prove the execution-level clauses of Theorem J.1 by explicit witness construction. We first prove (Post $\rightarrow$ Ref). The (Ref $\rightarrow$ Post) clause is not a symmetric arbitrary-source witness construction. It is a selected-prefix / RTL-consistency clause: it applies only when the source prefix has already been restricted by Theorem J.1 (or by Appendix L's snooping / witness-selection mechanism) to match a selected RTL_B execution prefix under the same fixed stimulus. The proof for that clause is given after the Post $\rightarrow$ Ref construction by choosing that selected RTL_B prefix and applying the compatibility and finite-ideal obligations relative to the chosen RTL_B witness, rather than constructing an RTL execution from an arbitrary Sys_ref run.

Fix $\tau_{\text{post}} \in \text{Exec_post}$ and consider a finite observable prefix of τ_{post} , followed, when needed, by maximal finite ε -normalization (B4/B5) to an ε -quiescent RTL_B cutpoint σ_{post} . The RTL_B execution may be displayed as observable cycle buckets $\beta_1 \beta_2 \dots$, but those buckets are used here only to identify the timing of that RTL_B execution and to identify explicitly atomic same-cycle units. They are not the prefix index for the cross-model compatibility proof.

Let $U(\tau_{\text{post}})$ be the finite set of observable units in the chosen RTL_B prefix, where a unit is either a singleton Σ -event or an explicitly atomic same-cycle transaction as defined in the cycle-bucket and required-prefix convention above. Let $<_J$ be the strict required-order relation from Theorem J.1: it is generated only by the explicit E1–E5 ordering/timestamp/issue-side obligations that impose required predecessors on observable units, by E4 channel/FIFO legality, by signal-anchor semantics, by paired synchronization/barrier semantics, and by explicitly stated signal/channel/synchronization atomicity constraints. It is not generated by raw per-process source order on distinct-interface message commits, and it is not generated by the full Appendix G causal-dependency graph $\rightarrow$.

Let $\text{Ideals}(U(\tau_{\text{post}}), <_J)$ be the finite ideals $H \subseteq U(\tau_{\text{post}})$, i.e. the finite down-closed subsets of observable units under $<_J$. The empty set $\emptyset$ is the initial ideal, and the complete chosen RTL_B prefix $U(\tau_{\text{post}})$ is itself the terminal ideal. Since $<_J$ is acyclic on $U(\tau_{\text{post}})$, topological enumerations exist.

The witness construction below does not require extension from every proper ideal, and it does not allow an arbitrary $<_J$ -minimal unit to be selected out of RTL_B witness order. Instead, fix once and for all a realizable RTL-time enumeration

$\gamma_1, \gamma_2, \dots, \gamma_m$

of the observable units in $U(\tau_{\text{post}})$, with the following properties:

- If $\text{clk}(\gamma_i) < \text{clk}(\gamma_j)$ in the chosen RTL_B execution prefix, then $i < j$.
 - Explicitly atomic same-cycle transactions, such as rendezvous Push_c(v)/Pop_c(v) transfers and paired SyncChannel/ac_sync transactions, appear as single units.
 - Within a single RTL_B commit cycle, units not ordered by $<_J$ may be listed in any order compatible with the selected RTL_B witness/replay attribution: for each participating process P, the unit listed next is one whose source operation is either reached as a next-frontier operation in the P-local replay state determined by the already-listed P-local units, or is already issued and pending under the chosen WC / issue-attribution witness.
 - The enumeration is obtained from the chosen RTL_B witness prefix itself after grouping

explicitly atomic same-cycle transactions; it is a proof device and does not add an observable order among units that are unordered by $<_J$.

For $0 \leq k \leq m$, define

$$H_k = \{ \gamma_i \mid 1 \leq i \leq k \}.$$

By the acyclicity argument above, every strict $<_J$ edge increases RTL_B commit cycle. Therefore the prefix consisting of all units before any given RTL_B commit cycle is down-closed under $<_J$. Within a single commit cycle, explicitly atomic same-cycle transactions are represented as single units, and the fixed enumeration lists any same-cycle units in an order compatible with the selected witness/replay attribution. This same-cycle listing is a witness-construction order only; it does not introduce additional strict $<_J$ edges. Hence each H_k is an ideal of $U(\tau_{\text{post}})$ under $<_J$.

We construct, by induction on k , a Sys_ref prefix $\tau_{\text{ref}}[H_k]$ ending in an ϵ -quiescent Sys_ref state $\sigma_{\text{ref}}[H_k]$, such that $\tau_{\text{ref}}[H_m]$ is the desired witness τ_{ref} . Here Sys_ref is as fixed in Remark 2. After each construction step, $\tau_{\text{ref}}[H_k]$ may be extended by a maximal finite ϵ^* -normalization suffix (B4/B5) to reach $\sigma_{\text{ref}}[H_k]$; this does not change its Σ -projection.

Invariant $\text{Inv}(H_k)$. The invariant below is stated for a prefix H_k of the fixed RTL-time ideal chain. When the notation $\text{Inv}(H)$ is used locally below, H denotes one of these chain prefixes, not an arbitrary ideal of $U(\tau_{\text{post}})$.

(I1) Required-prefix matching:

$\tau_{\text{ref}}[H]$, system has produced exactly the matched observable units in H , with the same Σ -labels/values and with all $<_J$ required-order constraints among those units preserved. The Sys_ref bucket decomposition used to realize H may differ from the RTL_B bucket decomposition, except that explicitly atomic same-cycle units must remain atomic.

(I2) Per-process replay-state agreement:

For every process P , the source-level state of P at $\sigma_{\text{ref}}[H]$ agrees with the deterministic source-level replay state determined by the P -local projection of H under the fixed-stimulus and WC witness assumptions. In particular, this agreement covers every source-level variable, control predicate, payload/value expression, and request-attribution fact that can influence future Σ -visible behavior of P or any Appendix K pending-request / drain-only fact of P .

(I3) Channel-history agreement:

For every explicit abstract channel c of Sys_ref, the committed Push_c/Pop_c history induced by H is the same on the Sys_ref witness side and on the RTL_B witness side under the event matching convention. Hence, for $B(c) > 0$ channels, the FIFO occupancy/head facts computed from that history agree; for $B(c) = 0$ channels, each committed transfer is represented only by an explicitly atomic rendezvous Push_c(v)/Pop_c(v) unit.

In particular, this agreement covers:

- any source-level variable read by BoundaryReq($\cdot, \cdot$);
- any source-level control predicate Pred_x($\cdot$) that decides reachability/selection of the next observable action(s);
- any payload/value expression of such next action(s); and
- for blocking Push/Pop operations, the source-level Issue/Commit attribution facts needed to

determine whether a dynamic operation instance q is already issued, not yet committed, and still the operation to which the asserted endpoint-owned request is attributed under Appendix C's Issue/Commit linkage.

Channel-side enablement facts are then determined at the chosen abstract boundary from this request-attribution state together with the channel-history facts preserved by $\text{Inv}(H)$.(I3): for $B(c)>0$ channels, the logical occupancy/head state induced by H ; for $B(c)=0$ rendezvous channels, the endpoint-request predicates determined by the replay states of the two endpoint processes.

For each process P , the RTL_B-side comparison state used in $\text{Inv}(H)$.(I2) is the deterministic source-level replay state determined by the P -local projection of H under the fixed-stimulus and WC witness assumptions. This is the object governed by Lemma I.DR. The corresponding Sys_ref state $\sigma_{\text{ref}}[H]$ is taken at an ϵ -quiescent cutpoint after realizing the matched required prefix H , followed if needed by finite ϵ -normalization.

Base case ($H = \emptyset$).

Let $\tau_{\text{ref}}[\emptyset]$ be the empty Sys_ref prefix under the fixed stimulus and $\sigma_{\text{ref}}[\emptyset]$ its initial state. The empty ideal $\emptyset$ contains no observable units. By the fixed-stimulus comparison setup, the initial source-level valuations, request-attribution facts, and reset-empty channel histories agree. Hence (I1), (I2), and (I3) hold.

Inductive step along the fixed RTL-time ideal chain ($H_k \rightarrow H_{\{k+1\}}$).

Assume $\text{Inv}(H_k)$, where $k < m$. Let $\gamma = \gamma_{\{k+1\}}$ be the next observable unit in the fixed RTL-time enumeration, and let $H^+ = H_{\{k+1\}} = H_k \cup \{\gamma\}$. By construction of the enumeration, H_k and H^+ are ideals under $\prec_J$, and every required $\prec_J$ predecessor of γ has already been matched in H_k .

The choice of γ is not arbitrary. It is the next unit in the selected RTL_B witness order after grouping explicitly atomic same-cycle transactions. Consequently, for each process P participating in γ , the P -local replay state determined by the P -local projection of H_k has the corresponding source operation either:

- reached as a next-frontier operation; or
- recorded, under the WC / issue-attribution witness, as already issued, still pending, and still attributed to the same dynamic source-level operation instance.

This witness-realizability condition is what makes the case analysis below applicable. If multiple unordered same-cycle units are available, the proof may choose any one satisfying this condition; such a choice is only a construction order for the Sys_ref witness and does not add an observable order among units unordered by $\prec_J$. Sys_ref is still not required to reproduce RTL_B's cycle-bucket decomposition, except that explicitly atomic same-cycle units remain atomic.

Existence of a matching Sys_ref extension.

We show there exists a finite Sys_ref extension from $\sigma_{\text{ref}}[H_k]$ that commits a matching unit γ' for $\gamma = \gamma_{\{k+1\}}$, followed, if needed, by finite ϵ -normalization to an ϵ -quiescent state $\sigma_{\text{ref}}[H_{\{k+1\}}]$:

$$\sigma_{\text{ref}}[H_k] \xrightarrow{\epsilon^*} \tilde{\sigma}_{\text{ref}} \xrightarrow{\gamma'} \hat{\sigma}_{\text{ref}} \xrightarrow{\epsilon^*} \sigma_{\text{ref}}[H_{\{k+1\}}].$$

Here γ' has the same Σ -label(s), value label(s), dynamic message-operation matching, and synchronization-transaction identity as γ . If γ is a singleton event, γ' is a singleton event. If γ is an explicitly atomic unit, γ' is the corresponding explicitly atomic Sys_ref unit.

The following cases use the witness-realizability property of the fixed RTL-time enumeration. Thus, when a case refers to the next-frontier information or to an already-issued pending request, that fact is supplied by $\text{Inv}(H_k).(I2)$ together with the selected RTL_B witness / WC request-attribution state, not merely by γ being $<_J$ -minimal.

If γ is a singleton process-local non-message Σ -event, such as a sequential-process anchored Read/Write event as in E2 or a one-sided synchronization endpoint that is not part of a paired atomic transaction, then the corresponding source-level operation of the relevant process P is selected from the next-frontier information determined by the P -local replay state in $\text{Inv}(H_k).(I2)$. Since $\sigma_{\text{ref}}[H_k]$ agrees with that replay state on the control predicates Pred_x used for next-action selection and on the value expressions, the same local predicate/value facts hold in Sys_{ref} . For sequential Write events, the value label is determined by the same source-level expression evaluation; for sequential anchored Reads, the value label is determined by the fixed stimulus plus E2 anchoring. Thus the matching Sys_{ref} event has the same Σ -label.

If γ is an explicitly atomic R2C combinational fixed-point signal-observation unit, then γ is not selected by a process-owned synchronization anchor and has no $\text{pred}_S/\text{succ}_S$ requirement. Instead, its formal occurrence is the cycle's ε -quiescent combinational fixed-point observation. Because H is down-closed under $<_J$, all causally prior sequential clock-boundary updates, stimulus values, and already-matched signal-driving facts needed to determine that fixed point have already been matched in H . By the R2C well-formedness premise, the relevant combinational network is deterministic and reaches a unique ε -fixed point; by $\text{Inv}(H).(I2)$ and the fixed-stimulus hypothesis, the corresponding Sys_{ref} and RTL_B fixed-point valuations agree on the observed signal boundary. Intermediate delta-cycle propagation and redundant re-evaluation are ε -steps and are not separately Σ -visible. Therefore Sys_{ref} can extend by ε^* to the corresponding fixed point and emit the matching atomic R2C unit containing the corresponding fixed-point Read/Write Σ -labels with the same value labels.

For a message-transfer event in γ , the matched dynamic source-level message-operation instance q is handled by a two-case classification.

Case 1: q is a not-yet-issued next-frontier message operation. Then q is selected from the message-operation slice of NextFront_P determined by the P -local replay state in $\text{Inv}(H).(I2)$. Since $\sigma_{\text{ref}}[H]$ agrees with that replay state on the source-level variables read by $\text{BoundaryReq}(q, \cdot)$, on the control predicates Pred_q used for next-action selection, and on the payload/value expressions, Sys_{ref} can issue the same boundary request for q with the same payload/value facts, subject to the same side-of-synchronization and same-interface ordering constraints.

Case 2: q is an already-issued pending message operation. Then q need not be a member of $\text{NextFront}_P(\sigma_{\text{ref}}[H])$; in particular, Appendix B's drain-only discipline allows an already-asserted non-frontier request to persist as protocol state while an earlier pending blocker remains frontier-minimal. In this case the relevant fact is not NextFront membership, but the request-attribution component of $\text{Inv}(H).(I2)$: q has already issued, has not yet committed, remains the operation to which the asserted endpoint-owned boundary request is attributed under Appendix C's Issue/Commit linkage, and has the same stable payload facts when q is a Push. Therefore Sys_{ref} contains the same pending request instance q at the compared cutpoint.

For buffered channels with $B(c) > 0$, the channel-side legality of the matching $\text{Push}_c/\text{Pop}_c$ commit is

checked against the FIFO history induced by H . By $\text{Inv}(H).(I3)$, the corresponding FIFO occupancy/head facts agree in Sys_ref and in the RTL_B witness history for the same required prefix H . Therefore the matching buffered $\text{Push_c}/\text{Pop_c}$ event has the same channel-side legality in Sys_ref as in RTL_B , subject to the same reset-empty, FIFO-order, no-underflow/no-overflow, and non-fall-through E4 rules. If a Push_c and a Pop_c occurred in the same RTL_B clock bucket but are not an explicitly atomic rendezvous unit, they may be realized in different Sys_ref cycles or in a different Sys_ref bucket grouping, provided the E4 history and all $\prec_J$ constraints are preserved.

For a rendezvous channel with $B(c)=0$, a committed transfer is an explicitly atomic observable unit containing the two endpoint events $\text{Push_c}(v)$ and $\text{Pop_c}(v)$. It is not matched by independently scheduling the two endpoints. If γ is such a rendezvous transfer, then the endpoint processes P and Q have the corresponding source-level boundary requests in the replay states determined by H . Each endpoint request may be present either because its operation is the not-yet-issued next-frontier operation just selected, or because it is an already-issued pending request preserved by the request-attribution state described above. By $\text{Inv}(H).(I2)$, the same endpoint request predicates and payload/value facts hold in Sys_ref . Therefore the matching $\text{Push_c}(v)/\text{Pop_c}(v)$ endpoint pair is jointly enabled in Sys_ref and commits as one atomic rendezvous unit. The Appendix G causal-dependency edge $\text{Push_c}(v) \rightarrow \text{Pop_c}(v)$ is not used here as a strict edge internal to the unit; the unit is added to the ideal all at once.

For a paired $\text{SyncChannel}/\text{ac_sync}$ transaction, γ is likewise an explicitly atomic unit containing the two matched endpoint events with the same dynamic synchronization-transaction identity. By the synchronization-pair well-formedness condition for $\approx$ and by $\text{Inv}(H).(I2)$, both endpoint processes reach the corresponding synchronization frontier with the same before/after source-state facts. Therefore Sys_ref commits the matching paired synchronization transaction as one atomic synchronization unit, preserving the induced cross-process ordering.

By the Appendix I.4 finite-prefix extension reasoning, together with Theorem J.1's progress premises and weak fairness, Sys_ref cannot diverge forever by taking only ϵ -steps while the matched next unit remains continuously enabled. Hence a finite ϵ^* extension exists that reaches a state in which γ' commits. Let $\tau_{\text{ref}}[H_{\{k+1\}}]$ be $\tau_{\text{ref}}[H_k]$ extended by this finite ϵ^* segment, the matching unit γ' , and then, if needed, a maximal finite ϵ^* -normalization suffix to reach $\sigma_{\text{ref}}[H_{\{k+1\}}]$ (B4/B5). Then (I1) holds for $H_{\{k+1\}}$ by construction; (I2) follows from deterministic replay on each process's P-local projection of $H_{\{k+1\}}$; and (I3) follows from applying the same E4 channel-history update for the matched channel event(s). Thus $\text{Inv}(H_{\{k+1\}})$ is established.

Under the fixed stimulus and the WC premise, apply Lemma I.DR (Deterministic Replay) to: (a) P 's execution within the chosen Sys_ref witness prefix $\tau_{\text{ref}}[H_{\{k+1\}}]$ reaching the ϵ -quiescent cutpoint $\sigma_{\text{ref}}[H_{\{k+1\}}]$, and (b) the source-level replay determined by the P-local projection of $H_{\{k+1\}}$ in the RTL_B witness. These two executions start from the same initial source-level state and have the same P-local observable-unit replay projection under the document's event-matching convention, including the fixed witness w and μ_Q / issue-attribution data where ϵ -modeled failed non-blocking $q \in Q_{\text{exec}}, P$ are relevant. Therefore Lemma I.DR, applied to the full $\text{Obs}_{\{\Sigma, P, w\}}$ slice under the fixed witness, implies that the source-side replay states agree for every source-level variable, control predicate, payload/value expression, Pending_P / Front_P / BoundaryReq fact, and request-attribution fact included in $\text{Inv}(H_{\{k+1\}}).(I2)$. Thus $\text{Inv}(H_{\{k+1\}}).(I2)$ holds in full as a source-side replay-state invariant. This use of a sequence is a witness-selected observable-unit replay sequence, not an intrinsic linearization of an unordered same-cycle bucket.

This does not claim that the raw RTL_B microstate request, pending, attribution, or rendezvous endpoint-request facts are determined from the bare P-local Σ -label sequence alone. When Corollary J.1 or

Appendix K later transfers those request-state facts between the selected RTL_B cutpoint ρ_{post} and the selected Sys_ref cutpoint σ_{ref} , the RTL_B-side counterpart is supplied by J.AbsConf for the same selected $(\rho_{\text{post}}, \sigma_{\text{ref}}, w)$.

Because P was arbitrary, the per-process replay-state agreement holds for all processes; and because all channel-history updates are matched under E4, $\text{Inv}(H_{\{k+1\}})$.(I3) holds as well.

Conclusion.

By induction along the fixed RTL-time ideal chain $H_0 \subseteq H_1 \subseteq \dots \subseteq H_m = U(\tau_{\text{post}})$, $\text{Inv}(H_m)$ holds for the complete finite ideal $U(\tau_{\text{post}})$ of observable units in the chosen RTL_B prefix. Taking $\tau_{\text{ref}} = \tau_{\text{ref}}[H_m]$ yields the required Sys_ref witness prefix for $(\text{Post} \rightarrow \text{Ref})$. The constructed $\tau_{\text{ref}, \text{system}}$ is compatible with $\tau_{\text{post}, \text{system}}$ under E1–E5 and the explicit channel, signal-anchor, and synchronization semantics, but it need not have the same observable cycle-bucket decomposition as $\tau_{\text{post}, \text{system}}$. The construction uses RTL-time order only as a witness-construction schedule; it does not add an observable order among units unordered by $<_J$, and it does not require the broader Appendix G causal-dependency graph $\rightarrow$ to be acyclic. Bucket equality is required only inside explicitly atomic units, such as rendezvous Push/Pop transfers and paired SyncChannel/ac_sync transactions.

At the terminal ϵ -quiescent prefix, the P-local projection of $U(\tau_{\text{post}})$ is exactly the P-local observable-unit replay projection of the chosen RTL_B prefix, under the selected witness/annotation package.

Therefore the replay-state agreement in $\text{Inv}(U(\tau_{\text{post}}))$.(I2) gives

the deterministic-replay part of the state-level bridge used by Corollary J.1 when it relates the selected RTL_B cutpoint ρ_{post} to the selected Sys_ref cutpoint σ_{ref} via the J.Abs/J.AbsConf abstraction relation and obtains the replay-determined frontier/guard/value correspondence at ϵ -quiescent cutpoints. The request/pending/attribution and rendezvous endpoint-request portions of that cutpoint correspondence are supplied by J.AbsConf for the same selected $(\rho_{\text{post}}, \sigma_{\text{ref}}, w)$, not by the replay-state argument alone.

Ref $\rightarrow$ Post clause. The reverse clause is discharged asymmetrically. Let $\tau_{\text{ref}} \in \text{Exec}_{\text{ref}}$ satisfy the selected/RTL-consistency premise of Theorem J.1. By that premise, choose the selected RTL_B prefix $\tau_{\text{post}}^* \in \text{Exec}_{\text{post}}$ under the same fixed stimulus whose required-prefix Σ -projection matches τ_{ref} ; when B1 holds, this selected prefix is the corresponding prefix of the unique RTL_B Σ -trace. The theorem's witness/RTL-consistency premise supplies the per-process compatibility, E4 channel-history, witness/request-attribution, and selected-cutpoint obligations needed to instantiate Proposition J.0 for the chosen pair $(\tau_{\text{ref}}, \tau_{\text{post}}^*)$. Therefore $\tau_{\text{post}} = \tau_{\text{post}}^*$ is the required post-side witness. This argument does not assert that an arbitrary Sys_ref execution can be implemented by RTL_B, and it does not rely on symmetry of $\approx$. $\square$

Definition J.Abs (RTL_B cutpoint-to-source-slice abstraction relation)

The Appendix J/K cutpoint arguments use an abstraction relation, not a universal concrete bit-level projection function from arbitrary RTL registers to source states. Write

$\rho_{\text{post}} \Downarrow_{\{ \text{Abs}, J, w \}} \sigma_{\text{ref}}$

to mean that the ϵ -quiescent RTL_B cutpoint microstate ρ_{post} is related, under the selected Appendix I / Appendix L witness w and the chosen Sys_ref abstract boundaries, to the source-level

cutpoint state σ_{ref} of Sys_{ref} . This relation is interpreted over the prescribed source reference model Sys_{ref} of Remark 2, including any explicit $\text{Sys}_{\text{B}}^{\text{elab}}$ staged, bundle, join, or sync-boundary channels introduced to represent the chosen RTL_{B} abstraction boundary.

The relation $\rho_{\text{post}} \Downarrow_{\{\text{Abs}, J, w\}} \sigma_{\text{ref}}$ requires at least the following source-level slice agreement:

(1) Observable-prefix agreement. The Σ -projected history of ρ_{post} matches the Σ -history of σ_{ref} under the Appendix J compatibility relation, including E1–E5, the selected witness w , and the same external stimulus.

(2) Per-process source-control/frontier slice. For each process P , the projected source-control point of ρ_{post} identifies the same remaining source-level frontier universe Ω_P and the same NextFront_P set as σ_{ref} , in the Lemma S2 sense. This is a source-level frontier over the fixed witness universe Ω_P ; it is not a claim that the raw RTL microstate alone uniquely determines a frontier independently of the chosen witness and abstraction boundary.

(3) Source-visible value slice. For every source-level variable, signal value, payload expression, guard, and witness-selected ϵ outcome needed to determine the next Σ -visible action or frontier enablement, the value projected from ρ_{post} agrees with the value in σ_{ref} . Micro-architectural registers, pipeline bookkeeping, speculative staging, and other ϵ -only implementation state are ignored except insofar as they determine this source-visible slice.

(4) Abstract channel-state slice. For every explicit abstract channel c of Sys_{ref} with $B(c) > 0$, the E4-visible logical occupancy occ_c , empty/full status, and logical head element when non-empty projected from ρ_{post} agree with the corresponding Sys_{ref} facts in σ_{ref} . Internal movement inside the RTL realization that does not commit a Σ -visible boundary transfer is ϵ -state and does not by itself change this abstract FIFO slice.

(5) Rendezvous endpoint-request slice. For every point-to-point rendezvous channel c with $B(c) = 0$ that is included in the Appendix K internal message-passing boundary / WFG analysis, the projected producer-side and consumer-side endpoint-request predicates in ρ_{post} agree with $\text{Req}_{\text{prod}}(c, \sigma_{\text{ref}})$ and $\text{Req}_{\text{cons}}(c, \sigma_{\text{ref}})$, respectively. These are raw endpoint-request facts at the chosen abstract boundary; they do not by themselves assert frontier-minimality.

(6) Blocking request attribution and pending slice. For every process P and every blocking message-operation frontier item $x \in \Omega_{\text{msg}, P}$ in P 's current source interval, with owning dynamic message-call instance $q = \text{MsgOf}_P(x)$, the projected RTL_{B} cutpoint records the same source-level attribution and issued-but-not-yet-committed status as σ_{ref} . Equivalently, $\text{Issue}(q)$ has occurred and $\text{Commit}(q)$ has not occurred in the projected RTL_{B} source slice iff q is pending in σ_{ref} , and the endpoint-owned BoundaryReq for x is attributed to q on the RTL_{B} side iff $\text{BoundaryReq}(x, \sigma_{\text{ref}})$ holds on the Sys_{ref} side.

(7) Enablement slice. ChannelEnabled and ChannelDisabled for pending blocking frontier items are computed from the preceding abstract channel-state, rendezvous endpoint-request, and BoundaryReq slices, over the explicit abstract channels of Sys_{ref} . In the elaborated case $\text{Sys}_{\text{ref}} = \text{Sys}_{\text{B}}^{\text{elab}}$, all Pending, BoundaryReq , ChannelEnabled , ChannelDisabled , and WFG facts are interpreted only at those explicit abstract channels.

$J.\text{Abs}$ is intentionally an abstraction relation. It does not require equality of arbitrary RTL microstate, nor does it require a tool-independent syntactic recipe for decoding every RTL register. It requires only the source-level state slice consumed by Corollary J.1 and Appendix K.

Obligation J.AbsConf (RTL_{B} cutpoint-abstraction conformance).

For an RTL_B implementation to be within the scope of Corollary J.1 and the Appendix K liveness / deadlock-preservation arguments, the tool flow, generated certificate, RTL/interface check, or other validation method shall discharge the following obligation:

For every reachable ϵ -quiescent RTL_B cutpoint ρ_{post} used by Appendix J or Appendix K under the chosen stimulus, witness-selection scheme, Sys_ref boundary choice, and ϵ -normalization convention, and for the particular Sys_ref witness prefix τ_{ref} , terminal cutpoint σ_{ref} , and witness w selected for the corresponding application of Theorem J.1 / Corollary J.1, the cutpoint-abstraction relation holds: $\rho_{\text{post}} \Downarrow_{\{\text{Abs}, J, w\}} \sigma_{\text{ref}}$.

Equivalently, J.AbsConf is not discharged by producing an arbitrary existential Sys_ref state or witness unrelated to the Sys_ref witness used by the proof. If multiple Sys_ref witness prefixes are admissible for the same RTL_B prefix, the proof/application shall choose one such witness prefix and discharge J.AbsConf for that same chosen triple $(\rho_{\text{post}}, \sigma_{\text{ref}}, w)$. The σ_{ref} and w used in Steps 3–4 of Corollary J.1 and in the Appendix K WFG transfer are therefore the same σ_{ref} and w selected by the Theorem J.1 witness construction, not a separate existential pair.

Moreover, finite ϵ -normalization steps used to reach ρ_{post} shall not change the Σ -projected history or the projected source-level request/pending/attribution slice except by the Issue/Commit linkage, E4 channel-realization semantics, and the explicit Sys_ref/Sys_B^elab boundary rules stated in this document.

This obligation is a tool/RTL-flow compliance obligation, analogous to the RTL-side scheduling obligations, E4 channel-realization obligations, automatic-flush obligations, and B-faithfulness obligations stated elsewhere in this document. Appendix J and Appendix K use J.AbsConf as a hypothesis tied to the selected Theorem J.1 / Corollary J.1 witness; they do not derive the RTL_B-to-source request/pending/attribution slice from the bare Σ -label sequence alone.

Corollary J.1 (State Correspondence at the End of a Matched Observable Prefix)

Purpose.

This corollary serves as the bridge between trace compatibility and state correspondence needed in Appendix K. The mapping target is the prescribed source reference model Sys_ref of Remark 2, not an unrelated raw rendezvous ($B(c)=0$) execution state. The cutpoint state relation used by this corollary is the J.Abs abstraction relation above, discharged by J.AbsConf for the RTL_B implementation and chosen abstract boundaries.

Statement. Assume the hypotheses of Theorem J.1 for Sys_ref vs RTL_B under the fixed stimulus, including the standing B1 assumption for RTL_B (unique Σ -projected trace under the fixed stimulus), and additionally use B4 and B5 for ϵ -normalization. The observable Σ projection is therefore unique (up to insertion/removal of finite ϵ -steps), although the corresponding source-side witness prefix/state in Sys_ref need not be unique as a full micro-state..

Let τ_{post} be any $\tau_{\text{post}} \in \text{Exec}_{\text{post}}$ (as defined in Theorem J.1). Choose one ϵ -normalization $\bar{\tau}_{\text{post}}$ obtained by extending τ_{post} by a (possibly empty) finite suffix ϵ^* to a terminal state $\bar{\sigma}_{\text{post}}$ that is ϵ -quiescent, meaning: no further ϵ -step is enabled from $\bar{\sigma}_{\text{post}}$ (so any further progress, once enabled, must proceed via an observable Σ -action rather than additional internal ϵ -steps). Take ϵ^* to be a maximal finite ϵ -extension of τ_{post} ; such a maximal finite extension exists under B4 (finite stutter bound). For the remainder of this corollary, interpret σ_{post} as this chosen ϵ -normalized terminal state $\bar{\sigma}_{\text{post}}$. No uniqueness claim about maximal ϵ -extensions is needed here; all conclusions below are

asserted relative to the chosen ε -normalized representative together with the matched Sys_ref witness supplied by Theorem J.1.

When referring below to “source-level variables,” the “next source-level frontier-item set,” the “logical FIFO state,” rendezvous endpoint-request predicates, Pending_P, BoundaryReq, or ChannelEnabled/ChannelDisabled in σ_{post} , interpret those notions through the J.Abs RTL_B cutpoint-to-source-slice abstraction relation, not through an implicit or tool-independent bit-level projection. Micro-architectural registers and bookkeeping are ignored except insofar as they contribute to the J.Abs source-level slice.

Let Sys_ref denote the prescribed source reference model of Remark 2. The state comparison below is relative to the chosen ε -normalized RTL_B representative ρ_{post} , the particular matched Sys_ref witness

prefix τ_{ref} and terminal cutpoint σ_{ref} selected from Theorem J.1 for this application, the selected Appendix I / Appendix L witness w , and the J.Abs abstraction relation

$\rho_{\text{post}} \Downarrow_{\{ \text{Abs}, J, w \}} \sigma_{\text{ref}}$

at the chosen abstract boundaries. Assume J.AbsConf is discharged for this same selected triple $(\rho_{\text{post}}, \sigma_{\text{ref}}, w)$, not merely for some unrelated existential Sys_ref state or witness. In particular, the pending-request, endpoint-request, and request-attribution facts needed by Appendix K are part of this abstraction relation; they are not reconstructed from the bare Σ -label sequence alone and are not derived

merely from deterministic replay of the same observable labels. Then the selected finite execution prefix τ_{ref} of Sys_ref ends in the reachable state σ_{ref} and satisfies:

(1) The observable prefixes match: $\tau_{\text{ref}, \text{system}} \approx \tau_{\text{post}, \text{system}}$ (compatibility under E1–E5).

(2) The terminal states correspond at the source level in this projection/witness sense: $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$, where “ $\equiv$ ” means:

(Note: “ $\equiv$ ” is intentionally the source-slice correspondence induced by J.Abs and discharged by J.AbsConf. It is a frontier/enable/value/abstract-channel/request-attribution correspondence (clauses (a)(b)(c)(d)(e)), not full micro-state equality and not a fact derivable from the Σ -label sequence alone. Internal pipeline, buffering, elaboration, and scheduling microstate may differ between Sys_ref and RTL_B provided those differences are ε -state that is invisible to Σ and WFG-inert as assumed in Appendix K. Clause (e) is included to make explicit the pending-request and attribution correspondence needed by Appendix K’s drain-only / drain-closure reasoning; it does not require equality of arbitrary RTL microstate.)

(a) For every process P , $\text{NextFront}_P(\sigma_{\text{ref}}) = \text{NextFront}_P(\sigma_{\text{post}})$, where $\text{NextFront}_P(\sigma)$ is as defined in Lemma S2 (the set of minimal remaining source-level frontier items in Ω_P with respect to P ’s source partial order $\leq_P$). Concretely, this means either:

- a (possibly multi-element) set of candidate message-operation frontier items $x \in \Omega_{\text{msg}, P}$, with owning message instance $q = \text{MsgOf}_P(x)$ and $\text{kind}(q) \in \{\text{Push}_c, \text{Pop}_c\}$, on distinct interfaces that are currently minimal candidates and may be issued and, if channel-enabled, committed in any order or together in one cycle, or
- an explicit synchronization-call item s , together with the same set of signal Read/Write action items that are logically anchored at s per E2.
- This frontier equality does not require the pre-HLS and post-HLS models to commit identical subsets of that message set in the same cycle; it only identifies the set of currently-minimal candidate frontier items.

Note. NextFront_P is a candidate frontier relative to the fixed witness universe Ω_P of Lemma S2 and does not by itself assert enablement or “pending blocking” status. Appendix K reasons about pending blocking transfers using $\text{Front}_P(\sigma)$; see Lemma K.0 (K.2.2) for the Front/NextFront bridge at ε -quiescent

cutpoints.

(b) By Lemma S1, for every process P , and for every item $x \in \text{NextFront}_P(\sigma_{\text{ref}})$ (equivalently $x \in \text{NextFront}_P(\sigma_{\text{post}})$ by clause (a)):

(i) For every frontier item x , any source-level control predicate used to decide that x is the next source-level frontier item is evaluated the same way in σ_{ref} and σ_{post} . If $x \in \Omega_{\text{msg},P}$ is a blocking message-operation frontier item, with owning message instance $q = \text{MsgOf}_P(x)$ and $\text{kind}(q) \in \{\text{Push}_c, \text{Pop}_c\}$, then the operation-attributive evaluation of $\text{BoundaryReq}(x, \cdot)$ is also the same in σ_{ref} and σ_{post} . If x is not a blocking message-operation frontier item, no persistent $\text{BoundaryReq}(x, \cdot)$ agreement is required by this clause. In particular, a successful non-blocking $\text{PushNB}/\text{PopNB}$ frontier item may contribute the corresponding committed $\text{Push}_c/\text{Pop}_c$ Σ -label, but it does not create a pending blocking request whose BoundaryReq must persist at an ε -quiescent cutpoint. Equivalently, σ_{ref} and σ_{post} agree on all source-level state variables read when evaluating the relevant guard/control predicate, and, when x is a blocking message-operation frontier item, the variables read when evaluating the operation-attributive $\text{BoundaryReq}(x, \cdot)$ through $q = \text{MsgOf}_P(x)$. Channel-side enablement of blocking Push/Pop is handled separately by clauses (c), (d), and (e). Failed non-blocking polls may be present in $Q_{\text{exec},P}$ for witness-matching purposes, but they are not frontier items and are not covered by this NextFront_P clause.

(ii) If x produces a value—i.e., $x \in \Omega_{\text{msg},P}$ with owning message instance $q = \text{MsgOf}_P(x)$ and $\text{kind}(q) = \text{Push}_c$ for some channel c , including the committed-transfer label of a successful non-blocking write when such an item is in Ω_P , or x is a signal Write action item (or set of such action items) anchored at the next synchronization call—then the value produced by x (payload/value expression) is the same in σ_{ref} and σ_{post} (hence σ_{ref} and σ_{post} agree on all source-level variables read by that expression). If x observes a value via signal Read action items anchored at the next synchronization call, those observed signal values are the same in σ_{ref} and σ_{post} because the stimulus is the same and E2 anchors the reads to that same synchronization call.

(iii) If $x \in \Omega_{\text{msg},P}$ with owning message instance $q = \text{MsgOf}_P(x)$ and $\text{kind}(q) = \text{Pop}_c$ for some channel c , including the committed-transfer label of a successful non-blocking read when such an item is in Ω_P , then the value returned by that Pop_c operation instance q is determined by the channel's logical FIFO contents after the matched observable prefix; by E4 and the matched Push/Pop history, that logical head element is the same for σ_{ref} and σ_{post} .

(c) For every channel c with $B(c) > 0$, the abstract FIFO state in σ_{ref} (empty/full predicate, and the logical head element when non-empty) agrees with the logical FIFO state induced by the matched $\text{Push}_c/\text{Pop}_c$ history of (1). Physical micro-architectural realization—pipeline registers, arbitration bookkeeping, and the implementation of buffering—is abstracted away by “ $\equiv$ ”, but the logical occupancy/ordering facts induced by the matched trace are not. Equivalently, letting $\text{occ}_c(t)$ denote the logical Σ -boundary occupancy used throughout Appendix K (and letting “empty/full” refer to this same logical occupancy), $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ implies σ_{ref} and σ_{post} agree on $\text{occ}_c(t)$ and on the logical head element when non-empty.

In particular, internal transfers within the concrete realization (e.g., movement between pipeline/buffering stages) that do not commit a boundary transfer are treated as ε and do not change this abstract FIFO state.

(d) For each point-to-point rendezvous channel c with $B(c) = 0$ that is included in the Appendix K internal message-passing boundary / WFG analysis, the raw endpoint-request predicates agree:

$$\text{Req}_{\text{prod}}(c, \sigma_{\text{ref}}) = \text{Req}_{\text{prod}}(c, \sigma_{\text{post}})$$

and

$$\text{Req}_{\text{cons}}(c, \sigma_{\text{ref}}) = \text{Req}_{\text{cons}}(c, \sigma_{\text{post}}),$$

where $\text{Req}_{\text{prod}}(c, \sigma)$ means that the producer-side boundary request on c is asserted at the ε -quiescent cutpoint σ , and $\text{Req}_{\text{cons}}(c, \sigma)$ means that the consumer-side boundary request on c is asserted at σ .

This is a raw boundary-request fact only; it does not assert that an asserted rendezvous request is frontier-minimal.

(e) For Appendix K drain-only reasoning, already-issued blocking request state agrees at the chosen abstract boundaries. More precisely, for every process P and every blocking message-operation frontier item $x \in \Omega_msg, P$ in P 's current interval between adjacent synchronization calls, with owning dynamic message-call instance $q = \text{MsgOf_P}(x)$:

$x \in \text{Pending_P}(\sigma_ref)$ iff $x \in \text{Pending_P}(\sigma_post)$,

where $\text{Pending_P}(\sigma)$ means that $\text{Issue}(q)$ has occurred and $\text{Commit}(q)$ has not yet occurred at σ , in the Appendix C source-level attribution sense, for the owning message instance $q = \text{MsgOf_P}(x)$. For every such common pending frontier item x :

- the endpoint-owned boundary request is attributed to $q = \text{MsgOf_P}(x)$ on one side iff it is attributed to q on the other side;
- $\text{BoundaryReq}(x, \sigma_ref) = \text{BoundaryReq}(x, \sigma_post)$; and
- $\text{ChannelEnabled}(x, \sigma_ref) = \text{ChannelEnabled}(x, \sigma_post)$, equivalently $\text{ChannelDisabled}(x, \sigma_ref) = \text{ChannelDisabled}(x, \sigma_post)$.

For $B(c) > 0$ channels, this enablement agreement follows from the common $B(c)$ and the logical occupancy/head-state agreement of clause (c). For $B(c) = 0$ rendezvous channels, it follows from the raw producer/consumer endpoint-request agreement of clause (d). In the elaborated case $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$, all of these Pending, BoundaryReq, ChannelEnabled, and ChannelDisabled facts are interpreted at the explicit abstract channels of $\text{Sys_B}^{\text{elab}}$.

Lemma S1 (Relevant source-level state agreement for next-frontier guards/payloads)

Purpose.

This lemma is the minimal per-process “state agreement” fact needed to justify Corollary J.1, clause (2b): matched observable prefixes determine enough of the source-level state so that, for the common next source-level frontier-item set, source-level control predicates agree, produced/observed values agree, and BoundaryReq agrees only for blocking message-operation frontier items $x \in \Omega_msg, P$ with owning message instance $q = \text{MsgOf_P}(x)$ and $\text{kind}(q) \in \{\text{Push_c}, \text{Pop_c}\}$. This is the fact Appendix K needs when reasoning about operation-attributive BoundaryReq/blockedness on the Sys_ref side. No persistent BoundaryReq predicate is defined or required for non-message frontier items such as synchronization-call items or signal-anchored action items, and no persistent BoundaryReq agreement is required for successful non-blocking frontier items merely because they contribute committed $\text{Push_c}/\text{Pop_c}$ Σ -labels.

Statement.

Fix a process P . Let τ_post, P be the projection of some reachable post-HLS (RTL_B) finite prefix onto P , and let τ_ref, P be a Sys_ref prefix. More precisely, let A_post, P and A_ref, P be the corresponding annotated P -local projection records, including the chosen witness w , the P -local dynamic universe $\Omega_P / Q_exec, P$, issue annotations, and μ_Q matching where needed. Assume $A_ref, P \approx A_post, P$ under the document's annotated Σ -matching/E1–E5 conventions; in prose this may be abbreviated as $\tau_ref, P \approx \tau_post, P$ when the annotation package is fixed by context. Let σ_post be the ϵ -normalized (ϵ -quiescent) terminal state of τ_post, P , and let σ_ref be the terminal state of τ_ref, P .

Terminology (Witness-compatible; WC).

Assume this comparison $\tau_ref, P \approx \tau_post, P$ is witness-compatible in the sense of WC (Appendix I): any ϵ -modeled non-blocking poll outcome (and any other ϵ -modeled internal choice that can affect P 's next Σ -visible control flow / next Σ -visible frontier) is fixed/selected consistently with the compared RTL_B

prefix $\tau_{\text{post},P}$ (e.g., via Appendix L’s witness-selection/snooping wrapper).

Remark (NB-CF as a sufficient condition). If the design satisfies NB-CF (Appendix I)—failed PopNB/PushNB polls do not influence the next Σ -visible control flow/frontier—then the witness is trivial and WC holds automatically.

Let $\text{NextFront}_P(\sigma)$ denote, relative to this fixed compared witness $\tau_{\text{ref},P} \approx \tau_{\text{post},P}$ (equivalently, relative to the associated $\Omega_P / \leq_P$ universe of the compared execution), P ’s next source-level frontier-item set: the minimal candidate set of source-level frontier items with respect to P ’s source partial order, as used in Corollary J.1. Let x be any item in that next frontier (so $x \in \text{NextFront}_P(\sigma_{\text{ref}})$, and equivalently $x \in \text{NextFront}_P(\sigma_{\text{post}})$ by the frontier-alignment lemma (S2) / Corollary J.1(2a)).

Then:

(1) Control-predicate agreement, plus boundary-request agreement for blocking message items only. For any source-level control predicate Pred_x that is evaluated (in the source semantics) to decide that x is the next source-level frontier item at this point (e.g., branch/loop condition determining control reachability of x), we have:

$$\text{Pred}_x(\sigma_{\text{ref}}) = \text{Pred}_x(\sigma_{\text{post}}).$$

If $x \in \Omega_{\text{msg},P}$ is a blocking message-operation frontier item with owning message instance $q = \text{MsgOf}_P(x)$ and $\text{kind}(q) \in \{\text{Push}_c, \text{Pop}_c\}$, then additionally the operation-attributive boundary-request predicate agrees:

$$\text{BoundaryReq}(x, \sigma_{\text{ref}}) = \text{BoundaryReq}(x, \sigma_{\text{post}}).$$

If x is not a blocking message-operation frontier item, no persistent $\text{BoundaryReq}(x, \cdot)$ agreement is required by this clause. In particular, a successful non-blocking PushNB/PopNB frontier item may contribute a committed Push_c/Pop_c Σ -label, but it does not create a pending blocking request whose BoundaryReq must persist at an ϵ -quiescent cutpoint. Equivalently: σ_{ref} and σ_{post} agree on the valuation of every source-level state variable read when evaluating $\text{Pred}_x(\cdot)$, and, when x is a blocking message-operation frontier item, every source-level state variable read when evaluating the operation-attributive $\text{BoundaryReq}(x, \cdot)$ through $q = \text{MsgOf}_P(x)$. Channel-side enablement of blocking Push/Pop is not part of this local guard clause; it is handled by the FIFO/rendezvous enablement clauses and the pending-request clause in the corresponding-cutpoint relation. Failed non-blocking polls may be present in $Q_{\text{exec},P}$ for witness-matching purposes, but they are not frontier items and are not covered by this NextFront_P / BoundaryReq clause.

(2) Produced-value agreement (payload/value expressions).

If x produces a value—i.e., $x \in \Omega_{\text{msg},P}$ with owning message instance $q = \text{MsgOf}_P(x)$ and $\text{kind}(q) = \text{Push}_c$ for some channel c , or x is a signal $\text{Write}(\text{sig}, \text{val})$ action item (or set of such write items) anchored at the next synchronization call—then the value produced by x is the same in σ_{ref} and σ_{post} . Equivalently: σ_{ref} and σ_{post} agree on the valuation of every source-level state variable read by x ’s payload/value expression.

(3) Pop return-value agreement.

If $x \in \Omega_{\text{msg},P}$ with owning message instance $q = \text{MsgOf}_P(x)$ and $\text{kind}(q) = \text{Pop}_c$ for some channel c , then the value returned by that Pop_c operation instance q is the same in σ_{ref} and σ_{post} , and is equal to the logical head element of c ’s abstract FIFO after the matched observable prefix (hence uniquely

determined by the matched Push/Pop history under the bounded-FIFO semantics).

(4) Signal-read agreement at the next sync anchor (when applicable).

If x observes values via signal $\text{Read}(\text{sig}, \cdot)$ action items anchored at the next synchronization call, then those observed signal values are the same in σ_{ref} and σ_{post} under the “fixed stimulus” interpretation used by Appendix I/J together with the E2 anchoring discipline.

Proof.

We prove (1)–(4) by reducing them to a single per-process invariant: “matched Σ -prefixes fix the valuation of the source-level variables relevant to the next frontier,” plus FIFO legality for Pop values.

Define the P-local observable-unit replay sequence of the matched prefixes as the projection of the fixed Appendix J observable-unit ideal/enumeration to P-local units under the event-matching convention:

$\tau_{\text{post},P} \Downarrow_P = u_1 u_2 \dots u_n$

$\tau_{\text{ref},P} \Downarrow_P = u_1 u_2 \dots u_n$

where equality means equality of matched observable units/ Σ -labels, including channel/signal identity and value labels for Push/Pop/Read/Write events, and where explicitly atomic same-cycle transactions are represented as single units. This sequence is not an intrinsic linear order on the unordered contents of a CycleBucket. The bucket supplies same-cycle membership only; the replay sequence is the witness-selected observable-unit projection used by the Appendix J ideal-chain construction. Units that are unordered by $\prec_J$ and do not affect P’s source replay state may commute without changing the deterministic replay slice, while P-local units are replayed only in a legal source/witness order. The replay key therefore consists of this P-local observable-unit sequence together with the fixed witness/annotation package, including w and μ_Q for ε -modeled failed non-blocking $q \in Q_{\text{exec},P}$ when those instances are needed by E3/E5.

For $k = 0..n$, let:

- $\rho_{\text{post}}[k]$ be the ε -quiescent RTL_B cutpoint after the first k P-local observable units.
- $\sigma_{\text{post}}[k]$ denote the source-level slice associated with $\rho_{\text{post}}[k]$ by the cutpoint-abstraction correspondence later named $J.\text{Abs}/J.\text{AbsConf}$ in Appendix J.
- $\sigma_{\text{ref}}[k]$ be the Sys_{ref} state after the first k P-local observable units.

(Existence of these ε -quiescent representatives is exactly the ε -normalization discipline used throughout Appendix I/J.)

Key invariant $I(k)$.

For every source-level state variable v of process P that can influence any future Ω_P frontier item that may later contribute Σ -visible behavior of P (in particular: any v that may be read by (i) $\text{BoundaryReq}(x, \cdot)$ for a message-operation frontier item $x \in \Omega_{\text{msg},P}$, interpreted through its owning message instance $q = \text{MsgOf}_P(x)$, (ii) a control predicate Pred_x deciding reachability/selection of the next frontier item(s), or (iii) a payload/value expression for the next frontier item(s)), we have:

$v(\sigma_{\text{ref}}[k]) = v(\sigma_{\text{post}}[k])$.

Here $\sigma_{\text{post}}[k]$ is not obtained by an implicit tool-independent bit-level projection from arbitrary RTL_B registers. It is the source-level replay/cutpoint slice associated with $\rho_{\text{post}}[k]$ by the same $J.\text{Abs}/J.\text{AbsConf}$ -style abstraction relation later used explicitly in Corollary J.1. In this S1/I.DR argument, only the Σ -relevant deterministic-replay part of that slice is used: under fixed stimulus and the WC premise, that Σ -relevant source-state slice is uniquely determined by the preceding P-local observable-unit replay sequence together with the fixed witness/annotation package. The additional request/pending/attribution facts needed later by Appendix K are supplied,

when used, by the full J.Abs/J.AbsConf cutpoint-abstraction obligation, not by deterministic replay alone.

Deterministic replay (Lemma I.DR).

Under the fixed stimulus and the WC premise, Lemma I.DR gives Σ -relevant source-state determinacy at ϵ -quiescent cutpoints: for a fixed witness, the Σ -relevant source-state slice after the first k P-local observable units is uniquely determined by the initial Σ -relevant source-state slice together with the P-local observable-unit replay prefix (including any Pop return value or anchored Read value).

Apply Lemma I.DR to the two source-level executions induced by the compared prefixes: (a) the Sys_ref execution of P producing $\tau_{\text{ref},P}$, and (b) the deterministic source-level replay corresponding to $\tau_{\text{post},P}$ under the fixed witness (WC), whose ϵ -quiescent cutpoint slices are denoted $\sigma_{\text{post}}[k]$. These two source-level executions start from the same initial Σ -relevant source-state slice (fixed-stimulus setup) and produce the same P-local observable-unit replay sequence $u_1 u_2 \dots u_n$ under the selected witness/annotation package (by annotated Σ /observable-unit matching). Therefore, for every k , the Σ -relevant deterministic-replay slices agree; in particular, every source-level variable, control predicate, and payload/value expression covered by $I(k)$ agrees between $\sigma_{\text{ref}}[k]$ and $\sigma_{\text{post}}[k]$. To the extent $I(k)$ is later used for BoundaryReq or request-attribution facts that are not determined by the bare P-local Σ -label sequence alone, those facts are read through the J.Abs/J.AbsConf cutpoint-abstraction

slice, as stated in Corollary J.1, rather than inferred from Lemma I.DR alone. Thus $I(k)$ holds for the Σ -relevant deterministic-replay portion for all k , and the later Corollary J.1/K uses of request/pending state are covered by the named cutpoint-abstraction obligation.

Conclusion of the invariant.

By induction, $I(n)$ holds at the terminal matched cutpoints $\sigma_{\text{ref}} = \sigma_{\text{ref}}[n]$ and $\sigma_{\text{post}} = \sigma_{\text{post}}[n]$.

Now discharge the lemma's four conclusions for any $x \in \text{NextFront}_P(\sigma_{\text{ref}})$:

(1) $\text{Pred}_x(\cdot)$, when present, is a source-level control predicate evaluated from source-level variables of P at the cutpoint. Since those variables agree by $I(n)$, the control-predicate evaluations agree:

$\text{Pred}_x(\sigma_{\text{ref}}) = \text{Pred}_x(\sigma_{\text{post}})$.

If $x \in \Omega_{\text{msg},P}$ is a blocking message-operation frontier item with owning message instance $q = \text{MsgOf}_P(x)$ and $\text{kind}(q) \in \{\text{Push}_c, \text{Pop}_c\}$, then $\text{BoundaryReq}(x, \cdot)$ is also an operation-attributive source-level predicate evaluated from source-level variables and request-attribution facts of P at the cutpoint, read through q . Since the relevant source-level variables agree by $I(n)$, and since any request-attribution facts not determined by the bare P-local observable sequence alone are supplied by the J.Abs/J.AbsConf cutpoint-abstraction slice as described above, the boundary-request evaluations agree: $\text{BoundaryReq}(x, \sigma_{\text{ref}}) = \text{BoundaryReq}(x, \sigma_{\text{post}})$.

If x is not a blocking message-operation frontier item, no persistent $\text{BoundaryReq}(x, \cdot)$ agreement is required by this clause, so there is no BoundaryReq conclusion to prove for that frontier item. Successful non-blocking frontier items are handled through their selected committed Σ -label/value facts when they commit, not through pending-request persistence at the ϵ -quiescent cutpoint. Failed non-blocking polls may be present in $Q_{\text{exec},P}$ for witness-matching purposes, but they are not members of NextFront_P and are not considered in this BoundaryReq frontier conclusion.

(2) Any payload/value expression for a Push or anchored Write reads some set of source-level variables of P. Those variables agree by $I(n)$, so the produced value agrees.

(3) For Pop_c , the returned value is the FIFO head after the matched history; this is identical on both

sides by the bounded-FIFO legality semantics and the matched Push/Pop history.

(4) For anchored signal reads at the next synchronization call, the observed values agree under the fixed-stimulus interpretation plus anchoring; this is the same mechanism used to justify matching $\text{Read}(\text{sig}, \text{val})$ labels in the first place.

Therefore, (1)–(4) hold, proving Lemma S1. ■

Lemma S2 (Prefix-to-frontier determinacy / “matched Σ -prefix $\Rightarrow$ same next source-level frontier-item set”)

Fix a process P . Let Sys_ref denote the prescribed source reference model of Appendix J, Remark 2: Sys in the raw rendezvous case, Sys_B in the ordinary bounded-FIFO case, and $\text{Sys_B}^{\text{elab}}$ in the elaborated back-annotated case. Let $\tau_{\text{ref}, \text{system}}$ be a finite Sys_ref execution prefix ending in state σ_{ref} , and let $\tau_{\text{post}, \text{system}}$ be a finite RTL_B execution prefix ending in state σ_{post} .

Assume:

(A1) $\tau_{\text{ref}, \text{system}} \approx \tau_{\text{post}, \text{system}}$ under E1–E5.

(A2) σ_{post} is the ε -normalized (ε -quiescent) endpoint associated with $\tau_{\text{post}, \text{system}}$ (as used in Corollary J.1).

(A3) $\leq_P$ is P ’s source-induced partial order on Ω_P generated by the document’s R-rules (R1–R4) and the chosen channel/synchronization semantics; the same Ω_P and $\leq_P$ are used on both the Sys_ref and RTL_B sides for the fixed compared witness. The observable alphabet Σ_P is the label/event projection of the items in Ω_P , not the universe over which pending frontier membership is defined.

Definition (Next source-level frontier-item set).

For any terminal state σ , define $\text{NextFront}_P(\sigma)$ as follows.

1. Let $\tau_P(\sigma)$ be the projection of the system prefix leading to σ onto P ’s Σ -events. Clarification (dynamic execution-call universe and frontier-item universe; fixed for this comparison). In this lemma, $Q_{\text{exec}, P}$ denotes the set of P ’s executed dynamic source-level message-call instances in the per-process execution / witness determined by the fixed external stimulus for the comparison $\tau_{\text{ref}, \text{system}} \approx \tau_{\text{post}, \text{system}}$, including, when applicable, any witness-selected failed non-blocking polls required by Appendix I.2. Separately, Ω_P denotes the set of P ’s dynamic source-level frontier items in that same per-process execution / witness. Thus Ω_P is a single shared frontier-item universe for both prefixes, Sys_ref and RTL_B : it does not depend on how a finite prefix is extended, nor on ε -interleavings between Σ -events. In particular, Ω_P excludes items on untaken control-flow paths, e.g. the “else” branch when the “if” branch was taken, excludes items from loop iterations that are not executed in the fixed-stimulus- and witness-determined per-process execution used for this comparison, and excludes failed non-blocking polls merely because they executed.

Because $Q_{\text{exec}, P}$ contains dynamic message-call instances while Ω_P contains frontier items, the message-operation slice of Ω_P is not the literal intersection $Q_{\text{exec}, P} \cap \Omega_P$. Let $\text{MsgOf}_P(x)$ be the partial projection from a frontier item $x \in \Omega_P$ to its owning dynamic message-call instance, defined exactly for message-operation frontier items. Define

$$\Omega_{\text{msg}, P} := \{ x \in \Omega_P \mid \exists q \in Q_{\text{exec}, P} : \text{MsgOf}_P(x) = q \}$$

and

$$Q_{\Omega,P} := \{ q \in Q_{\text{exec},P} \mid \exists x \in \Omega_{\text{msg},P} : \text{MsgOf}_P(x) = q \}.$$

The observable alphabet/projection Σ_P is derived from Ω_P : synchronization and signal items contribute their corresponding Σ labels when observed, and a message-operation frontier item $x \in \Omega_{\text{msg},P}$ with $\text{MsgOf}_P(x)=q$ contributes the committed Σ -event $m(q)$ only if q commits. A pending blocking message-operation frontier item may therefore be in Ω_P , in $\Omega_{\text{msg},P}$, and in $\text{NextFront}_P(\sigma)$, and its owning message instance may be in $Q_{\Omega,P}$, even though the committed Σ -event $m(q)$ is not yet present. A failed non-blocking poll $q \in Q_{\text{exec},P}$ that induces no frontier item in $\Omega_{\text{msg},P}$ is an ε -step and is matched only through WC / μ_Q when relevant; it is not an element of Ω_P , $\Omega_{\text{msg},P}$, $Q_{\Omega,P}$, Done_P , Remain_P , or NextFront_P . Note: even if one of the compared prefixes is deadlocked and therefore cannot realize further committed Σ -events, Ω_P remains this fixed witness universe and is not reduced by deadlock.

2. Let $\text{Done}_P(\sigma) \subseteq \Omega_P$ be the set of source-level frontier items of P that have been realized by σ . For synchronization and signal items, this means that the corresponding Σ -event has occurred in $\tau_P(\sigma)$. For a message-operation frontier item $x \in \Omega_{\text{msg},P}$ with $\text{MsgOf}_P(x)=q$, “realized” means that the owning message-call instance q has committed and its committed Σ -event $m(q)$ occurs in $\tau_P(\sigma)$. A blocking message-operation frontier item x whose owning message instance q has issued but not yet committed is not in $\text{Done}_P(\sigma)$, even though $\text{BoundaryReq}(x,\sigma)$, $\text{ChannelEnabled}(x,\sigma)$, and $\text{ChannelDisabled}(x,\sigma)$ may be defined at σ , read operation-attributively through $q = \text{MsgOf}_P(x)$. A failed non-blocking poll $q \in Q_{\text{exec},P}$ that induces no frontier item in $\Omega_{\text{msg},P}$ is not in $\text{Done}_P(\sigma)$ because it is not in Ω_P . Canonical matching is by source-level dynamic frontier-item identity / occurrence index, with Σ labels matched as before, e.g. “ k -th Push_c commit matches k -th Push_c commit”, “ k -th Sync matches k -th Sync ”, etc.

3. Let $\text{Remain}_P(\sigma) := \Omega_P \setminus \text{Done}_P(\sigma)$.

4. Define:

$$\text{NextFront}_P(\sigma) := \min_{\leq_P} \{ \text{Remain}_P(\sigma) \},$$

i.e. the set of $\leq_P$ -minimal remaining source-level frontier items for P .

This is exactly Corollary J.1’s “set of minimal (w.r.t. P ’s source partial order) remaining observable items,” but typed as source-level frontier items in Ω_P rather than already-committed Σ -events. It should be read as a candidate next source-level frontier-item set relative to the fixed witness universe Ω_P . In particular, because Ω_P is not reduced by deadlock, membership in $\text{NextFront}_P(\sigma)$ does not assert that the item is enabled or realizable as an immediate successor of σ when σ is deadlocked; it only asserts $\leq_P$ -minimality among the not-yet-realized items in Ω_P .

Claim.

Under (A1)–(A3),

$$\text{NextFront}_P(\sigma_{\text{ref}}) = \text{NextFront}_P(\sigma_{\text{post}}).$$

Proof.

Step 0 (Reduce to the per-process view).

It suffices to show that $\text{Done}_P(\sigma_{\text{ref}}) = \text{Done}_P(\sigma_{\text{post}})$; frontier equality then follows immediately from the shared Ω_P , by the definition above, and the shared $\leq_P$, by (A3).

Step 1 (Synchronization events completed are identical).

Under the document's canonical matching, synchronization events for P are matched by source order / occurrence index: the k -th sync in the source corresponds to the k -th sync in the observable history.

Under E1, and the sync-order constraints embedded in $\approx$, $\tau_{\text{ref},P}$ and $\tau_{\text{post},P}$ contain the same set, equivalently the same prefix, of P 's sync events. Hence the "current sync interval" is the same on both sides.

Step 2 (Anchored signal I/O events completed are identical).

Signal reads/writes are matched canonically by signal and occurrence index, with their anchoring to sync points enforced by E2 for sequential processes, and with R2C fixed-point signal-observation units matched by component identity and local R2C occurrence ordinal for combinational processes. Since Step 1 shows the same sync indices have been traversed for sequential-process signal IO, and E2 preserves the anchoring structure, $\tau_{\text{ref},P}$ and $\tau_{\text{post},P}$ contain the same set of P 's Σ -visible sequential signal read/write events. For combinational-process signal IO, R2C gives the corresponding equality of fixed-point Read/Write events in the matched component-local R2C occurrence units. Thus signal events contribute the same elements to $\text{Done}_P(\sigma_{\text{ref}})$ and $\text{Done}_P(\sigma_{\text{post}})$.

Step 3 (Committed message-operation items completed are identical).

By the Σ -event matching convention built into the definition of $\approx$, committed channel events are paired canonically by channel endpoint and ordinal occurrence: for each channel c , the k -th committed Push_c in τ_{ref} matches the k -th committed Push_c in τ_{post} , and likewise for Pop_c , with identical payload/value labels. The commutations/regroupings permitted by $\approx$ only affect the interleaving and same-cycle grouping of Σ -events on distinct independent endpoints; they do not change the per-endpoint projected sequence of committed events. That is, for any fixed endpoint e , $\text{proj}_e(\tau_{\text{ref},P})$ and $\text{proj}_e(\tau_{\text{post},P})$ are identical as sequences of Σ -labels up to the common prefix length. Therefore, for every endpoint-indexed source-level message-operation item q whose commit would be the endpoint event (e,k) , q has committed in $\tau_{\text{ref},P}$ iff the matched q has committed in $\tau_{\text{post},P}$, with the same committed Σ -label. Hence message-operation items contribute the same elements to $\text{Done}_P(\sigma_{\text{ref}})$ and $\text{Done}_P(\sigma_{\text{post}})$. Pending issued-but-uncommitted blocking operations remain outside Done_P on both sides; their request/enable correspondence is handled separately by the cutpoint correspondence clauses used by Appendix K.

Step 4 (Conclude Done equality, then frontier equality).

From Steps 1–3:

$$\text{Done}_P(\sigma_{\text{ref}}) = \text{Done}_P(\sigma_{\text{post}}).$$

Therefore:

$$\begin{aligned} & \text{Remain}_P(\sigma_{\text{ref}}) \\ &= \Omega_P \setminus \text{Done}_P(\sigma_{\text{ref}}) \\ &= \Omega_P \setminus \text{Done}_P(\sigma_{\text{post}}) \\ &= \text{Remain}_P(\sigma_{\text{post}}). \end{aligned}$$

Since $\leq_P$ is the same relation on both sides by (A3), taking $\leq_P$ -minimal elements preserves equality:

$$\min_{\leq_P} \{\text{Remain}_P(\sigma_{\text{ref}})\} = \min_{\leq_P} \{\text{Remain}_P(\sigma_{\text{post}})\}.$$

By definition of $\text{NextFront_P}(\cdot)$, this is:

$$\text{NextFront_P}(\sigma_{\text{ref}}) = \text{NextFront_P}(\sigma_{\text{post}}).$$

□

Proof of Corollary J.1

Step 0 (By definition, work with a chosen ϵ -normalized terminal state) By the ϵ -normalization defined in the Statement, choose one maximal finite ϵ -extension of the given prefix if needed, and continue to denote the resulting ϵ -normalized prefix by τ_{post} ; let σ_{post} be its ϵ -quiescent terminal state. This replacement preserves the observable prefix and is finite by B4. The remainder of the proof is carried out relative to this chosen ϵ -normalized representative; no claim about uniqueness or projection-equivalence of all maximal ϵ -extensions is needed here.

Step 1 (Get a matching source-level observable prefix) Fix the external test stimulus that produced the given post-HLS prefix τ_{post} . By the system-level prefix-matching property in Theorem J.1, applied to Sys_ref and RTL_B , there exists a finite execution prefix τ_{ref} of Sys_ref under that same stimulus such that $\tau_{\text{ref},\text{system}} \approx \tau_{\text{post},\text{system}}$ under E1–E5. Let σ_{ref} be the terminal state of this witness prefix τ_{ref} .

Step 2 (Align per-process control points) By Lemma S2, because $\tau_{\text{ref},\text{system}} \approx \tau_{\text{post},\text{system}}$ and E1/E2/E3/E4/E5 preserve per-process same-interface order, no-reverse constraints, side-of-sync constraints, and signal anchoring at synchronization points, each process P has executed the same per-endpoint observable history in both prefixes (up to commutation/regrouping of independent distinct-interface message commits). Here NextFront_P is understood exactly as in Lemma S2: it is the candidate next source-level frontier-item set relative to the fixed matched witness pair and its shared per-process universe Ω_{P} , not a stronger claim that the frontier is determined by raw microstate alone independent of the witness. Therefore, at the end of the prefixes,

$$\text{NextFront_P}(\sigma_{\text{ref}}) = \text{NextFront_P}(\sigma_{\text{post}}),$$

including the same logically anchored signal Read/Write action items at the next synchronization call when applicable.

Step 3 (Align the relevant source-level state and abstract channel slice) By Lemma S1, matched prefixes preserve the source-level state needed for next-action enablement and payloads exactly as in Appendix I, giving clause (2b). Clause (2c) holds for buffered channels because, under E4 and J.AbsConf, the abstract FIFO empty/full status, logical occupancy occ_c , and logical head element at the chosen Sys_ref boundary are the E4-visible channel-state slice represented by the RTL_B cutpoint. For ordinary Sys_B channels this slice is induced by the matched Push/Pop history of (1). For elaborated $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$ channels it is interpreted over the explicit staged, bundle, join, or sync-boundary abstract channels introduced by the elaboration. In both cases, internal RTL transfers that do not commit a boundary transfer are ϵ -state and do not change the abstract FIFO slice.

Clause (2d) holds for point-to-point rendezvous channels in the Appendix K internal message-passing boundary / WFG analysis by J.AbsConf: the J.Abs source slice for the chosen ϵ -quiescent RTL_B cutpoint includes the raw producer-side and consumer-side endpoint-request predicates at the chosen abstract boundary. This is therefore a discharged RTL_B cutpoint-abstraction fact, not a consequence of matched per-endpoint observable history alone and not a consequence of NextFront_P equality.

Step 4 (Align already-issued blocking request state) It remains to establish clause (2e), since NextFront_P equality by itself does not determine the state of already-issued but not-yet-committed blocking requests. This is exactly the blocking request attribution and pending slice required by J.Abs. For each blocking message-operation frontier item $x \in \Omega_{\text{msg},P}$ in P 's current interval between adjacent

synchronization calls, with owning dynamic message-call instance $q = \text{MsgOf_P}(x)$, $J.\text{AbsConf}$ gives the same source-level call-instance identity, endpoint/interface identity, attribution history, and issued-but-not-yet-committed status at the compared cutpoints. Hence

$x \in \text{Pending_P}(\sigma_{\text{ref}})$ iff $x \in \text{Pending_P}(\sigma_{\text{post}})$.

For every such common pending frontier item x , with $q = \text{MsgOf_P}(x)$, $J.\text{AbsConf}$ also gives agreement of the operation-attributive endpoint-owned request for q , so

$\text{BoundaryReq}(x, \sigma_{\text{ref}}) = \text{BoundaryReq}(x, \sigma_{\text{post}})$.

Non-withdrawability is used here only for its proper role: once a blocking request has issued, Appendix C's Issue/Commit linkage ensures that the endpoint-owned request remains asserted and attributed to the same q until commit, with stable Push payload when applicable. Non-withdrawability does not, by itself, prove that $\text{Issue}(q)$ has occurred at corresponding cutpoints in both models; that cross-model issued-but-not-yet-committed correspondence is supplied by $J.\text{AbsConf}$.

Channel enablement then agrees. For $B(c) > 0$ channels, this follows from the common $B(c)$, the E4 channel-realization semantics, and the logical occupancy/head-state agreement of clause (2c). For $B(c) = 0$ rendezvous channels, it follows from the raw producer-side and consumer-side endpoint-request agreement of clause (2d). In the elaborated case $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$, the same argument is interpreted over the explicit abstract channels of $\text{Sys_B}^{\text{elab}}$. Thus

$\text{ChannelEnabled}(x, \sigma_{\text{ref}}) = \text{ChannelEnabled}(x, \sigma_{\text{post}})$,

equivalently

$\text{ChannelDisabled}(x, \sigma_{\text{ref}}) = \text{ChannelDisabled}(x, \sigma_{\text{post}})$,

for every common pending frontier item x . Combining Steps 1–4 gives a terminal source-level state σ_{ref} with $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ in the $J.\text{Abs}/J.\text{AbsConf}$ sense. $\square$

J.3 Causal Dependency and What System-Level Compatibility Guarantees (Informative)

The system-level result of Appendix J establishes compatibility of the aggregate observable behavior, i.e. $\tau_{\text{ref}, \text{system}} \approx \tau_{\text{post}, \text{system}}$ over the alphabet Σ of channel operations, synchronization events, and signal Read/Write actions.

This compatibility is intentionally *observational*: it constrains what an external environment can distinguish at Σ , not internal RTL micro-timing.

As a consequence, Appendix J should be read as preserving explicitly required observable ordering, atomicity, and FIFO/synchronization semantics, not incidental latency. The causal-dependency relation ($\rightarrow$) defined in the “Causal Dependency Between Processes” section remains useful for explaining information flow and for documenting which interactions a designer intends to be functionally significant. However, $\rightarrow$ is not itself the strict induction order for Theorem J.1, and the theorem does not require the unquotiented dependency graph $\rightarrow$ to be acyclic. The proof order is the required-order relation $\prec_J$ over observable units.

Accordingly, the system-level theorem implies the following required-order preservation principle:

- If two observable units γ_1 and γ_2 are ordered by the required-order relation $\gamma_1 \prec_J \gamma_2$, then the matched Sys_ref and RTL_B executions preserve that required order. This follows because each elementary $\prec_J$ generator is preserved by the corresponding rule: synchronization source order by E1; signal-anchor timestamping by E2; issue-side and request-attribution obligations by E3; channel FIFO legality and rendezvous atomicity by E4; immediate synchronization-boundary constraints by E5; and paired-barrier semantics by the explicit synchronization well-formedness conditions. In particular, for each explicit abstract channel c , the matched executions preserve the committed $\text{Push_c}/\text{Pop_c}$ history:

for $B(c)=0$, a committed transfer is one explicitly atomic rendezvous $\text{Push}_c(v)/\text{Pop}_c(v)$ unit; for $B(c)>0$, the k -th committed Pop_c observes the k -th earlier unmatched Push_c according to reset-empty, FIFO-order, no-underflow/no-overflow, and non-fall-through E4 semantics.

- If two observable units are not ordered by $\prec_J$ and are not members of the same explicitly atomic unit, then their relative cycle placement or interleaving is not constrained by the methodology, and differences are treated as incidental latency variation. A designer who needs a particular cross-process ordering to be preserved must express it through an explicit Σ -visible mechanism such as message-passing FIFO order, a rendezvous/handshake atomic unit, explicit synchronization, or signal-anchor semantics.

This perspective is what makes the “single testbench / no surprises” implication precise: for the fixed-stimulus execution sets covered by Theorem J.1, any testbench that observes only Σ and encodes its expectations through causal dependencies (channels, barriers, or explicit handshakes) cannot distinguish the matched Sys_ref / RTL_B execution pairs provided by the theorem.

Equivalently, RTL_B introduces no new Σ -observable behavior relative to Sys_ref under that fixed stimulus, and source-to-RTL transfer is asserted only for the RTL-consistent source prefixes covered by Theorem J.1. (Here Sys_ref is as fixed in Remark 2. The rendezvous specialization Sys with $B(c)=0$ is covered only under the explicit conditions of Remark 4.)

Appendix K – Liveness Preservation for the Prescribed Source Reference Model

K.1 Scope, Notation, and Definition of Internal Message-Passing Deadlock

Terminology alignment

Throughout Appendix K, when evaluating predicates at an ε -quiescent cutpoint σ , let t_σ denote the cycle of that cutpoint and use the cutpoint shorthand $\text{occ}_c(\sigma) \triangleq \text{occ}_c(t_\sigma)$. For any dynamic source-level message-operation instance $q \in Q_{\text{exec},P}$ on an explicit abstract channel c of Sys_ref , use the shorthands $\text{BoundaryReq}(q,\sigma)$, $\text{ChannelEnabled}(q,\sigma)$, and $\text{ChannelDisabled}(q,\sigma)$ as defined in “Common Formal Definitions for Appendices I-K”; equivalently, when a cycle-index notation is needed, these mean $\text{BoundaryReq}(q,\sigma_t)$, $\text{ChannelEnabled}(q,\sigma_t)$, and $\text{ChannelDisabled}(q,\sigma_t)$ at the ε -quiescent cutpoint for cycle t . Thus ‘boundary request is asserted’ means $\text{BoundaryReq}(q,\sigma)$; ‘channel-enabled’ means $\text{ChannelEnabled}(q,\sigma)$; and ‘channel-disabled’ means $\text{ChannelDisabled}(q,\sigma)$, all evaluated for the specific operation instance q at the ε -quiescent ready/valid fixed point of the cutpoint cycle. These predicates are not applied to already-committed Σ -event labels except through the operation instance q that contributes $m(q)$ when it commits.

We work with a fixed design:

System Sys_ref : The collection of pre-HLS processes obeying the R-rules and B-rules, interpreted under the prescribed source reference model of Appendix J, Remark 2. In this appendix, capacities/occupancies/enableness predicates are interpreted at the chosen abstract boundaries of Sys_ref ; in elaborated cases, this means the explicit abstract staged/bundle/join channels of that model. Each explicit abstract channel c of Sys_ref has finite capacity $B(c) \geq 0$, chosen to match the corresponding RTL realization at that abstract boundary.

Post-HLS implementation RTL_B: The hardware implementation of the same processes in which each chosen abstract channel c is realized with finite capacity $B(c) \geq 0$. In this appendix, we compare Sys_ref (the prescribed source-side proof target) to RTL_B (the micro-architectural realization). The proof does not require mapping buffered RTL states to a distinct raw rendezvous ($B(c)=0$) state.

Witness-selection note (debug/simulation): Appendix K's liveness argument uses Corollary J.1 only to assert existence of a corresponding Sys_ref state σ_{ref} for a given ε -normalized RTL state σ_{post} (via the source-level correspondence $\equiv$). If, for practical debug, one wishes to construct a deterministic Sys_ref execution that tracks the unique RTL Σ -trace ($B1$) so that σ_{ref} / WFG_ref are reproducible, then the Appendix L snooping wrapper may be applied to select a witness Sys_ref execution aligned to RTL latency-sensitive events.

A global state σ of either system consists of:

1. For each process P : a control location (program point) and local state.
2. For each explicit abstract channel c of Sys_ref: its abstract FIFO state at the chosen Sys_ref boundary—its current occupancy $\text{occ}_c(t)$ and (for buffered channels) its ordered contents. Here $\text{occ}_c(t)$ counts all items that have been committed by Push_c but have not yet been committed by Pop_c at that chosen abstract boundary. In RTL_B, this count includes items residing anywhere in the concrete sub-realization that contributes to that particular abstract channel's back-annotated capacity $B(c)$. Thus internal movement within the concrete realization of one abstract channel c is ε and does not create additional committed Push_c/Pop_c Σ -events beyond the boundary events counted by occ_c ; however, transfers between distinct explicit abstract channels introduced in Sys_B^elab are represented in Sys_ref by those channels themselves and are not collapsed back into one outer Sys_B boundary.
3. Any additional architectural state not representing buffered messages on any channel (e.g., computation pipeline registers, arbitration state, bookkeeping, etc.).

We adopt the usual Wait-For Graph (WFG) abstraction, restricted to internal message-passing channels. Internal means: the producer and consumer of channel c are both processes of Sys_ref / RTL_B (i.e., both endpoints are in the modeled system). Channels whose complementary endpoint is the external environment/testbench (DUT boundary) are excluded from the WFG and from the deadlock definition in Appendix K. We write WFG_ref for the wait-for graph of Sys_ref and WFG_post for that of RTL_B.

- **Vertices:** Processes.
- **Edges:** There is a directed edge $P \rightarrow Q$ via channel c in state σ if there exists some frontier item $x \in \text{Front}_P(\sigma)$ on channel c , with owning message instance $q = \text{MsgOf}_P(x)$, such that x is channel-disabled (i.e., $\text{ChannelDisabled}(x, \sigma)$ holds), and Q is the unique process that is the complementary endpoint for q (producer/consumer partner for c). This edge definition applies uniformly for both buffered channels ($B(c) > 0$, enable is space/data availability via occ_c) and rendezvous channels ($B(c) = 0$, enable requires the complementary endpoint's boundary request to be true in the same cycle), hence WFGs may contain a mix of edges via both kinds of channels. Here $\text{Front}_P(\sigma)$ is the set of $\leq_P$ -minimal pending blocking message-operation frontier items $x \in \Omega_{\text{msg}, P}$ whose owning message instances $q = \text{MsgOf}_P(x)$ have $\text{kind}(q) \in \{\text{Push}_c, \text{Pop}_c\}$, have issued, and have not yet committed. $\text{Front}_P(\sigma)$ may contain multiple frontier items on distinct interfaces (reflecting the R/E freedom to issue/commit multiple Push/Pop in one cycle). P is “blocked on message passing” in σ as defined in Definition (Blocked on message passing) (K.1). Note: WFG edges may exist even when P is not blocked (e.g., one frontier item is channel-disabled while another is channel-enabled); however, internal message-passing deadlock (K.1) considers only sets D in which every $P \in D$ is blocked, so all WFG edges

relevant to deadlock reasoning originate from blocked processes with no channel-enabled frontier item. When $\text{Front_P}(\sigma)$ has multiple members, P may have multiple outgoing WFG edges (one per blocked frontier item).

(No deassert-before-commit assumption.) Blocking $\text{Push_c}/\text{Pop_c}$ requests are non-withdrawable: once the request corresponding to a frontier item $x \in \Omega_msg, P$ is asserted through its owning message instance $q = \text{MsgOf_P}(x)$, it is not deasserted before q commits (and Push_c payload remains stable while asserted). This rules out “try-and-withdraw” behavior for blocking transfers within the WFG abstraction.

All WFG reasoning is over ϵ -quiescent (ϵ -normalized) global states: internal pipeline/arbitration micro-steps are treated as ϵ and are not represented as separate WFG blocking points. Here, “ ϵ -quiescent” includes the fixed point of purely combinational ready/valid propagation, so K.1 enablement is evaluated only on those settled ready/valid values.

(WFG-inert ϵ premise.) Appendix K uses ϵ -steps only after the WFG-relevant boundary-request / attribution cutpoint has been fixed. More precisely, consider an ϵ -path $\sigma \xrightarrow{\epsilon^*} \sigma'$ that contains no Σ -visible committed $\text{Push_c}/\text{Pop_c}$ event, no synchronization event, no signal Read/Write event, and no source-level issue/attribution transition that creates, removes, or reassigns a pending blocking boundary request. Such ϵ -steps are observationally silent with respect to the WFG abstraction: they do not change (i) the potentially-blocking frontier $\text{Front_P}(\sigma)$ for any process P (i.e., which guarded blocking Push/Pop frontier items are minimal and pending), nor (ii) the truth or attribution of any boundary requests relevant to those frontier items, nor (iii) the channel-side enabling status (as defined in K.1) of any $x \in \text{Front_P}(\sigma)$, read through $q = \text{MsgOf_P}(x)$. Equivalently, these WFG-inert ϵ -steps do not change the channel state relevant to K.1 enabling (e.g., $\text{occ_c}(t)$ for $B(c) > 0$ buffered channels), and they do not create/remove rendezvous enablement for a frontier transfer except via Σ -visible committed $\text{Push_c}/\text{Pop_c}$ events.

This premise does not say that every non- Σ microstep is WFG-inert. In particular, an ϵ -normalization segment may include source-level issue/attribution steps that establish a persistent blocking request, such as moving from a cutpoint before a Pop has issued to a cutpoint where the Pop request is pending and BoundaryReq is true. Those steps may change Front_P , BoundaryReq , or request attribution, and are therefore not the ϵ -steps quantified over by the WFG-inert premise. Appendix K’s WFG construction is applied only at the resulting ϵ -quiescent cutpoints, after such request/attribution state has been fixed.

In particular (pipelined loops / overlapped iterations): when HLS introduces overlap that may initiate later-iteration message reads “early,” we assume the design obeys the Automatic flush (drain-only blocking discipline) defined in Appendix B. Under that discipline, once the process has reached a stable blocked frontier, overlapped execution does not introduce any later-iteration blocking Push/Pop frontier item into $\text{Front_P}(\sigma)$, so transient internal pipeline activity that merely moves already-accepted work inside the concrete realization remains WFG-inert ϵ and does not contribute wait-for edges. Overlapped execution in pipelined loops is modeled only as a potential retiming of ordinary Σ -visible boundary commits ($\text{Push_c}/\text{Pop_c}$) relative to the unpipelined source, and is accounted for by the back-annotated semantics at the chosen abstract boundary of Sys_ref (E4). In particular, the channel facts relevant to K.1 enabling/WFG edges—e.g., $\text{occ_c}(t)$ for $B(c) > 0$, and rendezvous enablement for $B(c) = 0$ —change only on Σ -visible committed $\text{Push_c}/\text{Pop_c}$ events at that boundary, or on explicit source-level issue/attribution steps before the WFG cutpoint is formed; internal movement within the concrete realization of a single abstract channel after that cutpoint is WFG-inert ϵ and does not affect K.1 enablement or introduce/remove WFG edges.

Precondition ($K\epsilon$: WFG-inert ϵ / no hidden micro-timing control decisions). All results in

Appendix K are stated under the precondition $K\epsilon$ that the narrowed WFG-inert ϵ premise above holds for the design at the ϵ -quiescent cutpoints used for WFG reasoning. If an implementation intentionally uses internal micro-timing after such a cutpoint to change Front_P membership, boundary-request attribution, or $\text{ChannelEnabled/ChannelDisabled}$ facts without a corresponding Σ -visible event or explicit source-level issue/attribution transition, then $K\epsilon$ is violated unless that behavior is made Σ -observable (e.g., via explicit modeling/snooping) or is witness-selected under the Appendix I.2 framework.

A common instance is branching on the success/failure of a non-blocking poll in a way that changes the next Σ -visible candidate frontier **NextFront_P(σ)** (Corollary J.1 / Lemma S2); in that case, either NB-CF must hold (Appendix I.2), or the poll outcomes must be witness-selected as stated there.

Non-blocking polling attempts and other purely internal actions do not contribute edges to the WFG; they are modeled as internal ϵ -steps. When a non-blocking call succeeds, that success is already represented at the Σ level as the corresponding committed Push_c/Pop_c event, but it does not itself add a wait-for edge because it is not a blocking operation.

SyncChannels and barrier well-formedness.

SyncChannel (barrier) operations are treated as pure synchronization events and are omitted from the Wait-For Graph, which tracks only blocking Push/Pop dependencies. We therefore interpret “deadlock” in this appendix as **internal message-passing deadlock** (i.e., a deadlocked set in which all processes are blocked on some internal Push/Pop dependency captured by the WFG). Any global stall at a barrier caused by mismatched or conditional participation (e.g., a process can permanently bypass the barrier or reach it a different number of times) is a specification-level error already present in the pre-HLS model; such stalls are not created by the HLS transformation and are excluded by an explicit barrier well-formedness assumption (A8 below), not by the internal message-passing deadlock premise. Under this assumption, omitting SyncChannels from the WFG is sound: a post-HLS deadlock implies the existence of a Push/Pop wait-cycle as characterized below.

Definition (Blocked on message passing). Using $\text{Front_P}(\sigma)$ as defined above, we say that P is blocked on message passing in state σ iff $\text{Front_P}(\sigma)$ is non-empty and, for every frontier item $x \in \text{Front_P}(\sigma)$, $\text{BoundaryReq}(x, \sigma)$ holds and $\text{ChannelDisabled}(x, \sigma)$ holds (equivalently, $\text{BoundaryReq}(x, \sigma) \wedge \neg \text{ChannelEnabled}(x, \sigma)$), read operation-attributively through the owning message instance $q = \text{MsgOf_P}(x)$. Note ($\text{ALL disabled} \Rightarrow \text{stall}$). If any frontier item $x \in \text{Front_P}(\sigma)$ is channel-enabled at the chosen Σ -visible boundary, then P is not “blocked on message passing” for WFG purposes. Consequently, an implementation may not be physically stalled at the chosen Σ boundary by a cross-channel “join” predicate while some frontier item $x \in \text{Front_P}(\sigma)$ at that boundary remains channel-enabled; any such conjunctive/join dependency must be represented as an explicit staged/bundle/join boundary channel so that, when the process is physically stalled, the relevant frontier items on that explicit boundary are all channel-disabled.

Definition (Drain-closed cutpoint for deadlock extraction). Let D be a non-empty set of processes. An ϵ -quiescent state σ is drain-closed for D iff no already-issued non-frontier blocking Push/Pop request of any process $P \in D$ is channel-enabled at σ . Equivalently, after the frontier members $\text{Front_P}(\sigma)$ are all disabled, there is no remaining already-issued downstream transfer of any process in D that can still commit as drain-only progress.

Here “already-issued downstream transfer” means an already-issued non-frontier blocking message-operation frontier item $x \in \text{Pending_P}(\sigma) \setminus \text{Front_P}(\sigma)$, with owning message instance $q = \text{MsgOf_P}(x)$, interpreted at the chosen abstract Sys_ref / RTL_B boundary and within the current source interval, i.e.,

the interval between the adjacent synchronization calls that bracket σ in P 's current execution; hidden internal pipeline staging or later-iteration prefetch absorbed into $B(c)$ is not a separate source-level operation for this definition unless it has been made an explicit abstract channel in $\text{Sys_B}^{\text{elab}}$. If such a non-frontier drain transfer is enabled, σ is not yet a stable deadlock cutpoint for D ; either that drain transfer must be allowed to commit finitely often until a drain-closed cutpoint is reached, or the resulting commit changes the WFG-relevant channel facts so that some frontier operation becomes enabled and the candidate deadlock disappears.

Finite drain note. At a blocked frontier satisfying the automatic-flush discipline, no new later blocking message-operation frontier item may be issued. Therefore the only downstream work that can still drain is work already accepted before the blocked condition. Because every explicit abstract channel has finite capacity $B(c)$, every process has finite ϵ -depth D_P when not externally stalled, and no new work may cross the blocked frontier, the number of D -owned downstream drain commits before reaching a drain-closed ϵ -quiescent cutpoint is finite. A coarse bound may be taken as a function of the sum of the relevant in-flight occupancies on explicit abstract channels plus the finite per-process ϵ -depths D_P ; the exact numeric bound is not used by Theorem K.1, only finiteness.

An internal message-passing deadlock is a reachable ϵ -quiescent state σ in which there exists a non-empty set of processes D such that σ is drain-closed for D and:

- Every process P in D is blocked on message passing, and in particular there exists at least one frontier item $x \in \text{Front_P}(\sigma)$ on an internal message-passing channel c (i.e., a channel included in the WFG), with owning message instance $q = \text{MsgOf_P}(x)$, such that $\text{BoundaryReq}(x, \sigma)$ holds and $\text{ChannelDisabled}(x, \sigma)$ holds.
- The vertices in D , together with the internal channels they access, form a strongly connected component in the WFG that has no outgoing edges (a closed cycle): processes in D can only wait on each other.

Intuitively, D is a set of processes that are waiting only on each other (via internal message-passing channels tracked by the WFG), with no remaining enabled drain-only transfer of any process in D that could change the WFG-relevant channel facts. Thus D can never be unblocked either by activity elsewhere in the modeled system or by already-issued downstream drain from within D . A process that is blocked solely on channels whose complementary endpoint is the external environment/testbench (excluded from the WFG) does not witness an internal message-passing deadlock in this appendix.

Terminated-process convention. For purposes of Appendix K, termination is interpreted per reset epoch. After a process P emits FINISH_P for a given reset epoch, the infinite execution is padded only by process-local idle stutter for P for the remainder of that epoch. This padding creates no new P -owned Σ -events, no new BoundaryReq , no new Front_P or NextFront_P item, and no new outgoing WFG edge from P . This epoch-local padding does not preclude a later reset boundary affecting P . If such a reset occurs and P later exits reset, the subsequent START_P is a new dynamic occurrence that begins a fresh reset epoch, and the earlier FINISH_P has no ordering, anchoring, or WFG force across that reset boundary. Any later termination of P is represented by a distinct dynamic FINISH_P occurrence. Thus a process blocked waiting for a complementary Push/Pop from a peer that has terminated in the current reset epoch is not, by itself, an internal message-passing deadlock in the K.1 sense. It is instead outside the K.1 deadlock notion unless the design includes an explicit modeled termination protocol that makes such waiting part of the internal channel protocol being analyzed.

Scope warning. This exclusion is only a scope convention for Theorem K.1. It does not imply that waiting forever for a terminated peer is benign or acceptable design behavior. If termination, EOF, done, cancellation, or end-of-stream behavior is part of the intended protocol, that behavior must be modeled

explicitly in Sys_ref and RTL_B, or verified separately outside the Appendix K internal message-passing-deadlock theorem.

Our notion of liveness in this appendix is: Liveness = absence of internal message-passing deadlock as defined above. (Starvation of a single process in an otherwise live system is ruled out separately by weak fairness.)

K.2 Assumptions and Imported Results

K.2.1 Standing Assumptions We assume throughout Appendix K:

A1. R-rules and B-rules. The prescribed source reference model Sys_ref and the post-HLS implementation RTL_B satisfy the process- and channel-level semantic rules defined earlier (R-rules and B-rules).

A2. Finite Pipeline Depth (FPD) / B4 finite ϵ -stutter. For each process P there is a finite bound D_P such that, along any consecutive ϵ -only evolution in which P is internally advancing toward its next observable Σ -action or its next Σ -action is locally enabled, and P is not externally stalled by a peer/environment/back-pressure condition, P executes at most D_P consecutive ϵ -steps before either (i) executing a Σ -action, or (ii) reaching a stable waiting state in which no further ϵ -step is available until some external/peer/environment condition changes the relevant enabling predicates. This is not a bound on time spent waiting for external stimulus, peer action, or back-pressure relief; such waiting is governed by WF/B2 and the channel-progress obligations B3. The system-level all-disabled quiescence bound used later in Appendix K is supplied by B5, with bound $\max_P D_P$.

A3. Weak Fairness (WF) (B2). If an action remains continuously enabled (its guard remains true), the scheduler eventually selects it.

A4. Channel Progress (B3 (Additional Semantic Assumptions (B-rules)); Appendix N). For each channel c with capacity B(c), assume the progress invariants of Appendix N hold. This is an obligation on the scheduler/environment (e.g., fairness of arbiters/back-pressure) and is not implied by the local R-rules alone.

A5. Source-Level Liveness Assumption under conservative serial-blocking source semantics. The prescribed source reference model Sys_ref (with capacities B(c) interpreted on its chosen abstract channels, including the explicit abstract channels of Sys_B^elab in the elaborated cases) is internally message-passing-deadlock-free under assumptions A1–A4 and the conservative serial-blocking source semantics defined below, where “deadlock” is the Appendix K WFG notion over blocking Push/Pop operations.

For A5 only, conservative serial-blocking source semantics means the following source-side liveness interpretation. Within each source interval between adjacent synchronization calls, a process does not issue a later source-order blocking Push/Pop operation until every earlier source-order blocking Push/Pop operation in that same interval has committed. Thus a later distinct-interface blocking request is not issued merely because the basic conceptual model would also permit parallel issue. This serial-blocking interpretation is used only to discharge the source-level liveness premise A5; it is not a restriction on the Appendix J trace-compatibility semantics, not a restriction on the selected Sys_ref witness used by Corollary J.1, and not a restriction on the RTL_B implementation’s allowed issue behavior.

A5 is discharged by proving that no reachable ϵ -quiescent state of Sys_ref, under the fixed stimulus and the conservative serial-blocking source semantics above, contains an internal message-passing deadlock in the Appendix K WFG sense. For purposes of A5, “reachable” means reachable along a finite prefix of an admissible Sys_ref / Exec_ref execution under the fixed stimulus that satisfies A1–A4, including the applicable weak-fairness and channel-progress obligations; A5 does not quantify over arbitrary unfair or

progress-violating raw scheduler interleavings. Non-blocking outcomes, signal/synchronization behavior, capacities $B(c)$, elaborated $\text{Sys_B}^{\text{elab}}$ boundaries, and the environment/stimulus assumptions remain governed by the other assumptions and appendices; A5 changes only the source-side scheduling policy used for the liveness check on blocking Push/Pop issue.

A source region whose liveness depends on favorable parallel issue of multiple blocking operations on distinct rendezvous interfaces does not discharge A5 merely because such parallel issue is permitted by the basic conceptual model or preserved by a particular RTL_B schedule. Such a region is outside the Appendix K liveness-preservation guarantee unless it is rewritten or modeled so that the conservative serial-blocking source semantics is live, or unless the region is verified separately outside Appendix K. Acceptable ways to bring the region back within Appendix K include, for example:

- rewriting the source so that liveness does not depend on parallel issue of distinct-interface blocking rendezvous operations;
- adding explicit buffering/capacity so the relevant channels are no longer rendezvous at the chosen abstract boundary;
- adding explicit synchronization or protocol structure that makes the required progress dependency part of the modeled source protocol; or
- isolating the region as latency-sensitive behavior and verifying it separately under an explicit witness-selection / snooping / RTL-scheduler certificate outside the A5 serial-liveness discharge.

This assumption does not assert freedom from SyncChannel/barrier specification errors, external-environment stalls, reset stalls, or other non-message-passing global stalls that Appendix K explicitly treats as out of scope.

A6. Point-to-point channels (single-producer/single-consumer). For each message-passing channel c (including buffered channels with $B(c) > 0$ and rendezvous channels with $B(c) = 0$), exactly one process performs all Push_c operations on c (the producer) and exactly one process performs all Pop_c operations on c (the consumer). Hence the complementary endpoint for any blocked Push_c/Pop_c is unique, and WFG edges are well-defined even for mixed WFGs that include both buffered and rendezvous channels.

If a design has a shared resource that would violate this uniqueness, it must be modeled via an explicit arbiter process plus point-to-point channels (as noted in “Common Formal Definitions” B(c)).

A7 (Determinism / witness selection / cutpoint abstraction). Assume B1 holds for RTL_B (post-HLS), so the Σ -labeled execution under the given stimulus is unique up to finite ϵ -stutter. Do not require B1 for Sys_ref: there may be multiple Sys_ref executions that are $\equiv$ to the same τ_{post} at the Σ /frontier level. Appendix K uses only the existence of such a selected Sys_ref witness (Corollary J.1), together with J.AbsConf for the same selected RTL_B cutpoint, Sys_ref cutpoint, and witness.

When a deterministic, reproducible Sys_ref witness is desired for simulation/debug, apply the Appendix L snooping wrapper to select a particular witness aligned with the latency-sensitive (arbiter-visible) ϵ -choices. We also rely on B4 (from the Additional Semantic Assumptions) and B5 (Appendix N) to justify ϵ -normalization / ϵ -quiescent endpoints, as required by Corollary J.1 (state correspondence). For every Corollary J.1 correspondence used to transfer Pending_P, BoundaryReq, rendezvous endpoint-request, ChannelEnabled/ChannelDisabled, Front_P, or WFG facts in Appendix K, the J.AbsConf obligation shall be discharged for the same selected triple $(\rho_{\text{post}}, \sigma_{\text{ref}}, w)$. A discharge for some unrelated existential Sys_ref cutpoint or witness is insufficient.

A8. Barrier well-formedness (SyncChannels). For each SyncChannel instance, the set of designated participant processes reaches the barrier the same number of times under the fixed stimulus/initial state; equivalently, no participant can permanently bypass a barrier call while another participant is waiting at that barrier. (Barrier stalls are therefore outside the behaviors considered in Appendix K’s internal message-passing deadlock analysis.)

A9. Single-transfer-per-cycle endpoint constraint (scalar channel interface). For every message-passing channel c , in any clock cycle t , at most one Push_c commit and at most one Pop_c commit may occur on c . If a design uses multi-lane/burst transfers on a logical resource, it must be modeled explicitly (e.g., k parallel point-to-point channels or a widened message) so that the Σ -level per-channel event model satisfies this constraint.

A10. Reset-empty FIFO assumption. After each reset boundary at which the compared execution begins or restarts, every buffered message-passing channel with $B(c) > 0$ has logical occupancy 0 at the chosen Σ boundary. The Appendix J/K occupancy equations and the per-channel Push/Pop precedence lemma are interpreted relative to that reset-empty initial channel state.

A11. WFG-inert ϵ ($K\epsilon$). The design satisfies Precondition $K\epsilon$ (WFG-inert ϵ / no hidden micro-timing control decisions) as stated in K.1.

No further standing assumption is introduced here beyond A1–A11. The conservative serial-blocking source-liveness requirement stated in A5 is part of the source-level liveness obligation, not a separate theorem conclusion derived from the local R-rules or from the no-reverse distinct-interface scheduling rule.

Scope of the liveness-preservation theorem. The Appendix K result should be read as a conditional preservation theorem: if the prescribed Sys_ref is internally message-passing-deadlock-free under A5’s conservative serial-blocking source semantics, if the compared RTL_B execution satisfies the imported fairness/progress and structural assumptions A1–A11, including the J.AbsConf cutpoint-abstraction obligation packaged in A7, and if the serial-source dominance lemma K.2b below applies, then an internal message-passing deadlock introduced by RTL_B would imply a corresponding witness-relative closed WFG deadlock in Sys_ref ; by K.2b, that deadlock yields a serial-blocking Sys_ref deadlock, contradicting A5. Appendix K does not by itself prove global source liveness, does not decompose source liveness into per-process obligations, and does not derive RTL-side scheduler/environment progress such as B2/B3/B5, WFG-inertness $K\epsilon$, J.AbsConf, or source-level serial liveness from the local R-rules. Those facts must be established by the source-level design argument, the RTL/tool-flow compliance evidence, the dominance lemma’s side conditions, or explicit environment assumptions before the liveness conclusion is applied.

The no-reverse scheduling rule for distinct-interface message operations is not, by itself, a liveness guarantee. It prevents one particular class of transformation — reversing source-order message calls — but it does not make every parallel-issue-dependent rendezvous protocol live under the conservative serial-blocking A5 semantics. Appendix K therefore uses the serial-blocking source semantics as the user-facing liveness check, while the proof may still use Corollary J.1 to obtain a selected Sys_ref witness cutpoint that reflects RTL_B ’s overlapped issue state. The bridge between those two facts is exactly Lemma K.2b below.

Example: blocking rendezvous operations whose liveness depends on parallel issue. Consider two rendezvous channels a and b with $B(a)=B(b)=0$ and two processes:

```
P1: b.Pop(); a.Push(v)
P2: a.Pop(); b.Push(w)
```

Under the conservative serial-blocking source semantics, each process issues only its first source-order blocking operation: P1 waits on Pop_b and P2 waits on Pop_a ; neither process reaches the complementary Push, so the system has a closed internal rendezvous WFG deadlock. If, instead, each process issues the two distinct-interface blocking operations in parallel, then both rendezvous transfers

can commit in the same cycle. This example is therefore outside the Appendix K liveness-preservation guarantee under A5 unless it is rewritten, buffered, explicitly synchronized, or verified separately outside Appendix K as a latency-sensitive / witness-selected parallel-issue protocol. The example also illustrates why K.2b is needed: the Sys_ref cutpoint obtained from the RTL_B witness may contain overlapped pending requests, but A5 is discharged against the conservative serial-blocking source semantics.

The Front/NextFront bridge used later in Appendix K is derived in Lemma K.0 below from the Appendix B drain-only blocking discipline and the Appendix C Issue/Commit linkage. The rendezvous endpoint-request agreement used later in Appendix K is carried by the corresponding-cutpoint relation $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ as stated authoritatively in Corollary J.1, not by any claim that an asserted rendezvous request must belong to $\text{Front}_P(\sigma)$. Appendix R's Corollary R.1 is only a compact finite-prefix restatement of that same correspondence.

K.2.2 Lemma K.0 — Front/NextFront Classification at ϵ -Quiescent Cutpoints

Purpose. Appendix K defines WFG edges using $\text{Front}_P(\sigma)$ (minimal pending blocking Push/Pop operation instances), while Corollary J.1's state correspondence is phrased in terms of $\text{NextFront}_P(\sigma)$ plus BoundaryReq agreement for message-operation items in that next frontier. The present lemma shows that, at ϵ -quiescent cutpoints, the asserted blocking message-operation slice $\text{BlockingMsgNextFront}_P(\sigma)$ classifies the pending blocking frontier. No extra standing assumption is needed.

Clarification

Throughout this section, NextFront_P is interpreted in the witness-relative sense of Lemma S2: it is the $\leq_P$ -minimal remaining source-level frontier-item set within the fixed matched witness universe Ω_P , not a claim of immediate enablement and not a stronger state-intrinsic frontier independent of that witness. The observable Σ -event contributed by a message-operation item exists only when that item commits; pending blocking items may therefore belong to NextFront_P without yet contributing a committed Σ -event.

Statement. Fix a compared execution / witness w (hence its associated per-process universes $Q_{\text{exec},P}$, Ω_P , $\Omega_{\text{msg},P}$, $Q_{\Omega,P}$, Σ_P and order $\leq_P$), an ϵ -quiescent global state σ occurring as a cutpoint of that execution (of either Sys_ref or RTL_B), and a process P . Define the blocking message-operation slice of the next source-level frontier-item set, relative to this fixed witness, by:

$\text{BlockingMsgNextFront}_P(\sigma) \triangleq \{ x \in \text{NextFront}_P(\sigma) \mid x \in \Omega_{\text{msg},P} \text{ and, for } q = \text{MsgOf}_P(x), q \text{ is defined and } q \text{ is a blocking source-level message-operation instance with } \text{kind}(q) \in \{\text{Push}_c, \text{Pop}_c\} \text{ for some channel } c \}.$

Then:

$\text{Front}_P(\sigma) = \{ x \in \text{BlockingMsgNextFront}_P(\sigma) \mid \text{BoundaryReq}(x, \sigma) \}.$

Consequently, for any corresponding ϵ -quiescent states $(\sigma_{\text{ref}}, \sigma_{\text{post}})$ compared under the same matched witness pair and satisfying $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ (Corollary J.1),

$\text{Front}_P(\sigma_{\text{ref}}) = \text{Front}_P(\sigma_{\text{post}}),$

and for every frontier item $x \in \text{Front}_P(\sigma_{\text{ref}})$, with owning dynamic message-call instance $q = \text{MsgOf}_P(x)$, the boundary request $\text{BoundaryReq}(x, \cdot)$ agrees in σ_{ref} and σ_{post} , read operation-

attributively through q .

Non-blocking PushNB/PopNB call instances are intentionally excluded from BlockingMsgNextFront_P unless they are represented elsewhere as committed non-blocking transfer frontier items in Ω_msg, P , with owning message instances in Q_Q, P , for non-WFG frontier/value reasoning. A successful non-blocking call may contribute the same committed Push_c/Pop_c Σ -label as a blocking call, and a failed non-blocking poll is ϵ , but neither case creates a pending blocking frontier member for WFG purposes. This exclusion is a predicate on blocking source-level operation frontier items in Ω_msg, P , not on the message-instance slice Q_Q, P itself, not on committed Σ -event labels, and not on failed polls in Q_exec, P that induce no Ω_msg, P frontier item.

Clarification: mixed blocking/non-blocking endpoints

The exclusion above is per owning process and per source-level operation instance; it does not remove the corresponding channel from the enablement or WFG reasoning for a blocking operation on the other endpoint of the same point-to-point channel. If P is blocked on a blocking Push_c or Pop_c in $Front_P(\sigma)$, then the complementary endpoint process on c may be the target of the resulting wait-for edge even if that complementary process uses PushNB_c or PopNB_c at its own source endpoint. In such a case, the non-blocking side may affect channel enablement only by committing a transfer, or by failing to commit and contributing only ϵ ; it does not itself become a wait-for source unless that process is also blocked on some separate blocking Push/Pop operation in its own Front set. Thus Appendix K's WFG is asymmetric for mixed endpoints: blocking endpoints can generate outgoing wait-for edges, while non-blocking endpoints can satisfy, fail to satisfy, or change occupancy for those edges through committed transfers, but non-blocking polls do not create pending blocking frontier members.

Corollary K.0a (Rendezvous endpoint-request agreement at corresponding cutpoints).

Let c be a point-to-point rendezvous channel ($B(c)=0$), and let $P_prod(c)$ and $P_cons(c)$ denote its unique producer and consumer processes. Define:

$Req_prod(c, \sigma) :\Leftrightarrow$ the producer-side boundary request on c is asserted at the ϵ -quiescent cutpoint σ ;

$Req_cons(c, \sigma) :\Leftrightarrow$ the consumer-side boundary request on c is asserted at the ϵ -quiescent cutpoint σ .

Then, for any corresponding ϵ -quiescent cutpoints $(\sigma_ref, \sigma_post)$ satisfying $\sigma_ref \equiv \sigma_post$,

$Req_prod(c, \sigma_ref) = Req_prod(c, \sigma_post)$

and

$Req_cons(c, \sigma_ref) = Req_cons(c, \sigma_post)$.

No equivalence is claimed here between an asserted rendezvous endpoint request and membership in $Front_P(\sigma)$; Appendix B explicitly allows already-asserted non-frontier blocking requests to persist as protocol state.

Proof. For the main equality:

($\subseteq$) Let $x \in Front_P(\sigma)$. Then $x \in Pending_P(\sigma)$, so x is a blocking source-level message-operation frontier item in Ω_msg, P with owning dynamic message-call instance $q_x = MsgOf_P(x)$, where $Issue(q_x)$ has occurred and $Commit(q_x)$ has not yet occurred in σ . By Appendix C's Issue/Commit linkage, $BoundaryReq(x, \sigma) = true$, read operation-attributively through q_x . Since q_x has not committed, $x \notin Done_P(\sigma)$, and therefore $x \in Remain_P(\sigma)$.

It remains to justify the lift from pending-blocking minimality to NextFront_P minimality over all of $Remain_P(\sigma)$. We show that no item $y \in Remain_P(\sigma)$ can satisfy $y <_P x$.

First, y cannot be a synchronization-call item. If a synchronization item precedes the current message interval containing x , then by R3/E1 and the definition of the current interval $I_P(\sigma)$, that synchronization call has already committed at the cutpoint σ and hence belongs to $\text{Done}_P(\sigma)$, contradicting $y \in \text{Remain}_P(\sigma)$. If y is a later synchronization call that closes the current interval, then $x <_P y$ rather than $y <_P x$. Thus no remaining synchronization item precedes x .

Second, y cannot be an anchored signal-action item. For a sequential process, R2/E2 place each signal Read at its pred_S anchor and each signal Write at its succ_S anchor for purposes of $\leq_P$ and frontier reasoning. Hence any signal item that precedes the current message interval has already been realized at its synchronization anchor and is in $\text{Done}_P(\sigma)$, while any signal item anchored at the later synchronization boundary does not precede x . For a combinational process or explicitly modeled combinational component, the corresponding R2C fixed-point signal-observation unit is realized at the ϵ -quiescent fixed point of its component-local observation cycle; an already-realized R2C unit is in $\text{Done}_P(\sigma)$, and a later one is not $<_P x$. Thus no remaining signal-action item precedes x .

Third, y cannot be an earlier same-interval message-operation frontier item. Let $q_y = \text{MsgOf}_P(y)$. Because $y <_P x$ for message-operation frontier items in the same interval implies $q_y <_{\text{src}} q_x$, R4/E3 issue-order gives $\text{Issue}(q_y) \leq \text{Issue}(q_x)$. Since $\text{Issue}(q_x)$ has occurred by σ , $\text{Issue}(q_y)$ has also occurred by σ . If q_y has committed, then $y \in \text{Done}_P(\sigma)$, contradicting $y \in \text{Remain}_P(\sigma)$. If q_y is a blocking operation and has not committed, then $y \in \text{Pending}_P(\sigma)$, contradicting the assumption that $x \in \text{Front}_P(\sigma)$ is $\leq_P$ -minimal among pending blocking message-operation frontier items. If q_y is a successful non-blocking operation, then its success is exactly its committed transfer, so y is already realized and belongs to $\text{Done}_P(\sigma)$. If q_y is a failed non-blocking poll, then it contributes only ϵ and is not an Ω_P frontier item at all. Hence no earlier same-interval message-operation frontier item remains before x .

Fourth, y cannot be a message-operation frontier item from an earlier source interval. Let s be the synchronization call that closes that earlier interval before the current interval containing x . By the first case above, s has already committed at σ . By R3/E5's blocking-commit-by-sync discipline, every blocking message request in $\text{pref}_S(s)$ from that earlier interval committed no later than s 's commit, and hence its $\Omega_{\text{msg},P}$ frontier item is in $\text{Done}_P(\sigma)$. A successful non-blocking operation from that interval is already realized by its committed transfer, and a failed non-blocking poll contributes no Ω_P frontier item. Therefore no earlier-interval message-operation item can lie in $\text{Remain}_P(\sigma)$.

Therefore x is $\leq_P$ -minimal in the full remaining frontier-item set $\text{Remain}_P(\sigma)$, not merely minimal among pending blocking items. Since x is also a blocking message-operation frontier item, it lies in the blocking message-operation slice of $\text{NextFront}_P(\sigma)$. That is, $x \in \text{BlockingMsgNextFront}_P(\sigma)$.

This is only a frontier-minimality statement. It does not assert that the implementation could not have already issued a later same-interval request. Appendix B explicitly allows such younger or downstream already-asserted requests to persist as non-frontier protocol state under the no-withdrawal and drain-only rules. Those requests simply do not enter $\text{Front}_P(\sigma)$ while x remains the earlier frontier-minimal pending blocker.

($\supseteq$) Let $x \in \text{BlockingMsgNextFront}_P(\sigma)$ and $\text{BoundaryReq}(x, \sigma) = \text{true}$. By definition, x is a blocking source-level message-operation frontier item in $\Omega_{\text{msg},P}$ with owning dynamic message-call instance $q_x =$

MsgOf_P(x). Appendix C's stable-attribution rule for asserted blocking requests applies to q_x : the asserted request at the ϵ -quiescent cutpoint is attributed to a unique currently outstanding issued blocking message-operation instance q on the same endpoint direction; hence $q \in \text{Pending_P}(\sigma)$. Because $\text{BoundaryReq}(x, \sigma)$ is read operation-attributively for the specific source-level message-operation frontier item x , through $q_x = \text{MsgOf_P}(x)$, that unique outstanding operation must in fact be q_x itself: attribution cannot change from q_x to a distinct same-direction operation without an intervening commit on that endpoint direction, and no such commit has occurred while the request remains outstanding at the cutpoint. Thus $q = q_x$, so the frontier item x represents a pending blocking message operation. Since x lies in $\text{BlockingMsgNextFront_P}(\sigma)$, x is in the blocking message-operation slice of $\text{NextFront_P}(\sigma)$. Therefore x is $\leq_P$ -minimal in the full remaining frontier-item set $\text{Remain_P}(\sigma)$, and in particular there is no earlier remaining pending blocking message-operation frontier item of P in the current source interval. Since the preceding paragraph showed that x itself represents a pending blocking message operation, x is $\leq_P$ -minimal among $\text{Pending_P}(\sigma)$, so $x \in \text{Front_P}(\sigma)$. Appendix B's clarification on frontier-minimality vs. other asserted requests ensures that any younger already-asserted request does not enter $\text{Front_P}(\sigma)$ while an earlier pending blocker remains frontier-minimal.

This proves

$$\text{Front_P}(\sigma) = \{ x \in \text{BlockingMsgNextFront_P}(\sigma) \mid \text{BoundaryReq}(x, \sigma) \}.$$

Now let $(\sigma_{\text{ref}}, \sigma_{\text{post}})$ be corresponding ϵ -quiescent states with $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$. By Corollary J.1(2a), NextFront_P agrees between σ_{ref} and σ_{post} ; hence the blocking message-operation slice $\text{BlockingMsgNextFront_P}$ agrees as well. By Corollary J.1(2b), BoundaryReq agrees for every blocking message-operation frontier item x in that common $\text{BlockingMsgNextFront_P}$, read operation-attributively through its owning dynamic message-call instance $q = \text{MsgOf_P}(x)$. No BoundaryReq predicate is asserted for non-message frontier items, and successful non-blocking frontier items do not create pending blocking frontier members for this lemma. Applying the displayed equality on both sides yields

$$\text{Front_P}(\sigma_{\text{ref}}) = \text{Front_P}(\sigma_{\text{post}}),$$

and BoundaryReq agrees for every frontier item x in that common Front set, read through $q = \text{MsgOf_P}(x)$.

For the rendezvous corollary, direct frontier-classification is not sufficient: Appendix B explicitly allows an already-asserted blocking request that is not in $\text{Front_P}(\sigma)$ to persist as protocol state while an earlier pending blocker remains frontier-minimal. Therefore we do not identify raw rendezvous endpoint-request assertion with frontier membership. Instead, for each point-to-point rendezvous channel c , the corresponding-cutpoint relation $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ carries equality of the producer-side and consumer-side endpoint-request predicates $\text{Req_prod}(c, \cdot)$ and $\text{Req_cons}(c, \cdot)$ across the compared ϵ -quiescent cutpoints because those raw endpoint-request predicates are included in the source-side state slice preserved by Corollary J.1's rendezvous endpoint-request clause. Appendix R's Corollary R.1 restates this same clause in compact finite-prefix form but does not define a separate correspondence relation. This is exactly the predicate later used in the rendezvous enabling condition. $\square$

K.2.3 Example K.0b — Front_P vs. $\text{BlockingMsgNextFront_P}$ Example

The following example illustrates the distinction between Front_P and $\text{BlockingMsgNextFront_P}$. In this example all message-operation items under discussion are blocking Push/Pop operations, so $\text{BlockingMsgNextFront_P}$ is the relevant WFG-facing slice of the source-level NextFront_P frontier over

Ω_P . The broader notation MsgNextFront_P , when used elsewhere, denotes the general message-operation-item slice and may also include successful non-blocking transfer items; it is not the object used by the Front/NextFront bridge for WFG construction.

```
void P() {
  while (1) {
    wait();           // sync point
    int x = in.Pop(); // blocking Pop
    out.Push(x + 1);  // blocking Push
  }
}
```

Consider two ε -quiescent cutpoints for this same process:

Cutpoint σ_0 : just after `wait()` has committed, before `in.Pop()` has issued

- $\text{BlockingMsgNextFront_P}(\sigma_0) = \{ \text{Pop_in} \}$
- $\text{BoundaryReq}(\text{Pop_in}, \sigma_0) = \text{false}$
- $\text{Front_P}(\sigma_0) = \emptyset$

Cutpoint σ_1 : `in.Pop()` has issued, `rdy` is asserted, but no data has arrived yet

- $\text{BlockingMsgNextFront_P}(\sigma_1) = \{ \text{Pop_in} \}$
- $\text{BoundaryReq}(\text{Pop_in}, \sigma_1) = \text{true}$
- $\text{Front_P}(\sigma_1) = \{ \text{Pop_in} \}$

So the difference is:

- $\text{BlockingMsgNextFront_P}$ says which blocking message-operation items are next candidates in the source-level frontier over Ω_P for WFG/frontier classification.
- Front_P says which of those next blocking message-operation items are actually outstanding pending blockers right now.

K.3 Lemma K.1 — Characterization of Internal Message-Passing Deadlock (Buffered and Rendezvous Cases)

Elaboration prerequisite. The channel boundary c used in this lemma is the chosen abstract boundary of the prescribed Sys_ref / RTL_B comparison after applying any required elaboration from Appendix J, Remark 2. In particular, synchronization-boundary ramp-down / epoch-gating is not treated as a hidden exception to E4 on an otherwise ordinary buffered channel. If such gating can withhold producer-facing availability while outer projected capacity would otherwise appear available, the relevant blocking point is represented by an explicit abstract channel of $\text{Sys_B}^{\text{elab}}$.

Statement: Let σ_{post} be a reachable ε -quiescent global state of the post-HLS system RTL_B (equivalently, the ε -normalization of some reachable state, which exists as a finite extension by B4/B5). Suppose there is a non-empty set of processes D that is internally message-passing deadlocked (as defined in K.1). Then:

Every process P in D is blocked on a blocking channel operation (Push or Pop), not on an internal step.

Buffered-channel case ($B(c) > 0$):

- If P is blocked on a frontier item $x \in \text{Front_P}(\sigma_{\text{post}})$, with owning message instance $q = \text{MsgOf_P}(x)$, $\text{kind}(q) = \text{Push_c}$, and $B(c) > 0$, then $\text{occ_c}(\sigma_{\text{post}}) = B(c)$ (channel is full at that cutpoint).
- If P is blocked on a frontier item $x \in \text{Front_P}(\sigma_{\text{post}})$, with owning message instance $q = \text{MsgOf_P}(x)$, $\text{kind}(q) = \text{Pop_c}$, and $B(c) > 0$, then $\text{occ_c}(\sigma_{\text{post}}) = 0$ (channel is empty at that cutpoint).

Rendezvous case ($B(c) = 0$):

- If P is blocked on a frontier item $x \in \text{Front_P}(\sigma_{\text{post}})$, with owning message instance $q = \text{MsgOf_P}(x)$,

$\text{kind}(q)=\text{Push_c}$, and $B(c)=0$, then the complementary endpoint is not simultaneously requesting the matching Pop_c in σ_{post} (i.e., the complementary Pop_c endpoint request is not true in that cycle, so rendezvous enabling for x is false).

- If P is blocked on a frontier item $x \in \text{Front_P}(\sigma_{\text{post}})$, with owning message instance $q = \text{MsgOf_P}(x)$, $\text{kind}(q)=\text{Pop_c}$, and $B(c)=0$, then the complementary endpoint is not simultaneously requesting the matching Push_c in σ_{post} .

The processes in D form a closed strongly connected component in the WFG.

Proof:

Internal Steps: Because σ_{post} is ϵ -quiescent (i.e., an ϵ -normalized endpoint that exists as a finite extension by B4/B5), no process has any enabled internal ϵ -step in σ_{post} . In particular, if some process had an internal step whose guard is true in σ_{post} , then σ_{post} would not be ϵ -quiescent: the ϵ -normalization could be extended by at least one additional ϵ -step. Therefore, no process in D is blocked on an internal step with a true guard; since each $P \in D$ is blocked on message passing (K.1), the blocking operation must be a blocking channel operation (Push or Pop).

Blocked Push: By the definition of “blocked on message passing” in K.1, if P is blocked due to a frontier item $x \in \text{Front_P}(\sigma_{\text{post}})$, with owning message instance $q = \text{MsgOf_P}(x)$ and $\text{kind}(q)=\text{Push_c}$, then $\text{BoundaryReq}(x, \sigma_{\text{post}})$ is true and $\text{ChannelEnabled}(x, \sigma_{\text{post}})$ is false.

- If $B(c)>0$, the channel-side enabling condition for x is space availability, i.e., $\text{occ_c}(\sigma_{\text{post}}) < B(c)$. Hence, if P is blocked on such a Push_c frontier item x in σ_{post} , necessarily $\text{occ_c}(\sigma_{\text{post}})=B(c)$ (channel is full).

- If $B(c)=0$ (rendezvous), the channel-side enabling condition for x is that the complementary Pop_c endpoint request is true in the same cycle. Since P is blocked, this rendezvous enabling condition is false; equivalently, the complementary endpoint is not simultaneously requesting Pop_c in σ_{post} .

Blocked Pop: Symmetric. By the definition of “blocked on message passing,” if P is blocked due to a frontier item $x \in \text{Front_P}(\sigma_{\text{post}})$, with owning message instance $q = \text{MsgOf_P}(x)$ and $\text{kind}(q)=\text{Pop_c}$, then $\text{BoundaryReq}(x, \sigma_{\text{post}})$ is true and $\text{ChannelEnabled}(x, \sigma_{\text{post}})$ is false.

- If $B(c)>0$, the channel-side enabling condition for x is data availability, i.e., $\text{occ_c}(\sigma_{\text{post}}) > 0$. Hence $\text{occ_c}(\sigma_{\text{post}})=0$ (channel is empty).

- If $B(c)=0$ (rendezvous), the channel-side enabling condition for x is that the complementary Push_c endpoint request is true in the same cycle. Since P is blocked, this rendezvous enabling condition is false; equivalently, the complementary endpoint is not simultaneously requesting Push_c in σ_{post} .

Closed Cycle: By definition of internal message-passing deadlock, processes in D cannot wait on processes outside D , or else an external action could unblock them.

K.4 Lemma K.2 — Dependency Refinement

We now relate the blocking dependencies in RTL_B to those in the prescribed source reference model Sys_ref . In cases involving synchronization-boundary ramp-down / epoch-gating, Sys_ref is the elaborated model $\text{Sys_B}^{\text{elab}}$ required by Appendix J, Remark 2, so the gated acceptance point is an explicit abstract boundary used by the WFG rather than a hidden disablement of an otherwise E4-enabled outer channel.

Statement: For any pair of corresponding states $(\sigma_{\text{ref}}, \sigma_{\text{post}})$ where $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ (Corollary J.1), the wait-for edges agree in both directions: for any processes P, Q , there is a wait-for edge $P \rightarrow Q$ in $\text{WFG_post}(\sigma_{\text{post}})$ iff there is a wait-for edge $P \rightarrow Q$ in $\text{WFG_ref}(\sigma_{\text{ref}})$.

(In particular, $\text{WFG_post} \subseteq \text{WFG_ref}$, and the reverse inclusion holds as well.) This covers both the ordinary case $\text{Sys_ref} = \text{Sys_B}$ and the elaborated case $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$. The statement holds for mixed WFGs containing edges via both buffered channels ($B(c)>0$) and rendezvous channels ($B(c)=0$),

with $B(c)$, $\text{occ}_c(\sigma)$, BoundaryReq , ChannelEnabled , and ChannelDisabled interpreted at the chosen ε -quiescent cutpoints on the chosen abstract channels of Sys_ref .

Proof: Since $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$, clause (2a) gives NextFront alignment for every process P , and clause (2b) gives operation-attributive BoundaryReq agreement for blocking message-operation items in the common $\text{BlockingMsgNextFront_P}$ at this ε -quiescent cutpoint. Successful non-blocking frontier items may contribute committed $\text{Push_c}/\text{Pop_c}$ Σ -labels, but they are not pending blocking-frontier members and are not used to form wait-for edges. By Lemma K.0, this lifts directly to alignment of the pending blocking frontiers: for every P ,
 $\text{Front_P}(\sigma_{\text{ref}}) = \text{Front_P}(\sigma_{\text{post}})$,
and $\text{BoundaryReq}(x, \sigma_{\text{ref}}) = \text{BoundaryReq}(x, \sigma_{\text{post}})$ for every frontier item $x \in \text{Front_P}$, read operation-attributively through its owning message instance $q = \text{MsgOf_P}(x)$.
Moreover, for buffered channels with $B(c) > 0$, the channel empty/full predicate agrees between σ_{ref} and σ_{post} (Corollary J.1, clause (2c)).

For rendezvous channels with $B(c) = 0$, the complementary-endpoint request predicate needed for channel enablement is transferred directly by the corresponding-cutpoint relation. Concretely, for each point-to-point rendezvous channel c in the Appendix K internal message-passing boundary / WFG analysis, Corollary J.1 gives equality of the raw producer-side and consumer-side endpoint-request predicates across $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$, with that equality supplied by the preserved source-side cutpoint state used in the correspondence — not by any claim that matched observable history alone determines all already-asserted rendezvous requests. Appendix R's Corollary R.1 restates this same clause in compact finite-prefix form but does not define a separate correspondence relation. This raw endpoint-request equality is the exact predicate used by the rendezvous enabling condition, and it does not require any identification of asserted requests with frontier membership.

We show that each RTL edge transfers to the source-level WFG by case-splitting on $B(c)$.

Case 1: Buffered channel ($B(c) > 0$).

Consumer (Blocked Pop): Suppose P waits for Q via Pop_c in the RTL system on a channel c with $B(c) > 0$. By Lemma K.1, $\text{occ}_c(\sigma_{\text{post}}) = 0$ in σ_{post} (empty). By $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ and Corollary J.1(2c), we have the same logical occupancy in σ_{ref} ; hence $\text{occ}_c(\sigma_{\text{ref}}) = 0$ in σ_{ref} as well. Under the buffered-channel semantics of Sys_ref at that abstract channel boundary, completion of P 's Pop_c requires a complementary Push_c by Q . Hence $P \rightarrow Q$ is also an edge in WFG_ref .

Producer (Blocked Push): Symmetric. If P waits for Q via Push_c on a channel c with $B(c) > 0$, Lemma K.1 gives $\text{occ}_c(\sigma_{\text{post}}) = B(c)$ (full) in σ_{post} . By $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ and Corollary J.1(2c), σ_{ref} has the same logical occupancy; hence $\text{occ}_c(\sigma_{\text{ref}}) = B(c)$ in σ_{ref} as well. Completion of P 's Push_c requires a complementary Pop_c by Q to make space. Hence $P \rightarrow Q$ is also an edge in WFG_ref .

Case 2: Rendezvous channel ($B(c) = 0$).

Producer (Blocked Push): Suppose P waits for Q in the RTL system via a frontier item $x \in \text{Front_P}(\sigma_{\text{post}})$ on channel c , with owning message instance $q = \text{MsgOf_P}(x)$, $\text{kind}(q) = \text{Push_c}$, and $B(c) = 0$. By Lemma K.1, the complementary Pop_c endpoint request on c is not asserted in σ_{post} . By rendezvous endpoint-request agreement across corresponding cutpoints, the complementary Pop_c endpoint request on c is also not asserted in σ_{ref} . Since $x \in \text{Front_P}(\sigma_{\text{post}})$, Front alignment under $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ (Lemma K.0)

gives $x \in \text{Front_P}(\sigma_{\text{ref}})$; and by BoundaryReq agreement for frontier items, $\text{BoundaryReq}(x, \sigma_{\text{ref}}) = \text{true}$. Thus in σ_{ref} the producer is requesting the Push_c operation represented by x , through $q = \text{MsgOf_P}(x)$, while the complementary Pop_c endpoint is not requesting on c . Therefore x is channel-disabled in σ_{ref} , and $P \rightarrow Q$ is an edge in WFG_ref .

Consumer (Blocked Pop): Symmetric. Suppose P waits for Q in the RTL system via a frontier item $x \in \text{Front_P}(\sigma_{\text{post}})$ on channel c , with owning message instance $q = \text{MsgOf_P}(x)$, $\text{kind}(q) = \text{Pop_c}$, and $B(c) = 0$. By Lemma K.1, the complementary Push_c endpoint request on c is not asserted in σ_{post} . By rendezvous endpoint-request agreement across corresponding cutpoints, the complementary Push_c endpoint request on c is also not asserted in σ_{ref} . Since $x \in \text{Front_P}(\sigma_{\text{post}})$, Front alignment under $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ (Lemma K.0) gives $x \in \text{Front_P}(\sigma_{\text{ref}})$; and by BoundaryReq agreement for frontier items, $\text{BoundaryReq}(x, \sigma_{\text{ref}}) = \text{true}$. Thus in σ_{ref} the consumer is requesting the Pop_c operation represented by x , through $q = \text{MsgOf_P}(x)$, while the complementary Push_c endpoint is not requesting on c . Therefore x is channel-disabled in σ_{ref} , and $P \rightarrow Q$ is an edge in WFG_ref .

Therefore every RTL wait-for dependency is also a source-level wait-for dependency, so $\text{WFG_post} \subseteq \text{WFG_ref}$.

Conversely, suppose $P \rightarrow Q$ is an edge in WFG_ref . By the edge definition in K.1, there exists some frontier item $x \in \text{Front_P}(\sigma_{\text{ref}})$ on channel c such that x is channel-disabled in σ_{ref} and Q is the unique complementary endpoint for c . From the Front/BoundaryReq alignment established above (via $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ and Lemma K.0), we have $x \in \text{Front_P}(\sigma_{\text{post}})$; and from the buffered (empty/full via occ_c) and rendezvous (complementary BoundaryReq) enabling-predicate agreement established above, x is also channel-disabled in σ_{post} . Hence $P \rightarrow Q$ is an edge in WFG_post . Therefore WFG_post and WFG_ref have exactly the same wait-for edges (in both directions) at corresponding cutpoints. $\square$

K.4a Lemma K.2a — Drain-Closure Transfer

Statement. Let σ_{ref} and σ_{post} be corresponding ϵ -quiescent cutpoints with $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$, and let D be a non-empty set of processes. Suppose σ_{post} is drain-closed for D in the sense of K.1. Then σ_{ref} is also drain-closed for D .

Proof. By K.1, drain-closure for D means that no already-issued non-frontier blocking Push/Pop request of any process $P \in D$ is channel-enabled at the cutpoint. We show that if σ_{ref} were not drain-closed for D , then σ_{post} would not be drain-closed for D either.

Assume, for contradiction, that σ_{ref} is not drain-closed for D . Then there exists a process $P \in D$ and a blocking message-operation frontier item $x \in \Omega_{\text{msg}, P}$, with owning dynamic message-call instance $q = \text{MsgOf_P}(x)$, such that:

- x is already issued and not yet committed in σ_{ref} , i.e. $x \in \text{Pending_P}(\sigma_{\text{ref}})$;
- x is not frontier-minimal, i.e. $x \notin \text{Front_P}(\sigma_{\text{ref}})$; and
- $\text{ChannelEnabled}(x, \sigma_{\text{ref}})$ holds.

Since x is pending and blocking, Appendix C's Issue/Commit linkage gives the endpoint-owned request $\text{BoundaryReq}(x, \sigma_{\text{ref}})$, with the request attributed through the owning dynamic source-level operation instance $q = \text{MsgOf_P}(x)$. Since x is non-frontier only because an earlier pending blocking operation remains frontier-minimal, x is not a WFG source at this cutpoint, but it is still a concrete outstanding boundary request whose possible commit is part of the drain-only protocol state.

By Corollary J.1, clause (e), the corresponding-cutpoint relation $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ preserves the already-issued blocking request state needed for the automatic-flush / drain-only discipline. Therefore:

- $x \in \text{Pending_P}(\sigma_{\text{post}})$;
- the endpoint-owned request in σ_{post} is attributed to the same dynamic source-level operation instance $q = \text{MsgOf_P}(x)$;
- $\text{BoundaryReq}(x, \sigma_{\text{post}})$ holds; and
- $\text{ChannelEnabled}(x, \sigma_{\text{post}})$ holds.

The last item is evaluated at the chosen abstract boundary of $\text{Sys_ref} / \text{RTL_B}$. For $B(c) > 0$ channels it follows from the common $B(c)$ and the shared logical occupancy/head-state facts of Corollary J.1, clause (c). For $B(c) = 0$ rendezvous channels it follows from the raw complementary endpoint-request agreement of Corollary J.1, clause (d). In the elaborated case $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$, these facts are interpreted at the explicit abstract channel on which x is pending.

Moreover, because $\text{Front_P}(\sigma_{\text{ref}}) = \text{Front_P}(\sigma_{\text{post}})$ by Lemma K.0 / Lemma K.2, x remains non-frontier in σ_{post} whenever it is non-frontier in σ_{ref} . Thus σ_{post} has an already-issued non-frontier blocking frontier item of a process in D that is channel-enabled, contradicting the assumption that σ_{post} is drain-closed for D .

Hence σ_{ref} is drain-closed for D . $\square$

K.4b Lemma K.2b — Serial-Source Dominance for Internal Deadlock

Statement. Fix the prescribed Sys_ref under the same fixed stimulus, capacities $B(c)$, elaborated abstract channels, non-blocking witness choices, and environment assumptions used by Appendix K. Assume A1–A4, A6–A11, the Appendix B automatic-flush / drain-only discipline, the Appendix C non-withdrawable blocking-request discipline, point-to-point channels (including each introduced $\text{Sys_B}^{\text{elab}}$ abstract channel at which ChannelDisabled is evaluated; see the elaborated-channel side condition in the proof), and the WFG-inert ϵ precondition $K\epsilon$. Suppose there is a reachable ϵ -quiescent Sys_ref cutpoint σ_{ref} under some admissible selected Sys_ref witness schedule, possibly one that reflects RTL_B overlapped issue through Corollary J.1 / J.AbsConf, such that σ_{ref} contains an internal message-passing deadlock in the K.1 sense for some non-empty process set D .

Then there exists a reachable ϵ -quiescent Sys_ref cutpoint σ_{ser} under the same fixed stimulus and the conservative serial-blocking source semantics of A5 such that σ_{ser} contains an internal message-passing deadlock in the K.1 sense, for some non-empty closed WFG component D_{ser} . In particular, an overlapped witness-relative Sys_ref deadlock is sufficient to contradict A5 once this lemma is established.

Proof. We turn the former sketch into a reduction whose only analytic content is a single point-to-point monotonicity step. The liberal witness run and the conservative serial-blocking run are runs of one transition system under two issue policies; we show that the deadlocking witness run can be transformed, one eager issue at a time, into a serial-blocking run that still deadlocks. We never reconstruct the witness state under serial issue — we preserve only enough channel blockedness to exhibit some internal deadlock, which is all that Theorem K.1 consumes. Throughout, an interval is the region of one process between two adjacent synchronization calls, $<_{\text{src}}$ is per-process source order, and per-interface source order (E3) means operations on one interface issue and commit in source order.

Two issue policies. The liberal (overlapped, witness-relative) and conservative serial-blocking executions share the same Sys_ref transition system: identical state space, capacities $B(c)$, explicit Sys_ref / Sys_B^{elab} boundaries, the predicates BoundaryReq / ChannelEnabled / ChannelDisabled, the fixed stimulus, and the fixed non-blocking outcome assignment (NB-CF, or witness-selected NB outcomes per A7 / J.AbsConf). They differ only in when a process may assert a blocking Push/Pop. Policy L (liberal) permits a process to assert a source-later same-interval blocking request before its source-earlier same-interval blocking requests have committed, subject to the R/E rules, the no-reverse distinct-interface rule, and the E5 synchronization-boundary constraints; the witness schedule from Corollary J.1 / J.AbsConf is an L-run. Policy S (serial) additionally forbids this: within each interval a source-later blocking request is asserted only after every source-earlier same-interval blocking request has committed. S is the restriction of L, and S is exactly A5's conservative serial-blocking source semantics. Call a blocking-issue transition eager if it asserts a request q while a source-earlier same-interval blocking request q_e of the same process is still uncommitted; for a finite L-run p let $e(p)$ be the number of eager issue transitions in p . Then $e(p)=0$ iff p is an S-run, and e ranges over the natural numbers.

Determinacy. Under the fixed stimulus and the fixed non-blocking outcome assignment, the operation a process issues at each step — its kind, its channel, and, for committed transfers, its payload value — is a function of the committed transfers feeding that process, determined jointly across processes and independent of the issue policy except through which blocking operations have committed. A process branches only on (i) the fixed stimulus, (ii) values returned by committed Pops, and (iii) non-blocking outcomes; (i) and (iii) are fixed, and each value in (ii) is the payload of the matching committed Push, fixed the same way. By induction along the committed-transfer order, each process's sequence of operations and payloads is therefore fixed; changing the issue policy can change only the timing of issue and how far a process gets, not the identity, the per-interface order, or the values of the operations it does issue. In particular “the same operation under both policies” is well defined, and per interface each policy issues the same ordered blocking-operation stream, truncated at the first operation it has not yet enabled. This discharges, once and for all, the cross-process value dependence that a per-process replay would otherwise smuggle in.

Inertness of eager requests. Suppose q is asserted eagerly and the operation q_e that made it eager is still uncommitted at a cutpoint σ . Then q is not the minimal pending blocking item of its process at σ : q_e is source-earlier and pending, so by Lemma K.0 the frontier $\text{Front}_P(\sigma)$ is q_e or an earlier pending item, and q is younger asserted protocol state, not a frontier member. Moreover a pending request is WFG-inert. By point-to-point channels the only transition that can consume q 's assertion is q 's own commit — a transfer on q 's channel with q 's unique complement — and while q is pending no such transfer has fired, so a pending Push has deposited no token and a pending Pop has removed none; q 's assertion leaves occ on its channel unchanged. By K ϵ no ϵ -internal step is enabled by a pending blocking assertion. Hence a pending eager request enables no transition of any other process, and deferring it changes no other process's frontier and disables no transition that occurred.

Monotonicity of serial deferral. This is the load-bearing step. Let p reach a drain-closed ϵ -quiescent cutpoint σ that is an internal deadlock (K.1 sense) for a non-empty set D , with $e(p)>0$, and let t be the temporally last eager issue of p , asserting q (on channel d , by process P) with earlier uncommitted q_e ; every transition of p after t is non-eager. Form p' from p by deferring q to its serial slot — q is asserted only after q_e commits, and is never asserted in this prefix if q_e never commits — while keeping every other transition that remains enabled in its p order. The only transitions whose status can change relative to p are q 's own commit, if q committed in p , and any transition causally downstream of that commit on channel d . Because d is point-to-point it has exactly one producer and one consumer; one of them is P and the other is a single complement $R \neq P$. Removing or delaying q 's commit therefore alters only the availability seen by R on channel d : a withheld Push q leaves one fewer token for R 's matching Pop, and a withheld Pop q leaves one fewer free slot for R 's matching Push, so R — and only R — can

lose enabling and block. No transition of any process other than R gains enabling, because on a point-to-point channel no third party reads channel d's occupancy, and P's own later operations on d are source-after q and are issued no earlier under S. Non-blocking outcomes are held at their witness-fixed values (A7 / J.AbsConf / NB-CF) and form no WFG edges, so they neither rescue nor are disturbed by this change. If q is re-asserted after q_e and re-commits, p' reaches σ unchanged; otherwise q's commit is excised and R halts blocked at its corresponding frontier. In both outcomes every frontier item channel-disabled at σ is still channel-disabled: rendezvous disabledness (absent complementary assertion) cannot be repaired by withholding issue, an empty buffer for a blocked Pop cannot be filled by withholding the unique producer's later Pushes, and a full buffer for a blocked Push cannot be freed by withholding the unique consumer's later Pops. Hence the operations on which the processes of D are blocked stay blocked, and D remains a blocked set, possibly enlarged by R and its dependents. This is the exact point at which point-to-point is needed for the truth of the lemma, not merely for its proof: it is what makes an eagerly committed operation pure help to a single complement rather than a constraint on some third process, and it is why an overlapped deadlock can never be an artifact that serialization escapes.

Extraction. Let σ' be the first ϵ -quiescent cutpoint p' reaches; a withheld blocking operation leaves its owner blocked, so the deferral reaches a quiescent state rather than diverging. At σ' every process is finished or blocked on a pending frontier item, and by the previous step every process of D is blocked. Let B be the non-empty set of processes blocked at σ' . Any $P' \in B$ blocked on a disabled frontier item x on channel c waits on the owner Q of c's unique complementary endpoint, a modeled process (external/environment channels are excluded from the K.1 WFG). Q is not finished: by Determinacy Q still owes the matching complementary operation on c — a rendezvous commit is simultaneous for both endpoints, and a buffered transfer that would enable x has not occurred — so Q has not issued all its operations and, being unfinished at an ϵ -quiescent cutpoint, is itself blocked, i.e. $Q \in B$. Thus every wait-for edge out of B stays in B. A finite non-empty digraph in which every vertex has an out-edge contains a terminal strongly connected component $D' \subseteq B$ that is non-empty and has no out-edge; the monotonicity step forbids any out-edge of D' that could be enabled, and drain-closure (below) forbids enabled drain inside D' . Hence D' is a closed internal WFG component at the drain-closed ϵ -quiescent σ' — an internal message-passing deadlock in the K.1 sense.

Reduction step. Combining the previous two paragraphs: from a finite L-run reaching a drain-closed ϵ -quiescent K.1 deadlock with $e(p) > 0$ we obtain a finite L-run p' reaching a drain-closed ϵ -quiescent K.1 deadlock for a non-empty closed set D' , with $e(p') = e(p) - 1$. The count drops by exactly one because the single eager issue t is removed — its deferred re-issue, if any, occurs only after q_e commits and is therefore not eager — and the deferral introduces no new eager issue. The measure strictly decreases.

Elaborated channels and the point-to-point side condition. For $\text{Sys}_B^{\text{elab}}$ the predicate ChannelEnabled/ChannelDisabled at the elaborated boundary is evaluated on the explicit introduced abstract channel (staged, bundle, or join) that carries the blocking point, and the monotonicity and extraction steps apply verbatim on that channel provided it is point-to-point at the boundary of evaluation. This requirement is a genuine side condition on which the truth of K.2b rests: an introduced join or bundle channel that multiplexes several producers or several consumers at the evaluation boundary breaks the argument, because occupancy is then not a function of a single producer/consumer pair and a withheld request of one contributor could free a different contributor's transfer. Such a boundary is outside this lemma and must be remodeled with per-endpoint point-to-point sub-channels or discharged separately. Under the Appendix B / E4 elaboration each introduced abstract channel is point-to-point by construction, so the side condition holds for the elaborated models in scope; the no-reverse and per-interface order rules continue to supply the per-endpoint ordering used above.

Drains. Two facts secure drain handling. The operations the deferral withholds are eager, hence non-frontier and pending-inert (Inertness above); by $K\epsilon$ together with the Appendix B automatic-flush and Appendix C non-withdrawable-request disciplines, removing such protocol state cannot create hidden ϵ -progress that enables a blocked frontier except through a Σ -visible commit, and Σ -visible commits are exactly the point-to-point transfers already controlled by the monotonicity step. And K.2b is applied only to a drain-closed witness cutpoint, as Theorem K.1 supplies it: if the witness shows an enabled drain-only transfer, the finite drain-normalization of Lemma K.2a is applied first to reach a drain-closed σ_{ref} with the same closed component. Because σ' is taken at ϵ -quiescence, no internal transfer — drain or otherwise — is enabled there, so σ' is drain-closed.

Induction. By hypothesis and Corollary J.1 / J.AbsConf there is an L-run reaching the witness-relative deadlock σ_{ref} , drain-closed after at most one application of Lemma K.2a. Apply the reduction step repeatedly; the natural-number measure e strictly decreases, so after finitely many steps the construction reaches an L-run p_S with $e(p_S)=0$ reaching a drain-closed ϵ -quiescent internal deadlock for a non-empty closed component D_{ser} . Since $e(p_S)=0$, p_S is an S-run and its cutpoint σ_{ser} is reachable under A5's conservative serial-blocking source semantics. Thus an overlapped witness-relative Sys_{ref} deadlock yields a serial-blocking Sys_{ref} deadlock, contradicting A5 and supplying exactly the bridge Theorem K.1 invokes. $\square$

Implementation note. K.2b is the single proof bridge that replaces the former scheduler-robust A5 quantification. The RTL_B / Corollary J.1 witness may still land on a Sys_{ref} cutpoint with multiple pending requests for a process, but A5 is consumed only after K.2b converts that witness-relative deadlock into a deadlock reachable under the conservative serial-blocking source semantics.

K.5 Theorem K.1 — Liveness Preservation

Statement:

If the prescribed source reference model Sys_{ref} is internally message-passing-deadlock-free under A5's conservative serial-blocking source semantics, the Appendix I/J correspondence prerequisites hold (in particular NB-CF, or else RTL-consistent witness-selected NB outcomes for latency-sensitive NB control flow), the cutpoint-abstraction obligation J.AbsConf is discharged as required by A7, and Lemma K.2b applies, then RTL_B is also internally message-passing-deadlock-free.

Here “deadlock” means the Appendix K WFG notion over blocking Push/Pop operations.

SyncChannel/barrier deadlocks, external-environment stalls, reset stalls, and other non-message-passing global stalls are treated as specification/environment issues and are out of scope here.

Proof (by Contradiction):

1. **Assume RTL_B reaches an internal message-passing deadlocked state σ_{post} in the Appendix K WFG sense.**
2. **Exec_post applicability at a deadlock cutpoint:** The reachability prefix ending at σ_{post} must be embedded in an infinite execution satisfying the Appendix J fairness/progress premises (B2/B3) while preserving the closed deadlock witness needed below. This embedding is not supplied merely by applying B6 to σ_{post} , because B6 gives idle-stutter extension directly only at a B5/global fixed point. For a partial internal message-passing deadlock cutpoint, the required continuation is obtained by the Appendix K fair drain-normalization argument: already-issued D-owned non-frontier requests that later become ChannelEnabled may commit as finite drain-only progress, outside-D and environment endpoints continue subject to the ordinary B2/B3 progress premises, and the D-owned frontier blockers remain ChannelDisabled within the closed WFG component. At σ_{post} , we are at an ϵ -quiescent and drain-closed cutpoint and (by the definition of internal message-passing deadlock in K.1) there exists a non-empty set D of processes such that every $P \in D$ is blocked on message passing, σ_{post} is drain-closed for D , and D is closed in

the WFG.

Thus, for each $P \in D$, all frontier blocking transfers are channel-disabled, and by drain-closure no already-issued non-frontier blocking transfer of P is channel-enabled at σ_{post} . Hence no blocking message transfer owned by a process in D is enabled at σ_{post} .

We first check that B3 cannot force progress of any D -owned frontier blocker. Consider a frontier item $x \in \text{Front_P}(\sigma_{\text{post}})$, with owning message instance $q = \text{MsgOf_P}(x)$, on which some $P \in D$ is blocked.

If $B(c) > 0$ and q is a blocked Pop_c , then $\text{occ_c}(\sigma_{\text{post}}) = 0$. B3 could force progress of x only if the complementary producer endpoint were persistently able to supply a Push_c that fills the empty channel. If that complementary Push_c were a frontier request owned by a process in D , then because $\text{occ_c}(\sigma_{\text{post}}) < B(c)$, that Push_c would be channel-enabled, contradicting the fact that all D -owned frontier blocking transfers are channel-disabled at the deadlock cutpoint. If the complementary Push_c were an already-issued non-frontier request owned by a process in D and enabled at σ_{post} , then it would be an enabled non-frontier drain candidate, contradicting drain-closure for D . If the complementary producer endpoint were owned by a process outside D on an internal channel included in the WFG analysis, then the blocked Pop_c represented by x would create an outgoing wait-for dependency from D , contradicting WFG closure. Thus B3 cannot force progress of this D -owned frontier Pop_c through any internal WFG channel without contradicting disabled-frontier, drain-closure, or WFG closure. The full-channel blocked-Push case is symmetric: if $B(c) > 0$ and q is a blocked Push_c , then $\text{occ_c}(\sigma_{\text{post}}) = B(c)$, and any complementary Pop_c on an internal WFG channel that could make space is either an enabled D -owned frontier/non-frontier transfer, contradicting disabled-frontier or drain-closure respectively, or else induces an outgoing wait-for dependency from D , contradicting WFG closure.

If $B(c) = 0$, the same conclusion holds for internal rendezvous channels included in the WFG analysis. A rendezvous transfer is channel-enabled only when the raw Push_c and Pop_c endpoint requests are both asserted at the same ϵ -quiescent cutpoint. Since x is blocked, the complementary endpoint request needed for that same-cycle rendezvous is absent at σ_{post} . If both raw endpoint requests were present, x would be channel-enabled and P would not be blocked on x . If the missing complementary endpoint were outside D on an internal channel included in the WFG analysis, the corresponding wait-for edge would leave D and contradict WFG closure; otherwise it is an internal disabled dependency already captured inside the closed WFG cycle. Hence B3 cannot force progress of any D -owned frontier rendezvous blocker on an internal WFG channel.

Environment-facing frontier items are handled separately. Such channels are not WFG edges and therefore WFG closure is not used to rule out later environment progress on them. If the fixed stimulus or environment-side progress later enables a D -owned frontier item on an environment-facing channel, the fair extension may simply take that transfer and continue. This does not invalidate the contradiction argument: the internal message-passing deadlock predicate is a reachable-state property at the ϵ -quiescent cutpoint, and the cutpoint remains available for the Corollary J.1 state transfer. Appendix K's contradiction is against the existence of such a reachable internal deadlock cutpoint, not against the stronger claim that every fair continuation must remain permanently deadlocked.

It remains to handle already-issued D -owned non-frontier requests. Such requests may persist under the no-withdrawal rule and are not WFG sources while an earlier pending blocking item remains frontier-minimal. Drain-closure says only that no such request is channel-enabled at σ_{post} ; it does not assert that outside- D or environment activity can never make such a non-frontier request enabled later. Therefore we do not require the infinite continuation to be

pure idle-stutter from σ_{post} . Instead, construct the continuation by fair drain-normalization: whenever B2/B3 makes a D-owned already-issued non-frontier request enabled and continuously serviceable, allow that request to commit as drain-only progress. Such a commit is permitted by the automatic-flush discipline because it is work already past the blocked frontier; it issues no new later blocking frontier item, does not withdraw any outstanding request, and does not advance new work across any disabled internal frontier item of a process in D. Only finitely many such D-owned drain commits can occur before reaching a new ϵ -quiescent drain-closed cutpoint σ_{post}' , unless a frontier item becomes enabled and commits, in which case the fair continuation simply proceeds and the original σ_{post} remains the reachable deadlock cutpoint used for the state-transfer contradiction. In the finite-drain case, this is exactly the finite-drain argument from K.1: at a blocked frontier satisfying automatic flush, no new later blocking message-operation frontier item may be issued; the only downstream work that can still drain is work already accepted before the blocked condition; every explicit abstract channel has finite capacity $B(c)$; every process has finite ϵ -depth D_P when not externally stalled; and no new work may cross the blocked internal frontier. Thus the number of D-owned downstream drain commits is finite.

If, during this finite drain-normalization, some D-owned internal frontier item becomes channel-enabled, then either the fair continuation takes that transfer and the proof uses the original reachable cutpoint σ_{post} for the Corollary J.1 transfer, or the contradiction proof uses a later ϵ -quiescent cutpoint if the same closed internal-deadlock witness persists after the forced drain. Otherwise, at the resulting cutpoint σ_{post}' , every process in D is still blocked on message passing at its internal frontier, D still has no outgoing WFG edge, and σ_{post}' is drain-closed for D.

The possible forced commits were non-frontier drain-only commits, so they do not by themselves create a new WFG source outside the closed frontier cycle. Any outside-D action on an internal WFG channel that could unblock a D-owned internal frontier item would still produce an outgoing wait-for dependency from D, contradicting closure; environment-facing frontier progress, if it occurs, is treated as ordinary fair continuation rather than as a WFG-closure contradiction.

For processes outside D, and for environment endpoints, choose an infinite continuation under the same stimulus that satisfies the applicable B2/B3 progress requirements. Interleave that continuation with the finite D-owned drain-normalization above. After the drain-normalized cutpoint σ_{post}' is reached, idle stutter is used only for D-owned internal frontier blockers that remain channel-disabled and whose complementary endpoints are internal to the closed WFG component. If an environment-facing frontier item is later enabled by the fixed stimulus, the continuation may commit it; this does not erase the already-reachable internal deadlock cutpoint used for the Corollary J.1 transfer. Therefore there exists an infinite continuation satisfying the Appendix J B2/B3 premises, and the finite prefix reaching the relevant ϵ -quiescent cutpoint lies in Exec_post .

Consequently, the finite prefix reaching the relevant ϵ -quiescent drain-closed cutpoint (σ_{post} itself if no forced drain-normalization is needed, otherwise σ_{post}') lies in Exec_post . In the remaining proof, replace σ_{post} by this drain-normalized cutpoint, and keep the same name σ_{post} for readability. Corollary J.1 therefore applies at the ϵ -quiescent drain-closed cutpoint used below.

3. **Extract Cycle:** Fix a non-empty set of processes D as guaranteed by the definition of internal message-passing deadlock in K.1: (i) every process $P \in D$ is blocked on message passing at σ_{post} , and (ii) D forms a strongly connected component in WFG_post with no outgoing edges

(i.e., D is closed: processes in D can only wait on each other). In the remainder of this proof, “deadlocked process” means “a process in D ”. We invoke Lemma K.1 only after fixing this D , to characterize what each $P \in D$ is blocked on and to obtain the associated full/empty or rendezvous-request facts at σ_{post} .

4. **Map to Source-Level Reference Semantics:** By Corollary J.1 (State Correspondence at the End of a Matched Observable Prefix), there exists a corresponding source-level state σ_{ref} of Sys_ref such that $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$.
5. **Transfer Cycle and Drain-Closure:** By Lemma K.2, for this corresponding pair $(\sigma_{\text{ref}}, \sigma_{\text{post}})$ the wait-for edges agree in both directions: for any processes P, Q , $P \rightarrow Q$ is an edge in WFG_post iff $P \rightarrow Q$ is an edge in WFG_ref . Since D is a closed SCC in WFG_post , every outgoing wait-for edge from any $P \in D$ targets a process in D . Therefore every outgoing wait-for edge from any $P \in D$ in WFG_ref also targets a process in D , so D has no outgoing edges in WFG_ref and forms a closed wait-for cycle there as well.
It remains to transfer the drain-closed part of the K.1 deadlock definition. Since σ_{post} is drain-closed for D by the assumed RTL_B deadlock and $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ by Corollary J.1, Lemma K.2a gives that σ_{ref} is also drain-closed for D . Moreover, by Lemma K.0 / Lemma K.2, the pending blocking frontiers agree between σ_{post} and σ_{ref} , and the relevant BoundaryReq and ChannelDisabled facts for frontier operations agree. Hence every process $P \in D$ is blocked on message passing in σ_{ref} , D is closed in WFG_ref , and σ_{ref} is drain-closed for D .
6. **Serial-dominance bridge and contradiction:** The preceding step shows that the selected Sys_ref witness contains a reachable ϵ -quiescent cutpoint σ_{ref} that is internally message-passing deadlocked in the full K.1 sense. This σ_{ref} may be witness-relative and may include already-issued pending requests introduced by RTL_B-style overlap; it therefore need not itself be a cutpoint reachable under A5’s conservative serial-blocking source semantics. Apply Lemma K.2b to this witness-relative Sys_ref deadlock. Lemma K.2b yields a reachable ϵ -quiescent Sys_ref cutpoint σ_{ser} , under the same fixed stimulus and under A5’s conservative serial-blocking source semantics, that is internally message-passing deadlocked in the K.1 sense. This contradicts the Source-Level Liveness Assumption (A5).
7. **Conclusion:** RTL_B cannot reach an internal message-passing deadlocked state in the Appendix K WFG sense. $\square$

Appendix L – Snooping Introduction, Implementation and Concerns

Snooping Introduction

If designs are completely latency insensitive, verification of the pre-HLS versus post-HLS models is straightforward. However, if the design contains some components such as arbiters which have latency-sensitive behavior, and if that latency-sensitive behavior is in some cases externally visible to the DUT, then verification becomes somewhat more complex. Techniques can be applied to simplify verification.

Consider a design which has an arbiter like Matchlib toolkit example 09*. The arbiter uses non-blocking PopNB() on its inputs, and blocking Push() on its output to emit the winner of the arbitration. Since the latency between the pre-HLS and post-HLS designs will differ, the order of transactions presented to the arbiter in the two scenarios will differ, and thus the order of the winners will differ. This may result in

verification mismatches between the two models if the order of the winners is externally visible to the DUT.

To force the pre-HLS and post-HLS simulations to match, we can run the two designs side-by-side. We can snoop the inputs to the arbiter in the post-HLS model, and only allow the inputs to the pre-HLS arbiter to proceed when the corresponding inputs are seen in the post-HLS model. This will force the order of the inputs to be equivalent between the pre-HLS and post-HLS models, and thus both arbiters will pick the same winners. When this technique is used, the pre-HLS simulation will be throttled by the post-HLS simulation, but the overall verification will still work properly.

Another related example involves interrupt request signals feeding into an interrupt controller within a CPU model. Typically, each interrupt request signal is a single bit `sc_signal<>`, indicating that an interrupt request is pending. If the requests originate from accelerator blocks that are being synthesized through HLS, then because of the latency differences between the pre-HLS and post-HLS models, the order of interrupt requests arriving at the interrupt controller will differ between the two models, and this will likely result in verification mismatches if the differences are externally visible to the DUT. To force the order of the requests to match, we snoop the requests arriving at the controller in the post-HLS model, and only then allow the requests to be seen in the pre-HLS model.

Simplified Snooping Approaches

In the snooping example directly above in which the arbiter is snooped, the entire post-HLS RTL DUT is simulated alongside the pre-HLS model to force the arbiter requests to be aligned in time. This is the most general case and assumes the input delays to the arbiter are difficult to determine via analysis.

Sometimes there are simpler cases where the input delays to the arbiter in the RTL DUT are easier to determine. For example, each input to the arbiter might arrive a fixed number of clock cycles after one of the primary inputs to the RTL DUT is pushed by the testbench. In this case, a much simpler model can be used to align the pre-HLS model with the post-HLS model. We can simply monitor the primary inputs to the pre-HLS model and then apply the fixed cycle delays to the pre-HLS arbiter inputs.

The two cases above illustrate two ends of a spectrum of possible approaches for extracting the delays from the RTL DUT. Between these two points there exist other possible approaches.

Snooping Implementation

To enable perfect matching between the pre-HLS and post-HLS system simulations, latency-sensitive global signals and latency-sensitive non-blocking message-passing operations need to be synchronized between the two simulations if their latency differences are externally visible to the DUT.

As explained earlier in this appendix, in the general case the entire post-HLS DUT RTL must be run alongside the pre-HLS system to achieve alignment. Examples of signals that need to be synchronized include global interrupt request signals (as discussed earlier in this appendix) and `rdy/vld` signal pairs for non-blocking operations on message-passing channels. All such synchronization signals and their corresponding handshake signals must be level-stable:

- A latency-sensitive signal s is **level-stable** if, once s becomes 1 in cycle t , it must remain 1 until the corresponding handshake signal h is 1 in some cycle $t' \geq t$.

Once the set of signals that need to be aligned between the two simulations is identified, the general rule to implement snooping is simple:

- For each of the pre-HLS and post-HLS simulations, make all readers of the signals see the logical AND of the values of each signal being driven in each separate simulation.

Often the post-HLS simulation will never run ahead of the pre-HLS simulation, because HLS typically only adds (rather than subtracts) latency within each process. This means that often the only signals that need to be delayed are on the pre-HLS side, and therefore the logical AND of the nets may not need to be driven on the post-HLS side. If this optimization technique is used, the logical AND of the nets should be compared with the actual value driven on the post-HLS side, and if they do not perfectly match then the optimization technique must not be used.

Definition L.1 (Witness selector / Snooping).

Fix an initial state, fixed external stimulus, and an RTL_B execution prefix τ_{post} . A witness selector W for a source process P is a partial strategy that, at each ϵ -quiescent source cutpoint σ_{ref} and each source-level choice point whose outcome is ϵ -modeled but may affect later Σ -visible behavior, returns the outcome selected by the matched RTL_B execution.

Such choice points include failed/successful outcomes of non-blocking PushNB/PopNB calls when the outcome affects later control flow, frontier membership, request attribution, or payload/guard values; and any other ϵ -only implementation choice that can affect the next Σ -visible frontier.

Cadence-sensitive non-blocking polling. If a source process computes externally visible behavior from the number or cadence of failed PushNB/PopNB polls — for example, retry counters, timeout counters, or arbitration policies whose winner depends on how long an input remained empty/full — then that polling logic is latency-sensitive in the sense of Appendix D. Such a process is not covered by the ordinary Appendix I/J latency-insensitive source-core argument merely by treating the failed polls as hidden ϵ -steps. To bring such a design into scope, the cadence-sensitive polling logic shall be isolated as a latency-sensitive local protocol block, or shall be aligned by an Appendix L snooping/witness construction that makes the selected source execution an admissible execution of the same isolated protocol behavior observed in RTL_B. The observable interface to the rest of the system shall then be the chosen boundary of the isolated block, not the internal failed-poll cadence itself.

The selected outcome must be causally available from the matched RTL_B prefix and the fixed global Σ -causal history. W is not allowed to depend on future RTL_B events beyond the matched prefix needed to identify the current source choice. For cadence-sensitive polling logic, the witness must select an admissible execution of the isolated latency-sensitive block; it may not manufacture a retry/timeout outcome that is inconsistent with the RTL_B behavior being used as the witness, the fixed stimulus, or the chosen observable boundary of that block.

Lemma L.2 (Snooping establishes WC).

Let τ_{post} be an RTL_B execution under fixed stimulus, and let W be the witness selector induced by the Appendix L snooping wrapper for the corresponding source execution. Assume:

1. the snooped signals / outcomes include every ϵ -modeled source choice whose result can affect the next Σ -visible control flow, frontier, request-attribution, guard value, or payload value;
2. the snooping wrapper does not add, remove, reorder, or relabel any Σ -visible event except by selecting ϵ -only source outcomes at the chosen observable boundary;

3. each selected ε -only outcome is consistent with the matched RTL_B prefix and the fixed global Σ -causal history;
4. failed non-blocking polls remain ε -events and successful non-blocking transfers produce exactly the corresponding committed Push_c / Pop_c Σ -event; and
5. if the source contains cadence-sensitive non-blocking polling whose externally visible behavior depends on the number or cadence of failed polls, that polling logic has been isolated or snoop-aligned as a latency-sensitive local protocol block as described in Appendix D and Definition L.1. The WC witness is then applied to the chosen observable boundary of that block, not to an unconstrained hidden failed-poll cadence inside the ordinary latency-insensitive source core.

Then the source execution selected by W satisfies the witness-compatibility premise WC used in Appendix I.2 and Appendix J.

Corollary L.3 (NB-CF identity witness).

If NB-CF holds for process P, then failed non-blocking poll outcomes do not affect the next Σ -visible control flow, frontier membership, request attribution, guard values, or payload values. Therefore the witness selector W may be taken to be the identity / arbitrary selector on failed non-blocking outcomes, and WC holds without additional snooping for those polls.

Corollary L.4 (Cadence-sensitive polling is handled by isolation).

If NB-CF does not hold because the source observes the number or cadence of failed PushNB/PopNB polls — for example, retry counters, timeout counters, or arbitration policies whose later Σ -visible behavior depends on how long a channel remained empty/full — then the design is latency-sensitive at that polling site. Such a site must be isolated or snoop-aligned under Appendix D / Appendix L before applying the ordinary Appendix I/J source-core proof. If no such isolation, snooping, or equivalent explicit timing model is supplied, the process is outside the scope of the Appendix I/J trace-compatibility theorem for the chosen observable boundary.

Snooping Concerns

The snooping technique is used to align pre-HLS and post-HLS latency-sensitive global signals and latency-sensitive non-blocking message-passing operations in cases where their latency differences are externally visible at the DUT boundary. This includes cadence-sensitive polling blocks, such as retry/timeout or polling-arbiter logic, when their externally visible behavior depends on the number or cadence of failed non-blocking polls. When such a wrapper is applied, the pre-HLS model is throttled to follow the latency choices made by the post-HLS RTL, and the resulting traces at the observable interfaces are forced to agree. Snooping does not make failed polls into committed message-transfer events; failed polls remain ε -steps. Rather, snooping selects an admissible execution of the latency-sensitive local protocol block, while the rest of the system is compared at the block's chosen observable boundary.

Readers with a formal background may be concerned by this technique, because it appears to use the post-HLS RTL implementation to modify the behavior of the pre-HLS specification. From a formal point of view, the important observation is that the pre-HLS model is intentionally under-specified with respect to micro-timing/latency: subject to the R-rules, B-rules, weak fairness, and the explicit Σ -visible ordering, FIFO, signal-anchor, synchronization, and atomicity constraints used by $\approx$, it can admit multiple ε -/latency-different executions that respect the same required-order constraints over the chosen observable units. This is compatible with B1, which asserts that the post-HLS Σ -projected trace is unique

under a fixed stimulus; the pre-HLS side may still have multiple admissible realizations that (when projected to Σ) match that unique RTL Σ -trace.

Snooping does not change what executions are allowed by the pre-HLS specification. Instead, it selects—purely for verification purposes—one admissible pre-HLS execution whose latency-sensitive events align with those observed in the RTL. In other words, the implementation is used to pick a witness execution of the specification, not to redefine the specification.

Experienced SoC architects tend to view this slightly differently, in terms of design tradeoffs and verification cost.

First, it is usually possible at the architectural level to avoid latency-sensitive behaviors entirely, for example by insisting that all communication be latency-insensitive and fully synchronized. However, the quality-of-results (QOR) costs of such designs may be unacceptable. Introducing latency-sensitive behavior—non-blocking arbiters, latency-sensitive global interrupt signals, and so on—is a deliberate choice made by the designer to meet performance, power, or area goals.

Second, in many practical systems, latency-sensitive behavior is not functionally observable at the DUT boundary under the trace-compatibility predicate $\approx$ with Σ instantiated to include only the DUT-boundary observables (Appendix G; Common Formal Definitions above). As an example, consider a DUT that contains a single-port RAM used to exchange data between two internal processes. An arbiter is required to control access to that RAM port, and the arbiter uses latency-sensitive non-blocking Pop operations on its request channels. During HLS, internal latencies will change, so the order in which the arbiter sees pending requests and chooses winners may differ between the pre-HLS and post-HLS models.

In this example:

- The individual RAM read/write operations and the internal arbitration decisions are not directly visible at the DUT interface.
- Only the higher-level IO of the two processes (for example, their message-passing interfaces to the rest of the system) is externally visible.

One might initially conclude that it is necessary to snoop the arbiter’s inputs to make the pre-HLS and post-HLS traces match. However, the modeling rules impose two additional constraints:

1. **Weak fairness for the arbiter.** The arbiter must satisfy the weak fairness assumptions, so that any request that remains pending is eventually granted in both the pre-HLS and post-HLS models.
2. **Causal-dependency discipline on shared memory.** The system must make any functionally significant shared-memory dependence explicit, either through synchronization that orders the relevant accesses or through declared array-access mapping / memory-serialization semantics. This discipline ensures that sufficient synchronization or declared serialization exists between the processes so that there are no read/write races through the RAM in either model.

Under these conditions, the different arbitration orders merely change the relative timing of internal operations and of externally visible actions that are not ordered by the explicit required Σ -constraints. They do not change the FIFO, synchronization, signal-anchor, atomicity, or other required ordering constraints at the DUT boundary. In the terminology of Appendices G and J, the differences are incidental variations in latency rather than changes to the required-order relation $\prec_J$ over the chosen

observable units, and therefore they are not considered observable differences in behavior at the DUT boundary. **In such cases, snooping is not required.** (See also Note 1 below).

(More precisely: the trace-compatibility predicate $\approx$ is parameterized by the chosen observable alphabet Σ . If internal functionality (such as the above RAM arbiter) uses channels/signals that are not designated observable in the chosen instantiation of Σ (see Common Formal Definitions), then mismatches on those internal actions are outside $\approx$ by construction: they are not in Σ . If those internal channels/signals are designated observable (e.g., by snooping for debug, or by expanding Σ for Appendix K deadlock analysis), then they are Σ -events and must match under $\approx$. In addition, even when B1 holds (unique post-HLS Σ -trace under fixed stimulus), the pre-HLS model may still admit multiple ϵ -/latency-different executions consistent with the same required Σ -ordering, FIFO, signal-anchor, synchronization, and atomicity constraints; Theorem J.1 captures the intended quantification (“existence of a matching witness execution prefix”) rather than requiring a single pre-chosen trace.)

Experienced SoC architects therefore try to avoid designs in which latency-sensitive internal behaviors leak directly into the observable behavior of the system under test, since this both complicates verification and makes RTL behavior less predictable. When they do introduce such behaviors—examples include non-blocking arbiters whose winners affect externally visible ordering, global interrupt request signals at the DUT boundary—they typically know exactly where those latency-sensitive interfaces are and can isolate them.

A useful analogy is a subsystem whose clock frequency is adjusted dynamically based on on-die temperature. As temperature changes, the externally visible behavior of the SoC can change (for example, in terms of throughput or timing of events), and designers may choose such a temperature-dependent scheme to meet overall system requirements. To verify such a system, we may wish to compare a concrete RTL trace captured at a specific temperature profile with a higher-level reference model. To do so, the reference model must be driven with the **same** temperature evolution as the RTL saw. If that temperature profile is not otherwise under direct control, the simplest way to obtain it is to “snoop” the temperature as observed in the RTL trace and replay it into the reference model. In this analogy, temperature is an external parameter of the environment rather than a fundamental part of the functional specification, but it still influences observable behavior. Snooping simply provides a mechanism to recover that parameter from the implementation when it cannot be easily prescribed a priori. Similarly, snooping of latency-sensitive IO provides a mechanism to supply implementation-specific latency choices — subject to the fairness assumptions and the explicit required Σ -ordering, FIFO, signal-anchor, synchronization, and atomicity constraints — back to the pre-HLS specification so that the two models can be compared under a common environment.

Note 1 (Unobservable non-blocking micro-timing).

Safety / functional equivalence. The trace-compatibility predicate $\approx$ is parameterized by the chosen observable alphabet Σ (Appendix G). If, for safety-only checking, we instantiate Σ to include only DUT-boundary observables (Σ_{DUT}) and we assume that any latency-sensitive internal behavior is not visible at that boundary under $\approx$ —i.e., it may change only internal micro-timing, but it does not change the values or presence of Σ_{DUT} events, and does not change the ordering of causally *dependent* Σ_{DUT} events—then snooping of those internal latency-sensitive interfaces is not required for proving Σ_{DUT} -safety. Any mismatches on actions outside Σ_{DUT} are outside $\approx$ by construction.

Liveness / deadlock analysis. For message-passing deadlock analysis (Appendix K WFG), any latency-sensitive interface whose ϵ -level choices can affect whether a blocking Push/Pop is enabled, or can create/remove a wait-for dependency without an intervening committed Σ -event, must be accounted

for. Practically, the default is to snoop and replay every such latency-sensitive (typically non-blocking) arbitration/probe interface in the DUT. Snooping can be avoided only if the design is certified “WFG-inert” with respect to that interface: it cannot change WFG edges except via committed Push_c/Pop_c (or explicit synchronization) events.

Stress Testing Pre-HLS Models for Latency Robustness

The formal trace-compatibility results in Appendices G–K establish that, under the scheduling rules and fairness assumptions, the post-HLS RTL is trace-compatible with the pre-HLS/source-reference model at all observable interfaces.

These results implicitly assume that the pre-HLS specification is *well-formed*: it must not rely on incidental, implementation-specific timing alignments for functional correctness. Designs that do rely on such incidental alignments fall outside the formal guarantees.

Designs that use non-blocking message-passing operations (e.g., PushNB/PopNB, ac_channel nb_read/nb_write) or latency-sensitive global signals are particularly vulnerable to this kind of fragility. For such designs, it is strongly recommended to subject the pre-HLS model to aggressive *latency stress tests* in which message and handshake latencies are varied across executions. The intent is to validate that the design behaves correctly across the range of weakly fair schedules permitted by the modeling rules, not just under one convenient execution order.

More concretely, verification should check that:

- **Causal dependencies are explicit.** All functionally significant causal-dependency relationships are enforced via message-passing, SyncChannel/ac_sync operations, explicit signal handshakes/anchors, declared memory-serialization constraints, or Appendix L snooping/witness-selection boundaries, rather than by relying on the incidental execution order of concurrent processes. In the terminology of Appendix G, the design shall not depend on the ordering of causally independent events for correctness.
- **Weak fairness does not hide latent deadlocks or starvation.** The design continues to make progress under adversarial but *weakly fair* scheduling—i.e., enabled actions may be delayed arbitrarily long but not forever—consistent with the B2/B3 obligations on the scheduler and environment summarized in Appendix N.

If the pre-HLS model fails under such randomized-latency stress scenarios, then the specification itself is outside the formal model of this document: it violates the design rule that well-formed systems must not rely on the relative ordering of causally independent events. In that situation, the trace-compatibility theorems still apply to well-formed traces, but they no longer guarantee that the “golden” specification is robust under the full range of latency variations allowed by the environment.

The Matchlib library provides practical mechanisms to automate these stress tests in pre-HLS simulation, including:

- **Random stall injection on message-passing channels**, to simulate variable communication delays while preserving rendezvous semantics.
- **Latency and capacity back-annotation**, to model specific per-channel buffer depths and delays, including the capacities B(c) chosen during HLS.

Worked examples of this methodology are provided in Catapult Matchlib examples 60* and 72*, which illustrate how to configure randomized stalls and back-annotated latencies when validating that a design remains well-formed and latency-robust.

Appendix M – Document Abstract

This document defines a precise user-level scheduling model for high-level synthesis (HLS) that enables system-level verification and debug to be carried out primarily on the pre-HLS SystemC model, while still permitting aggressive RTL optimizations in the synthesized design. It introduces a small set of uniform rules governing three classes of I/O operations — message-passing channels, signal I/O, and explicit synchronization — and organizes them into a “basic conceptual model” that preserves source-order synchronization, anchors signal reads and writes to their nearest synchronization points, and constrains the reordering of message-passing operations so that HLS cannot introduce new deadlocks merely by reversing source-order message calls. Deadlock behavior can still depend on bounded-capacity effects, overlapped execution, and progress assumptions; the full liveness/deadlock-preservation result is therefore stated separately and remains conditional on the Appendix K and Appendix N assumptions.

These rules are extended to pipelined loops, shared and external memories through an explicit array-access mapping layer and conflict-free reordering discipline, and direct-input pragmas that allow stable or explicitly synchronized signals to avoid unnecessary internal storage while preserving the intended Σ -visible correspondence under the stated stability and synchronization contracts.

The methodology is latency-insensitive by construction but accommodates latency-sensitive islands such as cycle-accurate transactors, non-blocking arbiters, and one-way handshake protocols through encapsulation, explicit synchronization, and the Appendix L snooping / witness-selection mechanism when needed. The document also provides concrete modeling guidelines, including rules for placing signal reads and writes around wait statements, coding rolled loops with signal I/O, and using Matchlib Connections and SyncChannel, so that digital verification engineers can write a single verification intent in SystemVerilog UVM or SystemC/C++ and reuse it across pre-HLS and post-HLS models with “no surprises,” subject to the stated well-formedness and side-condition obligations.

A major contribution is the formalization, in Appendix G and subsequent appendices, of an ordered observable trace-compatibility predicate between the prescribed source reference model Sys_ref and the post-HLS RTL model RTL_B , expressed as partial-order constraints on observable I/O actions and encapsulated in trace-compatibility rules E1–E5. The unrestricted safety direction is $\text{Post} \rightarrow \text{Ref}$: every compliant RTL_B behavior has a matching Sys_ref behavior under the fixed stimulus. The converse use of a particular source-side execution is not claimed for all Sys_ref traces; when it is needed, it is restricted to RTL-consistent source prefixes or to source executions selected by the Appendix L snooping / witness-selection mechanism.

For channels whose RTL implementations introduce finite buffering or staged realization structure, the correspondence is stated against the chosen source reference model Sys_ref : in ordinary bounded-FIFO cases, $\text{Sys_ref} = \text{Sys_B}$ with capacities $B(c)$ faithful to the selected abstract boundaries; in elaborated cases, $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$ with explicit staged, bundled, join, or epoch-gate abstract channels. The raw rendezvous case is recovered as the special case $B(c)=0$ at the relevant ordinary boundaries.

The trace-compatibility proofs are compositional in a strong local sense: each process is verified against the obligations at its own observable boundaries, while each abstract channel boundary supplies the methodology-defined rendezvous or bounded-FIFO ChannelEnabled/ChannelDisabled behavior required by E4. A producer or consumer process need not know whether the connected ordinary channel is implemented as rendezvous or with positive capacity; it need only satisfy its local endpoint scheduling and handshake obligations at the chosen boundary.

The liveness/deadlock result is more conditional. Appendix K preserves absence of internal message-passing deadlock from the prescribed Sys_ref to RTL_B only when the global source-level liveness assumption A5 holds under the conservative serial-blocking source semantics, when the serial-source dominance lemma connects any RTL-matched overlapped witness deadlock back to a serial-source deadlock, and when the RTL_B scheduler/environment, channel realization, abstraction relation, and ϵ -behavior satisfy the applicable fairness, progress, and structural side conditions, including B2/B3/B5, K ϵ , J.AbsConf, and A6–A11.

This trace-compositional methodology covers key HLS transformations including loop pipelining, added FSM states, memory-access reordering, direct-input late sampling under explicit contracts, and configurable channel buffering. It also explains why the methodology is not inherently limited to HLS-generated RTL: hand-written or otherwise generated RTL can use the same proof framework when its processes, channel realizations, selected abstract boundaries, and tool/RTL evidence satisfy the same implementation-side obligations. The proofs do not by themselves certify any particular HLS tool invocation or RTL instance; those obligations must be discharged by tool documentation, generated certificates, static checks, RTL/interface checks, or another validation method appropriate to the flow. Collectively, the scheduling rules, coding guidelines, and formal guarantees provide a tool-agnostic, Catapult-compatible foundation for industrial HLS use, a scalable verification methodology for RTL design more generally, and a concrete starting point for standardization efforts within bodies such as the Accellera Synthesis Working Group.

Keywords: High-level synthesis (HLS); SystemC; scheduling rules; latency-insensitive design; message-passing channels; ready/valid protocols; signal I/O; loop pipelining; direct input pragmas; shared memory; Sys_ref; RTL_B; trace compatibility; witness selection; formal verification; bounded FIFOs; B-faithfulness; liveness preservation; deadlock preservation; fairness; Catapult HLS; Matchlib; Accellera Synthesis Working Group.

Appendix N – Scheduler and Environment Fairness Assumptions

The formal results in Appendices I–K rely on several semantic assumptions about the post-HLS scheduler and its environment. The B-rule table in “Common Formal Definitions for Appendices I–K” gives the proof-level names B1–B6. This appendix restates the fairness/progress rules in operational ready/valid form. In particular, Appendix N’s “B3 Channel Progress Invariants” are exactly the P_push(c) and P_pop(c) obligations for each explicit abstract channel c; they are not additional assumptions beyond B3.

- **B2 (Weak fairness of the scheduler).** If the enabling predicate for an action (Push, Pop, Sync) remains continuously true from some cycle onward, the scheduler must eventually select that action within a finite, but unspecified, number of cycles.

- **B3 Channel Progress Invariants (ready/valid form).**

For every channel c with capacity $B(c)$, interpret “continuously enabled” in terms of continuous endpoint request, not as an immediate commit.

(**No deassert-before-commit assumption.**) For blocking Push_c/Pop_c transfers, these requests are non-withdrawable during the outstanding transfer attempt: once asserted for a transfer attempt, they are not deasserted before the corresponding commit, and Push_c payload remains stable while vld_c is asserted for that outstanding transfer. After the corresponding commit, the endpoint may deassert or may present a different request/payload for a later transfer.

Let vld_c denote the producer’s persistent request to transfer (e.g., valid=1 with a stable payload for a Push_c), and let rdy_c denote the consumer’s persistent request to transfer (e.g., ready=1 for a Pop_c). In the definitions below, “remains asserted continuously” is scoped to the outstanding interval from t_0 until the first matching discharge event. If the matching discharge never occurs, then the request must remain asserted for all later cycles.

- **P_{push}(c):** If vld_c is asserted at cycle t_0 while the channel is full ($occ_c = B(c)$), and both endpoint requests continue until the matching discharge event — i.e., vld_c remains asserted with stable payload and the complementary Pop_c endpoint request remains asserted with BoundaryReq(Pop_c, t) true until the first Pop_c commit on c — then some Pop_c commit must eventually occur, discharging the full condition. Equivalently: when both endpoints continuously request the matching transfer until discharge, the system cannot remain stuck forever in the full state without a Pop_c commit.

- **P_{pop}(c):** If rdy_c is asserted at cycle t_0 while the channel is empty ($occ_c = 0$), and both endpoint requests continue until the matching discharge event — i.e., rdy_c remains asserted and the complementary Push_c endpoint request remains asserted with stable payload and BoundaryReq(Push_c, t) true until the first Push_c commit on c — then some Push_c commit must eventually occur, discharging the empty condition. Equivalently: when both endpoints continuously request the matching transfer until discharge, the system cannot remain stuck forever in the empty state without a Push_c commit.

For $B(c)=0$ rendezvous channels: if both endpoint requests are asserted at cycle t_0 and both remain asserted until the matching rendezvous discharge event, then the rendezvous completion eventually occurs. If no rendezvous completion occurs, both requests must remain asserted for all later cycles.

These obligations rule out “permanent back-pressure loops” that are logically independent of the local R-rules. They do not require an endpoint request or Push payload to remain asserted forever after the matching transfer has already committed.

- **B5 (System quiescence closure).** If at some cycle no observable actions are enabled in any process, then within a bounded number of cycles the system reaches a fixed point and executes no further ϵ -steps. This prevents a dead, all-disabled state from being hidden behind an infinite tail of internal activity.

These B-rules are **assumptions on the execution environment**, not guarantees automatically provided by the HLS tool. In practice they place concrete requirements on arbiters, back-pressure, and external masters that interact with the post-HLS RTL.

Priority arbiter example: fair vs unfair priority

Consider a simple two-input priority arbiter inside the post-HLS RTL. Each input is driven by a message-passing channel; the arbiter issues Pop operations to select which request to serve in each cycle.

- Input 0: high-priority channel `c_high`
- Input 1: low-priority channel `c_low`

Both channels may have pending requests at the same time.

1. Fair priority arbiter (satisfies B2 / B3).

A fair implementation might still give `c_high` strict priority in *individual* decisions, but it ensures that a continuously pending `c_low` request cannot starve. In RTL terms, this can be realized by, for example:

- A **round-robin or rotating-priority** arbiter that periodically moves the “highest” priority to the next requester, or
- A **bounded-burst priority** scheme in which `c_high` may win at most *N* consecutive cycles while `c_low` is requesting; after that, the next grant is forced to `c_low`.

Under these implementations:

- If `Pop_low`’s `ChannelEnabled` predicate remains true indefinitely (the low-priority channel has a pending request and the relevant abstract boundary availability predicate holds), the scheduler/arbiter must eventually select `Pop_low`. The selected `Pop_low` then commits in the selected cycle. This satisfies B2 for that action.
- If the low-priority FIFO is full and keeps requesting service, the system ensures that some complementary `Pop_low` eventually commits, discharging data and freeing space. This is consistent with `P_push/P_pop` in B3; it is a channel-progress obligation that may be needed before a blocked producer’s Push becomes `ChannelEnabled`.

Intuitively, the arbiter is still “priority-based,” but its micro-architecture ensures that every continuously enabled requester is eventually selected, and that full/empty channel states covered by B3 cannot persist forever under the stated persistent-request premises.

2. Unfair priority arbiter (violates B2 / B3).

A more naive design might implement:

```
if (req_high) grant_high();  
else if (req_low) grant_low();
```

combined with an environment in which `req_high` can remain asserted indefinitely. In this case, even if `req_low` is also continuously asserted:

- `Pop_low`’s `ChannelEnabled` predicate may be true forever, but `Pop_low` is never selected by the scheduler/arbiter.
- Low-priority requests can starve indefinitely, even though they are continuously eligible for selection.

This behavior violates B2, because B2 requires eventual selection of any continuously enabled action. If `c_low`’s FIFO is full and the only way to make space is to service it, permanent starvation can also violate B3’s progress expectations for that channel, because the full condition may never be discharged under the stated persistent-request premises.

In such a design, the safety properties E1–E5 may still hold (trace-compatibility on actions that do occur), but the liveness/results that depend on B2/B3—especially the starvation-vs-deadlock arguments in Appendix K—no longer apply.

Patterns that typically satisfy the fairness assumptions

The following design patterns normally satisfy B2 and are compatible with B3/B5, provided the rest of the system is well-behaved:

- **Round-robin or rotating-priority arbiters.** Any requester that remains enabled will eventually be at the front of the rotation and will be granted.
- **Age-based or credit-based arbiters.** Requesters accumulate age or credits while waiting; the arbiter prefers older or more-starved requests, guaranteeing that long-pending actions eventually win.
- **Bounded-burst fixed priority.** Fixed priority is combined with a counter that limits how long a higher-priority requester can dominate while lower-priority requesters are pending. After the burst limit is reached, lower-priority requests are forced to win until the system is “caught up.”
- **Back-pressure with bounded stall.** When ready/valid or similar handshake signals are used, the design (or its environment) must enforce that ready cannot remain low forever while valid remains high, and vice versa. For example:
 - Downstream consumers are required (by specification) to service queues at least once every N cycles when data is present.
 - External bus masters are configured such that they cannot indefinitely defer reading from full DUT FIFOs that are logically part of the interface contract.
- **Clock-gating and power-management schemes that respect B5.** Once no observable actions are enabled, the design either:
 - Quietly stabilizes (no further internal toggling), or
 - Explicitly enters a low-power state from which it only wakes when some observable action again becomes enabled.

In each case, the intent is the same: continuous ChannelEnabled status implies eventual scheduler/arbiter selection and commit under B2; persistent full/empty/rendezvous-blocked request premises imply eventual discharge under B3; and once nothing is enabled, the system converges rather than oscillating internally.

Patterns that tend to violate the fairness assumptions

Conversely, the following patterns are likely to **break B2/B3/B5** and therefore fall outside the scope of the liveness arguments in this document:

- **Pure fixed-priority arbitration with unbounded high-priority traffic.** A static priority tree with no rotation or aging, combined with workloads in which a high-priority master can keep its request asserted indefinitely, can starve lower-priority channels forever.
- **“Best-effort” external masters with no progress guarantee.** For example:
 - A software driver that reads from a DUT output FIFO only when it happens to poll, and that may be pre-empted indefinitely by higher-priority threads.
 - An external bus or DMA engine that is architecturally allowed to ignore some requesters forever if higher-priority traffic remains heavy.
Such environments can violate **P_push/P_pop** by allowing FIFOs to remain full or empty indefinitely while the DUT is continuously requesting progress.
- **Circular back-pressure loops with no escape.** Two or more processes form a cycle in which each is waiting for the other’s channel to change state, and no other process can break the cycle. Without an explicit design-level guarantee that some process in the loop will eventually act (for example, by dropping priority or issuing a compensating Pop/Push), **B3** is not satisfied.

- **Internal oscillation without quiescence.** A scheduler or control FSM that can toggle internal ϵ -level state forever, even after all observable actions are disabled, violates **B5**. While such designs are uncommon in practice, patterns involving mis-configured clock gating, asynchronous feedback, or “keep-alive” timers that never expire can have this effect.

In all these cases, the trace-compatibility theorems **still describe what happens when actions do occur**, but the liveness claims that depend on B2/B3/B5 (for example, “a continuously enabled channel will not starve”) are no longer guaranteed. Designers and verification engineers should therefore either:

- Architect their arbiters and environments to satisfy these B-rules, or
- Treat the liveness guarantees in Appendix K as *out of scope* for those particular interfaces, and rely only on the safety-oriented parts of the model.

Appendix O – Support for Multiple Clock Domains (Informative Sketch)

This appendix is an informative sketch of how the single-clock formalism of Appendices G–K could be organized in a multi-clock design. The formal results of Appendices G–K are stated for a single global clock unless an explicit multi-clock semantic layer is added.

Within a single clock domain d , one may treat that domain as a synchronous island with a local cycle counter clk_d and apply the existing R- and E-rules to processes wholly inside that domain, interpreting $\text{clk}(\cdot)$ as $\text{clk}_d(\cdot)$ for local synchronization, signal I/O, and message-passing events. Inter-domain communication should be represented by explicit clock-domain-crossing components, such as CDC FIFOs, whose source-side and destination-side commit semantics are specified at their respective clock-domain boundaries.

A full formal lift requires additional definitions not supplied by Appendices G–K themselves: a global event order or partial order relating local-domain cycles, precise CDC commit semantics, occupancy sampling rules across source and destination clocks, synchronizer fairness/metastability abstraction assumptions, and progress obligations for CDC components. Once those additional definitions are supplied, the intended proof strategy is to treat each synchronous island using the existing single-domain rules and to treat each CDC component as an explicit channel/refinement boundary with its own stated E4-style legality and progress obligations. Without those additional definitions, Appendix O should not be read as claiming that the single-clock proofs apply unchanged to arbitrary multi-clock systems.

Appendix P – AI Discussion of Alternative Formal Frameworks

The following links provide an AI discussion of alternative formal frameworks compared to the one presented in this document:

https://drive.google.com/file/d/1ccU-eRW7H2ggh-AZyKnCOzO-KLPejob_/view?usp=sharing

<https://chatgpt.com/share/69457119-ec30-8006-8684-9a2a8b19f96f>

<https://drive.google.com/file/d/1R3-46DtZLsBn1hdTbLExYc0FVB50Gymz/view?usp=sharing>

Appendix Q – Multiple Input Pipelines Back-Annotation

Appendix J Remark 2 discusses back-annotation of pipelined loops with a single message passing input. In more complex cases such as HW pipelines with multiple message-passing inputs, the back-annotation mechanism may elaborate the Sys_B (source-level) simulation by introducing additional internal realization structure. In this document, we adopt the following simplified modeling discipline:

1. Terminology (elaboration and channel accounting). In an elaborated realization, the quantities $B(\cdot)$, $\text{occ_}(\cdot)$, and the E4 availability predicate are interpreted over the explicit abstract channels present in the elaborated model (including any introduced staged/bundle channels). When we continue to write a source-level channel name c at the outer DUT/testbench observation boundary, we mean the chosen outer abstract boundary channel associated with c in that elaboration; downstream staging that is reachable only through a join (and therefore may be withheld when “join not met”) is represented by distinct internal channels with their own $B(\cdot)$ and $\text{occ_}(\cdot)$, rather than as independent “slack” for c in isolation.
2. All buffering / capacity effects are represented explicitly as finite-capacity message channels (annotated with bounded capacity) that may appear upstream and/or downstream of any internal glue logic; and
3. Any internal “coupler” used to enforce mutual-stall between multiple inputs is purely combinational (stateless) handshake logic.

Observation-boundary convention for Appendix Q. In elaborated cases, distinguish the outer projected observation boundary from the proof-internal abstract boundaries. The outer Σ_{DUT} / testbench projection records only the chosen outer Push_c / Pop_c history after applying Π_{elab} . By contrast, Appendix K WFG reasoning is carried out over the explicit abstract channels of $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$, including introduced staged/bundle/join channels. Thus an introduced internal channel may be hidden by Π_{elab} from the outer DUT-visible trace while still being an explicit proof-internal boundary with its own $B(\cdot)$, $\text{occ_}(\cdot)$, BoundaryReq , $\text{ChannelEnabled/ChannelDisabled}$, Front_P , and WFG facts.

Concretely, a combinational coupler is a stateless component that (a) reads the upstream channels’ valid and data signals and computes/drives the downstream channels’ valid and data signals, and (b) reads downstream ready signals and upstream valid signals and then computes/drives upstream ready signals. The coupler contains no internal state and has no separate credit/capacity state; any shared pipeline capacity, per-input staging, skid/elastic buffering, or credit-like effects are modeled only by the explicit finite-capacity channels inserted by the back-annotation realization.

Example (two inputs, staged Pops, $\text{II}=1$, latency=4):

Consider a 4-stage RTL pipeline that (i) performs Pop_c1 in stage 1, (ii) performs Pop_c2 in stage 2, and (iii) performs Push_cout in stage 4, with $\text{II}=1$. To model the pipeline’s internal staging and the stage-2 input coupling in the source-level $\text{Sys_B}^{\text{elab}}$ simulation while keeping the same outer projected Σ boundary, the back-annotation elaboration may introduce the following internal realization structure:

- An explicit bounded **channel F1 of capacity 1** on the $c1$ path to represent stage-1 in-flight storage of values that have been accepted from $c1$ but have not yet reached the stage-2 join point.

- An explicit internal **rendezvous channel F2** on the c2 path at the stage-2 join boundary, with $B(F2)=0$. F2 represents the c2-side handoff into the stage-2 join. It is not additional c2-side buffering or slack, and it does not permit a c2 value to be accepted independently before the join is ready. Its purpose is to make the c2-side join blocking point an explicit proof-internal abstract boundary of $\text{Sys_B}^{\text{elab}}$, so that any mutual-stall condition involving c1/F1 and c2/F2 is represented as ordinary BoundaryReq / ChannelEnabled / ChannelDisabled facts on explicit internal channels rather than as a hidden cross-channel disablement predicate on the outer projected c2 boundary.
- A **purely combinational coupler/join** at the stage-2 boundary that enforces mutual stall: it allows the joined transfer to proceed only when (a) a token is available from F1, (b) the c2-side rendezvous over F2 is requested/enabled, and (c) downstream staging has space; it then presents the paired value(s) to the downstream staging. The join's possible refusal to proceed is therefore visible to Appendix K through the explicit internal boundaries F1, F2, and F34, even though those internal events are projected away from the outer DUT/testbench-visible Σ_{DUT} trace by Π_{elab} .
- An explicit bounded **channel F34 of capacity 2** after the coupler to represent the in-flight capacity of stages 3–4 for the joined/paired work.

This example illustrates why multi-input pipelines cannot always be captured by a single per-channel capacity number in isolation: c1 and c2 do not have independent “slack” because acceptance across the stage-2 join boundary is coupled. In this particular example, the c1 side has one stored stage-1 token available through F1, the c2 side has no independent pre-join storage and is therefore modeled by the rendezvous channel F2 with $B(F2)=0$, and the joined/paired work has two downstream storage slots through F34.

All storage-bearing buffering/capacity resides in the explicit bounded channels F1 and F34, and in any additional positive-capacity stages the realization uses. The explicit rendezvous channel F2 has $B(F2)=0$ and contributes no storage; it is an explicit proof-internal join boundary used to type the mutual-stall condition. The coupler itself remains stateless combinational handshake logic.

This elaboration is an implementation/refinement of the abstract bounded-FIFO channels at the chosen outer DUT/testbench observation boundary; it does not change the outer interface Σ_{DUT} or E4's per-channel FIFO meaning at that outer boundary. It may, however, introduce additional proof-internal Σ boundaries in $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$ for Appendix K blocking/WFG reasoning. Concretely, any back-annotation elaboration (including extra FIFO stages and/or combinational couplers) must satisfy:

- No new outer DUT-boundary observables: It introduces no new Σ_{DUT} -observable actions at the chosen DUT/testbench boundary, and it does not change the labeling of existing outer Σ_{DUT} events (Push_c(v), Pop_c(v), etc.).
- Boundary/E4 preservation at the outer projection: At the chosen outer DUT/testbench boundary, each outer Σ_{DUT} -visible committed Push_c/Pop_c event still denotes a committed transfer on the same abstract channel c, with per-channel FIFO order and the same E4 capacity/enablement interpretation under the annotated $B(c)$ and $\text{occ_c}(t)$. Any additional internal channels introduced by the elaboration (e.g., staged/bundle/join channels) are separate proof-internal abstract channels in $\text{Sys_B}^{\text{elab}}$ with their own $B(\cdot)$, $\text{occ_}\cdot(t)$, and E4 availability predicates; if they participate in Appendix K, their committed transfers are proof-internal Σ -events even when Π_{elab} hides them from Σ_{DUT} .
- No double-counting of internal staging: internal transfers within the concrete realization of a single explicit abstract channel that contributes to that channel's effective capacity (extra FIFO stages, skid/elastic buffering, FIFO→pipeline-stage handoffs, and value propagation through purely combinational couplers that does not cross an explicit abstract channel boundary) are ϵ -steps and do

not create additional committed Push_c/Pop_c events at that abstract boundary. By contrast, a transfer across an explicit staged/bundle/join channel introduced in Sys_B^elab is a committed Push/Pop event at that proof-internal abstract boundary. Such an event may be projected away from the outer DUT/testbench-visible Σ _DUT trace by Π _elab, but it is not ϵ for the Appendix K proof-internal WFG boundary.

- **Conservation / projection of internal staging (normative):** For each outer Σ _DUT-visible abstract channel c at the chosen DUT/testbench boundary, the elaborated realization shall admit a fixed projection/accounting map from the occupancies of the explicit internal channels introduced by the elaboration (including staged/bundle/join channels, as applicable) to the outer boundary occupancy $occ_c(t)$. This projection/accounting map is part of the realization and witnesses that the proof-internal occupancy bookkeeping is only a refinement of the outer boundary model: (i) every ϵ -step internal transfer and every committed transfer across an introduced proof-internal abstract channel preserves the projected outer boundary occupancy for each outer Σ _DUT-visible channel, except when it corresponds under Π _elab to an outer boundary commit, and (ii) each outer Σ _DUT-visible committed Push_c/Pop_c updates the projected outer boundary occupancy exactly as required by E4 (equivalently, exactly as the outer boundary $occ_c(t)$ defined from Σ _DUT-visible boundary commits). For bundled/joined work items, the projection may assign one proof-internal token to multiple outer Σ _DUT-visible channels as specified by the realization. Therefore, the internal capacities/occupancies $B(\cdot)$, $occ_c(t)$ do not introduce an additional independent outer Σ _DUT-visible state; they refine the same bounded-FIFO accounting already represented at the chosen outer boundary, while still serving as proof-internal Σ state for Appendix K when those internal channels are explicit abstract boundaries.

- **Multi-input pipelines / combinational couplers (mutual stall + explicit capacity):**

To preserve per-channel E4 at the Σ boundary, any downstream staging that is reachable only through a join (and therefore may be withheld when “join not met”) shall be modeled as distinct internal finite-capacity channels with their own $B(\cdot)$ and $occ_c(t)$, rather than being treated as additional independent “slack” for an upstream Σ -visible channel in isolation; the back-annotation elaboration may use combinational couplers to enforce the intended mutual-stall behavior when some required inputs are unavailable. Any “shared capacity” or “distributed staging” effects needed for such a pipeline shall be represented only by explicit finite-capacity channels in the realization (e.g., bounded staging FIFOs, bounded slot/credit channels, bounded bundle channels), not by coupler state. The coupler itself remains stateless combinational handshake logic and does not redefine the per-channel E4 capacity/availability predicates at the chosen observable boundary.

Projection/accounting invariant for Sys_B^elab (normative). Any elaborated reference model Sys_B^elab used for multi-input / coupler cases shall come with a projection map Π _elab from the explicit staged/bundle/join channels of the elaboration back to the chosen outer Σ -visible channel boundaries. This projection map has these roles:

- **Observable-boundary preservation.** When the internal staged/bundle/join events introduced by elaboration are hidden or projected away, the remaining outer-boundary Push_c(v) / Pop_c(v) history is the same boundary history that the non-elaborated model would expose at the chosen Σ -visible endpoints. Elaboration may add explicit internal abstract channels for proof and WFG purposes, but it may not create extra outer-boundary Push_c / Pop_c events, drop outer-boundary events, duplicate them, or change their payload labels.

- **Capacity/occupancy accounting.** For each outer channel c represented by an elaborated subnetwork, the outer-boundary availability facts used by E4 are preserved by the aggregate accounting of the explicit internal channels in the preimage/fiber $\Pi_elab^{-1}(c) = \{d : \Pi_elab(d) = c\}$. Internal

staged/bundle/join occupancies may refine where storage and blocking occur, but after projection they must implement the same externally visible capacity/acceptance behavior at the chosen boundary. Conversely, any cross-channel dependency or join condition that can block progress must appear as ordinary BoundaryReq / ChannelEnabled / ChannelDisabled facts on some explicit internal abstract channel of $\text{Sys_B}^{\text{elab}}$, not as a hidden extra predicate on an otherwise E4-enabled outer-boundary operation.

All examples and constraints in Appendix Q are to be read relative to this projection/accounting invariant.

Explicit join boundary requirement (normative): The mutual-stall point shall be an explicit staged/bundle/join boundary inside the elaborated realization (i.e., the endpoint of an explicit finite-capacity message channel). “Join not met” shall therefore be expressed as ordinary ChannelDisabled at that explicit internal boundary (because that boundary’s own E4 availability predicate fails in the ϵ -quiescent handshake fixed point). The realization must not force a Σ -visible operation on an abstract channel c at the chosen boundary to be ChannelDisabled solely due to the state of some other channel; any cross-channel dependency shall be expressed only via the explicit staged/bundle channels introduced by the elaboration. Operationally, the coupler is invisible at the outer DUT/testbench observation boundary: it only propagates ready/valid between the explicit staged/bundle channels inside the elaborated realization, and it does not change the projected outer $\text{occ}_c(t)$, which is defined solely by projected outer-boundary commits under Π_{elab} . This invisibility is only with respect to the outer projection; it does not hide any explicit staged/bundle/join channel from Appendix K’s proof-internal WFG boundary.

- **WFG compatibility (Appendix K):** The realization must not introduce a new blocking point that is invisible to the proof-internal abstract boundary of $\text{Sys_B}^{\text{elab}}$. In particular, if the consuming process cannot advance the pending blocking frontier $\text{Front_P}(\sigma)$ (Appendix K.1), then at least one blocking frontier operation (Push/Pop) at either the chosen outer boundary or an introduced explicit staged/bundle/join boundary is asserted with a true boundary request and is channel-disabled by the K.1 enablement test; the process is therefore “blocked on message passing” exactly as defined in K.1. Because couplers are purely combinational, they have no internal state transitions; any changes in readiness/validity induced by the coupler are purely a function of (i) downstream readiness and (ii) the same channel occupancies / Σ -visible committed transfers already accounted for by E4/K.1, with “downstream readiness” interpreted in the ϵ -quiescent (ϵ -normalized) state used for WFG evaluation.

Pure internal data movements that do not change any proof-internal BoundaryReq, ChannelEnabled/ChannelDisabled, Pending_P, or Front_P fact are ϵ -steps and are WFG-inert under the same pending-blocking-frontier / $\text{Front_P}(\sigma)$ discipline used elsewhere in Appendix K. By contrast, a staged/bundle/join channel boundary that can block progress is not hidden from Appendix K; it is part of the explicit $\text{Sys_B}^{\text{elab}}$ proof boundary, even if it is projected away from the outer Σ_{DUT} trace by Π_{elab} .

- **Combinational well-formedness:** The network of combinational couplers and ready/valid connections shall be combinational acyclic (no pure combinational ready/valid loops). Any required feedback that would otherwise create a combinational loop must pass through an explicit finite-capacity channel stage (and is therefore represented in the back-annotated realization and its effective capacities).

Accordingly, the formal development need not depend on the particular back-annotation construction, provided it yields an explicit source-side reference model $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$ (Appendix J, Remark 2)

equipped with a projection/accounting map Π_{elab} satisfying the invariant above. The elaborated model must respect E4, BoundaryReq, ChannelEnabled/ChannelDisabled, and the Appendix K blocking/WFG semantics at its explicit proof-internal abstract boundaries, while its projection back to the chosen outer Σ_{DUT} -visible boundaries must preserve the externally visible Push_c / Pop_c history and aggregate capacity/occupancy behavior. In these cases the proofs do not target the raw outer-boundary Sys or the non-elaborated outer-boundary Sys_B directly; they target the proof-internal explicit abstract channels of Sys_B^{elab} together with their Π_{elab} projection back to the outer DUT/testbench-visible boundary.

Lean-oriented clarification / proof-parameter convention

The formal theorems do not require a unique algorithm that constructs Sys_B^{elab} from RTL_B. Instead, the chosen comparison boundary Sys_ref is part of the theorem instance. For ordinary bounded-FIFO cases, Sys_ref may be Sys_B. For cases involving proof-relevant internal staging, multi-input joins, combinational couplers, sync-boundary epoch gates, or shared-capacity effects, Sys_ref shall be supplied as Sys_B^{elab}(E) for some well-formed elaboration package E.

Thus elaboration is not an extra semantic freedom inside the proof. It is an explicit input to the proof instance, and all Appendix I–K definitions are interpreted over that chosen Sys_ref.

Definition Q.1 (Elaboration package for Sys_B^{elab}).

For a chosen outer source reference boundary Sys_B and outer observable alphabet Σ_{DUT} , an elaboration package E consists of:

1. an elaborated source reference model Sys_B^{elab}(E);
2. a finite set of explicit abstract channels Chan_elab(E), each with finite capacity $B_E(d) \geq 0$ and cycle-boundary occupancy $\text{occ}_d(t)$;
3. a distinguished subset of outer-boundary channels Chan_outer and a projection/accounting map

$$\Pi_{\text{elab}} : \text{Chan_elab}(E) \rightarrow \text{Chan_outer} \cup \{\perp\};$$

4. a trace projection map $\pi_{\Sigma,E}$ from proof-internal Σ_{elab} traces to outer Σ_{DUT} traces; and
5. a state-accounting map A_E that computes each outer $\text{occ}_c(t)$ from the occupancies and token/accounting state of the elaborated channels in $\Pi_{\text{elab}}^{-1}(c)$.

The package is well formed only if the following obligations hold:

(a) Outer-trace preservation. $\pi_{\Sigma,E}$ neither creates, drops, duplicates, nor relabels any outer-boundary Push_c(v) / Pop_c(v) event.

(b) Occupancy preservation. For every outer channel c and every ε -quiescent cycle-boundary state σ at time t,

$$\text{occ}_c(\sigma) = A_E(c, \sigma),$$

and projected Push_c / Pop_c commits update A_E exactly as required by E4 for the outer channel c.

(c) Internal refinement. Any internal staged/bundle/join transfer either is projected away by $\pi_{\Sigma,E}$ or projects to a unique corresponding outer-boundary commit. Projected-away internal transfers preserve all outer occupancies $A_E(c, \sigma)$.

(d) No hidden cross-channel disablement. If progress can be blocked by a join, mutual-stall condition, sync-boundary gate, or shared-capacity condition, then that blocking condition appears as ordinary BoundaryReq / ChannelEnabled / ChannelDisabled status at some explicit abstract channel $d \in \text{Chan_elab}(E)$. It is not an additional hidden predicate on an otherwise E4-enabled outer-boundary operation.

(e) WFG visibility. Every proof-relevant blocking point introduced by the elaboration is represented at an explicit abstract boundary of $\text{Sys_B}^{\text{elab}}(E)$, and therefore may be used by Appendix K's Front_P, ChannelDisabled, and WFG definitions, even if its events are projected away from the outer Σ_{DUT} trace.

(f) Combinational well-formedness. Any combinational coupler logic in the elaboration is stateless and acyclic after ε -settling; any feedback or storage needed for correctness is represented by an explicit finite-capacity abstract channel.

When $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}(E)$, all references to $B(\cdot)$, $\text{occ}_\cdot$, BoundaryReq, ChannelEnabled/ChannelDisabled, Front_P, and the Appendix K WFG are interpreted over the explicit channels of $\text{Chan_elab}(E)$, with outer observations recovered only through $\pi_{\Sigma,E}$ and Π_{elab} .

Locality of elaboration

The elaboration package E is constructed locally, per process and per channel boundary. Each elaboration pattern in this appendix (multi-input pipelined-loop staging, sync-boundary epoch gating, R2C combinational coupler, etc.) is determined by the local channel structure of the process at the boundary in question — its number of input channels, its sync-boundary discipline, its pipelining configuration — and does not depend on the structure or elaboration of any other process. Independently chosen per-process elaborations compose into a system-level $\text{Sys_B}^{\text{elab}}(E)$ without further global modeling. Π_{elab} then projects the introduced internal channels back to the outer Σ_{DUT} alphabet on a per-channel basis. In this sense, the elaboration step preserves the per-process compositionality stated in the introduction: it refines each process's abstract boundary, it does not introduce cross-process modeling obligations.

Appendix R – Compact Formal Core for Appendices B–K

R.1 Purpose and scope

This appendix packages the common formal core already used by Appendices B, C, J, and K into a compact definition/lemma/theorem form. Its purpose is only to factor out the shared semantic skeleton and finite-prefix cutpoint view of the formal story. All terminology, assumptions, and proof targets remain those of the main document. In particular, the prescribed source-side semantic target remains exactly the Appendix J, Remark 2 target: $\text{Sys_ref} = \text{Sys_B}$ in the ordinary abstract back-annotated presentation using the case-split channel semantics of E4 ($B(c)=0$ as rendezvous, $B(c)>0$ as cycle-boundary non-fall-through bounded FIFO), and $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$ in the elaborated/back-annotated /

coupler cases. Thus the proofs here do not introduce any proof target separate from the Appendix J target family.

Definition R.1a (Elaboration projection/accounting map Π_{elab}).

In the elaborated case $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$, Π_{elab} denotes the fixed projection/accounting map associated with the chosen elaboration. It maps proof-internal executions, events, and channel-occupancy state of $\text{Sys_B}^{\text{elab}}$ to the chosen outer DUT/testbench-visible boundary view. Π_{elab} has the following roles:

- (1) Trace projection. Π_{elab} preserves the labels and order of the chosen outer Σ_{DUT} -visible boundary events, such as outer $\text{Push_c}(v)$ and $\text{Pop_c}(v)$, and hides or projects away introduced proof-internal staged/bundle/join channel events that are not part of the chosen outer observation boundary.
- (2) Occupancy projection. For each chosen outer Σ_{DUT} -visible abstract channel c , Π_{elab} maps the occupancies of the explicit internal channels introduced by the elaboration to the outer occupancy $\text{occ_c}(\sigma)$ used for the outer E4 interpretation.
- (3) Conservation/accounting. Internal ε -steps and committed transfers across introduced proof-internal abstract channels preserve the projected outer boundary history and projected outer occupancy, except when the elaboration designates such a transfer as corresponding to an outer boundary commit under Π_{elab} . Each projected outer $\text{Push_c}/\text{Pop_c}$ commit updates the projected outer occ_c exactly as required by E4. For bundled or joined work items, Π_{elab} may assign one proof-internal token to one or more outer channels as specified by the elaboration.
- (4) WFG visibility. Projection by Π_{elab} does not make an introduced proof-internal blocking boundary invisible to Appendix K. Any staged/bundle/join channel used for proof-internal blocking, BoundaryReq , $\text{ChannelEnabled}/\text{ChannelDisabled}$, Pending_P , Front_P , or WFG reasoning remains an explicit abstract channel of $\text{Sys_B}^{\text{elab}}$, even if its committed events are projected away from the outer Σ_{DUT} trace.

Thus Π_{elab} witnesses that $\text{Sys_B}^{\text{elab}}$ is a refinement of the chosen outer boundary model: it may expose additional proof-internal abstract channels for Appendix K, but it does not add independent outer DUT-visible behavior or alter the projected outer Push/Pop history and E4 occupancy accounting.

This appendix should therefore be read as a compact companion to the existing appendices, not as a replacement for the full modeling assumptions, witness constructions, fairness/progress premises, or elaboration conventions already stated there.

Appendix B continues to supply the automatic-flush / drain-only blocking discipline, Appendix C the Issue/Commit linkage, Appendix I the witness construction machinery, Appendix J the full execution-level / cutpoint-correspondence results, Appendix L the witness-selection / snooping wrapper where needed, Appendix N the cited progress premises, and Appendix K the wait-for-graph and deadlock-preservation layer.

In particular, Corollary J.1 is the authoritative statement of the cutpoint-correspondence relation $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ used by Appendices J–K. Any cutpoint-correspondence statement in Appendix R is only a compact finite-prefix restatement of Corollary J.1, not a second or independent definition of $\equiv$. If wording in Appendix R appears more abbreviated than Corollary J.1, the Corollary J.1 clauses govern. Similarly, whenever any abbreviated wording in this appendix about Issue, BoundaryReq attribution, or continuously asserted requests could be read more broadly than Appendix C, the full Appendix C Issue/Commit linkage governs.

R.2 Prescribed reference model

Definition R.1 (Prescribed source reference model Sys_ref).

For a fixed design and fixed external stimulus, let Sys_ref be exactly the prescribed source reference model of Appendix J, Remark 2:

- $\text{Sys_ref} = \text{Sys_B}$ in the ordinary abstract back-annotated presentation using the case-split channel semantics of E4: $B(c)=0$ is rendezvous, and $B(c)>0$ is cycle-boundary non-fall-through bounded FIFO.
- $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$ in the elaborated/back-annotated case.

All source-side semantic notions used below are interpreted with respect to this prescribed source reference model.

Remark R.1 (Interpretation at explicit abstract channels).

Whenever $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$, the quantities $B(\cdot)$, $\text{occ_}(t)$, E4, BoundaryReq, ChannelEnabled, ChannelDisabled, and the Appendix K blocking / wait-for-graph machinery are interpreted per explicit abstract channel, including any staged, bundle, or join channels introduced by elaboration. Any conjunctive/join dependency shall therefore be represented only via such explicit abstract channels, not as cross-channel disablement at the outer Σ -visible endpoints.

R.3 Observable alphabet and executions

Definition R.2 (Observable alphabet Σ).

Let Σ be the observable event alphabet consisting of:

- (1) committed message-transfer events $\text{Push_c}(v)$ and $\text{Pop_c}(v)$,
- (2) synchronization events, and
- (3) signal events $\text{Read}(\text{sig}, v)$ and $\text{Write}(\text{sig}, v)$, interpreted as anchored signal events for sequential processes under R2 and as ϵ -fixed-point cycle-bucket events for combinational processes under R2C.

Definition R.3 (ϵ -steps and compact trace notation).

Let ϵ denote internal micro-steps that are not observable at the proof-internal alphabet Σ , including internal staging/hand-off within the concrete realization of a single explicit abstract channel, late direct-input sampling between anchors, and failed non-blocking polls. In elaborated cases $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$, transfers across introduced staged/bundle/join channels are not ϵ merely because Π_{elab} hides them from the outer DUT/testbench-visible alphabet Σ_{DUT} ; if such a channel is an explicit abstract boundary used by Appendix K, its committed Push/Pop transfers are Σ -events for the proof-internal comparison.

A finite execution prefix τ is understood in the same sense as in Appendix J: it carries the inherited cycle partition / per-cycle observable buckets of the execution, together with any ϵ -steps between successive Σ -visible cutpoints. For compact notation one may write a linearization over $(\Sigma \cup \{\epsilon\})$, but only modulo permutation of Σ -events that occur in the same cycle and are not additionally ordered by the document's explicit Σ -visible constraints. Accordingly, $\tau|\Sigma$ denotes the observable projection together with that inherited cycle partition; same-cycle observable events are not assigned any extra order merely by this compact notation.

Definition R.4 (ϵ -quiescent cutpoint).

A state σ is ϵ -quiescent if no further ϵ -step is enabled from σ . For any finite prefix τ , let $\bar{\tau}$ denote a maximal finite ϵ -extension to an ϵ -quiescent endpoint, preserving the same observable cycle partition / bucket structure on $\tau|\Sigma$. The Appendix J / K state-comparison reasoning is always performed at such ϵ -quiescent cutpoints.

R.4 Source order and source-level frontier items

Definition R.5 (Per-process execution-call universe, frontier-item universe, observable projection, and source order).

For each process P , let Q_exec, P denote its execution-level set of dynamic source-level message-call instances for the particular execution / witness under the fixed external stimulus being analyzed. Q_exec, P includes blocking Push/Pop calls, successful non-blocking PushNB/PopNB calls, and failed non-blocking PushNB/PopNB polls.

Let Ω_P denote P 's local dynamic source-level frontier-item universe for that same execution / witness. Thus Ω_P is stimulus-dependent: it contains exactly the local synchronization-call items, signal-action items, and message-operation frontier items that belong to the realized execution being compared, and excludes items on untaken control-flow branches, unentered cases, and unexecuted loop iterations. For sequential processes, signal-action items are positioned by the R2 anchoring rule; for combinational processes, signal-action items are positioned in the observable cycle bucket determined by the R2C ϵ -fixed-point rule. Message-operation frontier items include reached blocking Push/Pop instances, whether pending or committed, and successful non-blocking PushNB/PopNB instances that contribute committed Push_c(v) / Pop_c(v) events. Failed non-blocking polls are ϵ -steps: they are members of Q_exec, P when executed, but they are not members of Ω_P merely because they executed.

Because Q_exec, P is a universe of dynamic message-call instances while Ω_P is a universe of source-level frontier items, their message-operation overlap is not a literal set intersection. Let $MsgOf_P(x)$ be the partial projection from a frontier item $x \in \Omega_P$ to its owning dynamic message-call instance, defined exactly for message-operation frontier items and undefined for pure synchronization or signal-anchor items. Define the message-frontier slice

$$\Omega_msg, P := \{ x \in \Omega_P \mid \exists q \in Q_exec, P : MsgOf_P(x) = q \}.$$

Define the corresponding message-instance slice induced by Ω_P as

$$Q_Q, P := \{ q \in Q_exec, P \mid \exists x \in \Omega_msg, P : MsgOf_P(x) = q \}.$$

Let Σ_P denote the corresponding observable event/label projection: synchronization and signal items contribute their Σ labels when observed, and a message-operation frontier item $x \in \Omega_msg, P$ with $MsgOf_P(x)=q$ contributes the committed Σ -event $m(q)$ only if q commits. Pending blocking message-operation frontier items may therefore be in Ω_P and Ω_msg, P , and their owning message-call instances may be in Q_Q, P , without yet contributing any committed Σ -event. Let $\leq_P$ denote the source-induced partial order on Ω_P , i.e. the order generated by the document's scheduling rules for synchronization calls, signal actions as positioned by R2 or R2C, and message-operation frontier items. The execution-level order constraints E3/E5 use the corresponding source-induced order on Q_exec, P .

Definition R.6 (Done_P, Remain_P, and NextFront_P relative to the fixed witness).

Fix the particular execution / witness under analysis, hence the associated Q_exec, P , Ω_P , Ω_msg, P , Q_Q, P , Σ_P , and $\leq_P$ from Definition R.5. For a state σ occurring as a cutpoint of that compared execution, let

$$Done_P(\sigma) \subseteq \Omega_P$$

be the set of local frontier items already realized by σ . For synchronization and signal items, "realized" means that the corresponding Σ -event has occurred. For a message-operation frontier item $x \in \Omega_msg, P$

with $\text{MsgOf_P}(x)=q$, “realized” means that q has committed and its committed Σ -event $m(q)$ has occurred. A pending issued-but-uncommitted blocking message-operation frontier item x is therefore not in $\text{Done_P}(\sigma)$, even though $\text{BoundaryReq}(x,\sigma)$, $\text{ChannelEnabled}(x,\sigma)$, and $\text{ChannelDisabled}(x,\sigma)$ may be defined at σ , read operation-attributively through $q = \text{MsgOf_P}(x)$. A failed non-blocking poll $q \in Q_{\text{exec},P}$ that induces no frontier item in $\Omega_{\text{msg},P}$ is not considered by Done_P , Remain_P , or NextFront_P , because it is an ϵ -step with no frontier item and no committed Σ -event.

Let

$\text{Remain_P}(\sigma) := \Omega_P \setminus \text{Done_P}(\sigma)$.

Then define the next source-level frontier-item set by

$\text{NextFront_P}(\sigma) := \min_{\leq P}(\text{Remain_P}(\sigma))$.

This is the Appendix J / Lemma S2 notion of the next source-level frontier-item set, interpreted relative to the fixed witness universe Ω_P . It may contain synchronization-call items, signal-anchored action items, and message-operation items. It is a frontier of source-level items, not a set of already-committed Σ -event labels.

Definition R.7 (Message-operation slice of the next frontier).

For the same fixed compared execution / witness, define

$\text{MsgNextFront_P}(\sigma) := \{ x \in \text{NextFront_P}(\sigma) \mid x \in \Omega_{\text{msg},P} \text{ and, for } q = \text{MsgOf_P}(x), q \text{ is defined and } \text{kind}(q) \in \{\text{Push_c}, \text{Pop_c}\} \text{ for some channel } c \}$.

This is only the message-operation frontier-item slice of the candidate next frontier; it is not yet the pending blocking frontier of Appendix B / K.

R.5 Commit, issue, and boundary requests

Definition R.8 (Commit).

For a message transfer at a chosen Σ -visible boundary endpoint, $\text{Commit}(q)$ is the cycle in which an external clocked observer sees both valid and ready high simultaneously at that endpoint. The committed payload is the value seen in that same cycle.

Definition R.9 (Issue).

For a source-level message operation instance q at a chosen Σ -visible boundary endpoint, $\text{Issue}(q)$ is the first cycle in which the calling process begins requesting the transfer corresponding to q at that endpoint. $\text{Issue}(q)$ is an auxiliary scheduler/witness timestamp used for rules such as R4, E3, and E5.

Definition R.10 (Endpoint-owned boundary request).

Fix a Σ -visible endpoint direction. Let $\text{req}(t)$ denote the endpoint-owned boundary request signal in cycle t , namely valid for a Push endpoint and ready for a Pop endpoint. The predicate $\text{BoundaryReq}(q, \sigma)$ records that this endpoint-owned request is asserted for the operation q at state σ . $\text{BoundaryReq}(q, \sigma)$ is operation-attributive: it is true only when the asserted endpoint-owned request at σ is attributed to the specific source-level operation instance q . In particular, if $\text{Issue}(q)$ has not yet occurred at σ , then $\text{BoundaryReq}(q, \sigma)$ is false.

Axiom R.1 (Issue/Commit linkage).

Fix a Σ -visible endpoint direction. For source-level message operation instances on that endpoint direction, the following all hold:

(1) Boundary-request soundness / non-withdrawal.

If q is blocking, then once issued its endpoint-owned request remains asserted until q commits, with stable payload while asserted for Push.

(2) Stable attribution while the same source-level request remains outstanding.

If the request remains asserted across a cycle in which no transfer commits on that endpoint direction, then the continued assertion is attributed to the same outstanding q only so long as the requesting source-level operation remains that same outstanding instance. For blocking Push/Pop, this is the mandatory non-withdrawable case. For non-blocking PushNB/PopNB, continuous assertion of the endpoint request signal does not collapse later executed non-blocking call instances into the same q ; each later executed source-level poll is a distinct $q' \in Q_{\text{exec},P}$ unless the witness explicitly identifies the same still-outstanding source-level request instance.

(3) Back-to-back issuance.

If q_0 and q_1 are same-direction source-level message operation instances, q_0 commits in cycle t , and q_1 is the next such operation issued back-to-back within the same source interval, then $\text{Issue}(q_1) = t + 1$, even if the request signal does not deassert between commits.

(4) Sync-boundary discipline.

If q_0 and q_1 are same-direction source-level message operation instances and $q_0 \in \text{pref}_S(s)$ and $q_1 \in \text{suff}_S(s)$ for a synchronization call s , then $\text{Issue}(q_1)$ occurs strictly after the commit of s . Any request assertion that persists while the process is still pending at s is attributed to the outstanding operation(s) in $\text{pref}_S(s)$, not to issuance of any operation in $\text{suff}_S(s)$.

Remark R.2 (Non-blocking polls).

For non-blocking message passing, a failed poll produces no Σ event and is modeled as an ϵ -step, while a successful poll contributes the corresponding committed $\text{Push}_c(v)$ or $\text{Pop}_c(v)$ event. Each executed PushNB/PopNB call is nevertheless a distinct dynamic source-level instance $q \in Q_{\text{exec},P}$ for its owning process P ; thus repeated failed polls in later loop iterations are distinct q 's even if the endpoint request remains continuously asserted. The ϵ -modeling concerns observability in Σ , not the dynamic-instance identity of the underlying source-level calls.

R.6 Channel enablement

Definition R.11 (ChannelEnabled / ChannelDisabled).

Let q be a source-level message operation instance on channel c , and write $\text{kind}(q) \in \{\text{Push}_c, \text{Pop}_c\}$ for its endpoint direction. At an ϵ -quiescent cutpoint σ , let t_σ denote the cycle of that cutpoint. Define: $\text{ChannelEnabled}(q, \sigma)$ to mean that $\text{BoundaryReq}(q, \sigma)$ holds and that the channel-side condition required for q to commit is satisfied after combinational settling at that cutpoint, and $\text{ChannelDisabled}(q, \sigma)$ to mean that $\text{BoundaryReq}(q, \sigma)$ holds but $\text{ChannelEnabled}(q, \sigma)$ does not.

Definition R.12 (Buffered channels).

If $B(c) > 0$ and q is a source-level message operation instance on c , then the buffered-channel enabling condition is:

- $\text{ChannelEnabled}(q, \sigma) \Leftrightarrow \text{BoundaryReq}(q, \sigma) \wedge \text{occ}_c(\sigma) < B(c)$, when $\text{kind}(q) = \text{Push}_c$
- $\text{ChannelEnabled}(q, \sigma) \Leftrightarrow \text{BoundaryReq}(q, \sigma) \wedge \text{occ}_c(\sigma) > 0$, when $\text{kind}(q) = \text{Pop}_c$

Thus, if q is a buffered Push_c operation that is channel-disabled, then $\text{BoundaryReq}(q, \sigma)$ holds and $\text{occ}_c(\sigma) = B(c)$; and if q is a buffered Pop_c operation that is channel-disabled, then $\text{BoundaryReq}(q, \sigma)$ holds and $\text{occ}_c(\sigma) = 0$.

Definition R.13 (Rendezvous channels).

If $B(c) = 0$ and q is a source-level message operation instance on c , then the rendezvous enabling condition is:

$\text{ChannelEnabled}(q, \sigma) \Leftrightarrow \text{BoundaryReq}(q, \sigma) \wedge (\text{the complementary endpoint request on } c \text{ is asserted at } \sigma)$

σ).

Equivalently:

- if $\text{kind}(q) = \text{Push_c}$, then

$\text{ChannelEnabled}(q, \sigma) \Leftrightarrow \text{BoundaryReq}(q, \sigma) \wedge$ (the complementary Pop_c endpoint request is asserted at σ)

- if $\text{kind}(q) = \text{Pop_c}$, then

$\text{ChannelEnabled}(q, \sigma) \Leftrightarrow \text{BoundaryReq}(q, \sigma) \wedge$ (the complementary Push_c endpoint request is asserted at σ)

Hence, if a rendezvous action q is channel-disabled, its own BoundaryReq holds but the complementary endpoint is not simultaneously requesting the matching partner action at that cutpoint.

R.7 Pending blocking frontier

Definition R.14 (Pending blocking operations).

Fix an ε -quiescent state σ of process P within the current interval $I_P(\sigma)$ between the adjacent synchronization calls that bracket σ in P 's current execution. Define

$\text{Pending_P}(\sigma) := \{ x \mid x \in \Omega_{\text{msg}, P} \text{ is a blocking source-level message-operation frontier item in that same interval } I_P(\sigma), \text{ and for } q = \text{MsgOf_P}(x), q \text{ is defined, Issue}(q) \text{ has occurred, and Commit}(q) \text{ has not yet occurred in } \sigma \}$.

By Appendix C's Issue/Commit linkage together with the definition of BoundaryReq , each member x of $\text{Pending_P}(\sigma)$ has its endpoint-owned request asserted at the cutpoint, read operation-attributively through its owning dynamic message-call instance $q = \text{MsgOf_P}(x)$.

Definition R.15 (Pending blocking frontier $\text{Front_P}(\sigma)$).

Define

$\text{Front_P}(\sigma) := \min_{\leq P}(\text{Pending_P}(\sigma))$

If several $\leq_P$ -minimal pending blocking message-operation frontier items are simultaneously outstanding, they form a frontier. This is the Appendix B / K notion of the pending blocking frontier (or minimal pending blocking frontier). It is distinct from $\text{NextFront_P}(\sigma)$, which is the broader source-level frontier-item set over Ω_P .

R.8 Automatic flush / drain-only blocking discipline

Definition R.16 (Automatic flush).

A pipelined implementation satisfies the automatic-flush discipline if, whenever $\text{Front_P}(\sigma)$ is non-empty and every frontier item $x \in \text{Front_P}(\sigma)$ is channel-disabled after ε -settling, the following all hold:

(1) Block point.

P is blocked on message passing at $\text{Front_P}(\sigma)$.

(2) No new later work.

While $\text{Front_P}(\sigma)$ remains non-empty and fully disabled, no new later blocking message-operation frontier item $y \in \Omega_{\text{msg}, P}$ is issued, where "later" means that, for some $x \in \text{Front_P}(\sigma)$, $x \leq_P y$ and $x \neq y$, with issue understood through the owning message instance $q_y = \text{MsgOf_P}(y)$.

(3) No withdrawal.

Already-asserted blocking requests are not withdrawn before the owning message instances commit.

(4) Frontier-minimality.

An already-asserted blocking request whose frontier item is not in $\text{Front_P}(\sigma)$ is not treated as a wait-for source unless and until that frontier item later becomes frontier-minimal.

(5) Drain-only downstream progress.

Work already past the blocked frontier may drain and commit when channel-enabled, but no new work advances past the blocked frontier while that frontier remains fully disabled.

(6) Sync-boundary capacity withdrawal — elaborated-boundary interpretation.

While a process is pending at an explicit synchronization call s , producer-facing availability for any back-annotated capacity belonging only to $\text{suff}_S(s)$ is withheld until s commits; work already accepted before s may still drain. For the Sys_ref proof model, this withdrawal is not an additional hidden enablement predicate on an otherwise ordinary $E4$ channel. It is represented only by choosing $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$ with explicit sync-boundary / epoch-gate abstract channels, or equivalent explicit staged realization structure, so that the refusal appears as ordinary ChannelDisabled behavior at an explicit abstract boundary.

Remark R.3 (ALL disabled $\Rightarrow$ stall).

The document’s intended policy is exactly the “ALL disabled $\Rightarrow$ stall” interpretation: the process stalls only when none of the frontier items in $\text{Front_P}(\sigma)$ is channel-enabled. Downstream drain is compatible with that stall provided no new later work is issued past the blocked frontier.

R.9 Observable compatibility and cutpoint correspondence

Definition R.17 (System-level observable compatibility).

For a witness prefix τ_{ref} of Sys_ref and a post-HLS prefix τ_{post} of RTL_B , define

$$\tau_{\text{ref}} \approx \tau_{\text{post}} :\Leftrightarrow E1 \wedge E2 \wedge E3 \wedge E4 \wedge E5$$

This is an ordered compatibility predicate, not a mathematical equivalence relation. The left argument supplies the Sys_ref witness prefix, and the right argument supplies the RTL_B post-HLS prefix constrained by $E1$ – $E5$. This appendix treats $E1$ – $E5$ as primitive named conjuncts, exactly as used by Appendix J.

Definition R.18 (Cutpoint correspondence $\equiv$).

This definition is not a separate or independent definition of $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ competing with Corollary J.1. It is the Appendix R restatement of the authoritative cutpoint-correspondence relation defined in Corollary J.1. Clauses (1)–(5) below correspond to Corollary J.1’s clauses (a)–(e) as follows: (1) $\leftrightarrow$ (a), (2a)–(2c) $\leftrightarrow$ (b), (3) $\leftrightarrow$ (c), (4) $\leftrightarrow$ (d), and (5) $\leftrightarrow$ (e). In case of apparent wording differences, Corollary J.1 governs.

Let σ_{ref} and σ_{post} be ϵ -quiescent terminal states of matched prefixes. All occurrences below of Ω_P , $\Omega_{\text{msg},P}$, $Q_{\Omega,P}$, $\leq_P$, NextFront_P , $\text{BlockingMsgNextFront}_P$, Pending_P , and Front_P are interpreted relative to the same fixed compared witness and its shared per-process source-level frontier-item universe, as in Lemma S2 / Corollary J.1. Thus the set equalities below are typed equalities over a common witness-relative frontier-item universe, not comparisons between independently generated dynamic-call universes.

Write

$$\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$$

iff all of the following hold:

(1) For every process P ,

$$\text{NextFront}_P(\sigma_{\text{ref}}) = \text{NextFront}_P(\sigma_{\text{post}}).$$

(2) For every process P , the Σ -relevant source-level facts for that common source-level frontier-item set agree across the two cutpoints, in the following typed sense; clause (5) separately records the additional pending-request facts needed for Appendix K drain-only reasoning:

(a) for every x in the common blocking message-operation-item slice

$$\text{BlockingMsgNextFront}_P(\sigma_{\text{ref}}) = \text{BlockingMsgNextFront}_P(\sigma_{\text{post}}),$$

where

$\text{BlockingMsgNextFront}_P(\sigma) \triangleq \{ x \in \text{NextFront}_P(\sigma) \mid x \in \Omega_{\text{msg},P} \text{ and, for } q = \text{MsgOf}_P(x), q \text{ is defined and } q \text{ is a blocking source-level message-operation instance with } \text{kind}(q) \in \{\text{Push}_c, \text{Pop}_c\} \text{ for some channel } c \},$

the operation-attributive boundary-request predicate $\text{BoundaryReq}(x, \cdot)$ agrees, read through the owning message instance $q = \text{MsgOf}_P(x)$;

(b) for every x in the common set NextFront_P , every source-level control predicate $\text{Pred}_x(\cdot)$ used to determine whether x is the next selected source-level frontier item agrees; and

(c) for every x in the common set NextFront_P , every source-level value / payload expression needed to determine x 's eventual Σ -label, if any, agrees.

Equivalently, σ_{ref} and the source-level projection of σ_{post} agree on all Σ -relevant source variables and request-attribution facts read by BoundaryReq for the common blocking message-operation-item slice $\text{BlockingMsgNextFront}_P$, by the next-item selection predicates for the common source-level frontier-item set, and by the payload/value expressions for that same common frontier. Successful non-blocking $\text{PushNB}/\text{PopNB}$ frontier items may contribute committed $\text{Push}_c/\text{Pop}_c$ Σ -labels, but they are not required by clause (2a) to have persistent BoundaryReq agreement at an ε -quiescent cutpoint; their selected committed-transfer labels and values are covered by clauses (2b) and (2c) together with the fixed witness.

(3) For each buffered abstract channel, the E4-relevant abstract FIFO state agrees, equivalently the empty/full status and the logical head information determined by the matched Push/Pop history agree.

(4) For each point-to-point rendezvous abstract channel c used in the Appendix K internal message-passing boundary / WFG analysis, the raw endpoint-request predicates agree across the two cutpoints:

$\text{Req}_{\text{prod}}(c, \sigma_{\text{ref}}) = \text{Req}_{\text{prod}}(c, \sigma_{\text{post}})$

and

$\text{Req}_{\text{cons}}(c, \sigma_{\text{ref}}) = \text{Req}_{\text{cons}}(c, \sigma_{\text{post}}).$

This rendezvous clause is an explicit component of the cutpoint-correspondence relation $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$. It is intentionally not derived from NextFront_P agreement, from clause (2)'s agreement on the common next-frontier slice, or from membership in $\text{Front}_P(\sigma)$. The reason is that Appendix B permits already-asserted non-frontier blocking requests to persist as protocol state while an earlier pending blocker remains frontier-minimal. Such raw endpoint-request state may be needed directly by the rendezvous enabling condition even when the asserted request is not itself a current frontier member. Clause (4) therefore records the required raw producer-side and consumer-side endpoint-request equality as part of the preserved cutpoint state.

(5) For Appendix K drain-only reasoning, already-issued blocking request state agrees at the chosen abstract boundaries. More precisely, for every process P and every blocking message-operation frontier item $x \in \Omega_{\text{msg},P}$ in P 's current interval between adjacent synchronization calls, with owning dynamic message-call instance $q = \text{MsgOf}_P(x)$:

$x \in \text{Pending}_P(\sigma_{\text{ref}})$ iff $x \in \text{Pending}_P(\sigma_{\text{post}}).$

For every such common pending frontier item x :

- the endpoint-owned boundary request is attributed to $q = \text{MsgOf}_P(x)$ on one side iff it is attributed to q on the other side;
- $\text{BoundaryReq}(x, \sigma_{\text{ref}}) = \text{BoundaryReq}(x, \sigma_{\text{post}})$; and
- $\text{ChannelEnabled}(x, \sigma_{\text{ref}}) = \text{ChannelEnabled}(x, \sigma_{\text{post}})$, equivalently $\text{ChannelDisabled}(x, \sigma_{\text{ref}}) = \text{ChannelDisabled}(x, \sigma_{\text{post}}).$

For $B(c) > 0$ channels, this enablement agreement follows from the common $B(c)$ and the logical occupancy/head-state agreement of clause (3). For $B(c) = 0$ rendezvous channels, it follows from the raw producer/consumer endpoint-request agreement of clause (4). In the elaborated case $\text{Sys_ref} = \text{Sys_B}^{\text{elab}}$, all of these Pending, BoundaryReq, ChannelEnabled, and ChannelDisabled facts are interpreted at the explicit abstract channels of $\text{Sys_B}^{\text{elab}}$.

R.10 Prefix-matching theorem

Theorem R.1 (Finite-prefix witness consequence of Theorem J.1)

Fix a finite post-HLS execution prefix $\tau_{\text{post}} \in \text{Exec_post}$ of RTL_B under a fixed external stimulus, where Exec_post is exactly the Appendix J execution-set scope under the same witness / fairness / progress premises used there. Then there exists a finite execution prefix τ_{ref} of Sys_ref under that same stimulus such that

$$\tau_{\text{ref}} \approx \tau_{\text{post}}$$

This theorem is a compact finite-prefix consequence of Appendix J's full execution-level result, not a replacement for that full execution-level statement. In particular, the controlling hypotheses are exactly Appendix J's execution-set scope conditions together with the relevant Appendix I / Appendix L witness machinery and the cited fairness/progress premises. Appendix K uses only the existence of such a matching source-side witness at the compared cutpoint, not uniqueness of that witness.

Corollary R.1 (Cutpoint correspondence; compact finite-prefix form of Corollary J.1).

This corollary is not a second definition of $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$. It is only the compact finite-prefix form of the authoritative cutpoint-correspondence relation defined in Corollary J.1. The clauses summarized below correspond to the clauses of Corollary J.1(2), including the explicit rendezvous endpoint-request clause. In case of apparent wording differences, Corollary J.1 governs.

Let $\tau_{\text{post}} \in \text{Exec_post}$ be as in Theorem R.1. Let ρ_{post} be the ε -quiescent RTL_B terminal cutpoint obtained from τ_{post} under the same ε -normalization convention used in Appendix J, and let σ_{ref} be the ε -quiescent terminal state of any witness prefix τ_{ref} supplied by Theorem R.1, under the same $\text{J.Abs}/\text{J.AbsConf}$ cutpoint-abstraction hypotheses used by Corollary J.1. Then

$$\sigma_{\text{ref}} \equiv \rho_{\text{post}},$$

where " $\equiv$ " is the compact notation for the Corollary J.1 source-slice correspondence induced by $\rho_{\text{post}} \Downarrow_{\{\text{Abs}, \text{J}, \text{w}\}} \sigma_{\text{ref}}$, not equality of arbitrary RTL microstate.

Equivalently, under exactly the same Appendix J execution-set scope, ε -normalization, and state-correspondence assumptions used to obtain the witness, matched prefixes satisfy the Corollary J.1 cutpoint-correspondence clauses: they yield the same next source-level frontier-item set over Ω_{P} ; the same operation-attributive BoundaryReq values on the common blocking message-operation-item slice $\text{BlockingMsgNextFront_P}$ of that frontier; the same source-level next-item selection facts and Σ -label-determining values, if any, for the common frontier; the same E4-visible abstract FIFO state at the compared ε -quiescent cutpoints; and, for point-to-point rendezvous channels included in the Appendix K internal message-passing boundary / WFG analysis, the same raw producer-side and consumer-side endpoint-request predicates at those compared ε -quiescent cutpoints. Successful non-blocking PushNB/PopNB frontier items may contribute committed Push_c/Pop_c Σ -labels, but they are not part of the pending blocking frontier and do not require persistent BoundaryReq agreement under this compact cutpoint restatement.

R.11 Explicit frontier-classification bridge

Definition R.19 (Derived blocking-frontier slice at ϵ -quiescent cutpoints).

At an ϵ -quiescent cutpoint σ and for a process P , define the asserted blocking message-operation-item slice of the next source-level frontier-item set by

$$\text{FrontFromNext_P}(\sigma) := \{ x \in \text{BlockingMsgNextFront_P}(\sigma) \mid \text{BoundaryReq}(x, \sigma) \},$$

where

$\text{BlockingMsgNextFront_P}(\sigma) \triangleq \{ x \in \text{NextFront_P}(\sigma) \mid x \in \Omega_{\text{msg},P} \text{ and, for } q = \text{MsgOf_P}(x), q \text{ is defined and } q \text{ is a blocking source-level message-operation instance with } \text{kind}(q) \in \{\text{Push_c}, \text{Pop_c}\} \text{ for some channel } c \}.$

Here $\text{BoundaryReq}(x, \sigma)$ is read operation-attributively for the specific source-level blocking message-operation frontier item x , through its owning dynamic message-call instance $q = \text{MsgOf_P}(x)$, exactly in the Appendix C sense: the asserted endpoint-owned request at the cutpoint is attributed to x only if q is the currently outstanding requesting source-level operation instance on that endpoint direction. For blocking Push/Pop, that attribution cannot change before commit. Non-blocking PushNB/PopNB call instances are excluded from $\text{BlockingMsgNextFront_P}$ unless represented by a frontier item in $\Omega_{\text{msg},P}$ for non-WFG committed-transfer reasoning; successful non-blocking calls may contribute Push_c/Pop_c Σ -labels, and failed polls are ϵ , but neither creates a pending blocking frontier member for WFG purposes. This definition is over source-level message-operation frontier items in $\Omega_{\text{msg},P} \subseteq \Omega_P$, not over the message-instance slice $Q_{\Omega,P}$ itself and not over already-committed Σ -event labels.

Remark R.4 (derived bridge, not extra premise).

Corollary R.1 aligns NextFront_P and the relevant operation-attributive BoundaryReq values only on the common blocking message-operation-item slice $\text{BlockingMsgNextFront_P}$ of that frontier. No BoundaryReq predicate is defined or required for non-message frontier items, and successful non-blocking frontier items do not create pending blocking frontier members. Appendix K.2.2 (Lemma K.0) then derives, from the Appendix B drain-only blocking discipline and the Appendix C Issue/Commit linkage, that this asserted blocking message-operation-item slice is exactly the pending blocking frontier.

R.12 Front / NextFront classification lemma

Lemma R.1 (Front/NextFront classification; compact restatement of Lemma K.0).

Fix an ϵ -quiescent state σ of either Sys_ref or RTL_B , and a process P . Then

$$\text{Front_P}(\sigma) = \text{FrontFromNext_P}(\sigma) = \{ x \in \text{BlockingMsgNextFront_P}(\sigma) \mid \text{BoundaryReq}(x, \sigma) \}.$$

Consequently, if $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$, then

$$\text{Front_P}(\sigma_{\text{ref}}) = \text{Front_P}(\sigma_{\text{post}}),$$

and $\text{BoundaryReq}(x, \cdot)$ agrees for every blocking message-operation frontier item

$$x \in \text{Front_P}(\sigma_{\text{ref}}) = \text{Front_P}(\sigma_{\text{post}}), \text{ read operation-attributively through } q = \text{MsgOf_P}(x).$$

This is a classification of the current pending blocking frontier only. It does not say that later same-interval requests cannot already have issued under pipelined overlap or downstream drain. Such already-issued later requests may persist as non-frontier protocol state under Appendix B's no-withdrawal and drain-only rules; their frontier items contribute to Front_P only if and when they later become frontier-minimal pending blocking message-operation frontier items.

Corollary R.1a (Rendezvous endpoint-request agreement; compact restatement of Corollary K.0a).

For a point-to-point rendezvous channel c with $B(c)=0$, define $\text{Req_prod}(c,\sigma)$ to mean that the producer-side boundary request on c is asserted at the ϵ -quiescent cutpoint σ , and $\text{Req_cons}(c,\sigma)$ to mean that the consumer-side boundary request on c is asserted at σ . Then, for any corresponding ϵ -quiescent cutpoints $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$,

$$\text{Req_prod}(c,\sigma_{\text{ref}}) = \text{Req_prod}(c,\sigma_{\text{post}})$$

and

$$\text{Req_cons}(c,\sigma_{\text{ref}}) = \text{Req_cons}(c,\sigma_{\text{post}}).$$

This is a raw endpoint-request agreement fact only; it does not identify an asserted rendezvous request with frontier membership.

R.13 Wait-for graph refinement

Definition R.20 (Wait-for graph).

At an ϵ -quiescent cutpoint σ , define the wait-for graph $\text{WFG}(\sigma)$ exactly as in Appendix K: its vertices are the modeled processes, and its directed edges are induced from the frontier members $\text{Front_P}(\sigma)$ by the corresponding channel-disabled dependencies on internal message-passing channels only. Equivalently, a directed edge $P \rightarrow Q$ is present when some frontier item $x \in \text{Front_P}(\sigma)$, with owning message instance $q = \text{MsgOf_P}(x)$, is channel-disabled at the chosen boundary and the unique complementary endpoint needed to enable q belongs to process Q .

Here “internal” means that both endpoints of the channel are modeled processes of Sys_ref / RTL_B . Channels whose complementary endpoint is the external environment/testbench (the DUT boundary) are excluded from the WFG and from the internal message-passing deadlock notion used in Appendix K. Buffered and rendezvous channels are both included, with $B(c)$, $\text{occ_c}(\sigma)$, BoundaryReq , ChannelEnabled , and ChannelDisabled interpreted at the chosen ϵ -quiescent cutpoint on the chosen abstract channels of Sys_ref .

Lemma R.2 (Dependency refinement; compact restatement of Lemma K.2).

Let σ_{ref} and σ_{post} be corresponding ϵ -quiescent cutpoints with $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$.

Then

$$\text{WFG_ref}(\sigma_{\text{ref}}) = \text{WFG_post}(\sigma_{\text{post}}).$$

Equivalently, for any processes P, Q , there is a wait-for edge $P \rightarrow Q$ in the post-HLS wait-for graph iff there is a wait-for edge $P \rightarrow Q$ in the source-reference wait-for graph. The proof uses Corollary R.1 for NextFront_P agreement, BoundaryReq agreement on the common blocking message-operation-item slice $\text{BlockingMsgNextFront_P}$, abstract FIFO-state agreement for buffered channels, and raw rendezvous endpoint-request agreement for point-to-point rendezvous channels; Lemma R.1 then lifts the next-frontier blocking message-operation-item agreement to Front_P . Corollary R.1a supplies the rendezvous endpoint-request predicate directly, without identifying asserted complementary requests with frontier membership.

R.14 Deadlock preservation

Theorem R.2 (Cutpoint-level closed-cycle preservation and one-way drain-closure transfer; local consequence of Theorem K.1).

Let σ_{ref} and σ_{post} be corresponding ε -quiescent cutpoints with $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$, satisfying the Appendix K assumptions — including the ε -normalization requirement and the broader witness / fairness / progress premises inherited from the Appendix I / J / L / N stack used to obtain the compared cutpoints. Then

WFG_post(σ_{post}) contains a closed internal message-passing wait-for cycle
iff
WFG_ref(σ_{ref}) contains a closed internal message-passing wait-for cycle.

Moreover, for any non-empty set D of processes forming such a closed internal wait-for cycle, the drain-closed property of K.1 transfers in the post-to-reference direction already established by Lemma K.2a:

if σ_{post} is drain-closed for D , then σ_{ref} is drain-closed for D .

Thus, for the deadlock-preservation use case, a post-HLS cutpoint satisfying the full K.1 closed-cycle-plus-drain-closure condition maps to a corresponding source-reference cutpoint satisfying the same K.1 condition. No converse drain-closure transfer is claimed here.

This is the local cutpoint-preservation conclusion used inside Appendix K's broader liveness/deadlock argument. The full global liveness/deadlock theorem remains Theorem K.1. The present appendix records the preserved closed-cycle consequence at corresponding ε -quiescent cutpoints and, when the full K.1 deadlock condition is being used for a post-HLS cutpoint, records the one-way transfer of drain-closure for the same process set D from σ_{post} to σ_{ref} . The result is stated relative to the prescribed source reference model Sys_{ref} and uses the derived frontier-classification result of Lemma R.1, the direct rendezvous endpoint-request agreement of Corollary R.1a, and the same outstanding-request/channel-enable correspondence used by Lemma K.2a, rather than any claim that an asserted rendezvous request must be frontier-minimal or any extra frontier-classification precondition. In the elaborated multi-input / coupler cases, that source-side target is $\text{Sys}_B^{\text{elab}}$, not merely the raw outer-boundary Sys_B .

R.15 Summary of dependency structure

For convenient reference, the compact dependency chain relevant to this appendix's condensed presentation is:

- (1) Appendix B defines $\text{Front}_P(\sigma)$ and the automatic-flush / drain-only blocking discipline.
- (2) Appendix C defines Commit, Issue, and the Issue/Commit linkage that makes pending blocking operations well-defined at Σ -visible boundaries.
- (3) Appendix G states the system-level observable-compatibility rules E1–E5 and the high-level functional-indistinguishability implication on which the later witness/correspondence stack relies.
- (4) Appendix I supplies the witness-construction machinery used to relate post-HLS behavior to the prescribed source reference model.
- (5) Appendix J proves the full execution-level theorem for Sys_{ref} and, from that theorem together with the required ε -normalization / state-correspondence assumptions, yields the cutpoint correspondence $\sigma_{\text{ref}} \equiv \sigma_{\text{post}}$ used here in compact finite-prefix form.
- (6) Appendix Q supplies the elaboration patterns for the multi-input / coupler cases, so that the relevant

source-side proof target and all $B(\cdot) / \text{occ}_\cdot(t) / \text{BoundaryReq} / \text{ChannelEnabled} / \text{ChannelDisabled} / \text{WFG}$ notions are interpreted on the explicit abstract channels of $\text{Sys_B}^{\text{elab}}$ rather than merely on the raw outer-boundary Sys_B .

(7) Appendix L provides the witness-selection / snooping wrapper where a deterministic or latency-aligned source-side witness is needed.

(8) Appendix N supplies the cited progress premises relied upon by the surrounding liveness/deadlock argument.

(9) Appendix K.2.2 proves the structural bridge from the asserted blocking message-operation slice $\text{BlockingMsgNextFront_P}$ to Front_P :

$\text{Front_P}(\sigma) = \{ x \in \text{BlockingMsgNextFront_P}(\sigma) \mid \text{BoundaryReq}(x, \sigma) \}$.

This bridge is intentionally not stated for the broader MsgNextFront_P slice, because MsgNextFront_P may include message-operation frontier items that are not pending blocking WFG causes, such as successful non-blocking transfer items. The rendezvous endpoint-request agreement used in wait-for refinement is supplied separately by the corresponding-cutpoint relation of Corollary J.1, with Corollary R.1 serving only as its compact finite-prefix restatement, rather than by any frontier-membership localization.

(10) Appendix K then refines wait-for edges at corresponding $\text{RTL_B} / \text{Sys_ref}$ cutpoints, preserves the witness-relative closed internal message-passing WFG cycle needed for the K.1 contradiction, and invokes Lemma K.2b to bridge any such RTL-matched overlapped Sys_ref deadlock to a deadlock reachable under $A5$'s conservative serial-blocking source semantics.

Appendix S – Lean Proof Strategy Document

The following document provides a strategy proposal for an automated Lean proof to certify all the formal material in this document:

https://github.com/Stuart-Swan/Matchlib-Examples-Kit-For-Accellera-Synthesis-WG/blob/master/matchlib_examples/doc/Lean_proof_strategy.pdf