

Scan-Pair Edge Model for Stationary Lidar Map Solving

Stuart Johnson and ChatGPT

May 25, 2026

1 Purpose

This note describes the mathematical model used to estimate the relative planar transform between two lidar scans. The resulting relative pose and covariance may be used as a factor-graph edge, for example as a GTSAM `BetweenFactor<Pose2>`.

The method is intended for an offline map-solving pipeline. Each station consists of one or more lidar scans acquired while the robot is stationary. The goal is to estimate relative transformations between scan bundles and then optimize the resulting pose graph.

2 Scan Bundles and Relative Pose

Let station i provide a target scan bundle

$$\mathcal{Q}_i = \{q_j\}_{j=1}^{M_i}, \quad (1)$$

where each $q_j \in \mathbb{R}^2$ is a lidar endpoint represented in the local frame of station i .

Let station k provide a source scan bundle

$$\mathcal{P}_k = \{p_l\}_{l=1}^{N_k}, \quad (2)$$

where each $p_l \in \mathbb{R}^2$ is represented in the local frame of station k .

The relative pose from station k into station i is

$$T_{ik} = (x, y, \theta) \in SE(2). \quad (3)$$

A source point transformed into the target frame is

$$\tilde{p}_l(T_{ik}) = R(\theta)p_l + t, \quad (4)$$

where

$$R(\theta) = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix}, \quad t = \begin{bmatrix} x \\ y \end{bmatrix}. \quad (5)$$

3 k-Nearest-Neighbor Gaussian Mixture Model

For each transformed source point $\tilde{p}_l$, the K nearest target points in $\mathcal{Q}_i$ are found using a KD-tree. Let this neighbor set be

$$\mathcal{N}_K(l; T_{ik}) \subset \{1, \dots, M_i\}. \quad (6)$$

The target scan bundle is modeled locally as a Gaussian mixture. Thus, the likelihood of transformed source point $\tilde{p}_l$ is approximated by

$$P_l(T_{ik}) = \sum_{j \in \mathcal{N}_K(l; T_{ik})} \alpha_j \mathcal{N}(\tilde{p}_l(T_{ik}); q_j, \Sigma_{lj}). \quad (7)$$

Equal mixture weights are used:

$$\alpha_j = \frac{1}{K}. \quad (8)$$

4 Isotropic Point Uncertainty Model

Each lidar endpoint is assigned an isotropic 2D covariance. For a point measured at range r , define

$$\sigma^2(r) = \sigma_r(r)^2 + (r\sigma_\theta)^2, \quad (9)$$

where $\sigma_r(r)$ is the range uncertainty model and σ_θ is the angular uncertainty. For a transformed source point p_l and target point q_j , the combined variance is

$$\sigma_{lj}^2 = \sigma_p^2(r_l) + \sigma_q^2(r_j), \quad (10)$$

where r_l and r_j are the original lidar ranges associated with points p_l and q_j . The Gaussian covariance is then

$$\Sigma_{lj} = \sigma_{lj}^2 I_2. \quad (11)$$

This model assumes independent Gaussian uncertainty in the source and target scan endpoints. It ignores anisotropic endpoint covariance, incidence-angle effects, visibility, occlusion, and spatial correlation between scan points.

5 Negative Log Likelihood Objective

For one source point and one target neighbor, define the squared residual

$$d_{lj}^2(T_{ik}) = \|\tilde{p}_l(T_{ik}) - q_j\|^2. \quad (12)$$

For the isotropic covariance model, the Gaussian argument is

$$E_{lj}(T_{ik}) = \frac{d_{lj}^2(T_{ik})}{2\sigma_{lj}^2}. \quad (13)$$

The normalized 2D Gaussian component is

$$\mathcal{N}(\tilde{p}_l; q_j, \sigma_{lj}^2 I_2) = \frac{1}{2\pi\sigma_{lj}^2} \exp(-E_{lj}). \quad (14)$$

Therefore, the log contribution of neighbor j is

$$b_{lj}(T_{ik}) = \log \alpha_j - \log(2\pi\sigma_{lj}^2) - E_{lj}(T_{ik}). \quad (15)$$

The negative log likelihood contribution of source point p_l is

$$J_l(T_{ik}) = -\text{logsumexp}_{j \in \mathcal{N}_K(l; T_{ik})} (b_{lj}(T_{ik})). \quad (16)$$

The total scan-pair objective is

$$J(T_{ik}) = \sum_{l=1}^{N_k} J_l(T_{ik}). \quad (17)$$

`logsumexp` is evaluated using a numerically stable form.

6 Relative Pose Estimate

The estimated relative pose is obtained by minimizing the scan-pair objective:

$$\hat{T}_{ik} = \arg \min_{T_{ik} \in SE(2)} J(T_{ik}). \quad (18)$$

The optimization uses a coarse-to-fine search over (x, y, θ) , followed by local refinement. The search region is bounded by a maximum spatial translation value of T_{ik} .

7 Covariance Approximation

Near the optimum, the objective is approximated locally as quadratic:

$$J(T) \approx J(\hat{T}) + \frac{1}{2} \delta^T H \delta, \quad (19)$$

where

$$\delta = \begin{bmatrix} \delta x \\ \delta y \\ \delta \theta \end{bmatrix} \quad (20)$$

represents a small perturbation around $\hat{T}$, and

$$H = \nabla^2 J(\hat{T}) \quad (21)$$

is the Hessian of the negative log likelihood. The relative-pose covariance is approximated by

$$\Sigma_{ik} \approx H^{-1}, \quad (22)$$

provided H is positive definite and well conditioned. The Hessian is estimated numerically using centered finite differences of $J(x, y, \theta)$ evaluated near the optimum.

8 Factor-Graph Edge

The scan-pair front-end returns:

$$\hat{T}_{ik}, \quad \Sigma_{ik}, \quad J(\hat{T}_{ik}), \quad (23)$$

plus diagnostic quantities such as match score, Hessian condition number, neighbor residual statistics, and bidirectional consistency if available.

For a pose graph with station poses X_i and X_k , this becomes a relative-pose constraint:

$$X_k \approx X_i \hat{T}_{ik}. \quad (24)$$

In GTSAM, this may be represented as a **BetweenFactor<Pose2>** with measurement $\hat{T}_{ik}$ and noise model derived from Σ_{ik} .

9 Bidirectional Consistency Check

The scan-pair objective is generally directional because $\mathcal{Q}_i$ is treated as the target GMM and $\mathcal{P}_k$ as the transformed source set. A useful diagnostic is to also estimate $\hat{T}_{ki}$ by reversing the roles of the scan bundles.

A useful consistency diagnostic is obtained by estimating the relative transform in both directions:

$$\hat{T}_{ik}, \quad \hat{T}_{ki}. \quad (25)$$

Ideally, these estimates should satisfy

$$\hat{T}_{ki} \approx \hat{T}_{ik}^{-1}. \quad (26)$$

Define the residual transform

$$T_{\text{err}} = \hat{T}_{ik} \hat{T}_{ki}. \quad (27)$$

If the two estimates are perfectly consistent, then

$$T_{\text{err}} = I, \quad (28)$$

where I is the identity element of $SE(2)$.

A local vector representation of the residual may be obtained using the Lie-group logarithm map:

$$e_{\text{bi}} = \text{Log}(T_{\text{err}}) \in \mathbb{R}^3. \quad (29)$$

The vector e_{bi} approximately represents translational and rotational inconsistency:

$$e_{\text{bi}} \approx \begin{bmatrix} \delta x \\ \delta y \\ \delta \theta \end{bmatrix}. \quad (30)$$

Large values of $\|e_{\text{bi}}\|$ indicate that the scan-pair registration is weak, ambiguous, or inconsistent. This is computed and provided as an edge metric.