

CSS-I

Manas Jyoti Das, PhD
Computer Science
SIUE

Cascading style sheet

- Latest version is v3
- CSS instruct the browser on how to style the HTML page

Styles

index.html

```
<!DOCTYPE html>
<html>
<head>
  <title>My Webpage</title>
  <link rel="stylesheet" type="text/css" href="style.css">
</head>
<body>
  <h1>Welcome to SIUE</h1>
  <p>This is a simple HTML webpage.</p>
  <p>You can add more content here.</p>
</body>
</html>
```

style.css

```
h1 {
  color: #007BFF; /* Change the color to blue */
  font-size: 24px; /* Change the font size to 24 pixels */
}
```

Styles

Different text styling options

```
h1 {  
  color: #007BFF; /* Change the color to blue */  
  font-size: 48px; /* Change the font size to 24 pixels */  
  text-align: center;  
  text-transform: capitalize;  
}
```

Working with id

index.html

```
<!DOCTYPE html>
<html>
<head>
  <title>My Webpage</title>
  <link rel="stylesheet" type="text/css" href="style.css">
</head>
<body>
  <h2 id="top_header">Welcome to SIUE</h2>
  <p id="HGHDJ">This is a simple HTML webpage.</p>
  <p>You can add more content here.</p>
</body>
</html>
```

style.css

```
#top_header {
  color: #2a7fda; /* Change the color to blue */
  font-size: 48px; /* Change the font size to 24 pixels */
  text-align: center;
  text-transform: capitalize;
}
#HGASDF{
color}
```

Different ways to use styling

```
<!DOCTYPE html>
<html>
<head>
  <title>My Webpage</title>
</head>
<body>
  <h2 style="color: #2a7fda; font-size: 48px;">Welcome to
SIUE</h2>
  <p>This is a simple HTML webpage.</p>
  <p>You can add more content here.</p>
</body>
</html>
```

```
<!DOCTYPE html>
<html>
<head>
  <title>My Webpage</title>
  <style>
    h2 {
      color: #2a7fda; /* Change the color to blue */
      font-size: 48px; /* Change the font size to 24 pixels */
      text-align: center;
      text-transform: capitalize;
    }

    p {
      color: #222;
      font-size: 18px;
    }
  </style>
</head>
<body>
  <h2 >Welcome to SIUE</h2>
  <p>This is a simple HTML webpage.</p>
  <p>You can add more content here.</p>
</body>
</html>
```

Different ways to style a web page

- Many ways to style a webpage
- Usually a website consists of many pages
- Most of the styling elements are used across the website
- If styles are only written for a single page for other pages need to copy the code, which is not ideal
- So better to use a separate CSS file to store all these styling information

Creating a layout

```
<!DOCTYPE html>
<html>
<head>
  <title>My Webpage</title>
  <link rel="stylesheet"
type="text/css" href="style.css">
</head>
<body>
  <h2 id="top_header">Welcome to
SIUE</h2>
  <div id="text_1">
    <p >This is a simple HTML
webpage.</p>
  </div>
  <p>You can add more content
here.</p>
</body>
</html>
```

```
#top_header {
  color: #2a7fda; /* Change the color to blue */
  font-size: 18px; /* Change the font size to 24 pixels */
  text-align: center;
  text-transform: capitalize;
}

#text_1{
  background-color: aqua;
  width: 100px;
  height: 50px;
}
```


CSS attributes

- Margin is border the element from other elements
- Padding is for within an element

```
#top_header {  
    color: #2a7fda; /* Change the color to blue */  
    font-size: 18px; /* Change the font size to 24 pixels */  
    text-align: center;  
    text-transform: capitalize;  
}  
  
#text_1{  
    background-color: aqua;  
    width: 500px;  
    height: 200px;  
    /*padding-left: 50px;  
    margin: 30px;*/  
}
```

CSS fonts

- Usually multiple font families are mentioned
- If a particular font is not available in the user's system it will default to next font family mentioned in font-family

```
#top_header {  
  color: #2a7fda; /* Change the color to blue */  
  font-size: 18px; /* Change the font size to 24 pixels */  
  text-align: center;  
  text-transform: capitalize;  
  font-family: Verdana, Geneva, Tahoma, sans-serif;  
}
```

Using style with same ids

```
<!DOCTYPE html>
<html>
<head>
  <title>My Webpage</title>
  <link rel="stylesheet" type="text/css" href="style.css">
</head>
<body>
  <h2 id="top_header">Welcome to SIUE</h2>
  <div id="text_1">
    <p>This is a simple HTML webpage.</p>
  </div>
  <div>
    <p>You can add more content here.</p>
  </div>
  <div id="text_2">
    <p>This is text-2</p>
  </div>
</body>
</html>
```

```
#text_1, #text_2{
  background-color: aqua;
  width: 500px;
  height: 200px;
  padding-left: 50px;
  margin: 30px;
}
```

Class attribute

```
<!DOCTYPE html>
<html>
<head>
  <title>My Webpage</title>
  <link rel="stylesheet" type="text/css" href="style.css">
</head>
<body>
  <h2 class="top_header">Welcome to SIUE</h2>
  <h2 class="top_header">Department of Computer
Science</h2>
  <div id="text_1">
    <p>This is a simple HTML webpage.</p>
  </div>
  <div>
    <p>You can add more content here.</p>
  </div>
  <div id="text_2">
    <p>This is text-2</p>
  </div>
</body>
</html>
```

```
.top_header {
  color: #2ada50; /* Change the color to blue */
  font-size: 18px; /* Change the font size to 24 pixels */
  text-align: center;
  text-transform: capitalize;
  font-family: Verdana, Geneva, Tahoma, sans-serif;
  font-weight: bold;
}
```

Priority

```
<!DOCTYPE html>
<html>
<head>
  <title>My Webpage</title>
  <link rel="stylesheet" type="text/css" href="style.css">
</head>
<body>
  <h2 class="top_header">Welcome to SIUE</h2>
  <h2 class="top_header">School of Engineering</h2>
  <h2>Department of Computer Science</h2>
  <div id="text_1">
    <p>This is a simple HTML webpage.</p>
  </div>
  <div>
    <p>You can add more content here.</p>
  </div>
  <div id="text_2">
    <p>This is text-2</p>
  </div>
</body>
</html>
```

- Inline
- Id
- Class
- type

```
h2{
  color: blueviolet;
}

.top_header {
  color: #2ada50; /* Change the color to blue */
  font-size: 18px; /* Change the font size to 24 pixels */
  text-align: center;
  text-transform: capitalize;
  font-family: Verdana, Geneva, Tahoma, sans-serif;
  font-weight: bold;
}
```

CSS selector

```
<!DOCTYPE html>
<html>
<head>
  <title>CSS Child</title>
  <style>
    div > p {
      background-color: lightblue;
      padding: 10px;
      margin: 5px;
    }
  </style>
</head>
<body>
  <div>
    <p>This is a direct child paragraph.</p>
    <p>This is another direct child paragraph.</p>
    <div>
      <p>This is a nested paragraph.</p>
    </div>
  </div>
  <p>This paragraph is not a direct child of the div.</p>
  <div>
    <p>Inside another div</p>
  </div>
</body>
</html>
```

- DOM structure

Linking to a external CSS source

```
<!DOCTYPE html>
<html>
<head>
  <title>CSS Child</title>
  <link rel="stylesheet" href="https://www.w3schools.com/w3css/4/w3.css">
</head>
<body>
  <div>
    <p class="w3-panel w3-pale-green">This is a direct child paragraph.</p>
    <p class="w3-panel w3-red">This is another direct child paragraph.</p>
  </div>
</body>
</html>
```

Thank you

See you all in the next class