

Properties of Regular Languages

1

For regular languages L_1 and L_2
we will prove that:

Union:	$L_1 \cup L_2$	} Are regular Languages
Concatenation:	$L_1 L_2$	
Star:	L_1^*	
Reversal:	L_1^R	
Complement:	$\overline{L_1}$	
Intersection:	$L_1 \cap L_2$	

Costas Busch - LSU

2

2

We say Regular languages are **closed under**

Union: $L_1 \cup L_2$

Concatenation: $L_1 L_2$

Star: L_1^*

Reversal: L_1^R

Complement: $\overline{L_1}$

Intersection: $L_1 \cap L_2$


Costas Busch - LSU

3

3


A useful transformation: use one accept state

NFA



2 accept states

**Equivalent
NFA**



1 accept state


Costas Busch - LSU

4


4

In General

NFA



Equivalent NFA




Costas Busch - LSU

5

5

Extreme case

NFA without accepting state



Add an accepting state
without transitions

Costas Busch - LSU

6


6

Take two languages


Regular language L_1 Regular language L_2

$$L(M_1) = L_1$$

$$L(M_2) = L_2$$

NFA M_1 

Single accepting state

NFA M_2 



Single accepting state

Costas Busch - LSU

7

7

Example




Costas Busch - LSU

8

8

Union

NFA for $L_1 \cup L_2$




Costas Busch - LSU

9

9

Example

NFA for $L_1 \cup L_2 = \{a^n b\} \cup \{ba\}$




Costas Busch - LSU

10

10

Concatenation

NFA for L_1L_2




Costas Busch - LSU

11

11

Example

NFA for $L_1L_2 = \{a^n b\} \{ba\} = \{a^n bba\}$




Costas Busch - LSU

12

12

Star Operation

NFA for L^*



$$w \in L^* \iff w = w_1 w_2 \wedge w_k : w_i \in L \quad \text{or} \quad w = \lambda$$


Costas Busch - LSU

13

13

Example

NFA for $L_1^* = \{a^n b\}^*$





Costas Busch - LSU

14

14

Reverse

NFA for L^R



1. Reverse all transitions



2. Make the initial state accept state and the accept state initial state

Costas Busch - LSU

15

15

Example




Costas Busch - LSU

16

16

Complement





1. Take the **DFA** that accepts L
2. Make accept states regular and vice-versa

Costas Busch - LSU

17

17

Example



Costas Busch - LSU


18

18

NFAs cannot be used for complement

Make accept states regular
and vice-versa


NFA M



$$L(M) = \{ \}$$

$$\overline{L(M)} = \Sigma^* = \{a, b\}^*$$

NFA M'



$$L(M') = \{ \lambda \} \neq \overline{L(M)}$$

it is **not** the
complement

Costas Busch - LSU


19

19

Same example with DFAs

Make accept states regular
and vice-versa


DFA M



$$L(M) = \{ \}$$

$$\overline{L(M)} = \Sigma^* = \{a, b\}^*$$

DFA M'



$$L(M') = \{a, b\}^* = \overline{L(M)}$$


it is the
complement

Costas Busch - LSU

20

20

Intersection




Costas Busch - LSU

21

21

DeMorgan's Law: $L_1 \cap L_2 = \overline{\overline{L_1} \cup \overline{L_2}}$



Costas Busch - LSU

22

22

Example

$$\left. \begin{array}{l} L_1 = \{a^n b\} \text{ regular} \\ L_2 = \{ab, ba\} \text{ regular} \end{array} \right\} \Rightarrow L_1 \cap L_2 = \{ab\} \text{ regular}$$

Costas Busch - LSU

23

23

Another Proof for Intersection Closure

Machine M_1 DFA for L_1 Machine M_2 DFA for L_2

Construct a new DFA M that accepts $L_1 \cap L_2$


M simulates in parallel M_1 and M_2

Costas Busch - LSU

24

24

States in M




Costas Busch - LSU


25

25


DFA M_1



DFA M_2




DFA M



Costas Busch - LSU


26

26



27

27




28


28

Example:

$$L_1 = \{a^n b\} \quad n \geq 0$$



$$L_2 = \{ab^m\} \quad m \geq 0$$




Costas Busch - LSU

29

29

DFA M for intersection

$$L(M) = \{a^n b\} \cap \{ab^m\} = \{ab\}$$



Costas Busch - LSU

30

30

Construction procedure for intersection

1. Build Initial State
2. For each new state and for each symbol
add transition to either an existing state
or create a new state and point to it
3. Repeat step 3 until no new states
are added
4. Designate accept states


Costas Busch - LSU

31

31

Automaton for intersection

$$L = \{a^n b\} \cap \{ab^m\} = \{ab\}$$



initial state


Costas Busch - LSU

32


32

Automaton for intersection

$$L = \{a^n b\} \cap \{ab^m\} = \{ab\}$$



add transition and new state
for symbol a




Costas Busch - LSU

33


33

Automaton for intersection

$$L = \{a^n b\} \cap \{ab^m\} = \{ab\}$$



add transition and new state
for symbol b



Costas Busch - LSU


34

34

Automaton for intersection

$$L = \{a^n b\} \cap \{ab^m\} = \{ab\}$$

Repeat until no new states can be added



Costas Busch - LSU

35


35

Automaton for intersection

$$L = \{a^n b\} \cap \{ab^m\} = \{ab\}$$

q_1 accept state for M_1

p_1 accept state for $M_2 \implies$ add Accept state



Costas Busch - LSU

36

36

Intersection DFA M :

simulates in parallel M_1 and M_2

accepts string w if and only if:

M_1 accepts string w

and M_2 accepts string w

$$L(M) = L(M_1) \cap L(M_2)$$