

# <Progress Report - Sprint 3>

SWPP 2020 Spring LLVM Project  
2020.06.13

## Team 4

Hyoung Uk Sul  
Ahyoung Oh  
Jaewook Lee  
Jaeun Lee

### Progress Report: Hyoung Uk Sul

#### [ Sprint 3 ] SimpleBackend Register Allocation Optimization Part 3

##### Change in Schedules (None)

Things were accomplished as planned in the previous sprint.

##### Done and Not Dones

##### Dones:

Up to the previous sprint, every change in depromotion focused on reducing the cost of the compiled program. To achieve such goal, I applied every method I could think up to better the performance of the compiler, relying heavily on my own heuristics rather than using already verified design methodologies. As a result, although the given benchmark tests and running "make test" passed, I feared that there could be some corner cases that catch this algorithm bad. Hence, an aspect of development that this sprint's version of depromotion algorithm focuses on is its safety. The updated implementation aims for and prevents many corner cases. Of course, it also introduces some new features to better the overall register allocation as well. The "Dones" of this sprint are the following.

1. Up to the previous sprint, the depromotion algorithm, upon facing eviction of a temporary register user, would simply put load instruction at every use of the value afterwards. This resulted in an inefficient handling of register allocation where there are multiple loads within the same basic block to load data for a temporary register user. There are many cases where these loads can be safely removed. Hence, this sprint's version of depromotion will check if there are duplicate loads within the same basic block, and if they have the same register ID and there is no dependency issue, it will remove such load instructions.
2. On the other hand, if an eviction indicated by the store to stack cannot reach a certain usage of evicted value, but yet there is another value that uses the same register ID in between, then there still occurs a dependency issue. Hence, adding loads must not rely on checking reachables blocks from the eviction point. Rather, it should check every usage of evicted value regardless of

eviction location. Thereby, this implementation fixes such issues and adds load instructions even at locations unreachable from eviction point.

3. If a value in the depromoted module turns out to be a constant (ex. add 1 2 will simply turn into a constant 3), then it does not need to and cannot use a register. However, the previous version deemed it will be a register user and hence evicted a register so that this constant value can then "use" a register. This caused a "ghost eviction" where there exists an eviction and no value uses the evicted register ID afterwards. This led to inefficient register allocation and general increase in cost of compiled programs. Hence, the new version fixes this and ensures that only valid instructions take up register IDs.
4. If a value is a ZExt instruction, but yet even its operand is another ZExt instruction, then there occurs a problem where there does not exist a value for this in a depromoted module. Hence, this implementation recursively retrieves ZExt operand until it is non-ZExt value.
5. LRU policy for assigning temporary registers to value is further enhanced. Up to this point, the policy utilized in depromotion was not strict LRU; rather, it only relied on point of creation to decide whether it is least recently used and should be evicted. However, this caused inefficiency in register handling and resulted in more load and store instructions introduced. Hence, this implementation applies strict LRU and every value's usage is recorded upon every use by other instructions as well. This resulted in a very good cost decrease in compiled programs.
6. Originally, the least number of temporary registers was 3. This was calculated upon the fact that the instruction that requires the most temporary registers required 3 temporary values. However, such calculation omitted the fact that the instruction itself also might need a register. Hence, now the value is 4.
7. When a cast instruction is only used once, in the instruction right after or two instructions after, the instruction's name was changed to its operand's name so that it can be ignored by the emitter. However, such an algorithm introduces errors where cast instruction is used only once two instructions after, but another instruction between the cast instruction and its usage is the instruction that evicts it. Hence, now the depromotion algorithm ensures that there is no eviction in between.

#### **Not Dones:**

Even though this is the last sprint, and all 6 weeks of development has been put into developing depromotion and register allocation, there are still some bits that could have been achieved but were not due to time and resource constraints. Some examples of such include:

1. The depromotion algorithm could have executed some register packing, but that would require a whole new sprint to be achieved.
2. Not all unnecessary cast instructions have been completely removed.
3. There could have been more accurate dependency tracking between registers to remove more unnecessary register allocations, but such job could not be done within polynomial time, and implementing heuristics would require yet again another sprint.

- Global variables are always loaded even if they have already been loaded previously; this can be handled by the backend, but this could not be done within 3 sprints with all other things to implement.

### Test Results:

The following shows the run of “test.sh” (explained in previous progress reports). This time, it compares the baseline compiler and the current version with **just the DepromoteRegisters turned on, everything else off**. Devoting all 3 sprints into depromotion algorithm, I was able to attain up to almost x4 times improvement on some cases, and at least around x2~3 improvement on most test cases.

```
StuartSul:swpp202001-team4 Stuart$ ./test.sh compare
_____TESTING bitcount1_____
input 1: PASSED with cost: 59.0000 (baseline: 218.2288)
input 2: PASSED with cost: 339.8000 (baseline: 1351.6672)
input 3: PASSED with cost: 100.6000 (baseline: 386.1456)
input 4: PASSED with cost: 17.4000 (baseline: 50.3120)
input 5: PASSED with cost: 27.8000 (baseline: 92.2912)
_____TESTING bitcount2_____
input 1: PASSED with cost: 85.8256 (baseline: 201.3744)
input 2: PASSED with cost: 544.9984 (baseline: 1256.4480)
input 3: PASSED with cost: 153.8512 (baseline: 357.6816)
input 4: PASSED with cost: 17.8000 (baseline: 45.0672)
input 5: PASSED with cost: 34.8064 (baseline: 84.1440)
_____TESTING bitcount3_____
input 1: PASSED with cost: 39.0000 (baseline: 135.0832)
input 2: PASSED with cost: 352.2000 (baseline: 1364.2656)
input 3: PASSED with cost: 93.0000 (baseline: 347.0112)
input 4: PASSED with cost: 17.4000 (baseline: 50.3120)
input 5: PASSED with cost: 28.2000 (baseline: 92.6976)
_____TESTING bitcount4_____
input 1: PASSED with cost: 9031.2656 (baseline: 25400.8304)
input 2: PASSED with cost: 9031.8496 (baseline: 25403.6560)
input 3: PASSED with cost: 9032.0496 (baseline: 25401.6144)
input 4: PASSED with cost: 9031.2368 (baseline: 25400.8016)
input 5: PASSED with cost: 9031.2400 (baseline: 25400.8048)
_____TESTING bitcount5_____
input 1: PASSED with cost: 97.4480 (baseline: 392.6752)
input 2: PASSED with cost: 224.8480 (baseline: 872.3872)
input 3: PASSED with cost: 115.6512 (baseline: 460.9920)
input 4: PASSED with cost: 79.2480 (baseline: 324.4704)
input 5: PASSED with cost: 97.4480 (baseline: 392.6496)
_____TESTING bubble_sort_____
input 1: PASSED with cost: 2024.7584 (baseline: 6628.9360)
input 2: PASSED with cost: 143991.8176 (baseline: 562437.2464)
input 3: PASSED with cost: 14212790.0339 (baseline: 61987402.0422)
_____TESTING collatz_____
```

input 1: PASSED with cost: 28.2064 (baseline: 68.4400)  
input 2: PASSED with cost: 28.2064 (baseline: 68.4400)  
\_\_\_\_\_TESTING gcd\_\_\_\_\_

input 1: PASSED with cost: 18.2000 (baseline: 46.5024)  
input 2: PASSED with cost: 34.8000 (baseline: 105.4816)  
input 3: PASSED with cost: 68.0000 (baseline: 223.4272)  
input 4: PASSED with cost: 297.8000 (baseline: 1043.0336)  
\_\_\_\_\_TESTING prime\_\_\_\_\_

input 1: PASSED with cost: 50.5568 (baseline: 117.4400)  
input 2: PASSED with cost: 3185.0672 (baseline: 6678.1008)  
input 3: PASSED with cost: 695783.3616 (baseline: 1548664.4224)  
input 4: PASSED with cost: 2542265.5536 (baseline: 5628813.2864)  
\_\_\_\_\_TESTING binary\_tree\_\_\_\_\_

input 1: PASSED with cost: 919.3712 (baseline: 2402.8096)  
input 2: PASSED with cost: 1762.5760 (baseline: 4310.6816)  
input 3: PASSED with cost: 27900.4352 (baseline: 66113.1696)  
input 4: PASSED with cost: 448803.6208 (baseline: 1033485.1248)  
input 5: PASSED with cost: 1316127748.4000 (baseline: 1977050335.0849)  
\_\_\_\_\_TESTING matmul1\_\_\_\_\_

input 1: PASSED with cost: 994.2240 (baseline: 2608.1088)  
input 2: PASSED with cost: 4824.3296 (baseline: 13201.6704)  
input 3: PASSED with cost: 210548.9120 (baseline: 594334.2144)  
\_\_\_\_\_TESTING matmul2\_\_\_\_\_

input 1: PASSED with cost: 945.7888 (baseline: 2804.3072)  
input 2: PASSED with cost: 4846.6720 (baseline: 15513.8560)  
input 3: PASSED with cost: 235669.8784 (baseline: 807544.4224)  
\_\_\_\_\_TESTING matmul3\_\_\_\_\_

input 1: PASSED with cost: 2932.3152 (baseline: 7797.6480)  
input 2: PASSED with cost: 2932.3152 (baseline: 7797.6480)  
input 3: PASSED with cost: 116840.8320 (baseline: 313852.4352)  
\_\_\_\_\_TESTING matmul4\_\_\_\_\_

input 1: PASSED with cost: 6385.5280 (baseline: 20952.6976)  
input 2: PASSED with cost: 6385.5280 (baseline: 20952.6976)  
input 3: PASSED with cost: 338179.8688 (baseline: 1155651.0784)  
\_\_\_\_\_TESTING rmq1d\_naive\_\_\_\_\_

input 1: PASSED with cost: 121.3296 (baseline: 370.2880)  
input 2: PASSED with cost: 788.6384 (baseline: 3041.7728)  
input 3: PASSED with cost: 1189.1024 (baseline: 4770.9952)  
input 4: PASSED with cost: 1414.1568 (baseline: 5578.9824)  
input 5: PASSED with cost: 466224.1232 (baseline: 2439922.4944)  
input 6: PASSED with cost: 2124241.5840 (baseline: 11471977.9616)  
input 7: PASSED with cost: 404726347.5792 (baseline: 2721615862.1304)  
\_\_\_\_\_TESTING rmq1d\_sparsetable\_\_\_\_\_

input 1: PASSED with cost: 874.2624 (baseline: 2568.7232)  
input 2: PASSED with cost: 7419.3488 (baseline: 22418.3616)  
input 3: PASSED with cost: 10834.6768 (baseline: 32883.3120)  
input 4: PASSED with cost: 9543.0928 (baseline: 27376.3424)  
input 5: PASSED with cost: 644409.1616 (baseline: 1956788.2496)  
input 6: PASSED with cost: 1103059.4816 (baseline: 2910040.9664)

input 7: PASSED with cost: 100306858.0569 (baseline: 135120657.9315)

\_\_\_\_\_TESTING rmq2d\_naive\_\_\_\_\_

input 1: PASSED with cost: 277.3936 (baseline: 715.2544)

input 2: PASSED with cost: 1527.6672 (baseline: 4967.7056)

input 3: PASSED with cost: 11901.4144 (baseline: 42847.2224)

input 4: PASSED with cost: 10701.2640 (baseline: 32249.0896)

input 5: PASSED with cost: 3973835.0816 (baseline: 22665902.4304)

\_\_\_\_\_TESTING rmq2d\_sparsetable\_\_\_\_\_

input 1: PASSED with cost: 3002.9456 (baseline: 8994.4592)

input 2: PASSED with cost: 17195.8304 (baseline: 52414.1120)

input 3: PASSED with cost: 94319.8544 (baseline: 289182.7600)

input 4: PASSED with cost: 133284.9056 (baseline: 330169.2336)

input 5: PASSED with cost: 884057682.4709 (baseline: 995120658.5224)

- New Test Cases:

FileCheck 1 (RegisterAllocationOpt-Test7.ll)	
Before Optimization	After Optimization
<div>Returned: 0 Cost: 71071.6400 Max heap usage (bytes): 80</div>	<div>Returned: 0 Cost: 20235.7472 Max heap usage (bytes): 80</div>
FileCheck 2 (RegisterAllocationOpt-Test8.ll)	
Before Optimization	After Optimization
<div>Returned: 0 Cost: 1782.1120 Max heap usage (bytes): 0</div>	<div>Returned: 0 Cost: 504.9696 Max heap usage (bytes): 0</div>
FileCheck 3 (RegisterAllocationOpt-Test9.ll)	
Before Optimization	After Optimization
<div>Returned: 0 Cost: 46966.2224 Max heap usage (bytes): 112</div>	<div>Returned: 0 Cost: 18050.4304 Max heap usage (bytes): 112</div>
GoogleTest (Memory Redundancy Test + Instruction Redundancy Test)	

```
Running 16 tests from 3 test cases.
Global test environment set-up.
1 test from MainTest
MainTest.CheckMain
RUN MainTest.CheckMain (9 ms)
OK 1 test from MainTest (9 ms total)

9 tests from MemoryEfficiencyTest
MemoryEfficiencyTest.ExtraAlloc1
RUN OK MemoryEfficiencyTest.ExtraAlloc1 (2 ms)
MemoryEfficiencyTest.ExtraAlloc2
RUN OK MemoryEfficiencyTest.ExtraAlloc2 (5 ms)
MemoryEfficiencyTest.ExtraAlloc3
RUN OK MemoryEfficiencyTest.ExtraAlloc3 (13 ms)
MemoryEfficiencyTest.DoubleLoad1
RUN OK MemoryEfficiencyTest.DoubleLoad1 (8 ms)
MemoryEfficiencyTest.DoubleLoad2
RUN OK MemoryEfficiencyTest.DoubleLoad2 (3 ms)
MemoryEfficiencyTest.DoubleLoad3
RUN OK MemoryEfficiencyTest.DoubleLoad3 (7 ms)
MemoryEfficiencyTest.ExtraStore1
RUN OK MemoryEfficiencyTest.ExtraStore1 (1 ms)
MemoryEfficiencyTest.ExtraStore2
RUN OK MemoryEfficiencyTest.ExtraStore2 (2 ms)
MemoryEfficiencyTest.ExtraStore3
RUN OK MemoryEfficiencyTest.ExtraStore3 (7 ms)
9 tests from MemoryEfficiencyTest (40 ms total)

6 tests from InstructionRedundancyTest
InstructionRedundancyTest.DuplicateLoad1
RUN OK InstructionRedundancyTest.DuplicateLoad1 (6 ms)
InstructionRedundancyTest.DuplicateLoad2
RUN OK InstructionRedundancyTest.DuplicateLoad2 (5 ms)
InstructionRedundancyTest.DuplicateLoad3
RUN OK InstructionRedundancyTest.DuplicateLoad3 (14 ms)
InstructionRedundancyTest.UnnecessaryCast1
RUN OK InstructionRedundancyTest.UnnecessaryCast1 (5 ms)
InstructionRedundancyTest.UnnecessaryCast2
RUN OK InstructionRedundancyTest.UnnecessaryCast2 (3 ms)
InstructionRedundancyTest.UnnecessaryCast3
RUN OK InstructionRedundancyTest.UnnecessaryCast3 (13 ms)
6 tests from InstructionRedundancyTest (46 ms total)

Global test environment tear-down
16 tests from 3 test cases ran. (95 ms total)
PASSED 16 tests.
```

## Progress Report: Ahyoung Oh

In sprint 3, I pushed two pull requests in total : 'Function Optimization' and 'Assembly Emitter Memory Access Optimization Part 2'. PR1 is about implementing existing passes as I was responsible for doing so in this sprint.

### [ Sprint 3 ] Function Optimization

#### Change in Schedules (None)

Things were accomplished as planned in the previous sprint.

#### Done and Not Dones

As I was responsible for implementing existing passes for this sprint, I've added two existing passes related to the function optimization.

1. Tail Call Elimination : This pass helps avoid allocating a new stack frame for a function because the caller will simply return the value that it gets from the callee. If it can prove that callees do not access their caller stack frame, they are marked as eligible for tail call elimination (by the code generator).
2. Sparse Conditional Constant Propagation : SCCP pass does sparse conditional constant propagation and merging, like following:

Assumes values are constant unless proven otherwise

- Assumes BasicBlocks are dead unless proven otherwise
- Proves values to be constant, and replaces them with constants
- Proves conditional branches to be unconditional  
(from llvm.org)

This pass works well with DCE pass so I've changed the order of the passes.

In addition to these two passes, I added one more existing pass named UnreachableBlockElimPass() during the code review process.

3. Unreachable Block Elimination : By implementing this pass, our team doesn't have to care more about unreachable basic block potentially being a problem.

#### Test Results:

- Existing Test Cases

This optimization decreased cost substantially in the following highlighted cases.

\_\_\_\_\_TESTING bitcount1\_\_\_\_\_

input 1: PASSED with cost: 58.2000 (sprint2: 58.2000) (sprint1: 75.4608) (baseline: 218.2288)  
input 2: PASSED with cost: 333.6000 (sprint2: 333.6000) (sprint1: 443.0064) (baseline: 1351.6672)  
input 3: PASSED with cost: 99.0000 (sprint2: 99.0000) (sprint1: 129.9120) (baseline: 386.1456)  
input 4: PASSED with cost: 17.4000 (sprint2: 17.4000) (sprint1: 21.0096) (baseline: 50.3120)  
input 5: PASSED with cost: 27.6000 (sprint2: 27.6000) (sprint1: 34.6224) (baseline: 92.2912)

\_\_\_\_\_TESTING bitcount2\_\_\_\_\_

input 1: PASSED with cost: 60.2000 (sprint2: 85.0256) (sprint1: 86.0256) (baseline: 201.3744)  
input 2: PASSED with cost: 335.6000 (sprint2: 538.7984) (sprint1: 539.7984) (baseline: 1256.4480)  
input 3: PASSED with cost: 101.0000 (sprint2: 152.2512) (sprint1: 153.2512) (baseline: 357.6816)  
input 4: PASSED with cost: 19.4000 (sprint2: 17.8000) (sprint1: 18.8000) (baseline: 45.0672)  
input 5: PASSED with cost: 29.6000 (sprint2: 34.6064) (sprint1: 35.6064) (baseline: 84.1440)

\_\_\_\_\_TESTING bitcount3\_\_\_\_\_

input 1: PASSED with cost: 39.0000 (sprint2: 39.0000) (sprint1: 49.4352) (baseline: 135.0832)  
input 2: PASSED with cost: 352.2000 (sprint2: 352.2000) (sprint1: 461.6064) (baseline: 1364.2656)  
input 3: PASSED with cost: 93.0000 (sprint2: 93.0000) (sprint1: 120.4992) (baseline: 347.0112)  
input 4: PASSED with cost: 17.4000 (sprint2: 17.4000) (sprint1: 21.0096) (baseline: 50.3120)  
input 5: PASSED with cost: 28.2000 (sprint2: 28.2000) (sprint1: 35.2224) (baseline: 92.6976)

\_\_\_\_\_TESTING bitcount4\_\_\_\_\_

input 1: PASSED with cost: 9030.6656 (sprint2: 9030.6656) (sprint1: 9783.1040) (baseline: 25400.8304)  
input 2: PASSED with cost: 9031.2496 (sprint2: 9031.2496) (sprint1: 9783.8912) (baseline: 25403.6560)  
input 3: PASSED with cost: 9031.4496 (sprint2: 9031.4496) (sprint1: 9783.8880) (baseline: 25401.6144)  
input 4: PASSED with cost: 9030.6368 (sprint2: 9030.6368) (sprint1: 9783.0752) (baseline: 25400.8016)  
input 5: PASSED with cost: 9030.6400 (sprint2: 9030.6400) (sprint1: 9783.0784) (baseline: 25400.8048)

\_\_\_\_\_TESTING bitcount5\_\_\_\_\_

input 1: PASSED with cost: 107.4816 (sprint2: 110.6816) (sprint1: 164.8288) (baseline: 392.6752)  
input 2: PASSED with cost: 222.3008 (sprint2: 236.7008) (sprint1: 332.8736) (baseline: 872.3872)  
input 3: PASSED with cost: 123.9008 (sprint2: 128.7008) (sprint1: 188.8384) (baseline: 460.9920)  
input 4: PASSED with cost: 91.0528 (sprint2: 92.6528) (sprint1: 140.8224) (baseline: 324.4704)  
input 5: PASSED with cost: 107.4560 (sprint2: 110.6560) (sprint1: 164.8288) (baseline: 392.6496)

\_\_\_\_\_TESTING bubble\_sort\_\_\_\_\_

input 1: PASSED with cost: 1873.5584 (sprint2: 1873.5584) (sprint1: 3644.9712) (baseline: 6628.9360)  
input 2: PASSED with cost: 130274.6176 (sprint2: 130274.6176) (sprint1: 315078.2912) (baseline: 562437.2464)  
input 3: PASSED with cost: 12714888.8343 (sprint2: 12714888.8343) (sprint1: 36245394.9259) (baseline: 61987402.0422)

\_\_\_\_\_TESTING collatz\_\_\_\_\_

input 1: PASSED with cost: 29.8064 (sprint2: 28.2064) (sprint1: 29.2448) (baseline: 68.4400)  
input 2: PASSED with cost: 29.8064 (sprint2: 28.2064) (sprint1: 29.2448) (baseline: 68.4400)

\_\_\_\_\_TESTING gcd\_\_\_\_\_

input 1: PASSED with cost: 20.4000 (sprint2: 18.2000) (sprint1: 22.2000) (baseline: 46.5024)  
input 2: PASSED with cost: 32.6000 (sprint2: 34.8000) (sprint1: 53.0384) (baseline: 105.4816)  
input 3: PASSED with cost: 57.0000 (sprint2: 68.0000) (sprint1: 114.7152) (baseline: 223.4272)  
input 4: PASSED with cost: 225.2000 (sprint2: 297.8000) (sprint1: 542.4528) (baseline: 1043.0336)

\_\_\_\_\_TESTING prime\_\_\_\_\_

input 1: PASSED with cost: 47.1568 (sprint2: 47.1568) (sprint1: 52.3568) (baseline: 117.4400)  
input 2: PASSED with cost: 2553.4896 (sprint2: 3169.6672) (sprint1: 3778.3760) (baseline: 6678.1008)  
input 3: PASSED with cost: 538353.9648 (sprint2: 685431.9616) (sprint1: 902276.9104) (baseline: 1548664.4224)  
input 4: PASSED with cost: 1974698.7648 (sprint2: 2509506.1536) (sprint1: 3309086.8640) (baseline: 5628813.2864)

\_\_\_\_\_TESTING binary\_tree\_\_\_\_\_

input 1: PASSED with cost: 903.9712 (sprint2: 920.3712) (sprint1: 1414.0816) (baseline: 2402.8096)



input 2: PASSED with cost: 1747.7488 (sprint2: 1764.1488) (sprint1: 2721.3600) (baseline: 4310.6816)  
input 3: PASSED with cost: 27992.7280 (sprint2: 28084.1280) (sprint1: 43829.8000) (baseline: 66113.1696)  
input 4: PASSED with cost: 451561.4128 (sprint2: 452297.8128) (sprint1: 715705.5104) (baseline: 1033485.1248)  
input 5: PASSED with cost: 1317017229.3856 (sprint2: 1317054853.7856) (sprint1: 1874833611.0864) (baseline: 1977050335.0849)

\_\_\_\_\_TESTING matmul1\_\_\_\_\_

input 1: PASSED with cost: 1080.0608 (sprint2: 1080.0608) (baseline: 2608.1088)  
input 2: PASSED with cost: 5593.2960 (sprint2: 5593.2960) (baseline: 13201.6704)  
input 3: PASSED with cost: 262675.9968 (sprint2: 262675.9968) (baseline: 594334.2144)

\_\_\_\_\_TESTING matmul2\_\_\_\_\_

input 1: PASSED with cost: 924.9600 (sprint2: 924.9600) (baseline: 2804.3072)  
input 2: PASSED with cost: 4607.4304 (sprint2: 4607.4304) (baseline: 15513.8560)  
input 3: PASSED with cost: 216849.7600 (sprint2: 216849.7600) (baseline: 807544.4224)

\_\_\_\_\_TESTING matmul3\_\_\_\_\_

input 1: PASSED with cost: 2935.5888 (sprint2: 2935.5888) (baseline: 7797.6480)  
input 2: PASSED with cost: 2935.5888 (sprint2: 2935.5888) (baseline: 7797.6480)  
input 3: PASSED with cost: 111759.8112 (sprint2: 111759.8112) (baseline: 313852.4352)

\_\_\_\_\_TESTING matmul4\_\_\_\_\_

input 1: PASSED with cost: 4754.8512 (sprint2: 4754.8512) (baseline: 20952.6976)  
input 2: PASSED with cost: 4754.8512 (sprint2: 4754.8512) (baseline: 20952.6976)  
input 3: PASSED with cost: 234463.7616 (sprint2: 234463.7616) (baseline: 1155651.0784)

\_\_\_\_\_TESTING rmq1d\_naive\_\_\_\_\_

input 1: PASSED with cost: 112.4976 (sprint2: 112.4976) (baseline: 370.2880)  
input 2: PASSED with cost: 802.5488 (sprint2: 802.5488) (baseline: 3041.7728)  
input 3: PASSED with cost: 1220.9936 (sprint2: 1220.9936) (baseline: 4770.9952)  
input 4: PASSED with cost: 1379.9520 (sprint2: 1379.9520) (baseline: 5578.9824)  
input 5: PASSED with cost: 470616.1904 (sprint2: 470616.1904) (baseline: 2439922.4944)  
input 6: PASSED with cost: 2125425.9712 (sprint2: 2125425.9712) (baseline: 11471977.9616)  
input 7: PASSED with cost: 404698149.5664 (sprint2: 404698149.5664) (baseline: 2721615862.1304)

\_\_\_\_\_TESTING rmq1d\_sparsetable\_\_\_\_\_

input 1: PASSED with cost: 810.1376 (sprint2: 810.1376) (baseline: 2568.7232)  
input 2: PASSED with cost: 7184.0880 (sprint2: 7184.0880) (baseline: 22418.3616)  
input 3: PASSED with cost: 10511.9632 (sprint2: 10511.9632) (baseline: 32883.3120)  
input 4: PASSED with cost: 9290.9248 (sprint2: 9290.9248) (baseline: 27376.3424)  
input 5: PASSED with cost: 627964.2848 (sprint2: 627964.2848) (baseline: 1956788.2496)  
input 6: PASSED with cost: 1095536.2560 (sprint2: 1095536.2560) (baseline: 2910040.9664)  
input 7: PASSED with cost: 103543434.6825 (sprint2: 103543434.6825) (baseline: 135120657.9315)

\_\_\_\_\_TESTING rmq2d\_naive\_\_\_\_\_

input 1: PASSED with cost: 277.5056 (sprint2: 277.5056) (baseline: 715.2544)  
input 2: PASSED with cost: 1558.0288 (sprint2: 1558.0288) (baseline: 4967.7056)  
input 3: PASSED with cost: 12268.1504 (sprint2: 12268.1504) (baseline: 42847.2224)  
input 4: PASSED with cost: 10646.2512 (sprint2: 10646.2512) (baseline: 32249.0896)  
input 5: PASSED with cost: 3966246.5872 (sprint2: 3966246.5872) (baseline: 22665902.4304)

\_\_\_\_\_TESTING rmq2d\_sparsetable\_\_\_\_\_

input 1: PASSED with cost: 2961.7776 (sprint2: 2961.7776) (baseline: 8994.4592)  
input 2: PASSED with cost: 16860.2464 (sprint2: 16860.2464) (baseline: 52414.1120)  
input 3: PASSED with cost: 92113.7072 (sprint2: 92113.7072) (baseline: 289182.7600)  
input 4: PASSED with cost: 125085.9872 (sprint2: 125085.9872) (baseline: 330169.2336)  
input 5: PASSED with cost: 878957463.0040 (sprint2: 878957463.0040) (baseline: 995120658.5224)

- New Test Cases : input .ll files are in the git repository

FileCheck 1 (Tail Call Elim)	
Before Optimization	After Optimization
<pre> interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 2022.5376 3   Max heap usage (bytes): 0 </pre>	<pre> interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 412.0000 3   Max heap usage (bytes): 0 </pre>
FileCheck 2	
Before Optimization	After Optimization
<pre> interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 141.4320 3   Max heap usage (bytes): 72 4 </pre>	<pre> interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 121.6064 3   Max heap usage (bytes): 72 4 </pre>
FileCheck 3	
Before Optimization	After Optimization
<pre> interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 6528.2048 3   Max heap usage (bytes): 0 4 </pre>	<pre> interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 2110.7472 3   Max heap usage (bytes): 0 4 </pre>

## [ Sprint 3 ] Reordering Memory Access (Assembly Emitter Memory Access Optimization Part 2)

### Change in Schedules (None)

Things were accomplished as planned in the previous sprint.

### Done and Not Dones

In this sprint, for “Assembly Emitter Memory Access Optimization Part 2”, the optimizations that could be done by modifying the AssemblyEmitter.cpp code are implemented.

The cases to emit reset are generalized to the function level. In sprint2, for part 1 of this optimization, a reset instruction was emitted only when it's 100% sure that the memory access has changed(either from heap to stack or from stack to heap) within the same block. However, it'd be more efficient if the memory access change could be detected within the same function. I've done this by analyzing the reachable blocks. So now, more reset instructions are emitted(due to cases like the head remaining in the stack for the BB1 and then the head moving to the heap for the next block).

### Not Done :

I wasn't able to erase instructions like `r1 = mul r13 1 64` shown below because they were more complicated than I've thought to erase those by modifying AssemblyEmitter.cpp.

```
r1 = mul r13 1 64
```

With the example above, I tried to narrow down the cases to where r1 has only one use and the user of that use is the instruction right after emitCopy. I did till that point of detection but it was hard to replace all the uses of r1 with r13 as they had different types which led to assertion error. Therefore, to be safe, after discussing with our teammates, I decided not to implement this optimization.

### Test Results:

- Existing Test Cases

This optimization decreased cost substantially in the following highlighted cases.

_____ TESTING bitcount1 _____
input 1: PASSED with cost: 58.2000 (sprint2: 58.2000) (sprint1: 75.4608) (baseline: 218.2288)
input 2: PASSED with cost: 333.6000 (sprint2: 333.6000) (sprint1: 443.0064) (baseline: 1351.6672)
input 3: PASSED with cost: 99.0000 (sprint2: 99.0000) (sprint1: 129.9120) (baseline: 386.1456)
input 4: PASSED with cost: 17.4000 (sprint2: 17.4000) (sprint1: 21.0096) (baseline: 50.3120)
input 5: PASSED with cost: 27.6000 (sprint2: 27.6000) (sprint1: 34.6224) (baseline: 92.2912)
_____ TESTING bitcount2 _____
input 1: PASSED with cost: 85.0256 (sprint2: 85.0256) (sprint1: 86.0256) (baseline: 201.3744)
input 2: PASSED with cost: 538.7984 (sprint2: 538.7984) (sprint1: 539.7984) (baseline: 1256.4480)
input 3: PASSED with cost: 152.2512 (sprint2: 152.2512) (sprint1: 153.2512) (baseline: 357.6816)

input 4: PASSED with cost: 17.8000 (sprint2: 17.8000) (sprint1: 18.8000) (baseline: 45.0672)

input 5: PASSED with cost: 34.6064 (sprint2: 34.6064) (sprint1: 35.6064) (baseline: 84.1440)

\_\_\_\_\_TESTING bitcount3\_\_\_\_\_

input 1: PASSED with cost: 39.0000 (sprint2: 39.0000) (sprint1: 49.4352) (baseline: 135.0832)

input 2: PASSED with cost: 352.2000 (sprint2: 352.2000) (sprint1: 461.6064) (baseline: 1364.2656)

input 3: PASSED with cost: 93.0000 (sprint2: 93.0000) (sprint1: 120.4992) (baseline: 347.0112)

input 4: PASSED with cost: 17.4000 (sprint2: 17.4000) (sprint1: 21.0096) (baseline: 50.3120)

input 5: PASSED with cost: 28.2000 (sprint2: 28.2000) (sprint1: 35.2224) (baseline: 92.6976)

\_\_\_\_\_TESTING bitcount4\_\_\_\_\_

input 1: PASSED with cost: 9030.6656 (sprint2: 9030.6656) (sprint1: 9783.1040) (baseline: 25400.8304)

input 2: PASSED with cost: 9031.2496 (sprint2: 9031.2496) (sprint1: 9783.8912) (baseline: 25403.6560)

input 3: PASSED with cost: 9031.4496 (sprint2: 9031.4496) (sprint1: 9783.8880) (baseline: 25401.6144)

input 4: PASSED with cost: 9030.6368 (sprint2: 9030.6368) (sprint1: 9783.0752) (baseline: 25400.8016)

input 5: PASSED with cost: 9030.6400 (sprint2: 9030.6400) (sprint1: 9783.0784) (baseline: 25400.8048)

\_\_\_\_\_TESTING bitcount5\_\_\_\_\_

input 1: PASSED with cost: 110.6816 (sprint2: 110.6816) (sprint1: 164.8288) (baseline: 392.6752)

input 2: PASSED with cost: 236.7008 (sprint2: 236.7008) (sprint1: 332.8736) (baseline: 872.3872)

input 3: PASSED with cost: 128.7008 (sprint2: 128.7008) (sprint1: 188.8384) (baseline: 460.9920)

input 4: PASSED with cost: 92.6528 (sprint2: 92.6528) (sprint1: 140.8224) (baseline: 324.4704)

input 5: PASSED with cost: 110.6560 (sprint2: 110.6560) (sprint1: 164.8288) (baseline: 392.6496)

\_\_\_\_\_TESTING bubble\_sort\_\_\_\_\_

input 1: PASSED with cost: 1852.5344 (sprint2: 1873.5584) (sprint1: 3644.9712) (baseline: 6628.9360)

input 2: PASSED with cost: 130064.3776 (sprint2: 130274.6176) (sprint1: 315078.2912) (baseline: 562437.2464)

input 3: PASSED with cost: 12712786.4343 (sprint2: 12714888.8343) (sprint1: 36245394.9259) (baseline: 61987402.0422)

\_\_\_\_\_TESTING collatz\_\_\_\_\_

input 1: PASSED with cost: 28.2064 (sprint2: 28.2064) (sprint1: 29.2448) (baseline: 68.4400)

input 2: PASSED with cost: 28.2064 (sprint2: 28.2064) (sprint1: 29.2448) (baseline: 68.4400)

\_\_\_\_\_TESTING gcd\_\_\_\_\_

input 1: PASSED with cost: 18.2000 (sprint2: 18.2000) (sprint1: 22.2000) (baseline: 46.5024)

input 2: PASSED with cost: 34.8000 (sprint2: 34.8000) (sprint1: 53.0384) (baseline: 105.4816)

input 3: PASSED with cost: 68.0000 (sprint2: 68.0000) (sprint1: 114.7152) (baseline: 223.4272)

input 4: PASSED with cost: 297.8000 (sprint2: 297.8000) (sprint1: 542.4528) (baseline: 1043.0336)

\_\_\_\_\_TESTING prime\_\_\_\_\_

input 1: PASSED with cost: 45.0576 (sprint2: 47.1568) (sprint1: 52.3568) (baseline: 117.4400)

input 2: PASSED with cost: 3211.6384 (sprint2: 3169.6672) (sprint1: 3778.3760) (baseline: 6678.1008)

input 3: PASSED with cost: 686185.0688 (sprint2: 685431.9616) (sprint1: 902276.9104) (baseline: 1548664.4224)

input 4: PASSED with cost: 2511565.3472 (sprint2: 2509506.1536) (sprint1: 3309086.8640) (baseline: 5628813.2864)

\_\_\_\_\_TESTING binary\_tree\_\_\_\_\_

input 1: PASSED with cost: 909.8592 (sprint2: 920.3712) (sprint1: 1414.0816) (baseline: 2402.8096)

input 2: PASSED with cost: 1749.4320 (sprint2: 1764.1488) (sprint1: 2721.3600) (baseline: 4310.6816)

input 3: PASSED with cost: 27962.1888 (sprint2: 28084.1280) (sprint1: 43829.8000) (baseline: 66113.1696)

input 4: PASSED with cost: 450872.3856 (sprint2: 452297.8128) (sprint1: 715705.5104) (baseline: 1033485.1248)

input 5: PASSED with cost: 1316899145.8368 (sprint2: 1317054853.7856) (sprint1: 1874833611.0864) (baseline: 1977050335.0849)

\_\_\_\_\_TESTING matmul1\_\_\_\_\_

input 1: PASSED with cost: 1080.0608 (sprint2: 1080.0608) (baseline: 2608.1088)

input 2: PASSED with cost: 5593.2960 (sprint2: 5593.2960) (baseline: 13201.6704)

input 3: PASSED with cost: 262675.9968 (sprint2: 262675.9968) (baseline: 594334.2144)

\_\_\_\_\_TESTING matmul2\_\_\_\_\_

input 1: PASSED with cost: 924.9600 (sprint2: 924.9600) (baseline: 2804.3072)  
input 2: PASSED with cost: 4607.4304 (sprint2: 4607.4304) (baseline: 15513.8560)  
input 3: PASSED with cost: 216849.7600 (sprint2: 216849.7600) (baseline: 807544.4224)  
\_\_\_\_\_TESTING matmul3\_\_\_\_\_

input 1: PASSED with cost: 2935.5888 (sprint2: 2935.5888) (baseline: 7797.6480)  
input 2: PASSED with cost: 2935.5888 (sprint2: 2935.5888) (baseline: 7797.6480)  
input 3: PASSED with cost: 111759.8112 (sprint2: 111759.8112) (baseline: 313852.4352)  
\_\_\_\_\_TESTING matmul4\_\_\_\_\_

input 1: PASSED with cost: 4754.8512 (sprint2: 4754.8512) (baseline: 20952.6976)  
input 2: PASSED with cost: 4754.8512 (sprint2: 4754.8512) (baseline: 20952.6976)  
input 3: PASSED with cost: 234463.7616 (sprint2: 234463.7616) (baseline: 1155651.0784)  
\_\_\_\_\_TESTING rmq1d\_naive\_\_\_\_\_

input 1: PASSED with cost: 112.4976 (sprint2: 112.4976) (baseline: 370.2880)  
input 2: PASSED with cost: 802.5488 (sprint2: 802.5488) (baseline: 3041.7728)  
input 3: PASSED with cost: 1220.9936 (sprint2: 1220.9936) (baseline: 4770.9952)  
input 4: PASSED with cost: 1379.9520 (sprint2: 1379.9520) (baseline: 5578.9824)  
input 5: PASSED with cost: 470616.1904 (sprint2: 470616.1904) (baseline: 2439922.4944)  
input 6: PASSED with cost: 2125425.9712 (sprint2: 2125425.9712) (baseline: 11471977.9616)  
input 7: PASSED with cost: 404698149.5664 (sprint2: 404698149.5664) (baseline: 2721615862.1304)  
\_\_\_\_\_TESTING rmq1d\_sparsetable\_\_\_\_\_

input 1: PASSED with cost: 810.1376 (sprint2: 810.1376) (baseline: 2568.7232)  
input 2: PASSED with cost: 7184.0880 (sprint2: 7184.0880) (baseline: 22418.3616)  
input 3: PASSED with cost: 10511.9632 (sprint2: 10511.9632) (baseline: 32883.3120)  
input 4: PASSED with cost: 9290.9248 (sprint2: 9290.9248) (baseline: 27376.3424)  
input 5: PASSED with cost: 627964.2848 (sprint2: 627964.2848) (baseline: 1956788.2496)  
input 6: PASSED with cost: 1095536.2560 (sprint2: 1095536.2560) (baseline: 2910040.9664)  
input 7: PASSED with cost: 103543434.6825 (sprint2: 103543434.6825) (baseline: 135120657.9315)  
\_\_\_\_\_TESTING rmq2d\_naive\_\_\_\_\_

input 1: PASSED with cost: 277.5056 (sprint2: 277.5056) (baseline: 715.2544)  
input 2: PASSED with cost: 1558.0288 (sprint2: 1558.0288) (baseline: 4967.7056)  
input 3: PASSED with cost: 12268.1504 (sprint2: 12268.1504) (baseline: 42847.2224)  
input 4: PASSED with cost: 10646.2512 (sprint2: 10646.2512) (baseline: 32249.0896)  
input 5: PASSED with cost: 3966246.5872 (sprint2: 3966246.5872) (baseline: 22665902.4304)  
\_\_\_\_\_TESTING rmq2d\_sparsetable\_\_\_\_\_

input 1: PASSED with cost: 2961.7776 (sprint2: 2961.7776) (baseline: 8994.4592)  
input 2: PASSED with cost: 16860.2464 (sprint2: 16860.2464) (baseline: 52414.1120)  
input 3: PASSED with cost: 92113.7072 (sprint2: 92113.7072) (baseline: 289182.7600)  
input 4: PASSED with cost: 125085.9872 (sprint2: 125085.9872) (baseline: 330169.2336)  
input 5: PASSED with cost: 878957463.0040 (sprint2: 878957463.0040) (baseline: 995120658.5224)

- New Test Cases : input .ll files are in the git repository

FileCheck 1	
Before Optimization	After Optimization

<pre>interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 323.8176 3   Max heap usage (bytes): 40 4</pre>	<pre>interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 136.4704 3   Max heap usage (bytes): 40 4</pre>
FileCheck 2	
Before Optimization	After Optimization
<pre>interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 1073.0656 3   Max heap usage (bytes): 64 4    </pre>	<pre>interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 104.8608 3   Max heap usage (bytes): 64 4</pre>
FileCheck 3	
Before Optimization	After Optimization
<pre>interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 318.5824 3   Max heap usage (bytes): 24 4</pre>	<pre>interpreter &gt; ≡ sf-interpreter.log 1   Returned: 0 2   Cost: 312.2752 3   Max heap usage (bytes): 24 4</pre>

## Progress Report: Jaewook Lee

### [ Sprint 3 ] Global Variable Load/Store Optimization

#### Change in Schedules : Loop Invariant Code Motion for GV Load -> General GV Load/Store Optimization

At first, I was planning to do the optimization only for the loop invariant code motion for global variable load instructions. First idea was just to hoist the load instruction. I noticed in sprint 2 that built-in passes are not hoisting GV load instructions in the loop. However, while implementing LICMGVLoadPass, I noticed that by hoisting several GV load instructions, the same load will be executed in the preheader block, thus causing unnecessary loads. Therefore, I implemented additional optimization that will replace the same load instructions.

Also, I noticed that GV load/store can be found in the AssemblyEmitter stage, which will reduce the cost when reset instruction is emitted before load or store. Therefore, I edited some parts in AssemblyEmitter.cpp.

#### Dones and Not Dones

##### Dones:

For this optimization I imported two important optimizations that are related to the global variables.

##### 1. LICMGVLoadPass

First, I made an optimization pass (function level) for LICM GV Load instructions. For some reason, while importing LICMPass during the sprint 2, the GV load instructions in the loop were not hoisted, although it could be. Therefore, I made this pass to hoist the GV load instructions in the loop to its preheader block. With this pass, the cost caused by repetition of GV Load in the loop is reduced.

LICMGVLoadPass Explanation :

This pass hoists the Global Variable(GV) Load Instruction I in the loop L to the preheader.

Before it hoists the load instruction it checks following conditions :

- a) Loop L has prehead where I can be hoisted.
- b) GV is not updated (stored) in the loop L
- c) No other load instruction that loads same GV is already hoisted  
(if there is one, replace use of I with it)

After hoisting, if GV is stored in the prehead block, use that value without loading it again.

Lastly, remove all the replaced load instructions.

##### 2. Added StackAccess Condition for "reset" instruction

Second, I added stack access conditions to increase the efficient use of "reset" instruction. This 'reset' instruction was implemented by our teammate in the sprint 2. However, we could not track heap/stack access by 100%. While making the pass related to the global variable, I discovered an additional way to track



heap-access(GlobalVariable Load or Store) and added this condition in the AssemblyEmitter.cpp file. This is expected to reduce the cost of head-traveling between stack and heap.

## Test Results:

The cost of test cases that were using global variable in the loop were all reduced as you can see from the capture below. Also, some cases which used global variables but not in the loops were also reduced because of “reset” instruction that was added before its load/store instructions. You can see the increase in the some inputs of rmq2d\_separable. After analyzing the assembly code, I found out that that is because when the global variable’s size is 32, using it directly without loading again will cause some additional bitcast operations. However, since in most cases, cost will be reduced, we decided to keep this optimization.

TESTING bitcount1	TESTING bitcount1
input 1: PASSED with cost: 58.2000, heap usage: 0	input 1: PASSED with cost: 58.2000, heap usage: 0
input 2: PASSED with cost: 333.6000, heap usage: 0	input 2: PASSED with cost: 333.6000, heap usage: 0
input 3: PASSED with cost: 99.0000, heap usage: 0	input 3: PASSED with cost: 99.0000, heap usage: 0
input 4: PASSED with cost: 17.4000, heap usage: 0	input 4: PASSED with cost: 17.4000, heap usage: 0
input 5: PASSED with cost: 27.6000, heap usage: 0	input 5: PASSED with cost: 27.6000, heap usage: 0
TESTING bitcount2	TESTING bitcount2
input 1: PASSED with cost: 85.0256, heap usage: 0	input 1: PASSED with cost: 85.0256, heap usage: 0
input 2: PASSED with cost: 538.7984, heap usage: 0	input 2: PASSED with cost: 538.7984, heap usage: 0
input 3: PASSED with cost: 152.2512, heap usage: 0	input 3: PASSED with cost: 152.2512, heap usage: 0
input 4: PASSED with cost: 17.8000, heap usage: 0	input 4: PASSED with cost: 17.8000, heap usage: 0
input 5: PASSED with cost: 34.6064, heap usage: 0	input 5: PASSED with cost: 34.6064, heap usage: 0
TESTING bitcount3	TESTING bitcount3
input 1: PASSED with cost: 39.0000, heap usage: 0	input 1: PASSED with cost: 39.0000, heap usage: 0
input 2: PASSED with cost: 352.2000, heap usage: 0	input 2: PASSED with cost: 352.2000, heap usage: 0
input 3: PASSED with cost: 93.0000, heap usage: 0	input 3: PASSED with cost: 93.0000, heap usage: 0
input 4: PASSED with cost: 17.4000, heap usage: 0	input 4: PASSED with cost: 17.4000, heap usage: 0
input 5: PASSED with cost: 28.2000, heap usage: 0	input 5: PASSED with cost: 28.2000, heap usage: 0
TESTING bitcount4	TESTING bitcount4
input 1: PASSED with cost: 9030.6656, heap usage: 1024	input 1: PASSED with cost: 9028.5696, heap usage: 1024
input 2: PASSED with cost: 9031.2496, heap usage: 1024	input 2: PASSED with cost: 9029.1536, heap usage: 1024
input 3: PASSED with cost: 9031.4496, heap usage: 1024	input 3: PASSED with cost: 9029.3536, heap usage: 1024
input 4: PASSED with cost: 9030.6368, heap usage: 1024	input 4: PASSED with cost: 9028.5408, heap usage: 1024
input 5: PASSED with cost: 9030.6400, heap usage: 1024	input 5: PASSED with cost: 9028.5440, heap usage: 1024
TESTING bitcount5	TESTING bitcount5
input 1: PASSED with cost: 110.6816, heap usage: 64	input 1: PASSED with cost: 97.2480, heap usage: 64
input 2: PASSED with cost: 236.7088, heap usage: 64	input 2: PASSED with cost: 223.2480, heap usage: 64
input 3: PASSED with cost: 128.7088, heap usage: 64	input 3: PASSED with cost: 115.2512, heap usage: 64
input 4: PASSED with cost: 92.6528, heap usage: 64	input 4: PASSED with cost: 79.2480, heap usage: 64
input 5: PASSED with cost: 110.6560, heap usage: 64	input 5: PASSED with cost: 97.2480, heap usage: 64
TESTING bubble_sort	TESTING bubble_sort
input 1: PASSED with cost: 1873.5584, heap usage: 80	input 1: PASSED with cost: 1873.5584, heap usage: 80
input 2: PASSED with cost: 130274.6176, heap usage: 800	input 2: PASSED with cost: 130274.6176, heap usage: 800
input 3: PASSED with cost: 12714888.8343, heap usage: 8000	input 3: PASSED with cost: 12714888.8343, heap usage: 8000
TESTING collatz	TESTING collatz
input 1: PASSED with cost: 28.2064, heap usage: 0	input 1: PASSED with cost: 28.2064, heap usage: 0
input 2: PASSED with cost: 28.2064, heap usage: 0	input 2: PASSED with cost: 28.2064, heap usage: 0
TESTING gcd	TESTING gcd
input 1: PASSED with cost: 18.2000, heap usage: 0	input 1: PASSED with cost: 18.2000, heap usage: 0
input 2: PASSED with cost: 34.8000, heap usage: 0	input 2: PASSED with cost: 34.8000, heap usage: 0
input 3: PASSED with cost: 68.0000, heap usage: 0	input 3: PASSED with cost: 68.0000, heap usage: 0
input 4: PASSED with cost: 297.8000, heap usage: 0	input 4: PASSED with cost: 297.8000, heap usage: 0
TESTING prime	TESTING prime
input 1: PASSED with cost: 47.1568, heap usage: 40	input 1: PASSED with cost: 47.1568, heap usage: 40
input 2: PASSED with cost: 3169.6672, heap usage: 72	input 2: PASSED with cost: 3102.2976, heap usage: 72
input 3: PASSED with cost: 685431.9616, heap usage: 6040	input 3: PASSED with cost: 679769.4240, heap usage: 6040
input 4: PASSED with cost: 2509506.1536, heap usage: 16472	input 4: PASSED with cost: 2491601.9840, heap usage: 16472
TESTING binary_tree	TESTING binary_tree
input 1: PASSED with cost: 920.3712, heap usage: 144	input 1: PASSED with cost: 920.3712, heap usage: 144
input 2: PASSED with cost: 1764.1488, heap usage: 144	input 2: PASSED with cost: 1772.2448, heap usage: 144
input 3: PASSED with cost: 28084.1280, heap usage: 1176	input 3: PASSED with cost: 28167.2864, heap usage: 1176
input 4: PASSED with cost: 452297.8128, heap usage: 14136	input 4: PASSED with cost: 453944.2224, heap usage: 14136
input 5: PASSED with cost: 1317054853.7856, heap usage: 1660152	input 5: PASSED with cost: 1317395111.0048, heap usage: 1660152
TESTING matmul1	TESTING matmul1
input 1: PASSED with cost: 1080.0608, heap usage: 96	input 1: PASSED with cost: 1080.0608, heap usage: 96
input 2: PASSED with cost: 5593.2960, heap usage: 384	input 2: PASSED with cost: 5593.2960, heap usage: 384
input 3: PASSED with cost: 262675.9968, heap usage: 6144	input 3: PASSED with cost: 262675.9968, heap usage: 6144



```

58 _____ TESTING matmul2 _____
59 input 1: PASSED with cost: 924.9600, heap usage: 96
60 input 2: PASSED with cost: 4607.4304, heap usage: 384
61 input 3: PASSED with cost: 216849.7600, heap usage: 6144
62 _____ TESTING matmul3 _____
63 input 1: PASSED with cost: 2935.5888, heap usage: 384
64 input 2: PASSED with cost: 2935.5888, heap usage: 384
65 input 3: PASSED with cost: 111759.8112, heap usage: 6144
66 _____ TESTING matmul4 _____
67 input 1: PASSED with cost: 4754.8512, heap usage: 384
68 input 2: PASSED with cost: 4754.8512, heap usage: 384
69 input 3: PASSED with cost: 234463.7616, heap usage: 6144
70 _____ TESTING rmq1d_naive _____
71 input 1: PASSED with cost: 112.4976, heap usage: 8
72 input 2: PASSED with cost: 802.5488, heap usage: 16
73 input 3: PASSED with cost: 1220.9936, heap usage: 24
74 input 4: PASSED with cost: 1379.9520, heap usage: 40
75 input 5: PASSED with cost: 470616.1904, heap usage: 400
76 input 6: PASSED with cost: 2125425.9712, heap usage: 2000
77 input 7: PASSED with cost: 404698149.5664, heap usage: 40000
78 _____ TESTING rmq1d_sparsestable _____
79 input 1: PASSED with cost: 810.1176, heap usage: 48
80 input 2: PASSED with cost: 7184.0880, heap usage: 96
81 input 3: PASSED with cost: 10511.9632, heap usage: 104
82 input 4: PASSED with cost: 9290.9248, heap usage: 192
83 input 5: PASSED with cost: 627964.2848, heap usage: 2432
84 input 6: PASSED with cost: 1095536.2560, heap usage: 16128
85 input 7: PASSED with cost: 103543434.6825, heap usage: 494720
86 _____ TESTING rmq2d_naive _____
87 input 1: PASSED with cost: 277.5056, heap usage: 24
88 input 2: PASSED with cost: 1558.0288, heap usage: 32
89 input 3: PASSED with cost: 12268.1504, heap usage: 80
90 input 4: PASSED with cost: 10646.2512, heap usage: 408
91 input 5: PASSED with cost: 3966246.5872, heap usage: 48808
92 _____ TESTING rmq2d_sparsestable _____
93 input 1: PASSED with cost: 2961.7776, heap usage: 64
94 input 2: PASSED with cost: 16860.2464, heap usage: 112
95 input 3: PASSED with cost: 92113.7072, heap usage: 264
96 input 4: PASSED with cost: 125085.9872, heap usage: 2648
97 input 5: PASSED with cost: 878957463.0040, heap usage: 1670984

```

<before optimization>

```

58 _____ TESTING matmul2 _____
59 input 1: PASSED with cost: 924.9600, heap usage: 96
60 input 2: PASSED with cost: 4607.4304, heap usage: 384
61 input 3: PASSED with cost: 216849.7600, heap usage: 6144
62 _____ TESTING matmul3 _____
63 input 1: PASSED with cost: 2929.5504, heap usage: 384
64 input 2: PASSED with cost: 2929.5504, heap usage: 384
65 input 3: PASSED with cost: 111735.6576, heap usage: 6144
66 _____ TESTING matmul4 _____
67 input 1: PASSED with cost: 4527.8304, heap usage: 384
68 input 2: PASSED with cost: 4527.8304, heap usage: 384
69 input 3: PASSED with cost: 219934.4304, heap usage: 6144
70 _____ TESTING rmq1d_naive _____
71 input 1: PASSED with cost: 112.4976, heap usage: 8
72 input 2: PASSED with cost: 802.5488, heap usage: 16
73 input 3: PASSED with cost: 1220.9936, heap usage: 24
74 input 4: PASSED with cost: 1379.9520, heap usage: 40
75 input 5: PASSED with cost: 470616.1904, heap usage: 400
76 input 6: PASSED with cost: 2125425.9712, heap usage: 2000
77 input 7: PASSED with cost: 404698149.5664, heap usage: 40000
78 _____ TESTING rmq1d_sparsestable _____
79 input 1: PASSED with cost: 797.9184, heap usage: 48
80 input 2: PASSED with cost: 6860.5184, heap usage: 96
81 input 3: PASSED with cost: 10075.5920, heap usage: 104
82 input 4: PASSED with cost: 8139.9152, heap usage: 192
83 input 5: PASSED with cost: 601300.2128, heap usage: 2432
84 input 6: PASSED with cost: 900089.2480, heap usage: 16128
85 input 7: PASSED with cost: 86940401.4154, heap usage: 494720
86 _____ TESTING rmq2d_naive _____
87 input 1: PASSED with cost: 248.2368, heap usage: 24
88 input 2: PASSED with cost: 1480.6688, heap usage: 32
89 input 3: PASSED with cost: 12039.2992, heap usage: 80
90 input 4: PASSED with cost: 9245.9648, heap usage: 408
91 input 5: PASSED with cost: 3772717.7728, heap usage: 48808
92 _____ TESTING rmq2d_sparsestable _____
93 input 1: PASSED with cost: 2870.0320, heap usage: 64
94 input 2: PASSED with cost: 16736.2224, heap usage: 112
95 input 3: PASSED with cost: 91865.4720, heap usage: 264
96 input 4: PASSED with cost: 125268.4560, heap usage: 2648
97 input 5: PASSED with cost: 880157411.5775, heap usage: 1670984

```

<after optimization>

- New Test Cases: input.ll files are provided in the git repository

FileCheck 1	
Before Optimization	After Optimization
<pre> 1 Returned: 0 2 Cost: 3743.2048 3 Max heap usage (bytes): 8016 </pre>	<pre> 1 Returned: 0 2 Cost: 2307.5264 3 Max heap usage (bytes): 8016 </pre>
FileCheck 2	
Before Optimization	After Optimization
<pre> 1 Returned: 0 2 Cost: 12021.2368 3 Max heap usage (bytes): 1624 </pre>	<pre> 1 Returned: 0 2 Cost: 9557.8048 3 Max heap usage (bytes): 1624 </pre>
FileCheck 3	

Before Optimization	After Optimization
<pre>1  Returned: 0 2  Cost: 7286.8464 3  Max heap usage (bytes): 16</pre>	<pre>1  Returned: 0 2  Cost: 2854.8832 3  Max heap usage (bytes): 16</pre>

## **Progress Report: Jaeeun Lee**

### **[ Sprint 3] Function Inlining Pass**

#### **Change in Schedules (None)**

Things were accomplished as planned in the previous sprint.

#### **Dones and Not Dones**

##### **Dones:**

Function inlining is a classic technique in program optimization in which a function call is simply replaced with an actual function body. The purpose of this optimization is to reduce function call overhead and to preserve program state, that is, stack and register status, which naturally lead to further overhead reduction.

I needed to be aware of the fact that in sprint 1 and sprint 2, there is a function outlining pass that outlines blocks if the function uses a lot of registers. To make both function inlining and outlining cost-effective, I previously planned and thought it would be right to run the inlining pass before running the outline pass and also trying to target cases only when inlining is cheaper. However, it turns out actually that inlining before outlining reduces costs in more cases. While changing the orders from running the inline pass after outline pass, I could reduce 4 more test cases. So I decided to run the inling pass after the outlining pass.

While there is an existing Function Inlining pass, I decided to implement my own, only targeting cases where the function is 'small enough' to inline. And by meaning 'small enough' it means if the function is declaring less than 14 registers. Also, I made sure that after inlining the targeted functions, I erased useless functions that are not called anymore. However, since the pass is running after the outlining pass, I did not erase the functions that were outlined & then inlined again, due to safety issues

##### **Not Dones:**

Originally, I did try to inline recursively, for example, if there is a function call in another function call, I tried to inline this as well, however I found out that there are many cases that this might actually be quite dangerous & also they increased the costs for many cases, so I did not implement this part on purpose.

#### **Test Results:**

- Existing Test Cases

<pre> 1 jaeun:test jaeuns ./test.sh 2 TESTING bitcount1 3 input 1: PASSED with cost: 58.2000, heap usage: 0 4 input 2: PASSED with cost: 333.6000, heap usage: 0 5 input 3: PASSED with cost: 99.0000, heap usage: 0 6 input 4: PASSED with cost: 37.4000, heap usage: 0 7 input 5: PASSED with cost: 27.6000, heap usage: 0 8 TESTING bitcount2 9 input 1: PASSED with cost: 85.0256, heap usage: 0 10 input 2: PASSED with cost: 538.7904, heap usage: 0 11 input 3: PASSED with cost: 152.2512, heap usage: 0 12 input 4: PASSED with cost: 17.8000, heap usage: 0 13 input 5: PASSED with cost: 34.6864, heap usage: 0 14 TESTING bitcount3 15 input 1: PASSED with cost: 39.0000, heap usage: 0 16 input 2: PASSED with cost: 352.2000, heap usage: 0 17 input 3: PASSED with cost: 93.0000, heap usage: 0 18 input 4: PASSED with cost: 37.4000, heap usage: 0 19 input 5: PASSED with cost: 28.2000, heap usage: 0 20 TESTING bitcount4 21 input 1: PASSED with cost: 9030.6656, heap usage: 1024 22 input 2: PASSED with cost: 9031.2496, heap usage: 1024 23 input 3: PASSED with cost: 9031.4496, heap usage: 1024 24 input 4: PASSED with cost: 9030.6368, heap usage: 1024 25 input 5: PASSED with cost: 9030.6400, heap usage: 1024 26 TESTING bitcount5 27 input 1: PASSED with cost: 110.6816, heap usage: 64 28 input 2: PASSED with cost: 236.7008, heap usage: 64 29 input 3: PASSED with cost: 128.7008, heap usage: 64 30 input 4: PASSED with cost: 92.6528, heap usage: 64 31 input 5: PASSED with cost: 110.6560, heap usage: 64 32 TESTING bubble_sort 33 input 1: PASSED with cost: 1873.5584, heap usage: 80 34 input 2: PASSED with cost: 130274.6376, heap usage: 800 35 input 3: PASSED with cost: 12714888.8343, heap usage: 8000 36 TESTING collatz 37 input 1: PASSED with cost: 28.2064, heap usage: 0 38 input 2: PASSED with cost: 28.2064, heap usage: 0 39 TESTING gcd 40 input 1: PASSED with cost: 18.2000, heap usage: 0 41 input 2: PASSED with cost: 34.8000, heap usage: 0 42 input 3: PASSED with cost: 68.0000, heap usage: 0 43 input 4: PASSED with cost: 297.8000, heap usage: 0 44 TESTING prime 45 input 1: PASSED with cost: 47.1568, heap usage: 40 46 input 2: PASSED with cost: 3169.6672, heap usage: 72 47 input 3: PASSED with cost: 685431.9616, heap usage: 6040 48 input 4: PASSED with cost: 2509586.1536, heap usage: 16472 49 TESTING binary_tree 50 input 1: PASSED with cost: 920.3712, heap usage: 144 51 input 2: PASSED with cost: 9764.1408, heap usage: 144 52 TESTING matmul3 53 input 1: PASSED with cost: 2935.5888, heap usage: 384 54 input 2: PASSED with cost: 2935.5888, heap usage: 384 55 input 3: PASSED with cost: 111759.8112, heap usage: 6144 56 TESTING matmul4 57 input 1: PASSED with cost: 4754.8512, heap usage: 384 58 input 2: PASSED with cost: 4754.8512, heap usage: 384 59 input 3: PASSED with cost: 234463.7616, heap usage: 6144 60 TESTING rmq1d_naive 61 input 1: PASSED with cost: 112.4976, heap usage: 8 62 input 2: PASSED with cost: 802.5488, heap usage: 16 63 input 3: PASSED with cost: 1220.9936, heap usage: 24 64 input 4: PASSED with cost: 1379.9520, heap usage: 40 65 input 5: PASSED with cost: 470616.1904, heap usage: 400 66 input 6: PASSED with cost: 2125425.9712, heap usage: 2000 67 input 7: PASSED with cost: 404698149.5664, heap usage: 40000 68 TESTING rmq1d_sparsestable 69 input 1: PASSED with cost: 810.1376, heap usage: 48 70 input 2: PASSED with cost: 7184.0880, heap usage: 96 71 input 3: PASSED with cost: 10511.9632, heap usage: 104 72 input 4: PASSED with cost: 9200.9248, heap usage: 192 73 input 5: PASSED with cost: 627964.2848, heap usage: 2432 74 input 6: PASSED with cost: 1095536.2560, heap usage: 16128 75 input 7: PASSED with cost: 103543434.6825, heap usage: 494720 76 TESTING rmq2d_naive 77 input 1: PASSED with cost: 277.5056, heap usage: 24 78 input 2: PASSED with cost: 1558.0288, heap usage: 32 79 input 3: PASSED with cost: 12268.1504, heap usage: 80 80 input 4: PASSED with cost: 10466.2512, heap usage: 408 81 input 5: PASSED with cost: 3966246.5872, heap usage: 48808 82 TESTING rmq2d_sparsestable 83 input 1: PASSED with cost: 2961.7776, heap usage: 64 84 input 2: PASSED with cost: 16868.2464, heap usage: 112 85 input 3: PASSED with cost: 92133.7072, heap usage: 264 86 input 4: PASSED with cost: 125085.9872, heap usage: 2648 87 input 5: PASSED with cost: 878957463.0040, heap usage: 1670984 </pre>	<pre> 1 jaeun:test jaeuns ./test.sh 2 TESTING bitcount1 3 input 1: PASSED with cost: 54.2000, heap usage: 0 4 input 2: PASSED with cost: 329.6000, heap usage: 0 5 input 3: PASSED with cost: 95.0000, heap usage: 0 6 input 4: PASSED with cost: 13.4000, heap usage: 0 7 input 5: PASSED with cost: 23.6000, heap usage: 0 8 TESTING bitcount2 9 input 1: PASSED with cost: 85.0256, heap usage: 0 10 input 2: PASSED with cost: 538.7904, heap usage: 0 11 input 3: PASSED with cost: 152.2512, heap usage: 0 12 input 4: PASSED with cost: 17.8000, heap usage: 0 13 input 5: PASSED with cost: 34.6864, heap usage: 0 14 TESTING bitcount3 15 input 1: PASSED with cost: 35.0000, heap usage: 0 16 input 2: PASSED with cost: 348.2000, heap usage: 0 17 input 3: PASSED with cost: 89.0000, heap usage: 0 18 input 4: PASSED with cost: 13.4000, heap usage: 0 19 input 5: PASSED with cost: 24.2000, heap usage: 0 20 TESTING bitcount4 21 input 1: PASSED with cost: 9030.6656, heap usage: 1024 22 input 2: PASSED with cost: 9031.2496, heap usage: 1024 23 input 3: PASSED with cost: 9031.4496, heap usage: 1024 24 input 4: PASSED with cost: 9030.6368, heap usage: 1024 25 input 5: PASSED with cost: 9030.6400, heap usage: 1024 26 TESTING bitcount5 27 input 1: PASSED with cost: 110.6816, heap usage: 64 28 input 2: PASSED with cost: 236.7008, heap usage: 64 29 input 3: PASSED with cost: 128.7008, heap usage: 64 30 input 4: PASSED with cost: 92.6528, heap usage: 64 31 input 5: PASSED with cost: 110.6560, heap usage: 64 32 TESTING bubble_sort 33 input 1: PASSED with cost: 1806.3696, heap usage: 80 34 input 2: PASSED with cost: 129770.2448, heap usage: 800 35 input 3: PASSED with cost: 12708587.0215, heap usage: 8000 36 TESTING collatz 37 input 1: PASSED with cost: 28.2064, heap usage: 0 38 input 2: PASSED with cost: 28.2064, heap usage: 0 39 TESTING gcd 40 input 1: PASSED with cost: 18.2000, heap usage: 0 41 input 2: PASSED with cost: 34.8000, heap usage: 0 42 input 3: PASSED with cost: 68.0000, heap usage: 0 43 input 4: PASSED with cost: 297.8000, heap usage: 0 44 TESTING prime 45 input 1: PASSED with cost: 47.1600, heap usage: 40 46 input 2: PASSED with cost: 3065.8560, heap usage: 72 47 input 3: PASSED with cost: 685421.5904, heap usage: 6040 48 input 4: PASSED with cost: 2509495.7824, heap usage: 16472 49 TESTING binary_tree 50 input 1: PASSED with cost: 920.3712, heap usage: 144 51 input 2: PASSED with cost: 9764.1408, heap usage: 144 52 TESTING matmul3 53 input 1: PASSED with cost: 2935.5888, heap usage: 384 54 input 2: PASSED with cost: 2935.5888, heap usage: 384 55 input 3: PASSED with cost: 111759.8112, heap usage: 6144 56 TESTING matmul4 57 input 1: PASSED with cost: 4754.8512, heap usage: 384 58 input 2: PASSED with cost: 4754.8512, heap usage: 384 59 input 3: PASSED with cost: 234463.7616, heap usage: 6144 60 TESTING rmq1d_naive 61 input 1: PASSED with cost: 107.4976, heap usage: 8 62 input 2: PASSED with cost: 752.5488, heap usage: 16 63 input 3: PASSED with cost: 1145.9936, heap usage: 24 64 input 4: PASSED with cost: 1329.9520, heap usage: 40 65 input 5: PASSED with cost: 465616.1904, heap usage: 400 66 input 6: PASSED with cost: 2120425.9712, heap usage: 2000 67 input 7: PASSED with cost: 404648149.5664, heap usage: 40000 68 TESTING rmq1d_sparsestable 69 input 1: PASSED with cost: 800.0256, heap usage: 48 70 input 2: PASSED with cost: 7165.9728, heap usage: 96 71 input 3: PASSED with cost: 10493.8448, heap usage: 104 72 input 4: PASSED with cost: 9268.8000, heap usage: 192 73 input 5: PASSED with cost: 627930.0160, heap usage: 2432 74 input 6: PASSED with cost: 1095493.3472, heap usage: 16128 75 input 7: PASSED with cost: 103543356.5737, heap usage: 494720 76 TESTING rmq2d_naive 77 input 1: PASSED with cost: 272.5056, heap usage: 24 78 input 2: PASSED with cost: 1508.0288, heap usage: 32 79 input 3: PASSED with cost: 11768.1504, heap usage: 80 80 input 4: PASSED with cost: 10466.2512, heap usage: 408 81 input 5: PASSED with cost: 3945901.5872, heap usage: 48808 82 TESTING rmq2d_sparsestable 83 input 1: PASSED with cost: 2875.4016, heap usage: 64 84 input 2: PASSED with cost: 15943.6768, heap usage: 112 85 input 3: PASSED with cost: 86586.9296, heap usage: 264 86 input 4: PASSED with cost: 100808.2912, heap usage: 2648 87 input 5: PASSED with cost: 632796201.1241, heap usage: 1670984 </pre>
--	--

<before optimization>

<after optimization>

- New Test Cases : input .ll files are in the git repository

FileCheck 1	
Before Optimization	After Optimization

Returned: 0 Cost: 5225.9296 Max heap usage (bytes): 400	Returned: 0 Cost: 5028.6208 Max heap usage (bytes): 400
FileCheck 2	
Before Optimization	After Optimization
Returned: 0 Cost: 5292.8032 Max heap usage (bytes): 400	Returned: 0 Cost: 5091.0144 Max heap usage (bytes): 400
FileCheck 3	
Before Optimization	After Optimization
Returned: 0 Cost: 5288.8032 Max heap usage (bytes): 400	Returned: 0 Cost: 5090.5872 Max heap usage (bytes): 400