```
[harshithaj@Harshithas-MacBook-Air-2 dsa % gcc lab4.c -o out4
[harshithaj@Harshithas-MacBook-Air-2 dsa % ./out4
 Linked List:
 10 -> 20 -> 25 -> 30 -> NULL
[harshithaj@Harshithas-MacBook-Air-2 dsa % gcc lab5.c -o out5
[harshithaj@Harshithas-MacBook-Air-2 dsa % ./out5
 Linked List after deletion:
 NULL
[harshithaj@Harshithas-MacBook-Air-2 dsa % gcc lab6.c -o out6
[harshithaj@Harshithas-MacBook-Air-2 dsa % ./out6
 Doubly Linked List:
 10 <-> 20 <-> 25 <-> 30 <-> NULL
[harshithaj@Harshithas-MacBook-Air-2 dsa % gcc lab7.c -o out7
[harshithaj@Harshithas-MacBook-Air-2 dsa % ./out7
 Backward Traversal:
 30 <-> 10 <-> NULL
[harshithaj@Harshithas-MacBook-Air-2 dsa % gcc lab8.c -o out8
[harshithaj@Harshithas-MacBook-Air-2 dsa % ./out8
 Circular List:
 30 -> 20 -> 10 -> (back to head)
[harshithaj@Harshithas-MacBook-Air-2 dsa % gcc lab9.c -o out9
[harshithaj@Harshithas-MacBook-Air-2 dsa % ./out9
 Circular List after deletion:
 10 -> 30 -> (back to head)
```