```
10 -> 30 -> (back to head)
[harshithaj@Harshithas-MacBook-Air-2 dsa % gcc lab10.c -o out10
[harshithaj@Harshithas-MacBook-Air-2 dsa % ./out10
 Top element = 30
 Popped element = 30
 Top element = 20
 Stack is not empty
[harshithaj@Harshithas-MacBook-Air-2 dsa % gcc lab11.c -o out11
[harshithaj@Harshithas-MacBook-Air-2 dsa % ./out11
 10 -> 20 -> 30 -> NULL
 Front element = 10
 Queue is not empty
[harshithaj@Harshithas-MacBook-Air-2 dsa % gcc lab12.c -o out12
[harshithaj@Harshithas-MacBook-Air-2 dsa % ./out12
 10 pushed to stack
 20 pushed to stack
 30 pushed to stack
 Top element is: 30
 Popped element: 30
 Popped element: 20
 Stack is not empty
[harshithaj@Harshithas-MacBook-Air-2 dsa % gcc lab13.c -o out13
[harshithaj@Harshithas-MacBook-Air-2 dsa % ./out13
 Queue: 10 20 30 40 50
 Deleted element = 10
 Deleted element = 20
 Queue: 30 40 50
 Front element = 30
 Queue is not empty
```