

| Comment | Description | Designator | Footprint | LibRef | Quantity |
|--------------------------|--|--|-------------------------------|--------------------------|----------|
| CL10A106MP8NNNC | CAP CER 10UF 10V | C1, C17, C26 | 0603[1608] | CL10A106MP8NNNC | 3 |
| CGA3E2X7R1E104K08 0AA | X5R 0603 CAP CER 0.1UF 25V X7R 0603 | C2, C3, C4, C5, C18, C22, C23, C24, C27, C28 | 0603[1608] | CGA3E2X7R1E104K08 0AA | 10 |
| CL10A105KP8NNNC | CAP CER 1UF 10V X5R 0603 | C6 | 0603[1608] | CL10A105KP8NNNC | 1 |
| CGA3E2X7R1H103K08 0AA | CAP CER 10000PF 50V X7R 0603 | C7 | 0603[1608] | CGA3E2X7R1H103K08 0AA | 1 |
| 06035A240JAT2A | CAP CER 24PF 50V NPO 0603 | C8, C9 | 0603[1608] | 06035A240JAT2A | 2 |
| C1608X5R1C225K080 AB | CAP CER 2.2UF 16V X5R 0603 | C10, C11 | 0603[1608] | C1608X5R1C225K080 AB | 2 |
| | CAP CER 10000PF 50V COG/NPO 0603 | C19 | 0603[1608] | GRM1885C1H103JA01 | 1 |
| TAJD157K016RNJ | CAP TANT 150UF 10% 16V 2917 | C25 | TAJD157K016RNJ | TAJD157K016RNJ | 1 |
| CDSOD323-T12C | TVS DIODE 12V 28.3V SOD323 | D1, D5 | CDSOD323-T12C | CDSOD323-T12C | 2 |
| LTST-C191KGKT | LED GREEN CLEAR SMD 0603 | D2, D3, D4 | LTST-C191KGKT | LTST-C191KGKT | 3 |
| SF-0603FP500M-2 | FUSE BOARD MOUNT 5A 32VDC 0603 | F1, F2 | SF-0603FP500M-2 | SF-0603FP500M-2 | 2 |
| TSW-106-07-G-D | 0.025" SQ Post Header, Through-hole, Vertical, -55 to 125 degC, 2.54 mm Pitch, 12-Pin, Male, RoHS | 11 | SMTC-TSW-106-07-X-D | CMP-1024-00379-1 | 1 |
| 5745782-4 | Female D-Sub Connector, Pitch 2.74 mm, 2 Row, 15 Position, Height 12.93 mm, Tail Length 3.18 mm, -55 to 105 degC, RoHS, Tray | J2 | TECO-5745782-4_V | CMP-2000-05646-1 | 1 |
| SSW-104-01-F-S | CONN RCPT 4POS FEMALE 0.1 GOLD PCB | J3 | SSW-104-01-F-S | SSW-104-01-F-S | 1 |
| SSW-106-01-F-S | CONN RCPT 6POS FEMALE 0.1 GOLD PCB | J4, J7, J8 | SSW-106-01-F-S | SSW-106-01-F-S | 3 |
| SSW-108-01-F-S | CONN RCPT 8POS FEMALE 0.1 GOLD PCB | J5, J6 | SSW-108-01-F-S | SSW-108-01-F-S | 2 |
| 0430450400 | CONN HEADER R/A 4POS 3MM | J9 | 0430450400 | 0430450400 | 1 |
| 43045-0427 | Checked Conn Header 4 POS 3mm Solder ST Thru-Hole 4 Terminal 1 Port Micro-Fit 3.0 Tray Headers and Wire Housings 0.735 | J10 | 43045-0427 | 43045-0427 | 1 |
| CPT-9019S-SMT | 9 mm, 25 Vp-p Vdc, 65 dB, Surface Mount _SMT_, Piezo Audio Transducer Buzzer | LS | CUI_CPT-9019S-SMT | CPT-9019S-SMT | 1 |
| RC0603FR-0730KL | RES SMD 30K OHM 1% 1/10W 0603 | R1 | 0603[1608] | RC0603FR-0730KL | 1 |
| ERJ-3GEYJ103V | RES SMD 10K OHM 5% 1/10W 0603 | R2, R6, R11, R15, R16, R17, R18 | 0603[1608] | ERJ-3GEYJ103V | 7 |
| RC1608F331CS | RES SMD 330 OHM 1% 1/10W 0603 | R3, R4, R5, R7, R8 | 0603[1608] | RC1608F331CS | 5 |
| RT0603DRE076K49L | RES SMD 6.49KOHM 0.5% 1/10W 0603 | R19, R20 | 0603[1608] | RT0603DRE076K49L | 2 |
| STM32F405RGT6 | IC MCU 32BIT 1MB FLASH 64LQFP | U1 | TSQFP50P1200X1200X 160-64N | STM32F405RGT6 | 1 |
| LSM9DS1TR | IMU ACCEL/GYRO/MAG I2C/SPI 24LGA | U3 | LSM9DS1TR | LSM9DS1TR | 1 |
| MC14504BDR2G | IC TRNSLTR UNIDIRECTIONAL 16SOIC | U4 | MC14504BDR2G | MC14504BDR2G | 1 |
| MS560702BA03-50 | BAROMETRIC PRESSURE SENSOR | U5 | MS560702BA03-50 | MS560702BA03-50 | 1 |
| W25Q16JVSSIQ | FLASH - NOR Memory IC 16Mb _2M x 8_ SPI - Quad I/O 133MHz 8- SOIC | U6 | W25Q16JVSSIQ | W25Q16JVSSIQ | 1 |
| ABLS-8.000MHZ-B2-T | CRYSTAL 8.0000MHZ 18PF SMD | Y1 | ABLS-8.000MHZ-B2-T | ABLS-8.000MHZ-B2-T | 1 |