

Studlet Frontend

This is a React frontend for the Studlet application. It is built with TypeScript programming language and Create React App script. Also it uses `react-router` for client-side routing `bootstrap` for styling and `react-bootstrap` for bootstrap components in React, and `axios` for HTTP requests, and `react-cookie` for handling cookies.

Documentation is generated using typedoc and typedoc-plugin-markdown. And then it is merged using concat-md and pandoc to convert it to a pdf file.

Folder Structure

The project is organized as follows:

- `public/`: static resources, such as images and the favicon
- `src/`: the source code for the frontend
 - `img/`: folder with images used by the typescript code
 - `model/`: data models for the app
 - `setupTests.ts`: Jest setup file
 - `App.tsx`: the main application component
 - `index.tsx`: the entry point for the app
 - `*.tsx`: other TypeScript files in the src directory with components
- `.env`: environment variables for the app (see below)

Cloning the Repository

To clone the repository, run the following command:

```
git clone https://github.com/StudletOrg/StudletFrontend.git
```

Environment Variables

The app expects the following environment variables to be set:

- `REACT_APP_API_URL`: the URL of the Studlet Backend API server

To set these variables, create a `.env` file in the root of the project and add the following lines:

```
REACT_APP_API_URL="http://localhost:8080"
```

Running the App

To run the app, navigate to the root of the project and run the following command:

```
npm start
```

This will start the development server and open the app in a browser.

Table of Contents

- Add Grade
 - AddGrade
 - * Index
 - Functions
 - * Function: default()
- Add Student To Group
 - AddStudentToGroup
 - * Index
 - Functions
 - * Function: default()
- App Test
 - App.test
- App
 - App
 - * Index
 - Functions
 - * Function: default()
- App Navbar
 - AppNavbar
 - * Index
 - Functions
 - * Function: default()
 - Interfaces
 - * Interface: ThisStudent
- Create Note
 - CreateNote
 - * Index
 - Functions
 - * Function: default()
- Dashboard
 - Dashboard
 - * Index
 - Functions
 - * Function: default()
 - Interfaces
 - * Interface: DashboardSubjectsProp
 - * Interface: Subject
- Dashboard Card
 - DashboardCard
 - * Index
 - Functions
 - * Function: default()
- Error
 - Error

- * Index
 - Functions
 - * Function: default()
- Font Size Changer
 - FontSizeChanger
 - * Index
 - Functions
 - * Function: default()
 - Type Aliases
 - * Type Alias: FontSizeType
- Grades
 - Grades
 - * Index
 - Functions
 - * Function: default()
- Group Details
 - GroupDetails
 - * Index
 - Functions
 - * Function: default()
- Home
 - Home
 - * Index
 - Functions
 - * Function: default()
- Login Form
 - LoginForm
 - * Index
 - Functions
 - * Function: default()
- Logo
 - Logo
 - * Index
 - Functions
 - * Function: default()
- Studlet Frontend
 - Folder Structure
 - Cloning the Repository
 - Environment Variables
 - Running the App
- Register Form
 - RegisterForm
 - * Index
 - Functions
 - * Function: default()
 - Interfaces

- * Interface: RegisterData
 - Type Aliases
 - * Type Alias: RegisterFormProps
 - * Type Alias: RoleType
- Side Menu
 - SideMenu
 - * Index
 - Functions
 - * Function: default()
- Student Groups
 - StudentGroups
 - * Index
 - Functions
 - * Function: default()
- Teacher Grades
 - TeacherGrades
 - * Index
 - Functions
 - * Function: default()
- User Details
 - UserDetails
 - * Index
 - Functions
 - * Function: default()
 - Interfaces
 - * Interface: Student
- Validation
 - Validation
 - * Index
 - Variables
 - * Variable: emailRegex
 - * Variable: passwordRegex
- Documents
 - Studlet Frontend
 - * Folder Structure
 - * Cloning the Repository
 - * Environment Variables
 - * Running the App
- Index
 - index
- Model
 - Grade
 - * model/Grade
 - * Interfaces
 - Group
 - * model/Group

- * Interfaces
 - Student
 - * model/Student
 - * Interfaces
- studlet v0.1.0
 - Documents
 - Modules

Add Grade

studlet v0.1.0 • Docs

studlet v0.1.0 / AddGrade

AddGrade

Index

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / AddGrade / default

Function: default()

default(): Element

A React component for adding a grade for a specific student in a specific group.

This component retrieves the group ID and student ID from the URL parameters, allows the user to select a grade from a dropdown, and submits the grade to the server. It handles success and error messages based on the submission result.

Returns Element

The rendered component.

Component

Example

```
// Usage
<AddGrade />
```

State `gradeValue` - The selected grade value, which can be a number or an empty string.

State `success` - A message indicating successful grade addition, or null if no message.

State `error` - A message indicating an error during grade addition, or null if no message.

Defined in `src/AddGrade.tsx:29`

Add Student To Group

studlet v0.1.0 • Docs

studlet v0.1.0 / AddStudentToGroup

AddStudentToGroup

Index

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / AddStudentToGroup / default

Function: default()

default(): Element

A React component for adding a student to a specific group.

This component retrieves the group ID and field of study ID from the URL parameters, allows the user to search for students by name, last name and email, and submits the selected student to the server to be added to the group. It handles success and error messages based on the submission result.

Returns `Element`

The rendered component.

Component

State `message` - A message indicating successful student addition, or null if no message.

State `error` - A message indicating an error during student addition, or null if no message.

State `students` - An array of students to be displayed in the list.

State `filterText` - The text entered by the user to filter the student list.

Defined in `src/AddStudentToGroup.tsx:28`

App Test

studlet v0.1.0 • Docs

studlet v0.1.0 / App.test

App.test

App

studlet v0.1.0 • Docs

studlet v0.1.0 / App

App

Index

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / App / default

Function: default()

default(): Element

The main application component.

This component is the root of the application and is responsible for rendering the main layout.

Returns Element

The main application component.

Defined in src/App.tsx:79

App Navbar

studlet v0.1.0 • Docs

studlet v0.1.0 / AppNavbar

AppNavbar

Index

Interfaces

- ThisStudent

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / AppNavbar / default

Function: `default()`

`default(props): null | ReactElement<any, any>`

A navigation bar component that is used in the main application layout.

This component assumes that the user is already authenticated and that the authentication token is stored in the local storage under the key 'jwtToken'.

The component displays the user name and a logout button. When the logout button is clicked, the component removes the authentication token from the local storage and calls the `onLogout` function if it is provided.

Parameters • `props: AppNavbarProps`

The component props.

Returns `null | ReactElement<any, any>`

A navigation bar React element.

Defined in `src/AppNavbar.tsx:55`

Interfaces

studlet v0.1.0 • **Docs**

studlet v0.1.0 / AppNavbar / ThisStudent

Interface: **ThisStudent**

Represents a student with personal information and roles.

ThisStudent

Properties

dateofbirth

dateofbirth: `Date`

The date of birth of the student.

Defined in

`src/AppNavbar.tsx:36`

email

email: `string`

The email address of the student.

Defined in

src/AppNavbar.tsx:35

firstname

firstname: `string`

The first name of the student.

Defined in

src/AppNavbar.tsx:33

id

id: `number`

The unique identifier for the student.

Defined in

src/AppNavbar.tsx:37

lastname

lastname: `string`

The last name of the student.

Defined in

src/AppNavbar.tsx:34

roles

roles: `[string]`

An array of roles assigned to the student (e.g., ["student", "member"]).

Defined in

src/AppNavbar.tsx:38

Create Note

studlet v0.1.0 • Docs

studlet v0.1.0 / CreateNote

CreateNote

Index

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / CreateNote / default

Function: default()

default(): Element

A React component for creating a new note for a specific group.

This component retrieves the group ID from the URL parameters, allows the user to enter a title and content for the note, and submits the note to the server. It handles success and error messages based on the submission result.

Returns Element

The rendered component.

Component

Example

```
// Usage
<CreateNote />
```

State title - The title of the note, which can be an empty string.

State content - The content of the note, which can be an empty string.

State groups - The list of groups associated with the user.

State selectedGroupId - The ID of the selected group, which can be null.

State success - A message indicating successful note creation, or null if no message.

State error - A message indicating an error during note creation, or null if no message.

Defined in src/CreateNote.tsx:40

Dashboard

studlet v0.1.0 • Docs

studlet v0.1.0 / Dashboard

Dashboard

Index

Interfaces

- DashboardSubjectsProp
- Subject

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / Dashboard / default

Function: default()

default(): Element

Returns Element

Defined in src/Dashboard.tsx:51

Interfaces

studlet v0.1.0 • Docs

studlet v0.1.0 / Dashboard / DashboardSubjectsProp

Interface: DashboardSubjectsProp

Properties

subjects?

optional subjects: Subject[]

Defined in

src/Dashboard.tsx:36

studlet v0.1.0 • Docs

studlet v0.1.0 / Dashboard / Subject

Interface: Subject

Properties

id

id: number

Defined in

src/Dashboard.tsx:31

nazwa

nazwa: string

Defined in

src/Dashboard.tsx:32

Dashboard Card

studlet v0.1.0 • Docs

studlet v0.1.0 / DashboardCard

DashboardCard

Index

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / DashboardCard / default

Function: default()

default(props): Element

A React component that renders a card for displaying grades or related information.

This component accepts props to customize the title, body content, CSS class, and inline styles.

Parameters • **props: GradesCardProps**

The properties for the DashboardCard component.

Returns Element

The rendered card component.

Component

Defined in src/DashboardCard.tsx:30

Error

studlet v0.1.0 • Docs

studlet v0.1.0 / Error

Error

Index

Functions

- [default](#)

Functions

[studlet v0.1.0](#) • [Docs](#)

[studlet v0.1.0](#) / [Error](#) / [default](#)

Function: `default()`

`default()`: `Element`

Renders a 404 error page with a link to navigate back to the home page.

This component displays a message indicating that the requested page could not be found, along with a navigation link for the user to return to the home page.

Returns `Element`

A JSX element representing the 404 error page.

Defined in `src/Error.tsx:12`

Font Size Changer

[studlet v0.1.0](#) • [Docs](#)

[studlet v0.1.0](#) / [FontSizeChanger](#)

FontSizeChanger

Index

Type Aliases

- [FontSizeType](#)

Functions

- [default](#)

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / FontSizeChanger / default

Function: default()

default(props): Element

A React component for changing the font size of the application.

This component allows users to select a font size from three options: normal, large, and extra-large. The selected font size is stored in a cookie, which persists across sessions.

Parameters • **props: FontSizeChangerProps**

The properties for the FontSizeChanger component.

Returns **Element**

The rendered font size changer component.

Component

Defined in src/FontSizeChanger.tsx:37

Type Aliases

studlet v0.1.0 • Docs

studlet v0.1.0 / FontSizeChanger / FontSizeType

Type Alias: FontSizeType

FontSizeType: "normal" | "large" | "extralarge"

Represents the available font size options.

Defined in src/FontSizeChanger.tsx:13

Grades

studlet v0.1.0 • Docs

studlet v0.1.0 / Grades

Grades

Index

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / Grades / default

Function: default()

default(): Element

A React component that displays all grades for the current student.

This component fetches the current user's data and their associated grades from the API. It groups the grades by their respective group IDs and displays them in a structured format.

Returns Element

The rendered component displaying the student's grades.

Component

Defined in src/Grades.tsx:50

Group Details

studlet v0.1.0 • Docs

studlet v0.1.0 / GroupDetails

GroupDetails

Index

Functions

- [default](#)

Functions

[studlet v0.1.0](#) • [Docs](#)

[studlet v0.1.0](#) / [GroupDetails](#) / [default](#)

Function: `default()`

`default()`: `Element`

GroupDetails component that displays information about a specific group.

This component fetches and displays details of a group, including the group ID, number of students, subject, professor information, grades, and announcements. It handles loading states and error handling for API requests.

Returns `Element`

The rendered GroupDetails component, which shows group information, grades, and announcements.

Component

Defined in `src/GroupDetails.tsx:27`

Home

[studlet v0.1.0](#) • [Docs](#)

[studlet v0.1.0](#) / [Home](#)

Home

Index

Functions

- [default](#)

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / Home / default

Function: default()

default(): Element

Home component that determines whether to display the Dashboard or the LoginForm.

This component checks for the presence and validity of a JWT token in cookies to determine if the user is logged in. If the token is valid, it renders the Dashboard; otherwise, it renders the LoginForm.

Returns Element

The rendered Home component, which conditionally displays either the Dashboard or the LoginForm based on the user's authentication status.

Component

Defined in src/Home.tsx:19

Login Form

studlet v0.1.0 • Docs

studlet v0.1.0 / LoginForm

LoginForm

Index

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / LoginForm / default

Function: default()

default(): Element

LoginForm component for user authentication.

This component allows users to log in by providing their email and password. It handles form submission, validation, and error display.

Returns Element

The rendered LoginForm component.

Component

Defined in src/LoginForm.tsx:28

Logo

studlet v0.1.0 • Docs

studlet v0.1.0 / Logo

Logo**Index****Functions**

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / Logo / default

Function: default()

default(): Element

Logo component that displays the application logo and name.

This component renders an image and a text label side by side, representing the branding of the application.

Returns Element

The rendered Logo component, which includes an image and the application name.

Component

Defined in `src/Logo.tsx:13`

studlet v0.1.0 • Docs

Studlet Frontend

This is a React frontend for the Studlet platform. It is built with Create React App and uses React Router for client-side routing.

Folder Structure

The project is organized as follows:

- `public/`: static resources, such as images and the favicon
- `src/`: the source code for the frontend
 - `img/`: folder with images used by the typescript code
 - `model/`: data models for the app
 - `setupTests.ts`: Jest setup file
 - `App.tsx`: the main application component
 - `index.tsx`: the entry point for the app
 - `*.tsx`: other TypeScript files in the `src` directory with components
- `.env`: environment variables for the app (see below)

Cloning the Repository

To clone the repository, run the following command:

```
git clone https://github.com/StudletOrg/StudletFrontend.git
```

Environment Variables

The app expects the following environment variables to be set:

- `REACT_APP_API_URL`: the URL of the Studlet Backend API server

To set these variables, create a `.env` file in the root of the project and add the following lines:

```
REACT_APP_API_URL="http://localhost:8080"
```

Running the App

To run the app, navigate to the root of the project and run the following command:

```
npm start
```

This will start the development server and open the app in a browser.

Register Form

studlet v0.1.0 • Docs

studlet v0.1.0 / RegisterForm

RegisterForm

Index

Interfaces

- RegisterData

Type Aliases

- RegisterFormProps
- RoleType

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / RegisterForm / default

Function: default()

default(props): Element

RegisterForm component for user registration.

This component provides a form for users to register by entering their personal information and account credentials. It includes validation for the input fields and handles form submission.

Parameters • **props:** RegisterFormProps

The props for the RegisterForm component.

Returns Element

The rendered RegisterForm component.

Component

Defined in src/RegisterForm.tsx:61

Interfaces

studlet v0.1.0 • Docs

studlet v0.1.0 / RegisterForm / RegisterData

Interface: RegisterData

Interface representing the data required for user registration.

This interface defines the structure of the registration data, including personal information and account credentials.

RegisterData

Properties

confirmPassword

confirmPassword: string

The password confirmation for validation.

Defined in

src/RegisterForm.tsx:27

email

email: string

The email address of the user.

Defined in

src/RegisterForm.tsx:25

firstName

firstName: `string`

The first name of the user.

Defined in

`src/RegisterForm.tsx:23`

lastName

lastName: `string`

The last name of the user.

Defined in

`src/RegisterForm.tsx:24`

password

password: `string`

The password chosen by the user.

Defined in

`src/RegisterForm.tsx:26`

role

role: `RoleType`

The role assigned to the user (e.g., student, teacher, moderator).

Defined in

`src/RegisterForm.tsx:28`

Type Aliases

studlet v0.1.0 • Docs

studlet v0.1.0 / RegisterForm / RegisterFormProps

Type Alias: RegisterFormProps

RegisterFormProps: object

Type representing the props for the RegisterForm component.

Type declaration

onCancel()?

optional **onCancel:** () => void

Returns

void

onRegister()?

optional **onRegister:** (data) => void

Parameters

- **data:** RegisterData

Returns

void

Defined in src/RegisterForm.tsx:38

studlet v0.1.0 • Docs

studlet v0.1.0 / RegisterForm / RoleType

Type Alias: RoleType

RoleType: "student" | "teacher" | "moderator"

Type representing the possible roles for a user.

Defined in src/RegisterForm.tsx:48

Side Menu

studlet v0.1.0 • Docs

studlet v0.1.0 / SideMenu

SideMenu

Index

Functions

- [default](#)

Functions

[studlet v0.1.0](#) • [Docs](#)

[studlet v0.1.0](#) / [SideMenu](#) / [default](#)

Function: default()

default(props): `null | ReactElement<any, any>`

SideMenu component that renders the navigation menu.

This component displays a vertical navigation menu based on the user's roles. It includes default menu options and additional options for professors. The active link is highlighted based on the current location.

Parameters • props

Returns `null | ReactElement<any, any>`

The rendered SideMenu component containing navigation links.

Component

Defined in `src/SideMenu.tsx:44`

Student Groups

[studlet v0.1.0](#) • [Docs](#)

[studlet v0.1.0](#) / [StudentGroups](#)

StudentGroups

Index

Functions

- [default](#)

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / StudentGroups / default

Function: default()

default(): Element

StudentGroups component that displays the groups a student is assigned to.

This component fetches and displays the student's groups, including details about the group number, professor, and student count. It handles loading states and displays a message if no groups are found.

Returns Element

The rendered StudentGroups component, which shows the student's assigned groups.

Component

Defined in src/StudentGroups.tsx:48

Teacher Grades

studlet v0.1.0 • Docs

studlet v0.1.0 / TeacherGrades

TeacherGrades

Index

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / TeacherGrades / default

Function: default()

default(): Element

A component that displays the grades of students in selected groups.

This component fetches groups and their associated students with grades from an API. It allows teachers to view, add, edit, and remove grades for students.

Returns Element

The rendered TeacherGrades component.

Component

Defined in src/TeacherGrades.tsx:70

User Details

studlet v0.1.0 • Docs

studlet v0.1.0 / UserDetails

UserDetails

Index

Interfaces

- Student

Functions

- default

Functions

studlet v0.1.0 • Docs

studlet v0.1.0 / UserDetails / default

Function: default()

default(): Element

A component that displays the details of the current user (student).

This component fetches the current user's data from an API and displays the user's details including ID, name, date of birth, email, and roles.

Returns `Element`

The rendered UserDetails component.

Component

Defined in `src/UserDetails.tsx:35`

Interfaces

studlet v0.1.0 • Docs

studlet v0.1.0 / UserDetails / Student

Interface: Student

Represents a student user. Student

Properties

dateofbirth

dateofbirth: `string`

The date of birth of the student as a string.

Defined in

`src/UserDetails.tsx:22`

email

email: `string`

The email address of the student.

Defined in

`src/UserDetails.tsx:21`

firstname

firstname: string

The first name of the student.

Defined in

src/UserDetails.tsx:19

id

id: number

The unique identifier for the student.

Defined in

src/UserDetails.tsx:18

lastname

lastname: string

The last name of the student.

Defined in

src/UserDetails.tsx:20

roles

roles: string[]

An array of roles assigned to the student.

Defined in

src/UserDetails.tsx:23

Validation

studlet v0.1.0 • Docs

studlet v0.1.0 / Validation

Validation

Index

Variables

- emailRegex
- passwordRegex

Variables

studlet v0.1.0 • Docs

studlet v0.1.0 / Validation / emailRegex

Variable: emailRegex

```
const emailRegex: RegExp
```

A regular expression for validating email addresses.

This regex checks for the following criteria: - Starts with alphanumeric characters, dots, underscores, percent signs, plus signs, or hyphens. - Followed by the “@” symbol. - Contains a domain name with alphanumeric characters and dots. - Ends with a top-level domain of at least two alphabetic characters.

Constant

Defined in src/Validation.ts:12

studlet v0.1.0 • Docs

studlet v0.1.0 / Validation / passwordRegex

Variable: passwordRegex

```
const passwordRegex: RegExp
```

A regular expression for validating passwords.

This regex checks for the following criteria: - At least 8 characters long. - Contains at least one letter (uppercase or lowercase). - Contains at least one digit.

Constant

Defined in src/Validation.ts:24

Documents

studlet v0.1.0 • Docs

studlet v0.1.0 / README

Studlet Frontend

This is a React frontend for the Studlet platform. It is built with Create React App and uses React Router for client-side routing.

Folder Structure

The project is organized as follows:

- **public/**: static resources, such as images and the favicon
- **src/**: the source code for the frontend
 - **img/**: folder with images used by the typescript code
 - **model/**: data models for the app
 - **setupTests.ts**: Jest setup file
 - **App.tsx**: the main application component
 - **index.tsx**: the entry point for the app
 - ***.tsx**: other TypeScript files in the src directory with components
- **.env**: environment variables for the app (see below)

Cloning the Repository

To clone the repository, run the following command:

```
git clone https://github.com/StudletOrg/StudletFrontend.git
```

Environment Variables

The app expects the following environment variables to be set:

- **REACT_APP_API_URL**: the URL of the Studlet Backend API server

To set these variables, create a **.env** file in the root of the project and add the following lines:

```
REACT_APP_API_URL="http://localhost:8080"
```

Running the App

To run the app, navigate to the root of the project and run the following command:

```
npm start
```

This will start the development server and open the app in a browser.

Index

studlet v0.1.0 • Docs

[studlet v0.1.0 / index](#)

index

Model

Grade

studlet v0.1.0 • Docs

[studlet v0.1.0 / model/Grade](#)

model/Grade

Index

Interfaces

- [Grade](#)

Interfaces

studlet v0.1.0 • Docs

[studlet v0.1.0 / model/Grade / Grade](#)

Interface: Grade Represents a student's grade in a specific subject.

Grade

Properties `grade`

`grade`: number

The numerical value of the grade.

Defined in

`src/model/Grade.ts:12`

`id`

id: number

The unique identifier for the grade entry.

Defined in

src/model/Grade.ts:10

subject

subject: string

The name of the subject for which the grade is assigned.

Defined in

src/model/Grade.ts:11

Group

studlet v0.1.0 • Docs

studlet v0.1.0 / model/Group

model/Group

Index

Interfaces

- Group
- Note

Interfaces

studlet v0.1.0 • Docs

studlet v0.1.0 / model/Group / Group

Interface: Group Represents a group of students in a specific subject.

Group

Properties groupId

groupId: number

The unique identifier for the group.

Defined in

src/model/Group.ts:41

groupNumber

groupNumber: string

The number assigned to the group.

Defined in

src/model/Group.ts:42

notes?

optional notes: Note[]

An optional array of notes related to the group.

Defined in

src/model/Group.ts:50

professor

professor: object

The professor associated with the group.

email

email: null | string

firstName

firstName: null | string

lastName

lastName: null | string

Defined in

src/model/Group.ts:43

studentCount

studentCount: number

The number of students in the group.

Defined in

src/model/Group.ts:48

subject

subject: string

The subject associated with the group.

Defined in

src/model/Group.ts:49

studlet v0.1.0 • Docs

studlet v0.1.0 / model/Group / Note

Interface: Note Represents a note created by an author.

Note

Properties author

author: object

The author of the note.

firstName

firstName: string

id

id: number

lastName

lastName: string

Defined in

src/model/Group.ts:19

content

content: null | string

The content of the note. Can be null if no content is provided.

Defined in

src/model/Group.ts:18

creationDate

creationDate: string

The date when the note was created, in ISO 8601 format.

Defined in

src/model/Group.ts:17

id

id: number

The unique identifier for the note.

Defined in

src/model/Group.ts:15

title

title: string

The title of the note.

Defined in

src/model/Group.ts:16

Student

studlet v0.1.0 • Docs

studlet v0.1.0 / model/Student

model/Student

Index

Interfaces

- Student

Interfaces

studlet v0.1.0 • Docs

studlet v0.1.0 / model/Student / Student

Interface: Student Represents a student with personal information.

Student

Properties email

email: string

The email address of the student.

Defined in

src/model/Student.ts:14

firstname

firstname: string

The first name of the student.

Defined in

src/model/Student.ts:12

id

id: number

The unique identifier for the student.

Defined in

src/model/Student.ts:11

lastname

lastname: string

The last name of the student.

Defined in

src/model/Student.ts:13

studlet v0.1.0 • Docs

studlet v0.1.0

Documents

- README

Modules

- AddGrade
- AddStudentToGroup
- App
- App.test
- AppNavbar
- CreateNote
- Dashboard
- DashboardCard
- Error
- FontSizeChanger
- Grades
- GroupDetails
- Home
- index
- index
- LoginForm
- Logo
- model/Grade
- model/Group
- model/Student
- RegisterForm
- SideMenu
- StudentGroups
- TeacherGrades
- UserDetails
- Validation