

THE PRESENT WORK WAS SUBMITTED TO THE DEPARTMENT OF CONTINUUM  
MECHANICS

**RHEINISCH-WESTFÄLISCHE TECHNISCHE HOCHSCHULE AACHEN**  
FACULTY OF MECHANICAL ENGINEERING

## **MASTER THESIS**

# **NONLINEAR MATERIAL PARAMETER IDENTIFICATION OF SOFT MATERIALS BASED ON AN INVERSE FINITE ELEMENT METHOD APPROACH**

Presented by:	Nadia Pinedo Oruna, B.Sc.
Study programme:	General Mechanical Engineering M.Sc.
Matriculation number:	397 011
Reviewer:	Univ.-Prof. Dr.-Ing. Mikhail Itskov
Supervisor:	Rasul Abdulsalamov, M.Sc.
External supervisor:	Prof. Kazumi Matsui



## Declaration of Authorship

I declare that this work has been composed by myself, and describes my own work, unless otherwise acknowledged in the text.

All sentences or passages quoted in this paper from other people's work have been specifically acknowledged by clear cross-referencing to author, work and page(s). Any photos and illustrations which are not the work of the author have been used with the explicit permission of the originator and are specifically acknowledged.

This work has not been and will not be submitted for any other degree or the obtaining of ECTS points at the RWTH Aachen University or any other institution of higher education.

Aachen, 1<sup>st</sup> of January 3000

---

Nadia Pinedo Oruna, B.Sc.



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	State of the art . . . . .	2
1.1.1	Experimental techniques for soft materials . . . . .	2
	Uniaxial testing . . . . .	2
	Aspiration experiment . . . . .	2
	Indentation . . . . .	2
1.1.2	Material Modeling of Soft Tissues . . . . .	2
1.1.3	Inverse Finite Element Method for Parameter Identification . . . . .	2
	Synthetic soft materials . . . . .	3
	Biomaterials . . . . .	4
1.1.4	Standard Verification and Validation for computational solid mechanics (ASME) . . . . .	4
	VV40 . . . . .	4
<b>2</b>	<b>Inverse Finite Element Method for Material Parameter Identification</b>	<b>5</b>
2.1	Experimental model . . . . .	5
2.2	Material model framework assumptions . . . . .	5
2.3	Computational model . . . . .	5
2.4	Material model . . . . .	5
<b>A</b>	<b>Frequently Asked Questions</b>	<b>7</b>
A.1	How do I change the colors of links? . . . . .	7
	<b>Bibliography</b>	<b>9</b>



# List of Figures





# List of Tables



# 1 Introduction

Precise knowledge about the biomechanical characterization of soft tissues has received attention in medical research, e.g., medical image analysis and visualization. For many years, the obtained medical diagnosis have come from assumptions of experts or accumulated experience. This information, although proven to be useful, has its limitations when computed-assisted systems like, medical diagnosis, therapy, and training, rely on more quantifiable data[3]. To gather this data, it is important to gain access to the tissues and perform in-vivo testing experiments. For organs, this procedure is nearly impossible to achieve, due to the involvement of an invasive procedure, and the lack of constant and reproducible external and internal factors.

One of the complications associated with the extraction of the organ is that some material properties may change despite examination of the same organ. Their biomechanical properties depend on other factors, such as changes in blood pressure, changes in material properties over time, symptoms from diseases, etc. Furthermore, another encountered issue is the lack of replication, due to the use of different individuals organs, which includes more external factors to add to the equation. Moreover, given a tissue sample, it is difficult to characterize the organ's material properly due to its anisotropy property. The material properties change, resulting in an inaccurate result.

In the situation where the soft material's data can be gather in a constant, fast and reliable process, the data enables the system to predict the behavior of soft tissues and give pre-operative calculations. This shows that material models represent a vital part for medical research, specially for the use of computational models, as their help to increase the accuracy of the simulation and its applications in other systems.

In soft materials analyses, a nonlinear situation is mostly encountered, for which a finite element method becomes a common approach. The application of the finite element method facilitates the analysis of complex structures with complex material behavior, and aids in solving of continuum mechanical problems. Nevertheless, in order to simulate a material with this complexity also requires complex algorithms with high computational costs.

One of the goals of this study to identify the key parameters of the soft materials, and their influence in the construction of a material model. These key parameters the attempt to approximate such a complex material will be done, and this simplified material model will be validated for its future applications in medical research.

With the application of the experiment testing, and the finite element method it is possible to identify some key material parameters through an inverse finite element method approach. With this method a framework can be established and the results of computational model can be matched to the experimental data, and afterwards be validated with other experiments.

## 1.1 State of the art

### 1.1.1 Experimental techniques for soft materials

- Soft synthetics materials like soft gels are one example for soft synthetic materials. These are commonly applied for tissue engineering applications. Nevertheless, due to their elastic modulus range (kPa) present some challenges for the design of experimental testing[4].

#### Uniaxial testing

This method allows the validation of several computational models as it provides with searched parameters done with other experimental procedure.

#### Aspiration experiment

Tissue aspiration experiments introduces an aspiration tube which is put against the soft tissue, generating a vacuum. An advantageous feature of this experiment is that it can be performed in-vivo and ex-vivo. With the help of a mirror placed next to aspiration hole, the reflection of the side-view of the tissue can be captured with a video camera. This camera captures the images of the illuminated surface of the material and the aspiration pressure is captured through a sensor. Through this process the captured profile of the tissue is obtained and this can be used to characterize the deformation and analyze the viscoelastic properties of the soft tissue[3].

#### Indentation

Indentation have being gaining popularity in the last decades and it is now one of the most spread experiments for material parameter identification.(?)

Indentation possesses advantageous characteristics for the mechanical characterization of soft materials. [4]

As some materials do not allow the use of uniaxial or biaxial tensile testing, the use of indentation testing is essential for this case.

-indentation in materials - Indentation in soft materials (organs) - Why is indentation relevant in organs -what advantages and disadvantages does indentation provides - why is relevant for this project

### 1.1.2 Material Modeling of Soft Tissues

Relevant papers tends to use hyperelastic models to represent soft materials as the viscoelasticity is usually neglected.

For example, in the Aspiration experiment conducted by Kauer the material they used to model the polymer established in the experiment is:

As derivative from this formula for the uteri metrial modeling the formula used was:

### 1.1.3 Inverse Finite Element Method for Parameter Identification

An inverse finite element (FE) approach requires usually a certain experimental model, which generates certain information e. g. load-displacement curve, and through a verified computational model match the given data curve to obtain further information of the material's behavior e. g., stress-strain curve.

Specially for nonlinear cases [2], where the complexity of the problems increases, and the interest is focused to generate an action which results in a certain output response, is where an inverse finite element approach can be helpful to discover a certain variable going from an output data. Through an iterative process it is possible to describe the material's behavior and validate the output data it through other established testing e. g., uniaxial testing.

Though this approach does not always give a hundred percent match in all obtain points or zones, it allows the researcher to understand the influences of certain parameters for the materials. This is specially useful for complex materials as biomaterials.

Biomaterials, as mentioned previously, depends on multiple external factors, e.g., blood pressure, affected diseases and the their material properties is constantly changing. This issue does not allow the researcher to develop a proper material model which is usable for multiple use-cases.

Therefore, the importance of the inverse element method as relevant key for estimating constantly changing parameters in soft materials.

For biomechanical models, where the models require knowledge from local properties [1], as the biomaterial is not isotropic; it is possible to identify a parameter e.g. Young's Modulus from a 3D model. The model can be matched to multiple experiments and multiple samples in different areas, which allows a better representation of the material for further analysis.

The inverse FE approach can used by optimizing the searched parameter by matching the simulated data to a section of a experimental curve and extending this process through some iterations. Nevertheless, it is important to clarify that this method also requires making assumptions to some values. Furthermore, it is relevant to document these assumptions for the further analysis. With the combination of assumptions, experimental data, and a optimized and matched simulation curve, it is possible to solve the complexity of biomechanical models.

In next sections some of the experimental models and the material models for bio and soft materials are going to be explained to get a further understanding in how is possible to get a reliable computational model for further reasearch

### Synthetic soft materials

Synthetics materials are commonly used to validate an inverse parameter identification process. Usually these synthetic, soft materials provide similar mechanical behavior to it's biomaterials counterparts. This characterization allows to validate a proposed inverse finite element approach process before its applicatoin with a biomaterial, where the measurements to gather the experimental data are some in-vivo, and more challenging to recreate.

For example, Silgel, a very soft gel-like material [3] was used for the experimental validation of the inverse finite element method proposed, to characterized the tissue of a human uteri. In this work, the tensile behavior of the material was predicted through the parameters obtained in the aspiration method. The matching procedure is optimize through an objective function, which consists of the squared differences between the simulation and exprimental data. With an optimization algorithm an optimal set of the following parameters was found: the material parameters  $\mu_i$  [N/m<sup>2</sup>] and the bulk Modulus  $\kappa$  [N/m<sup>2</sup>]. This method showed good prediction quality of the mentioned material parameters.

## **Biomaterials**

Biomaterials as mentioned before, represent a challenge due its difficult access and lesser replicability. Therefore these materials are usually used for the experimetnal validation of a methd applied previously in synthetic materials. Following the first example of the Silgel in the previous section, the inverse finite element parameter estimation is applied now on human uteri [3] through in vivo and ex vivo measurements of the human tissue of different patients. It was mentioned, that in comparison from the silgel the uterus possesses a complex multi layered structure with strongly anistropic and viscoelastic properties. Nevertheless, five material parameters were determined, based on the strain energy function to model a human uterus (Yamada 1970). Through the same inverse method applied with the synthetic material, the obtained parameters facilitated the prediction of stress-elongation curves for tensile experiments. The resulting curves showed the difference of stiffness for in vivo and ex vivo measurements and the material singularity for each uterus.

### **1.1.4 Standard Verification and Validation for computational solid mechanics (ASME)**

VV40

## 2 Inverse Finite Element Method for Material Parameter Identification

### 2.1 Experimental model

The chosen experimental technique was indentation. In Fig.. the ellipsoidal specimen with the a first radius  $r_1$  of 30 mm and a second radius  $r_2$  of 60 mm is positioned in a rest status(?) on a fixed platform that suits the ellipsoidal geometry of the specimen. A metal pin with a rounded head with a radius  $r_3$  3 mm is attached by the holding grips followed by a force load cell. The measured force data showed a very small number, so the first 50 N load cell displayed a lot of noise in the measured data. Therefore, the load cell was change to 10N to reduce this interference. The 10 N load cell displayed the initial contact between the indenter and the specimen in a finer way. In order to get the measurement of the load and unloading process of the indentation a displacement sensor was attached to the tensile machine

### 2.2 Material model framework assumptions

### 2.3 Computational model

The quasi static nature of the indentation experiment allows the use of a static structural analysis.

Their a two main factors which increases the complexity of the validation of the simulation and those are, the contact nonlinearity, and the element distortion due to indentation experiment. These issues make the computational time expensive, as it requires to manual solutions for the meshing in the area of importance, and small time steps.

A force-displacement curve, shown in Fig... is generated from the first assumption, for this case

For both cases

### 2.4 Material model

In an ideal and first scenario, this material can be assumed as linear, isotropic, elastic and nearly incompressible. For this case, there are two main variables, the Young's Modulus  $E$ , and the Poisson's ratio  $\nu$ .





# A Frequently Asked Questions

## A.1 How do I change the colors of links?

The color of links can be changed to your liking using:

```
\hypersetup{urlcolor=red}, or  
\hypersetup{citecolor=green}, or  
\hypersetup{allcolor=blue}.
```

If you want to completely hide the links, you can use:

```
\hypersetup{allcolors=.}, or even better:  
\hypersetup{hidelinks}.
```

If you want to have obvious links in the PDF but not the printed text, use:

```
\hypersetup{colorlinks=false}.
```



# Bibliography

- [1] Chen Ket Chai et al. "Local axial compressive mechanical properties of human carotid atherosclerotic plaques-characterisation by indentation test and inverse finite element analysis". In: *Journal of Biomechanics* 46 (10 June 2013). indentation test/experiment, biomechanical models (compute stress and strain); models requires knowlegde of local biomechanical properties; using inverse FE and assuming isotropic neo-hookean behaviour; Young moduli is found from 6 to 891kPa median 30 kPa; Biomechanical models have shown to provide a better risk assessment for the treatment of atherosclerosis diseases but models depends strongly on material properties of the plaque components; Experimental data on the mechanical properties are scarce and show large variability 30kPa (soft) to 1 MPa stiff; this represents global stiffness -; therefore experimental technique for micro indentation test on soft biological materials to investigate the compressive Youngs moduli of different plaque components; Cox 2005 indentation set up; Data analysis: 3D fe model; local shear modulus G estimated by fitting the model to force-indentation-depth curve; least square method to fit experimental data to simulated;  $E=3G$ ; non Gaussian distribution; standard deviation; mean difference indentation test is reproducible; , pp. 1759–1766. ISSN: 00219290. DOI: 10.1016/j.jbiomech.2013.03.017.
- [2] Asif Husain, D. K. Sehgal, and R. K. Pandey. "An inverse finite element procedure for the determination of constitutive tensile behavior of materials using miniature specimen". In: *Computational Materials Science* 31 (1-2 Sept. 2004).  
 ; Abstract; ; Determination of constitutive tensile behavior; Experimental load vs displacement curve; demonstrate the effectiveness of the inverse procedure; ; Introduction; ; Inverse problems involve determining the unknown causes of known consequences; ; Experimental procedure; ; specimen material; steel like materials, details; specimen geometry; extra details of the samples polished...; set up; specimen holder; punch load ; where is the specimen; which machine; speed; how many times; result curves ya muestran resultado simulacion y exper; ; Inverse fe procedure; ; initial slope up to yielding simulation and exp is matched to determine E; inputs: E and true stress vs true plastic strain data; first linear part find E and match P1 ; max equivalent stress = yield stress; eq plastic strain = 0; uniaxial true stress vs. true plastic strain (calculated); assumed values data point; until nth; mechanical behavior of the material E, yield, and data points is known; Inverse finite element simulation of disk shaped ; rigid head; how many nodes, element type, contact pair option, pp. 84–92. ISSN: 09270256. DOI: 10.1016/j.commatsci.2004.01.039.

- [3] M. Kauer et al. "Inverse finite element characterization of soft tissues". In: *Medical Image Analysis* 6 (2002), pp. 275–287. URL: [www.elsevier.com/locate/media](http://www.elsevier.com/locate/media).
- [4] Kaifeng Liu, Mark R. VanLandingham, and Timothy C. Ovaert. "Mechanical characterization of soft viscoelastic gels via indentation and optimization-based inverse finite element analysis". In: *Journal of the Mechanical Behavior of Biomedical Materials* 2 (4 Aug. 2009). Abstract; Polymer gels are widely accepted as candidate materials for tissue engineering, drug delivery, and orthopedic load-bearing applications. Soft gels elastic modulus are in kPa range; Soft gels mechanical characterizations presents challenges; sample preparation; fixture design; gripping, and or load measurement accuracy; , pp. 355–363. ISSN: 17516161. DOI: 10.1016/j.jmbbm.2008.12.001.