



MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

MDP, Q-Learning & ADP: Concepts and Algorithms

Chunyue Song
[csong\(at\)zju.edu.cn](mailto:csong(at)zju.edu.cn)

College of Control Science and Engineering, Zhejiang University

December 26, 2018

1 / 23



MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Outline

- 1 Gamble
- 2 MDP
- 3 Algorithm
- 4 Model-free Learning
- 5 Approximate Dynamic Programming

2 / 23



MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Exploration - Exploitation

Average Reward: $Q(k) = \frac{1}{n} \sum_{i=1}^n v_i$

$$Q_n(k) = Q_{n-1}(k) + \frac{1}{n}(v_n - Q_{n-1}(k))$$

3 / 23



MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Exploration - Exploitation

Average Reward: $Q(k) = \frac{1}{n} \sum_{i=1}^n v_i$

$$Q_n(k) = Q_{n-1}(k) + \frac{1}{n}(v_n - Q_{n-1}(k))$$

Greedy Algorithms

3 / 23



Exploration - Exploitation

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

Average Reward: $Q(k) = \frac{1}{n} \sum_{i=1}^n v_i$

$$Q_n(k) = Q_{n-1}(k) + \frac{1}{n} (v_n - Q_{n-1}(k))$$

Greedy Algorithms

- 1 Input: K, R, T, ϵ .
- 2 $r = 0$;
- 3 $\forall i = 1, 2, \dots, K : Q(i) = 0, \text{count}(i) = 0$;
- 4 for $t = 1, 2, \dots, T$, do
- 5 if $\text{rand}() < \epsilon$ then $k = \text{uniform}\{1, K\}$
- 6 else $k = \arg \max_i Q(i)$
- 7 end if
- 8 $v = R(k), r = r + v$
- 9 $Q(k) = \frac{Q(k) \times \text{count}(k) + v}{\text{count}(k) + 1}$
- 10 $\text{count}(k) = \text{count}(k) + 1$
- 11 end for
- 12 Output: r .

3 / 23



Exploration - Exploitation

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

$$\text{Boltzmann Distr.: } P(k) = \frac{e^{\frac{Q(k)}{\tau}}}{\sum_{i=1}^K e^{\frac{Q(i)}{\tau}}}$$

4 / 23



Exploration - Exploitation

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

$$\text{Boltzmann Distr.: } P(k) = \frac{e^{\frac{Q(k)}{\tau}}}{\sum_{i=1}^K e^{\frac{Q(i)}{\tau}}}$$

Softmax Algorithms

$$\text{Boltzmann Distr.: } P(k) = \frac{e^{\frac{Q(k)}{\tau}}}{\sum_{i=1}^K e^{\frac{Q(i)}{\tau}}}$$

Softmax Algorithms

- 1 Input: K, R, T, τ .
- 2 $r = 0$;
- 3 $\forall i = 1, 2, \dots, K : Q(i) = 0, \text{count}(i) = 0$;
- 4 for $t = 1, 2, \dots, T$, do
- 5 $k = P(k)$, and $v = R(k)$
- 6 $r = r + v$
- 7 $Q(k) = \frac{Q(k) \times \text{count}(k) + v}{\text{count}(k) + 1}$
- 8 $\text{count}(k) = \text{count}(k) + 1$
- 9 end for
- 10 Output: r .

4 / 23



Exploration - Exploitation

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming



MDP: Markov Decision Process

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

MDP Model

- $MDP = \langle X, A, P, R \rangle$.
- X : State Space; A : Action Space;
 $P : X \times A \rightarrow X(P_{x \rightarrow \hat{x}}^a)$; $R : X \times A \rightarrow \mathbb{R}^+(R_{x \rightarrow \hat{x}}^a)$.

5 / 23



MDP: Markov Decision Process

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

MDP Model

- $MDP = \langle X, A, P, R \rangle$.
- X : State Space; A : Action Space;
 $P : X \times A \rightarrow X(P_{x \rightarrow \hat{x}}^a)$; $R : X \times A \rightarrow \mathbb{R}^+(R_{x \rightarrow \hat{x}}^a)$.

Objective Function

- $$\begin{cases} \min_{\pi} \mathbb{E}_{\pi}[\sum_{t=0}^{+\infty} \gamma^t r_{t+1} | x_0 = x], \\ \min_{\pi} \mathbb{E}_{\pi}[\frac{1}{T} \sum_{t=0}^T r_{t+1} | x_0 = x]. \end{cases}$$

5 / 23



MDP: Markov Decision Process

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

MDP Model

- $MDP = \langle X, A, P, R \rangle$.
- X : State Space; A : Action Space;
 $P : X \times A \rightarrow X(P_{x \rightarrow \hat{x}}^a)$; $R : X \times A \rightarrow \mathbb{R}^+(R_{x \rightarrow \hat{x}}^a)$.

Objective Function

- $$\begin{cases} \min_{\pi} \mathbb{E}_{\pi}[\sum_{t=0}^{+\infty} \gamma^t r_{t+1} | x_0 = x], \\ \min_{\pi} \mathbb{E}_{\pi}[\frac{1}{T} \sum_{t=0}^T r_{t+1} | x_0 = x]. \end{cases}$$

Policy: π Vs. Action: $a, a = \pi(x)$

5 / 23



Value Function

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Model-based Learning

6 / 23



Value Function

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

Model-based Learning

State Value Function: $V^\pi(\cdot)$

6 / 23



Value Function

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

Model-based Learning

State Value Function: $V^\pi(\cdot)$

$$\begin{cases} V_\gamma^\pi(x) = \mathbb{E}_\pi[\sum_{t=0}^{+\infty} \gamma^t r_{t+1} | x_0 = x], \\ V_T^\pi(x) = \mathbb{E}_\pi[\frac{1}{T} \sum_{t=0}^T r_{t+1} | x_0 = x]. \end{cases}$$

6 / 23



Value Function

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

Model-based Learning

State Value Function: $V^\pi(\cdot)$

$$\begin{cases} V_\gamma^\pi(x) = \mathbb{E}_\pi[\sum_{t=0}^{+\infty} \gamma^t r_{t+1} | x_0 = x], \\ V_T^\pi(x) = \mathbb{E}_\pi[\frac{1}{T} \sum_{t=0}^T r_{t+1} | x_0 = x]. \end{cases}$$

State-action Value Function: $Q^\pi(x, a)$

6 / 23



Value Function

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

Model-based Learning

State Value Function: $V^\pi(\cdot)$

$$\begin{cases} V_\gamma^\pi(x) = \mathbb{E}_\pi[\sum_{t=0}^{+\infty} \gamma^t r_{t+1} | x_0 = x], \\ V_T^\pi(x) = \mathbb{E}_\pi[\frac{1}{T} \sum_{t=0}^T r_{t+1} | x_0 = x]. \end{cases}$$

State-action Value Function: $Q^\pi(x, a)$

$$\begin{cases} Q_\gamma^\pi(x, a) = \mathbb{E}_\pi[\sum_{t=0}^{+\infty} \gamma^t r_{t+1} | x_0 = x, a_0 = a], \\ Q_T^\pi(x, a) = \mathbb{E}_\pi[\frac{1}{T} \sum_{t=0}^T r_{t+1} | x_0 = x, a_0 = a]. \end{cases}$$

6 / 23



DP: Dynamic Programming

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Bellman equation

$$\begin{cases} V_{\gamma}^{\pi}(x) = \sum_{a \in A} \pi(x, a) \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (R_{x \rightarrow \dot{x}}^a + \gamma V_{\gamma}^{\pi}(\dot{x})), \\ V_T^{\pi}(x) = \sum_{a \in A} \pi(x, a) \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a \left(\frac{1}{T} R_{x \rightarrow \dot{x}}^a + \frac{T-1}{T} V_{T-1}^{\pi}(\dot{x}) \right). \end{cases}$$

7 / 23



DP: Dynamic Programming

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Bellman equation

$$\begin{cases} V_{\gamma}^{\pi}(x) = \sum_{a \in A} \pi(x, a) \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (R_{x \rightarrow \dot{x}}^a + \gamma V_{\gamma}^{\pi}(\dot{x})), \\ V_T^{\pi}(x) = \sum_{a \in A} \pi(x, a) \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a \left(\frac{1}{T} R_{x \rightarrow \dot{x}}^a + \frac{T-1}{T} V_{T-1}^{\pi}(\dot{x}) \right). \end{cases}$$

$$\begin{cases} Q_{\gamma}^{\pi}(x, a) = \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (R_{x \rightarrow \dot{x}}^a + \gamma V_{\gamma}^{\pi}(\dot{x})), \\ Q_T^{\pi}(x, a) = \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a \left(\frac{1}{T} R_{x \rightarrow \dot{x}}^a + \frac{T-1}{T} V_{T-1}^{\pi}(\dot{x}) \right). \end{cases}$$

7 / 23



DP: Dynamic Programming

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Bellman equation

$$\begin{cases} V_{\gamma}^{\pi}(x) = \sum_{a \in A} \pi(x, a) \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (R_{x \rightarrow \dot{x}}^a + \gamma V_{\gamma}^{\pi}(\dot{x})), \\ V_T^{\pi}(x) = \sum_{a \in A} \pi(x, a) \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a \left(\frac{1}{T} R_{x \rightarrow \dot{x}}^a + \frac{T-1}{T} V_{T-1}^{\pi}(\dot{x}) \right). \end{cases}$$

$$\begin{cases} Q_{\gamma}^{\pi}(x, a) = \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (R_{x \rightarrow \dot{x}}^a + \gamma V_{\gamma}^{\pi}(\dot{x})), \\ Q_T^{\pi}(x, a) = \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a \left(\frac{1}{T} R_{x \rightarrow \dot{x}}^a + \frac{T-1}{T} V_{T-1}^{\pi}(\dot{x}) \right). \end{cases}$$

Policy: $a = \pi(x)$

- Deterministic: $\pi : X \mapsto A, a = f(x)$.

7 / 23



DP: Dynamic Programming

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Bellman equation

$$\begin{cases} V_{\gamma}^{\pi}(x) = \sum_{a \in A} \pi(x, a) \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (R_{x \rightarrow \dot{x}}^a + \gamma V_{\gamma}^{\pi}(\dot{x})), \\ V_T^{\pi}(x) = \sum_{a \in A} \pi(x, a) \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a \left(\frac{1}{T} R_{x \rightarrow \dot{x}}^a + \frac{T-1}{T} V_{T-1}^{\pi}(\dot{x}) \right). \end{cases}$$

$$\begin{cases} Q_{\gamma}^{\pi}(x, a) = \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (R_{x \rightarrow \dot{x}}^a + \gamma V_{\gamma}^{\pi}(\dot{x})), \\ Q_T^{\pi}(x, a) = \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a \left(\frac{1}{T} R_{x \rightarrow \dot{x}}^a + \frac{T-1}{T} V_{T-1}^{\pi}(\dot{x}) \right). \end{cases}$$

Policy: $a = \pi(x)$

- Deterministic: $\pi : X \mapsto A, a = f(x)$.
- Probabilistic: $\pi : X \times A \mapsto \mathbb{R}$, the probability of choosing action a on state x , $\sum_a \pi(x, a) = 1$.

7 / 23



Policy Evaluation

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Policy Evaluation

8 / 23



Policy Evaluation

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Policy Evaluation

- 1 Input: $MDP = \langle X, A, P, R \rangle$; the policy π ; the horizon T .
- 2 $\forall x \in X : V(x) = 0$;
- 3 for $t = 1, 2, \dots$, do
- 4 $\forall x \in X$:

$$V'(x) = \sum_{a \in A} \pi(x, a) \sum_{\hat{x} \in X} P_{x \rightarrow \hat{x}}^a \left(\frac{1}{t} R_{x \rightarrow \hat{x}}^a + \frac{t-1}{t} V(\hat{x}) \right);$$
- 5 if $t = T + 1$ then
- 6 break
- 7 else $V = V'$
- 8 end if
- 9 end for
- 10 Output: $V(x)$.

8 / 23



Optimal Policy

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

$$\pi^* = \arg \max_{\pi} V^{\pi}(x), \forall x \in X, V^*(x) = V^{\pi^*}(x)$$

9 / 23



Optimal Policy

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

$$\pi^* = \arg \max_{\pi} V^{\pi}(x), \forall x \in X, V^*(x) = V^{\pi^*}(x)$$

Bellman Equation

$$\begin{cases} V_{\gamma}^*(x) = \max_{a \in A} \sum_{\hat{x} \in X} P_{x \rightarrow \hat{x}}^a (R_{x \rightarrow \hat{x}}^a + \gamma V_{\gamma}^*(\hat{x})), \\ V_T^*(x) = \max_{a \in A} \sum_{\hat{x} \in X} P_{x \rightarrow \hat{x}}^a \left(\frac{1}{T} R_{x \rightarrow \hat{x}}^a + \frac{T-1}{T} V_{T-1}^*(\hat{x}) \right). \end{cases}$$

9 / 23



Optimal Policy

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

$$\pi^* = \arg \max_{\pi} V^{\pi}(x), \forall x \in X, V^*(x) = V^{\pi^*}(x)$$

Bellman Equation

$$\begin{cases} V_{\gamma}^*(x) = \max_{a \in A} \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (R_{x \rightarrow \dot{x}}^a + \gamma V_{\gamma}^*(\dot{x})), \\ V_T^*(x) = \max_{a \in A} \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (\frac{1}{T} R_{x \rightarrow \dot{x}}^a + \frac{T-1}{T} V_{T-1}^*(\dot{x})). \end{cases}$$

$$V^*(x) = \max_{a \in A} Q^{\pi^*}(x, a)$$

9 / 23



Optimal Policy

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

$$\pi^* = \arg \max_{\pi} V^{\pi}(x), \forall x \in X, V^*(x) = V^{\pi^*}(x)$$

Bellman Equation

$$\begin{cases} V_{\gamma}^*(x) = \max_{a \in A} \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (R_{x \rightarrow \dot{x}}^a + \gamma V_{\gamma}^*(\dot{x})), \\ V_T^*(x) = \max_{a \in A} \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (\frac{1}{T} R_{x \rightarrow \dot{x}}^a + \frac{T-1}{T} V_{T-1}^*(\dot{x})). \end{cases}$$

$$V^*(x) = \max_{a \in A} Q^{\pi^*}(x, a)$$

$$\begin{cases} Q_{\gamma}^*(x, a) = \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (R_{x \rightarrow \dot{x}}^a + \gamma \max_{a'} Q_{\gamma}^*(\dot{x}, a')), \\ Q_T^*(x, a) = \sum_{\dot{x} \in X} P_{x \rightarrow \dot{x}}^a (\frac{1}{T} R_{x \rightarrow \dot{x}}^a + \frac{T-1}{T} \max_{a'} Q_{T-1}^*(\dot{x}, a')). \end{cases}$$

9 / 23



Policy Iteration

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

$$\begin{aligned} \blacksquare V^{\pi}(x) &\leq Q^{\pi}(x, \pi'(x)) = \sum_{x' \in X} P_{x \rightarrow x'}^{\pi'(x)} (R_{x \rightarrow x'}^{\pi'(x)} + \gamma V^{\pi}(x')) \\ &\leq \sum_{x' \in X} P_{x \rightarrow x'}^{\pi'(x)} (R_{x \rightarrow x'}^{\pi'(x)} + \gamma Q^{\pi}(x', \pi'(x'))) = \dots = V^{\pi'}(x). \end{aligned}$$

10 / 23



Policy Iteration

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

$$\begin{aligned} \blacksquare V^{\pi}(x) &\leq Q^{\pi}(x, \pi'(x)) = \sum_{x' \in X} P_{x \rightarrow x'}^{\pi'(x)} (R_{x \rightarrow x'}^{\pi'(x)} + \gamma V^{\pi}(x')) \\ &\leq \sum_{x' \in X} P_{x \rightarrow x'}^{\pi'(x)} (R_{x \rightarrow x'}^{\pi'(x)} + \gamma Q^{\pi}(x', \pi'(x'))) = \dots = V^{\pi'}(x). \end{aligned}$$

$$\pi^*(x) = \arg \max_{a \in A} Q^{\pi}(x, a)$$

10 / 23



Policy Iteration

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

- 1 Input: $MDP = \langle X, A, P, R \rangle$ and the horizon T .
- 2 $\forall x \in X : V(x) = 0, \pi(x, a) = \frac{1}{|A(x)|}$;
- 3 Loop
- 4 for $t = 1, 2, \dots$, do
- 5 $\forall x \in X$:

$$V'(x) = \sum_{a \in A} \pi(x, a) \sum_{\hat{x} \in X} P_{x \rightarrow \hat{x}}^a (\frac{1}{t} R_{x \rightarrow \hat{x}}^a + \frac{t-1}{t} V(\hat{x}));$$
- 6 if $t = T + 1$ then
- 7 break; else $V = V'$
- 8 end if
- 9 end for
- 10 $\forall x \in X : \pi' = \arg \max_{a \in A} Q(x, a)$
- 11 if $\forall x \in X : \pi'(x) = \pi(x)$ then
- 12 break; else $\pi = \pi'$
- 13 end if
- 14 End loop
- 15 Output: π^* .

11/23



Value Iteration

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

- 1 Input: $MDP = \langle X, A, P, R \rangle, \theta$ and the horizon T .
- 2 $\forall x \in X : V(x) = 0$;
- 3 for $t = 1, 2, \dots$, do
- 4 $\forall x \in X : V'(x) = \max_{a \in A} \sum_{\hat{x} \in X} P_{x \rightarrow \hat{x}}^a (\frac{1}{t} R_{x \rightarrow \hat{x}}^a + \frac{t-1}{t} V(\hat{x}));$
- 5 if $\max_{x \in X} |V(x) - V'(x)| < \theta$ then
- 6 break; else $V = V'$
- 7 end if
- 8 end for
- 9 Output: $\pi^*(x) = \arg \max_{a \in A} Q(x, a)$

12/23



Remark

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

**For every state x , we will have an optimal action
 $a = f^*(x)$!**

13/23



Remark

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm
Model-free
Learning

Approximate
Dynamic
Programming

**For every state x , we will have an optimal action
 $a = f^*(x)$!**

There no the generalization ability problem!

13/23



Monte Carlo Simulation

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

No R , No P .

14/23



Monte Carlo Simulation

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

No R , No P .

Sampling to get R

14/23



Monte Carlo Simulation

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

No R , No P .

Sampling to get R

We start from x_0 , implement one policy π , and get the following trajectory

$\langle (x_0, a_0, r_1); (x_1, a_1, r_2); \dots, (x_{T-1}, a_{T-1}, r_T), x_T \rangle$

14/23



On-policy Learning

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

- 1 Input: Environment: E , Action Space: A , Initial state: x_0 and the horizon T .
- 2 $Q(x, a) = 0$, $count(x, a) = 0$, $\pi(x, a) = \frac{1}{|A(x)|}$;
- 3 for $s = 1, 2, \dots$, do
- 4 In the environment E and implement π to produce $\langle (x_0, a_0, r_1); (x_1, a_1, r_2); \dots, (x_{T-1}, a_{T-1}, r_T), x_T \rangle$;
- 5 for $t = 0, 1, \dots, T - 1$ do
- 6 $R = \frac{1}{T-t} \sum_{j=t+1}^T r_j$, $Q(x_t, a_t) = \frac{Q(x_t, a_t) \times count(x_t, a_t) + R}{count(x_t, a_t) + 1}$;
- 7 $count(x_t, a_t) = count(x_t, a_t) + 1$;
- 8 end for
- 9 For all detected state x : $\pi(x) = \left\{ \arg \max_{a'} Q(x, a'), Pr(1 - \epsilon) \right.$
 $\left. a \in A, Pr(\epsilon) \right.$
- 10 end for
- 11 Output: π^*

15/23



Off-policy Learning

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

- 1 Input: Environment: E , Action Space: A , Initial state: x_0 and the horizon T .
- 2 $Q(x, a) = 0$, $count(x, a) = 0$, $\pi(x, a) = \frac{1}{|A(x)|}$;
- 3 for $s = 1, 2, \dots$, do
- 4 In the environment E and implement $\pi(Pr(\epsilon))$ to produce $\langle (x_0, a_0, r_1); (x_1, a_1, r_2); \dots, (x_{T-1}, a_{T-1}, r_T), x_T \rangle$;
- 5 $p_i = \begin{cases} 1 - \epsilon + \epsilon/|A|, & a_i = \pi(x_i) \\ \epsilon/|A|, & a_i \neq \pi(x_i) \end{cases}$
- 6 for $t = 0, 1, \dots, T - 1$ do
- 7 $R = \frac{1}{T-t} (\sum_{i=t+1}^T r_i) \prod_{i=t+1}^{T-1} \frac{\mathbb{I}(a_i = \pi(x_i))}{p_i}$, $Q(x_t, a_t) = \frac{Q(x_t, a_t) \times count(x_t, a_t) + R}{count(x_t, a_t) + 1}$;
- 8 $count(x_t, a_t) = count(x_t, a_t) + 1$;
- 9 end for
- 10 $\pi(x) = \arg \max_{a'} Q(x, a')$
- 11 end for
- 12 Output: π^*

16/23



Remark

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

DP evaluate Q at each step!

17/23



Remark

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

DP evaluate Q at each step!

Monte Carlo evaluate Q after each sampling according to each trajectory!

17/23



Remark

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

DP evaluate Q at each step!

Monte Carlo evaluate Q after each sampling according to each trajectory!

- $Q_{t+1}^\pi(x, a) = Q_t^\pi(x, a) + \frac{1}{t+1} (R_{t+1} - Q_t^\pi(x, a)) = Q_t^\pi(x, a) + \alpha (R_{t+1} - Q_t^\pi(x, a))$
- $Q_t^\pi(x, a) = \sum_{x' \in X} P_{x \rightarrow x'}^a (R_{x \rightarrow x'}^a + \gamma V^\pi(x')) = \sum_{x' \in X} P_{x \rightarrow x'}^a (R_{x \rightarrow x'}^a + \gamma \sum_{a' \in A} \pi(x', a') Q_t^\pi(x', a'))$
- $Q_{t+1}^\pi(x, a) = Q_t^\pi(x, a) + \alpha (R_{x \rightarrow x'}^a + \gamma Q_t^\pi(x', a') - Q_t^\pi(x, a))$

17/23



Sarsa

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

- 1 Input: Environment: E , Action Space: A , Initial state: x_0 , discounted factor γ and step α .
- 2 $Q(x, a) = 0, \pi(x, a) = \frac{1}{|A(x)|}$;
- 3 $x = x_0, a = \pi(x)$;
- 4 for $t = 1, 2, \dots$, do
- 5 $r, x' =$ the state when implement a ;
- 6 $a' = \pi^e(x')$;
- 7 $Q(x, a) = Q(x, a) + \alpha(r + \gamma Q(x', a') - Q(x, a))$;
- 8 $\pi(x) = \arg \max_{a''} Q(x, a'')$;
- 9 $x = x', a = a'$;
- 10 end for
- 11 Output: π^*

18 / 23



Q-Learning

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

- 1 Input: Environment: E , Action Space: A , Initial state: x_0 , discounted factor γ and step α .
- 2 $Q(x, a) = 0, \pi(x, a) = \frac{1}{|A(x)|}$;
- 3 $x = x_0$;
- 4 for $t = 1, 2, \dots$, do
- 5 $r, x' =$ the state when implement $a = \pi^e(x)$;
- 6 $a' = \pi(x')$;
- 7 $Q(x, a) = Q(x, a) + \alpha(r + \gamma Q(x', a') - Q(x, a))$;
- 8 $\pi(x) = \arg \max_{a''} Q(x, a'')$;
- 9 $x = x'$;
- 10 end for
- 11 Output: π^*

19 / 23



Value Function Approximation

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Assumption: Linear Function: $V_\theta(x) = \theta^T x$,

20 / 23



Value Function Approximation

MDP,
Q-Learning
and ADP
C. Song

Gamble

MDP

Algorithm

Model-free
Learning

Approximate
Dynamic
Programming

Assumption: Linear Function: $V_\theta(x) = \theta^T x$,

- $E_\theta = \mathbb{E}_{x \sim \pi}[(V^\pi(x) - V_\theta(x))^2]$;
- $-\frac{\partial E_\theta}{\partial \theta} = \mathbb{E}_{x \sim \pi}[2(V^\pi(x) - V_\theta(x))x]$,
- $\theta = \theta + \alpha(V^\pi(x) - V_\theta(x))x = \theta + \alpha(r + \gamma V_\theta^T x' - \theta^T x)x$,


20 / 23



Approximate Dynamic Programming

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP
Algorithm
Model-free
Learning
Approximate
Dynamic
Programming



21 / 23



Acknowledgement

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP
Algorithm
Model-free
Learning
Approximate
Dynamic
Programming

Thanks for Your Attention!



<http://person.zju.edu.cn/ChunyueSong>

22 / 23



Acknowledgement

MDP,
Q-Learning
and ADP
C. Song

Gamble
MDP
Algorithm
Model-free
Learning
Approximate
Dynamic
Programming

Reference

- Zhihua Zhou, Machine Learning, Tsinghua University Press, Beijing, China.

23 / 23