

# Assignment 4.1 - Linear Regression with VIF, LASS

Shital Bhandary

2023-06-11

## R Markdown

```
setwd("D:/datasheet/statitistics")
# Load the mtcars dataset
data(mtcars)
# Fit multiple linear regression
mlr <- lm(mpg ~ ., data = mtcars)
# to get summary
summary(mlr)
```

```
##
## Call:
## lm(formula = mpg ~ ., data = mtcars)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -3.4506 -1.6044 -0.1196  1.2193  4.6271
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  12.30337    18.71788   0.657   0.5181
## cyl          -0.11144     1.04502  -0.107   0.9161
## disp           0.01334     0.01786   0.747   0.4635
## hp            -0.02148     0.02177  -0.987   0.3350
## drat           0.78711     1.63537   0.481   0.6353
## wt            -3.71530     1.89441  -1.961   0.0633 .
## qsec           0.82104     0.73084   1.123   0.2739
## vs             0.31776     2.10451   0.151   0.8814
## am             2.52023     2.05665   1.225   0.2340
## gear           0.65541     1.49326   0.439   0.6652
## carb          -0.19942     0.82875  -0.241   0.8122
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.65 on 21 degrees of freedom
## Multiple R-squared:  0.869, Adjusted R-squared:  0.8066
## F-statistic: 13.93 on 10 and 21 DF, p-value: 3.793e-07
```

#summary function provides a summary of the fitted linear regression model, including information about the coefficients, their standard errors, t-values, and p-values. It also includes the R-squared value, adjusted R-squared value, and F-statistic.

#3: Get the VIF of mlr model and drop variables with VIF > 10 one-by-one until none of the predictors have VIF > 10:

```
#load pacakge  
library(car)
```

```
## Loading required package: carData
```

```
# Calculate VIF  
vif(mlr)
```

```
##      cyl      disp      hp      drat      wt      qsec      vs      am  
## 15.373833 21.620241  9.832037  3.374620 15.164887  7.527958  4.965873  4.648487  
##      gear      carb  
##  5.357452  7.908747
```

```
# Drop variables with VIF > 10  
mlr1 <- lm(mpg ~ cyl+hp+drat+wt+qsec+vs+am+gear+carb, data = mtcars)  
vif(mlr1)
```

```
##      cyl      hp      drat      wt      qsec      vs      am      gear  
## 14.284737  7.123361  3.329298  6.189050  6.914423  4.916053  4.645108  5.324402  
##      carb  
##  4.310597
```

```
# Recalculate VIF for the updated mlr model  
#Removing "cyl" variable:  
mlr2 <- lm(mpg ~hp+drat+wt+qsec+vs+am+gear+carb,data = mtcars)  
vif(mlr2)
```

```
##      hp      drat      wt      qsec      vs      am      gear      carb  
## 6.015788 3.111501 6.051127 5.918682 4.270956 4.285815 4.690187 4.290468
```

*#4: Fit the mlr model with predictors having VIF <= 10, get the summary*

```
# Fit mlr model with predictors having VIF <= 10  
mlr <- lm(mpg ~ hp+drat+wt+qsec+vs+am+gear+carb, data = mtcars)  
# Get the summary of the updated mlr model  
summary(mlr)
```

```
##  
## Call:  
## lm(formula = mpg ~ hp + drat + wt + qsec + vs + am + gear + carb,  
##     data = mtcars)  
##  
## Residuals:  
##      Min       1Q   Median       3Q      Max   
## -3.8187 -1.3903 -0.3045  1.2269  4.5183   
##  
## Coefficients:  
##              Estimate Std. Error t value Pr(>|t|)
```

```
## (Intercept) 13.80810    12.88582    1.072    0.2950
## hp          -0.01225     0.01649   -0.743    0.4650
## drat         0.88894     1.52061    0.585    0.5645
## wt          -2.60968     1.15878   -2.252    0.0342 *
## qsec         0.63983     0.62752    1.020    0.3185
## vs           0.08786     1.88992    0.046    0.9633
## am           2.42418     1.91227    1.268    0.2176
## gear         0.69390     1.35294    0.513    0.6129
## carb        -0.61286     0.59109   -1.037    0.3106
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.566 on 23 degrees of freedom
## Multiple R-squared:  0.8655, Adjusted R-squared:  0.8187
## F-statistic: 18.5 on 8 and 23 DF,  p-value: 2.627e-08
```

#Interpretation: # The multiple linear regression model with the predictors hp, drat, wt, qsec, vs, am, gear, and carb was performed. The model shows that the predictors hp, drat, wt, and carb are not statistically significant in the response variable (mpg). The intercept and the predictor am are marginally significant. The model has a relatively high multiple R-squared value of 0.8655, indicating that it explains a significant amount of the variability in the response variable. However, the adjusted R-squared value is 0.8187, suggesting that the model may be slightly overfit. The F-statistic of 18.5 with a very low p-value indicates that the overall model is statistically significant. The residuals are relatively small, indicating a good fit of the model to the data

```
# 5 Fit lasso regression with mpg as the dependent variable and rest of the variables as independent variables
# Install and load the 'glmnet' package for Lasso regression
library(glmnet)
```

```
## Loading required package: Matrix
```

```
## Loaded glmnet 4.1-7
```

```
# Prepare the data
x <- as.matrix(mtcars[, -1]) # Independent variables
y <- mtcars$mpg # Dependent variable

# Fit LASSO regression with cross-validation
cv_model <- cv.glmnet(x, y, alpha = 1)
# Print the cv_model object
cv_model
```

```
##
## Call:  cv.glmnet(x = x, y = y, alpha = 1)
##
## Measure: Mean-Squared Error
##
##      Lambda Index Measure      SE Nonzero
## min 0.6648    23   8.188 2.089         4
## 1se 1.5357    14   9.908 2.617         3
```


```
#6: Get the best lambda value from the lasso regression, plot cv_model
```

```

# Get the best lambda value
best_lambda <- cv_model$lambda.min

# Plot cv_model
plot(cv_model)

```



#7: Fit the best lasso regression model (best\_model) using the best\_lambda value obtained above # Fit the best LASSO regression model

```

best_model <- glmnet(x, y, alpha = 1, lambda = best_lambda)
# Print the best_model object
best_model

```

```

##
## Call:  glmnet(x = x, y = y, alpha = 1, lambda = best_lambda)
##
##      Df  %Dev Lambda
## 1    4 82.81 0.6648

```

```

# 8. Get the coefficients of the best_model and identify the important variables
# Extract the coefficients from the best_model
coefficients <- coef(best_model, s = best_lambda)
# Identify the important variables with non-missing values
important_variables <- rownames(coefficients)[coefficients[, 1] != 0]
# Print the coefficients and important variables
coefficients

```

```
## 11 x 1 sparse Matrix of class "dgCMatrix"
##              s1
## (Intercept) 36.44441107
## cyl         -0.89269853
## disp         .
## hp          -0.01282277
## drat         .
## wt          -2.78337592
## qsec         .
## vs           .
## am           0.01364372
## gear         .
## carb         .
```

#9. Fit the multiple linear regression model using the independent variables obtained from the best\_model above

```
# Get the independent variables from the best_model
independent_vars <- rownames(coefficients)[coefficients[, 1] != 0]
independent_vars
```

```
## [1] "(Intercept)" "cyl"          "hp"          "wt"          "am"
```

```
# Fit the multiple linear regression model
mlr_best <- lm(mpg ~ cyl+hp+wt+am+carb, data = mtcars)
summary(mlr_best)
```

```
##
## Call:
## lm(formula = mpg ~ cyl + hp + wt + am + carb, data = mtcars)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.1890 -1.3760 -0.5532  1.5119  5.3251
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  35.62507    3.13296   11.371 1.37e-11 ***
## cyl         -0.81680    0.58482   -1.397   0.174
## hp          -0.01572    0.01607   -0.978   0.337
## wt          -2.36223    0.94461   -2.501   0.019 *
## am           2.07807    1.54075    1.349   0.189
## carb        -0.50441    0.46766   -1.079   0.291
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.502 on 26 degrees of freedom
## Multiple R-squared:  0.8555, Adjusted R-squared:  0.8277
## F-statistic: 30.79 on 5 and 26 DF,  p-value: 3.904e-10
```

#10. Compare the statistically significant variables obtained from step 4 and step9 #Step 4 Model: • The significant variables at the 0.05 level are: wt. • The significant variables at the 0.1 level are: None. •

The significant variables at the 0.5 level are: hp, carb. #Step 9 Model: • The significant variables at the 0.05 level are: wt. • The significant variables at the 0.1 level are: None. • The significant variables at the 0.5 level are: None. It is important to note that the significance levels may vary depending on the chosen threshold (e.g., 0.05, 0.1, 0.5). In both models, the R-squared values are relatively high, indicating a good fit to the data. Comparing the significant variables between the two models provides insights into the impact of variable selection using VIF dropouts (step 4) and LASSO regression (step 9) on the inclusion and significance of predictors. The selection of the most appropriate approach depends on the specific requirements of the analysis, such as interpretability, model complexity, and predictive performance.

#11. Write a summary for handling multicollinearity with VIF dropouts and LASSO regression Both VIF dropouts and LASSO regression are effective methods for addressing multicollinearity in regression analysis. VIF dropouts manually remove highly correlated predictors based on VIF values, while LASSO regression automatically selects important predictors by shrinking less relevant coefficients to zero. Choosing the most appropriate approach depends on the specific requirements of the analysis and the goals of the model.