terminal

Sample	Value
alpha	12.5
beta	18.2
gamma	10.8
delta	15.6

terminal The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements.

The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements.

The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers.