terminal A wide table should take its own row, with no narrow text column.

terminal

Field 0	Field 1	Field 2	Field 3	Field 4	Field 5	Field 6	Field 7
item0-0	item0-1	item0-2	item0-3	item0-4	item0-5	item0-6	item0-7
item1-0	item1-1	item1-2	item1-3	item1-4	item1-5	item1-6	item1-7
item2-0	item2-1	item2-2	item2-3	item2-4	item2-5	item2-6	item2-7
item3-0	item3-1	item3-2	item3-3	item3-4	item3-5	item3-6	item3-7

terminal The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers. The agent reads the table and compares the recorded measurements. The observation remains associated with its tool result and the next action. Once the table ends, the text should use the full available width again. This example uses synthetic data so that the layout can be inspected independently of benchmark answers.