

```

No.      Time      Source      Destination      Protocol Length Info
 518 14.082217    10.21.143.214    128.119.245.12    IPv4      1514    Fragmented IP
protocol (proto=UDP 17, off=0, ID=f06d) [Reassembled in #519]
Frame 518: 1514 bytes on wire (12112 bits), 1514 bytes captured (12112 bits) on interface en0, id
0
Ethernet II, Src: c6:19:77:e6:6b:1a (c6:19:77:e6:6b:1a), Dst: IETF-VRRP-VRID_32 (00:00:5e:
00:01:32)
Internet Protocol Version 4, Src: 10.21.143.214, Dst: 128.119.245.12
 0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
 0000 00.. = Differentiated Services Codepoint: Default (0)
  .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
Total Length: 1500
Identification: 0xf06d (61549)
001. .... = Flags: 0x1, More fragments
...0 0000 0000 0000 = Fragment Offset: 0
Time to Live: 1
Protocol: UDP (17)
Header Checksum: 0x9434 [validation disabled]
[Header checksum status: Unverified]
Source Address: 10.21.143.214
Destination Address: 128.119.245.12
[Reassembled IPv4 in frame: 519]
[Stream index: 10]
Data (1480 bytes)
0000  f0 6c 82 9b 07 bc 6d fe 00 00 00 00 00 00 00 00  .l....m.....
0010  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0020  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0030  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0040  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0050  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0060  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0070  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0080  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0090  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
00a0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
00b0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
00c0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
00d0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
00e0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
00f0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0100  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0110  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0120  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0130  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0140  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0150  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0160  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0170  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0180  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0190  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
01a0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
01b0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
01c0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
01d0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
01e0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
01f0  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0200  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0210  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0220  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....
0230  00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  .....

```

No.	Time	Source	Destination	Protocol	Length	Info
519	14.082240	10.21.143.214	128.119.245.12	UDP	534	61548 → 33435
Len=1972						
Frame 519: 534 bytes on wire (4272 bits), 534 bytes captured (4272 bits) on interface en0, id 0						

[illegible]

[illegible]