Absolute Maximum Ratings (Notes 1 and 2)

Supply Voltage (V_{CC}) (Note 3)	6.5V
Voltage at Any Pin Except Control Inputs	−0.3V to (V_{CC} + 0.3V)
Voltage at Control Inputs (START, OE, CLOCK, ALE, EXPANSION CONTROL, ADD A, ADD B, ADD C, ADD D)	−0.3V to 15V
Storage Temperature Range	−65°C to +150°C
Package Dissipation at T_A = 25°C	875 mW
Lead Temperature (Soldering, 10 seconds)	300°C

Operating Ratings (Notes 1 and 2)

Temperature Range (Note 1)	$T_{MIN} \le T_A \le T_{MAX}$
ADC0816CJ	$-55°C \le T_A \le +125°C$
ADC0816CCJ, ADC0816CCN, ADC0817CCN	$-40°C \le T_A \le +85°C$
Range of V_{CC} (Note 1)	4.5 V_{DC} to 6.0 V_{DC}
Voltage at Any Pin Except Control Inputs	0V to V_{CC}
Voltage at Control Inputs (START, OE, CLOCK, ALE, EXPANSION CONTROL, ADD A, ADD B, ADD C, ADD D)	0V to 15V

Electrical Characteristics

Converter Specifications: $V_{CC} = 5\ V_{DC} = V_{REF(+)}$, $V_{REF(-)} = GND$, $V_{IN} = V_{COMPARATOR\ IN}$, $T_{MIN} \le T_A \le T_{MAX}$ and $f_{CLK} = 640$ kHz unless otherwise stated.

Parameter		Conditions	Min	Typ	Max	Units
	ADC0816					
	Total Unadjusted Error (Note 5)	25°C			± 1/2	LSB
		T_{MIN} to T_{MAX}			± 3/4	LSB
	ADC0817					
	Total Unadjusted Error (Note 5)	0°C to 70°C			± 1	LSB
		T_{MIN} to T_{MAX}			± 1 1/4	LSB
	Input Resistance	From Ref(+) to Ref(−)	1.0	4.5		kΩ
	Analog Input Voltage Range	(Note 4) V(+) or V(−)	GND−0.10		V_{CC}+0.10	V_{DC}
$V_{REF(+)}$	Voltage, Top of Ladder	Measured at Ref(+)		V_{CC}	V_{CC}+0.1	V
$\frac{V_{REF(+)}+V_{REF(-)}}{2}$	Voltage, Center of Ladder		V_{CC}/2−0.1	V_{CC}/2	V_{CC}/2+0.1	V
$V_{REF(-)}$	Voltage, Bottom of Ladder	Measured at Ref(−)	−0.1	0		V
	Comparator Input Current	f_c = 640 kHz, (Note 6)	−2	±0.5	2	μA

Electrical Characteristics

Digital Levels and DC Specifications: ADC0816CJ $4.5V \le V_{CC} \le 5.5V$, $-55°C \le T_A \le +125°C$ unless otherwise noted.
ADC0816CCJ, ADC0816CCN, ADC0817CCN $4.75V \le V_{CC} \le 5.25V$, $-40°C \le T_A \le +85°C$ unless otherwise noted.

Parameter		Conditions	Min	Typ	Max	Units
ANALOG MULTIPLEXER						
R_{ON}	Analog Multiplexer ON Resistance	(Any Selected Channel)				
		T_A = 25°C, R_L = 10k		1.5	3	kΩ
		T_A = 85°C			6	kΩ
		T_A = 125°C			9	kΩ
ΔR_{ON}	Δ ON Resistance Between Any 2 Channels	(Any Selected Channel) R_L = 10k		75		Ω
$I_{OFF(+)}$	OFF Channel Leakage Current	V_{CC} = 5V, V_{IN} = 5V,				
		T_A = 25°C		10	200	nA
		T_{MIN} to T_{MAX}			1.0	μA
$I_{OFF(-)}$	OFF Channel Leakage Current	V_{CC} = 5V, V_{IN} = 0,				
		T_A = 25°C	−200			nA
		T_{MIN} to T_{MAX}	−1.0			μA
CONTROL INPUTS						
$V_{IN(1)}$	Logical "1" Input Voltage		V_{CC}−1.5			V
$V_{IN(0)}$	Logical "0" Input Voltage				1.5	V
$I_{IN(1)}$	Logical "1" Input Current (The Control Inputs)	V_{IN} = 15V			1.0	μA
$I_{IN(0)}$	Logical "0" Input Current (The Control Inputs)	V_{IN} = 0	−1.0			μA
I_{CC}	Supply Current	f_{CLK} = 640 kHz		0.3	3.0	mA