

Student 22 **Mohammed Subahaan H** 192572165RC

9 / 10 submitted

Q1. Operators in Python

ANSWER

Operators are the symbol in python to perform multiple operations like arithmetic operations , relational operation , logical operation etc.,
Different types of operator:

1. Arithmetic operators (+ , - , * , % , ** , / , //)
2. Relational operators (< , <= , > , >= , == , !=)
3. logical operators (and , or , not)
4. bitwise operators (& , || , ^)
5. membership operators (in , not in)

Q2. Operators

ANSWER

/ (Division) gives the output (quotient) with two decimal values
eg. 10/3 = 3.33
// (Floor division) gives the output (quotient) with no decimal values
eg. 10//3 = 3
% (Modulus) gives the remainder after the division
eg. 10%3 = 1
** (exponential operator) gives the power values
eg. 2**3 = 8

Q3. for and while loop

ANSWER

for loop works with known end value whereas while loop works until the given condition fails without knowing the end values.

syntax (for):
for (for_variable) in (iterable_variable_for_range):
 block of code

syntax (while):
while(condition):
 block of code

Q4. range()

ANSWER

range() function is used to give the range of numbers for for loop.
range(start , end , step):
start - starting value for the range of numbers (optional)
end - ending value of the range of numbers , operate until it reach end -1 .
step - used to skip the numbers (optional)

1.range(5)
output:0,1,2,3,4

2.range(1,6)
output:1,2,3,4,5

3.range(1,10,2)
output: 1,3,5,7,9

Q5. String

ANSWER

string is a collection characters in python. string is only operatable when it is in quotes (' ' , " " , "" "")
string is immutable , because we cant modify a string in the same memory location

eg.
str="hello"

Q6. String Slice

ANSWER

ytho	=> s[1 : 5]
nohtyP	=> s[: -1]
Pto	=> s[: : 2]
hon	=> s[-3 : :]

Q7. List**ANSWER**

list is a collection of different types of data.
list is mutable whereas string is immutable.
list is enclosed within square brackets[] with elements separated by commas(,) whereas string is enclosed within quotes.
eg.
a=[2 , 2.45 , "s" , "hello"]

Q8. List Slice**ANSWER**

[30,40,50,60]	=>	L[2 : 6]
[10,20,30,40]	=>	L[: 4]
[10,30,50,70]	=>	L[: :2]
[70,60,50,40,30,20,10]	=>	L[: : -1]
[40,50,60]	=>	L[- 4: -1]

Q9. Index**ANSWER**

positive indexing starts with 0 from the 1st element.
negative indexing starts with -1 from the last element.
Postive indexing ----->
0 1 2 3 4
h e l l o
-5 -4 -3 -2 -1
<----- negative indexing

Q10. length

— Not Submitted —