Operating Systems

ASSIGNMENT 1

CO1: *Apply the concepts of operating system types, structures and system calls to demonstrate their functions in various computing environments – history of operating systems, mainframe, desktop, multiprocessor, distributed, clustered, real-time and handheld systems, OS structure, services, system calls, system design, CPU states, memory hierarchy and I/O systems.*

Assignment Title: Evaluate and Justify the Operating-System Design of a Smart Hospital (Total Marks - 50)

Nature of Assignment: Individual
Duration: 1 Week
Submission Date: _____

Bloom's Levels Assessed: K5 – Evaluate (every task in this assignment is at K5 level)

Mandatory Execution and GitHub Submission

- **Every student must individually execute every task in this assignment**, including all "Complete the Code" programs.
- Create a GitHub repository named **CSA04-<RegisterNumber>-Assignment1** and share it with the course faculty (public, or private with the faculty added as a collaborator).
- Keep one folder for each task (for example: Task01, Task02 … or Q1, Q2 …), containing the C source files, shell scripts, configuration files (Dockerfile, YAML), command outputs and screenshots.
- Include a README.md with your name, register number, compiler and version (for example gcc 13), the Linux distribution and version used, the exact gcc command used to compile (for example gcc -std=c11 -Wall -Wextra -pthread), the steps to run each program, and a short note of the result of each task.
- Commit your work progressively – at least one commit for each task. The commit history will be checked; a single upload of all files on the last day will not be accepted.
- Submit the GitHub link below and on the cover page of your report. **An assignment submitted without a working GitHub link will not be evaluated.**

GitHub Repository Link: _____

How to Answer the Additional Questions

Complete the Code: Copy the given code into your repository, replace every TODO with working code without changing the rest of the program, execute it and compare your output (or result) with the expected output.

Alternative Concept and Complexity Analysis: Describe how the solution would change if the alternative concept were used, with code or pseudocode, and analyse and compare the time complexity and space complexity of both solutions using Big-O notation, supported by your own measurements wherever possible.

Scenario — Operating Systems for a Smart Hospital

A 500-bed hospital is replacing its computer systems. It needs: bedside patient monitors that must raise an alarm within 10 milliseconds of an abnormal reading; nurses' handheld tablets; doctors' desktop workstations; a central database server for patient records that must never stop; an imaging server that processes MRI scans using many processors; and a link to two partner hospitals that share records.

The IT team has proposed using one general-purpose operating system everywhere. The clinical staff are concerned that alarms may be delayed, the database may stop during updates, and the tablets' batteries will not last a shift.

The number of devices may grow:

1 ward (40 monitors, 10 tablets) → 1 hospital (500 monitors, 120 tablets, 80 workstations) → a group of 3 hospitals sharing records

You are required to evaluate the requirements of every part of the system, judge which type and structure of operating system suits each, examine how programs obtain OS services through system calls, and defend a complete operating-system plan for the hospital.

Design Challenge:

The hospital is adding remote patient monitoring at home and a cloud-based records service.

Re-evaluate your original design and determine whether it should be retained, modified or redesigned.

TASK 1 – Evaluate the Requirements of Each Computing Environment 4 Marks

Bloom's Level: K5 – Evaluate

Evaluate what each part of the hospital needs from its operating system.

Discuss:

- Response-time, reliability, throughput, battery and security requirements of each device
- Which requirements conflict (for example: fast response and many users on one machine)
- Which requirements are critical to patient safety
- How the lessons from the history of operating systems (batch, time-sharing, personal, mobile) apply to each environment

You are expected to **rank the requirements of each environment and justify the ranking**.

Alternative Concept and Complexity Analysis

If the whole hospital used a single general-purpose operating system on every device, instead of a different type of OS for each environment, what would the solution be? Evaluate the worst-case alarm response time (unbounded scheduling delay versus a guaranteed deadline), the memory needed on each device, and the administration effort.

Evidence Expected

A ranked requirement table for every environment with a justification for each ranking.

TASK 2 – Judge the Type of Operating System for Each Environment **3 Marks**

Bloom's Level: K5 – Evaluate

Compare the types of operating systems for the hospital.

Discuss:

- Mainframe, desktop, multiprocessor, distributed, clustered, real-time (hard and soft) and handheld systems
- Which type best fits the monitors, tablets, workstations, database server, imaging server and partner link
- Symmetric versus asymmetric multiprocessing for the imaging server
- A clustered system with fail-over for the database server

Alternative Concept and Complexity Analysis

If the database server used a single large multiprocessor machine instead of a cluster of smaller machines with fail-over, what would the solution be? Evaluate the availability (a single point of failure versus fail-over within seconds), the cost, and how throughput grows with the number of processors (time) and the memory available (space).

Evidence Expected

A justified choice of operating-system type for each environment, with the rejected alternatives and reasons.

TASK 3 – Evaluate Operating-System Structures **4 Marks**

Bloom's Level: K5 – Evaluate

Evaluate the possible structures of the operating system.

Discuss:

- Simple (monolithic), layered, microkernel, modular (loadable kernel modules) and hybrid structures
- The effect of each structure on reliability, performance and ease of updating
- Which structure suits the patient monitors and which suits the database server
- How Linux, Windows, Android and a real-time OS such as FreeRTOS or QNX are structured

Alternative Concept and Complexity Analysis

If the bedside monitors used a monolithic kernel instead of a microkernel, what would the solution be? Evaluate the time cost of a service request (one system call versus message passing between servers), the memory taken by the kernel, and the effect of a faulty driver on the whole system.

Evidence Expected

A comparison of structures against the hospital's requirements, with a defended choice for two environments.

TASK 4 – Evaluate the Services an Operating System Must Provide **4 Marks**

Bloom's Level: K5 – Evaluate

Evaluate the services each environment needs.

Discuss:

- User interface, program execution, I/O operations, file systems, communication, error detection, resource allocation, accounting, protection and security
- Which services can be removed from the bedside monitor to make it smaller and faster
- Which services are essential for the database server
- How the OS protects one patient's records from another user's programs

Alternative Concept and Complexity Analysis

If the tablets used a full desktop operating system with every service enabled instead of a reduced handheld OS, what would the solution be? Evaluate the memory and storage used by the extra services (space), the start-up time and the battery life (time).

Evidence Expected

A service table for each environment with justified inclusions and exclusions.

TASK 5 – Examine System Calls — 4 Marks

Bloom's Level: K5 – Evaluate

Examine how a program obtains OS services.

Discuss:

- The categories of system calls (process control, file management, device management, information maintenance, communication, protection)
- What happens step by step when a program calls read(): library call, trap, mode switch, kernel work, return
- How parameters are passed to the kernel (registers, a block in memory, the stack)
- How strace shows the system calls made by a program

Alternative Concept and Complexity Analysis

If programs called the C library functions fopen, fread and fwrite instead of the open, read and write system calls directly, what would the solution be? Evaluate the number of system calls for a file of n bytes (about n / 4096 with library buffering versus n / b for a buffer of b bytes) and the extra buffer space used by the library.

Evidence Expected

A step-by-step explanation of a system call with strace evidence from a real program.

TASK 6 – Evaluate the Cost of System Calls — 4 Marks

Bloom's Level: K5 – Evaluate

Evaluate how the number of system calls affects performance.

Discuss:

- Why each system call costs much more than an ordinary function call
- How the buffer size changes the number of read() and write() calls when the database copies a file

- How library buffering (fread, fwrite) reduces the number of system calls
- The best buffer size for the hospital's backup program, using your measurements

Complete the Code

Complete TODO 1 below using the read() and write() system calls, and execute the program on Linux.

```
#define _POSIX_C_SOURCE 200809L
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>

/* Copy src to dst with the read() and write() system calls, using a buffer of
   bufsize bytes. Returns the number of read() calls made, or -1 on error. */
long copy_file(const char *src, const char *dst, size_t bufsize)
{
    char buf[8192];
    int in = open(src, O_RDONLY);
    if (in < 0) return -1;
    int out = open(dst, O_WRONLY | O_CREAT | O_TRUNC, 0644);
    if (out < 0) { close(in); return -1; }
    long calls = 0;
    ssize_t n;
    // TODO 1: Loop: read up to bufsize bytes into buf (count every read call in calls);
    //   stop when read returns 0 (end of file) or -1; write exactly the n bytes that
    //   were read

    close(in);
    close(out);
    return calls;
}

int main(void)
{
    FILE *f = fopen("records.dat", "w");     /* a 10,000-byte test file */
    for (int i = 0; i < 10000; i++) fputc('A' + i % 26, f);
    fclose(f);

    size_t sizes[] = {1, 512, 4096};
    for (int i = 0; i < 3; i++)
        printf("buffer %4zu bytes: %5ld read() calls\n", sizes[i],
               copy_file("records.dat", "copy.dat", sizes[i]));
    unlink("records.dat");
    unlink("copy.dat");
    return 0;
}
```

Expected output:

```
buffer    1 bytes: 10001 read() calls
buffer  512 bytes:    21 read() calls
buffer 4096 bytes:     4 read() calls
```

Run the program under strace -c and compare the number of read() calls reported with the program's output.

Alternative Concept and Complexity Analysis

If the backup program used memory-mapped files (mmap) instead of read() and write() with a buffer, what would the solution be? Evaluate the number of system calls (a few versus about n / b), the copying between kernel and user space, and the memory used for very large files.

Evidence Expected

Measured system-call counts and times for different buffer sizes, with a justified recommendation.

TASK 7 – Evaluate Process Control System Calls — 4 Marks

Bloom's Level: K5 – Evaluate

Evaluate how a command shell on the database server starts and manages programs.

Discuss:

- What fork(), exec(), wait() and exit() each do
- How a shell runs a command, and how it obtains the command's exit status
- What a zombie and an orphan process are, and how the OS deals with them
- Why fork() followed by exec() is used instead of a single "create process" call

Complete the Code

Complete TODO 1 below using fork(), execlp() and waitpid(), and execute the program on Linux.

```
#define _POSIX_C_SOURCE 200809L
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/wait.h>

int main(void)
{
    printf("shell: running job 1\n");
    fflush(stdout);                          /* empty the buffer before fork() */
    // TODO 1: Create a child with fork(). In the child, replace the program with
    //   execlp("expr", "expr", "6", "*", "7", (char *)NULL) and exit(127) if exec
    //   fails. In the parent, wait for the child with waitpid() and print "job 1 exit
    //   status N" using WEXITSTATUS



    printf("shell: running job 2\n");
    fflush(stdout);
    pid = fork();
    if (pid == 0) _exit(3);                  /* a child that fails with code 3 */
    waitpid(pid, &status, 0);
    printf("job 2 exit status %d\n", WEXITSTATUS(status));
    return 0;
}
```

Expected output:

```
shell: running job 1
42
job 1 exit status 0
shell: running job 2
job 2 exit status 3
```

Explain why stdout is flushed before each fork(). Then remove the second fflush(stdout), change _exit(3) to exit(3), redirect the output to a file and explain why "shell: running job 2" now appears twice.

Alternative Concept and Complexity Analysis

If commands were run with posix_spawn() or with threads instead of fork() followed by exec(), what would the solution be? Evaluate the time to start 1,000 commands, the memory copied or shared (copy-on-write), and the isolation between commands.

Evidence Expected

A working program that runs commands like a shell, with process diagrams and a reasoned evaluation.

TASK 8 – Evaluate CPU States and Protection — 3 Marks

Bloom's Level: K5 – Evaluate

Evaluate how the hardware protects the hospital system.

Discuss:

- User mode and kernel mode, privileged instructions and the mode bit
- Interrupts, traps and the timer interrupt
- What would happen to the monitors if any program could disable interrupts
- How the hardware stops one program from reading another program's memory

Alternative Concept and Complexity Analysis

If the monitors used polling (checking the sensor in a loop) instead of interrupts, what would the solution be? Evaluate the worst-case delay before an abnormal reading is noticed (the polling interval versus the interrupt latency) and the CPU time and power wasted by polling.

Evidence Expected

A reasoned explanation of CPU modes, interrupts and protection, applied to the monitors.

TASK 9 – Evaluate the Memory Hierarchy and I/O Systems — 4 Marks

Bloom's Level: K5 – Evaluate

Evaluate how data moves between storage levels and devices.

Discuss:

- The levels of the memory hierarchy (registers, cache, main memory, SSD, hard disk, network storage) with typical access times and sizes
- Where MRI images, patient records and monitor readings should be kept
- Programmed I/O, interrupt-driven I/O and DMA, and which suits the MRI scanner
- The effect of caching on the speed of record look-up

Alternative Concept and Complexity Analysis

If the MRI scanner transferred images with interrupt-driven I/O (one interrupt per word) instead of DMA, what would the solution be? Evaluate the number of interrupts and the CPU time for a 500 MB image, and the memory buffers needed in each method.

Evidence Expected

A justified data-placement plan and I/O method for each device, using typical access times.

TASK 10 – Measure and Compare **4 Marks**

Bloom's Level: K5 – Evaluate

Measure the behaviour of your programs on a Linux system.

Discuss:

- The number of system calls made by your copy program for different buffer sizes (strace -c)
- The time spent in user mode and in kernel mode (the time command)
- The time to create 1,000 processes with fork() and to create 1,000 threads
- How the measurements support or contradict your earlier judgements

Alternative Concept and Complexity Analysis

If threads were created instead of processes for the measurements, what would the result be? Evaluate the creation time for 1,000 threads versus 1,000 processes and the memory used by each, and explain the difference using what each one shares.

Evidence Expected

Measured results in tables, compared with expectations, with explained differences.

TASK 11 – Recommend and Defend the Operating-System Plan **4 Marks**

Bloom's Level: K5 – Evaluate

Recommend the complete operating-system plan for the hospital.

Discuss:

- The type and structure of operating system for each environment
- The services, protection and I/O methods each will use
- The limitations and risks of your plan
- Whether the plan remains suitable for the group of three hospitals

Your recommendation must be based on **evidence from your own analysis and measurements**.

Alternative Concept and Complexity Analysis

If the whole system were moved to virtual machines on two large servers, instead of separate physical machines for each environment, what would the solution be? Evaluate the effect on response time for the monitors, the memory and processor overhead of virtualisation, and the effect on reliability.

Evidence Expected

A technically justified plan supported by analysis and measurements.

DAY-4 DESIGN CHALLENGE

TASK 12 – Re-evaluate and Adapt the Design 8 Marks

Bloom's Level: K5 – Evaluate

Changed Requirement

The hospital adds **remote monitoring devices in patients' homes** that send readings over the internet, and moves patient records to a **cloud service** shared with the partner hospitals.

Re-evaluate your original design. You may **RETAIN → MODIFY → or REDESIGN** your original solution.

A. Impact Analysis – 2 Marks

Identify which operating-system types, services and protection mechanisms are affected.

Evidence Expected

A clear analysis of how the changed requirements affect the original design.

B. Evaluation of the Original Design – 2 Marks

Evaluate whether your plan can support home devices and cloud records, considering response time, reliability and security.

Evidence Expected

A technically supported evaluation of the original design.

C. Adaptation or Redesign – 2 Marks

Describe the revised plan (for example: an embedded real-time OS on home devices, a distributed system for shared records).

Evidence Expected

An appropriate design response.

D. Evidence-Based Defence – 2 Marks

Defend your decision using evidence and the trade-offs involved.

Evidence Expected

A well-supported final decision integrating evidence and the changed requirements.

MARK DISTRIBUTION

Task	Bloom's Level	Marks
Task 1 – Requirements of Each Environment	K5 – Evaluate	4
Task 2 – Types of Operating Systems	K5 – Evaluate	3
Task 3 – Operating-System Structures	K5 – Evaluate	4
Task 4 – Operating-System Services	K5 – Evaluate	4
Task 5 – System Calls	K5 – Evaluate	4
Task 6 – Cost of System Calls	K5 – Evaluate	4
Task 7 – Process Control System Calls	K5 – Evaluate	4
Task 8 – CPU States and Protection	K5 – Evaluate	3

Task	Bloom's Level	Marks
Task 9 – Memory Hierarchy and I/O	K5 – Evaluate	4
Task 10 – Measurement and Comparison	K5 – Evaluate	4
Task 11 – Final Recommendation	K5 – Evaluate	4
Subtotal		**42**
Task 12 – Day-4 Design Challenge	K5 – Evaluate	**8**
TOTAL		**50**

Submission Requirements

- **GitHub repository link (mandatory)** containing the executed code for every task, including every completed "Complete the Code" program, script and configuration file, with input files, output screenshots and a README.md.
- Your assignment report containing the required evidence for Tasks 1–12, including requirement tables, diagrams, strace and time outputs, measurements and complexity analyses.

Assessment Verification

Students may be asked to explain, execute or modify any part of their code during a brief verification discussion/viva. The student should be able to explain and defend the work submitted as their own.