OPERATING SYSTEMS

ASSIGNMENT 2 – CO2

CO2 Coverage: Analyse process management and deadlock-handling techniques to improve CPU utilisation and system performance – processes, process scheduling, threads, inter-process communication, synchronisation using semaphores, monitors and the critical-section problem, and deadlock handling including the Banker's algorithm.

Nature of Assignment: Individual
Duration: 1 Week
Total Marks: 50
Submission Date: _____

Bloom's Levels Assessed: K5 – Evaluate (every task in this assignment is at K5 level)

Mandatory Execution and GitHub Submission

- **Every student must individually execute every task in this assignment**, including all "Complete the Code" programs.
- Create a GitHub repository named **CSA04-<RegisterNumber>-Assignment2** and share it with the course faculty (public, or private with the faculty added as a collaborator).
- Keep one folder for each task (for example: Task01, Task02 … or Q1, Q2 …), containing the C source files, shell scripts, configuration files (Dockerfile, YAML), command outputs and screenshots.
- Include a README.md with your name, register number, compiler and version (for example gcc 13), the Linux distribution and version used, the exact gcc command used to compile (for example gcc -std=c11 -Wall -Wextra -pthread), the steps to run each program, and a short note of the result of each task.
- Commit your work progressively – at least one commit for each task. The commit history will be checked; a single upload of all files on the last day will not be accepted.
- Submit the GitHub link below and on the cover page of your report. **An assignment submitted without a working GitHub link will not be evaluated.**

GitHub Repository Link: _____

How to Answer the Additional Questions

Complete the Code: Copy the given code into your repository, replace every TODO with working code without changing the rest of the program, execute it and compare your output (or result) with the expected output.

Alternative Concept and Complexity Analysis: Describe how the solution would change if the alternative concept were used, with code or pseudocode, and analyse and compare the time complexity and space complexity of both solutions using Big-O notation, supported by your own measurements wherever possible.

Q1 – Processes and Process States 6 Marks

Bloom's Level: K5 – Evaluate

Problem Context – Online Examination Server

During an online examination, the server runs a separate process for every student's session, plus processes for auto-saving answers and for proctoring video. When 2,000 students log in together, the server becomes slow and some sessions appear to "hang".

Your Challenge

Draw the process-state diagram (new, ready, running, waiting, terminated) and the process control block (PCB). Write a program that creates child processes with fork() and observe them with ps and /proc.

Evaluation

Evaluate where the time goes when 2,000 processes are active: context-switch cost, memory per process, and time spent waiting for I/O. Judge whether a separate process per student is a sound design.

Design Decision

Decide between one process per student, one thread per student and a fixed pool of worker processes, and defend your decision.

Alternative Concept and Complexity Analysis

If each student session were a thread inside one server process, instead of a separate process, what would the solution be? Evaluate the context-switch time and the memory per session (a few KB of stack versus a full address space), and the effect of one session crashing.

Evidence Expected

A state diagram, a PCB description, a working fork() program with ps evidence and a defended design decision.

Q2 – CPU Scheduling 8 Marks

Bloom's Level: K5 – Evaluate

Problem Context – Cloud Video-Encoding Service

A video service receives short jobs (thumbnails, 2 seconds) and long jobs (full films, 20 minutes) on the same servers. Customers complain that small jobs wait behind large ones, while the company wants the processors fully used.

Your Challenge

Compute the Gantt chart, waiting time, turnaround time and response time for the same set of jobs under FCFS, SJF, SRTF, priority and Round Robin scheduling. Implement Round Robin.

Evaluation

Evaluate how the time quantum affects Round Robin (try 1, 3, 5 and 20), the risk of starvation in SJF and priority scheduling, and how ageing removes it. Explain how a multilevel feedback queue treats short and long jobs.

Design Decision

Recommend the scheduling policy for the video service and justify it with your calculated averages.

Complete the Code

Complete TODO 1 below and execute the program.

```
#include <stdio.h>

#define N 4

int main(void)
{
    const char *name[N] = {"P1", "P2", "P3", "P4"};
    int arrival[N] = {0, 1, 2, 3};
    int burst[N] = {8, 4, 9, 5};
    int quantum = 3;

    int left[N], finish[N], queue[64], head = 0, tail = 0, added[N] = {0};
    for (int i = 0; i < N; i++) left[i] = burst[i];
    int time = 0, done = 0;
    queue[tail++] = 0;
    added[0] = 1;
    printf("Gantt:");
    while (done < N) {
        int p = queue[head++];
        // TODO 1: Run p for min(quantum, left[p]) time units: print " P(time-newtime)",
        //   advance time, reduce left[p]; add every process that has now arrived and is
        //   not yet added to the queue; then put p back at the end of the queue if it
        //   still has time left, otherwise record finish[p] and count it as done

    }
    double tw = 0, tt = 0;
    printf("\nProcess  TAT  WT\n");
    for (int i = 0; i < N; i++) {
        int tat = finish[i] - arrival[i], wt = tat - burst[i];
        tt += tat;
        tw += wt;
        printf("%-7s %4d %3d\n", name[i], tat, wt);
    }
    printf("Average TAT = %.2f, average WT = %.2f\n", tt / N, tw / N);
    return 0;
}
```

Expected output:

```
Gantt: P1(0-3) P2(3-6) P3(6-9) P4(9-12) P1(12-15) P2(15-16) P3(16-19) P4(19-21)
P1(21-23) P3(23-26)
Process  TAT  WT
P1        23  15
P2        15  11
P3        24  15
P4        18  13
Average TAT = 20.00, average WT = 13.50
```

Run the program with quantum 1 and quantum 20, and evaluate how the average waiting time and the number of context switches change.

Alternative Concept and Complexity Analysis

If the service used a multilevel feedback queue (short quantum for new jobs, longer quanta for jobs that use them up) instead of a single Round Robin queue, what would the solution be? Evaluate the average waiting time for short and long jobs, the scheduling cost per decision (O(1) per queue versus O(n) for SJF) and the risk of starvation.

Evidence Expected

Correct Gantt charts and averages for every algorithm, a working Round Robin program, a quantum study and a justified recommendation.

Q3 – Threads — 6 Marks

Bloom's Level: K5 – Evaluate

Problem Context – Traffic-Camera Number-Plate Reader

A city traffic system reads number plates from 64 cameras. The first version processes the cameras one after another and falls behind during peak hours.

Your Challenge

Process the camera frames with POSIX threads (one thread per camera, and a pool of 4, 8 and 16 threads). Determine:

- Which resources threads share and which each thread has of its own
- The difference between user-level and kernel-level threads and the many-to-one, one-to-one and many-to-many models
- The speed-up obtained on your machine, and why it stops increasing
- What happens to shared counters when two threads update them without protection

Alternative Concept and Complexity Analysis

If the camera frames were processed by several processes instead of threads, what would the solution be? Evaluate the creation and switching time, the memory used (separate address spaces versus shared), and how the results would be combined (IPC versus shared variables).

Evidence Expected

A working multithreaded program, measured speed-ups for each pool size and a reasoned evaluation of the thread models.

Q4 – Inter-Process Communication — 6 Marks

Bloom's Level: K5 – Evaluate

Problem Context – Weather Station Data Pipeline

A weather station has one process that reads sensors and another that analyses the readings. They must exchange data continuously without losing readings.

Your Challenge

Implement the exchange using a pipe, and then using shared memory or a message queue. Determine:

- How the pipe signals end of data to the reader
- The difference between the shared-memory and message-passing models
- Which method copies the data and which does not
- Which method needs extra synchronisation, and why

Growth Investigation

Measure the time to transfer 1 MB, 10 MB and 100 MB with each method, and evaluate the results.

Complete the Code

Complete TODO 1 below and execute the program on Linux.

```
#define _POSIX_C_SOURCE 200809L
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>

/* The parent (sensor reader) sends readings to the child (analyser) through a pipe. */
int main(void)
{
    int fd[2];
    if (pipe(fd) == -1) { perror("pipe"); return 1; }
    pid_t pid = fork();
    if (pid == 0) {
        close(fd[1]);                          /* child only reads */
        int r, count = 0, sum = 0, max = 0;
        // TODO 1: Read one int at a time from fd[0] until read returns 0 (the parent
        //   closed the pipe); keep the count, the sum and the maximum

        printf("analyser: %d readings, average %.1f, max %d\n", count,
               count ? (double)sum / count : 0.0, max);
        close(fd[0]);
        fflush(stdout);
        _exit(0);
    }
    close(fd[0]);                              /* parent only writes */
    int readings[] = {31, 33, 36, 34, 41, 38};
    for (int i = 0; i < 6; i++)
        if (write(fd[1], &readings[i], sizeof readings[i]) < 0) perror("write");
    close(fd[1]);                              /* signals end of data to the child */
    waitpid(pid, NULL, 0);
    printf("reader: done\n");
    return 0;
}
```

Expected output:

```
analyser: 6 readings, average 35.5, max 41
reader: done
```

Remove close(fd[1]) in the parent and explain why the child never finishes.

Alternative Concept and Complexity Analysis

If the readings were exchanged through shared memory with a semaphore instead of a pipe, what would the solution be? Evaluate the time to transfer n readings (two copies through the kernel for a pipe versus none for shared memory) and the synchronisation needed.

Evidence Expected

Two working IPC implementations, measured transfer times and a justified choice of method.

Q5 – Synchronisation: Critical Sections, Semaphores and Monitors — 11 Marks

Bloom's Level: K5 – Evaluate

Problem Context – Railway Ticket Booking

Thousands of agents book seats on the same trains at the same time. Without synchronisation the same seat is sometimes sold twice; with a single global lock the system becomes very slow.

Design Starting Point

You are given only the following principle:

A solution to the critical-section problem must guarantee mutual exclusion, progress and bounded waiting.

Your Challenge

Convert this principle into a design. Determine:

- Why Peterson's solution satisfies the three requirements for two processes, and why it may fail on modern processors
- How counting and binary semaphores (wait and signal) protect the seat counter
- How the bounded-buffer (producer–consumer), readers–writers and dining-philosophers problems are solved with semaphores
- How a monitor with condition variables makes the solution easier to get right

Test Your Design

Run the bounded-buffer program with 1 and with 4 producers and consumers, and show that every item is consumed exactly once.

Deployment Decision

Decide between one lock for the whole booking system, one lock per train and one lock per coach. Measure the throughput of each and defend your choice.

Complete the Code

Complete TODO 1 and TODO 2 below using the semaphores and the mutex, and execute the program (compile with -pthread).

```
#define _POSIX_C_SOURCE 200809L
#include <stdio.h>
#include <pthread.h>
#include <semaphore.h>

#define SIZE 5
#define ITEMS 20

int buffer[SIZE], in = 0, out = 0;
sem_t empty, full;
pthread_mutex_t lock = PTHREAD_MUTEX_INITIALIZER;
long consumed_sum = 0;

void *producer(void *arg)
{
    (void)arg;
    for (int item = 1; item <= ITEMS; item++) {
        // TODO 1: Wait on empty, lock the mutex, put item at buffer[in], advance in
        //   circularly, unlock, then post full

    }
    return NULL;
}

void *consumer(void *arg)
{
    (void)arg;
    for (int k = 0; k < ITEMS; k++) {
        // TODO 2: Wait on full, lock the mutex, take the item at buffer[out], advance
        //   out circularly, unlock, post empty and add the item to consumed_sum

    }
    return NULL;
}

int main(void)
{
    sem_init(&empty, 0, SIZE);
    sem_init(&full, 0, 0);
    pthread_t p, c;
    pthread_create(&p, NULL, producer, NULL);
    pthread_create(&c, NULL, consumer, NULL);
    pthread_join(p, NULL);
    pthread_join(c, NULL);
    printf("items consumed: %d, sum = %ld (expected %d)\n", ITEMS, consumed_sum,
           ITEMS * (ITEMS + 1) / 2);
    sem_destroy(&empty);
    sem_destroy(&full);
    return 0;
}
```

Expected output:

```
items consumed: 20, sum = 210 (expected 210)
```

Run the program 100 times and show that the sum is always 210. Then remove the mutex and evaluate whether the result is still correct with several producers and consumers.

Alternative Concept and Complexity Analysis

If the shared counter were protected by atomic operations (C11 atomic_fetch_add) or by a spin lock instead of a semaphore and mutex, what would the solution be? Evaluate the time per update with 1, 4 and 16 threads, the CPU time wasted by spinning, and which method suits a long critical section.

Evidence Expected

A student-derived synchronisation design, working semaphore code, test evidence and a measured, defended locking decision.

DAY-4 DESIGN CHALLENGE

Q6 – Deadlock Handling and the Banker's Algorithm — 13 Marks

Bloom's Level: K5 – Evaluate

Problem Context – Shared Laboratory Equipment Scheduler

A research centre runs jobs that need several shared resources at once (GPUs, licences for simulation software and high-speed storage). Jobs sometimes wait for each other forever and the whole cluster stops until an administrator intervenes.

A. Characterise Deadlock – 2 Marks

State the four necessary conditions for deadlock and show them in a resource-allocation graph for the cluster.

Complete the Code

Complete TODO 1 below and execute the program.

```
#include <stdio.h>
#include <string.h>

#define P 5
#define R 3

int avail[R] = {3, 3, 2};
int maxm[P][R] = {{7, 5, 3}, {3, 2, 2}, {9, 0, 2}, {2, 2, 2}, {4, 3, 3}};
int alloc[P][R] = {{0, 1, 0}, {2, 0, 0}, {3, 0, 2}, {2, 1, 1}, {0, 0, 2}};

/* Returns 1 if the state is safe and stores a safe sequence in seq. */
int is_safe(int seq[P])
{
    int work[R], finish[P] = {0}, count = 0;
    memcpy(work, avail, sizeof work);
    while (count < P) {
        int found = 0;
        for (int p = 0; p < P; p++) {
            if (finish[p]) continue;
            // TODO 1: If need = maxm[p] - alloc[p] is <= work for every resource, let p
            //   finish: add alloc[p] to work, mark finish[p], append p to seq and set
            //   found = 1

        }
        if (!found) return 0;
    }
    return 1;
}

void request(int p, const int req[R])
{
    for (int r = 0; r < R; r++)
        if (req[r] > maxm[p][r] - alloc[p][r] || req[r] > avail[r]) {
            printf("P%d request: must wait (not available)\n", p);
            return;
        }
    for (int r = 0; r < R; r++) { avail[r] -= req[r]; alloc[p][r] += req[r]; }
    int seq[P];
    if (is_safe(seq)) {
        printf("P%d request: granted, safe sequence", p);
        for (int i = 0; i < P; i++) printf(" P%d", seq[i]);
        printf("\n");
    } else {
        for (int r = 0; r < R; r++) { avail[r] += req[r]; alloc[p][r] -= req[r]; }
        printf("P%d request: denied (unsafe)\n", p);
    }
}

int main(void)
{
    int seq[P];
    if (is_safe(seq)) {
        printf("initial state safe:");
        for (int i = 0; i < P; i++) printf(" P%d", seq[i]);
        printf("\n");
    }
    request(1, (int[R]){1, 0, 2});
    request(4, (int[R]){3, 3, 0});
    request(0, (int[R]){0, 2, 0});
    return 0;
}
```

Expected output:

```
initial state safe: P1 P3 P4 P0 P2
P1 request: granted, safe sequence P1 P3 P4 P0 P2
P4 request: must wait (not available)
P0 request: denied (unsafe)
```

Show by hand why the request of P0 for (0, 2, 0) leads to an unsafe state.

Alternative Concept and Complexity Analysis

If deadlock were handled by detection and recovery (running a detection algorithm every few minutes and aborting a job) instead of the Banker's algorithm, what would the solution be? Evaluate the time per request ($O(m \times n^2)$ for every Banker's check versus no check), the cost of detection, and the work lost when a job is aborted.

Evidence Expected

A correct resource-allocation graph identifying all four conditions.

B. Compare the Strategies – 3 Marks

Evaluate prevention (removing one condition), avoidance (Banker's algorithm), detection and recovery, and ignoring deadlock (the ostrich approach) for the cluster.

Evidence Expected

A reasoned comparison of the four strategies for this environment.

C. Apply the Banker's Algorithm – 4 Marks

Implement the safety algorithm and the resource-request algorithm. Find a safe sequence for the given state and decide whether each request can be granted.

Evidence Expected

A working implementation with correct safe sequences and decisions.

D. Predict Before Implementing – 1 Mark

Predict how the running time of the Banker's algorithm grows with the number of processes n and resource types m.

Evidence Expected

A clear, testable prediction.

E. Measure – 1 Mark

Measure the time of the safety algorithm for 10, 100 and 1,000 processes and compare it with your prediction.

Evidence Expected

Measured times compared with the prediction.

F. Defend the Final Design – 2 Marks

Recommend the deadlock strategy for the research centre and justify it, including the cost of the Banker's algorithm and the need to know maximum demands in advance.

Evidence Expected

A critical, evidence-based recommendation.

MARK DISTRIBUTION

Question	Assessed Area	Bloom's Level	Marks
Q1	Processes and process states	K5 – Evaluate	6
Q2	CPU scheduling	K5 – Evaluate	8
Q3	Threads	K5 – Evaluate	6

Question	Assessed Area	Bloom's Level	Marks
Q4	Inter-process communication	K5 – Evaluate	6
Q5	Synchronisation: critical sections, semaphores and monitors	K5 – Evaluate	11
Q6	Day-4 Design Challenge – Deadlock handling and Banker's algorithm	K5 – Evaluate	13
	TOTAL		**50**

Submission Requirements

GitHub repository link (mandatory) containing the executed code for every task, including every completed "Complete the Code" program, script and configuration file, with input files, output screenshots and a README.md.

- Your assignment report containing the required evidence for Q1–Q6
- C source code for all programs
- Gantt charts, diagrams, outputs and timings used as evidence

Assessment Verification

Students may be asked to explain any part of their design, code, calculations or results during a brief verification discussion/viva.

Overall Assessment Expectation

> **Model → Design → Implement → Measure → Compare → Evaluate → Recommend**