

Task Description:

1. Create a shell script to print the HTTP error code of guvi.in & print, the success/failure message based on the error code response

Output:

```
ubuntu@ip-172-31-40-179:~$ ls -l
total 4
drwxrwxr-x 2 ubuntu ubuntu 4096 Oct  6 18:52 home
ubuntu@ip-172-31-40-179:~$ nano check_http_status.sh
ubuntu@ip-172-31-40-179:~$ ls -l
total 8
-rw-rw-r-- 1 ubuntu ubuntu 504 Oct  6 20:45 check_http_status.sh
drwxrwxr-x 2 ubuntu ubuntu 4096 Oct  6 18:52 home
ubuntu@ip-172-31-40-179:~$ chmod +x check_http_status.sh
ubuntu@ip-172-31-40-179:~$ ./check_http_status.sh
HTTP Status Code for https://guvi.in: 301
Success: The website is reachable and responded successfully.
ubuntu@ip-172-31-40-179:~$ ^C
ubuntu@ip-172-31-40-179:~$ ls -l
total 8
-rwxrwxr-x 1 ubuntu ubuntu 504 Oct  6 20:45 check_http_status.sh
drwxrwxr-x 2 ubuntu ubuntu 4096 Oct  6 18:52 home
ubuntu@ip-172-31-40-179:~$
```

```
# vi check http status.sh
```

The screenshot shows the AWS CloudShell interface. At the top, there's a navigation bar with the AWS logo, a search bar, and various system icons. The main area is a terminal window with a dark background and light-colored text. A script is being executed, which defines a function 'check_http_status.sh' that takes a URL as input and uses 'curl' to check its status code. The script has several conditional statements to handle different status codes (200, 300, 400, 500) and print corresponding messages. Below the terminal output, there's a summary section titled 'i-01af4e12251b2da8d (DemoProgram)' which lists public and private IP addresses. The bottom right corner has a close button.

2. Given a file, replace all occurrence of the word "give" with "learning" from 5th line till the end in only those lines that contain the word "welcome"

Output:

aws

Q Search

[Alt+S]

1

Asia Pacific (Mumbai)

Account ID: 6399-6664-7088

Subanalakshmi R

```
ubuntu@ip-172-31-40-179:~$ ls -l
total 8
-rwxrwxr-x 1 ubuntu ubuntu 504 Oct 6 20:57 check_http_status.sh
drwxrwxr-x 2 ubuntu ubuntu 4096 Oct 6 18:52 home
ubuntu@ip-172-31-40-179:~$ nano replace.sh
ubuntu@ip-172-31-40-179:~$ vi replace.sh
ubuntu@ip-172-31-40-179:~$ ./replace.sh
-bash: ./replace.sh: Permission denied
ubuntu@ip-172-31-40-179:~$ sed -i '5,$ {/welcome/ s/give/learning/g}' replace.sh
ubuntu@ip-172-31-40-179:~$ vi replace.sh
ubuntu@ip-172-31-40-179:~$ ls -l
total 12
-rwxrwxr-x 1 ubuntu ubuntu 504 Oct 6 20:57 check_http_status.sh
drwxrwxr-x 2 ubuntu ubuntu 4096 Oct 6 18:52 home
-rw-rw-r-- 1 ubuntu ubuntu 163 Oct 6 21:10 replace.sh
ubuntu@ip-172-31-40-179:~$
```

i-01af4e12251b2da8d (DemoProgram)

PublicIPs: 3.111.187.109 PrivateIPs: 172.31.40.179

File before changes

The image shows a screenshot of an AWS CloudShell terminal window. The top navigation bar includes the AWS logo, a search bar, and icons for help, notifications (with a red '1'), and settings. The right side of the bar shows the account ID '6399-6664-7088' and the user 'Subanatakshmi R'. The terminal area has a dark background with light blue text. It displays a script with seven lines: '1. Hello give world', '2. welcome to guvi', '3. good day', '4. welcome and give again', '5. welcome to guvi give', '6. another line welcome give', and '7. bye have a nice day'. The word 'nice' is highlighted in yellow. Below the script, there are several lines of tilde '~' representing empty lines. At the bottom, a status bar shows the command 'replace.sh' with its location '7L, 155B' and a progress indicator '1,1' and 'All'. The bottom-most bar contains the instance ID 'i-01af4e12251b2da8d (DemoProgram)' and a blue 'X' icon.

File after changes

