proposal_category [table]

proposal_category_id	int4 not null	Unique identifier of proposal category
proposal_category_name	varchar not null	Proposal category name (e.g., Openuse, Keck, Gemini, and UH)
proposal_category_description	varchar	Proposal category description (e.g., Openuse, Time exchange, etc.
created_at	timestamp	The date and time in UTC when the record was created
updated_at	timestamp	The date and time in UTC when the record was last updated

partner [table]

partner_id	int4 not null	Unique identifier of the partner
partner_name	varchar not null	Name of the partner (e.g., subaru, gemini, keck, and uh)
partner_description	varchar	Description of the partner
created_at	timestamp	The date and time in UTC when the record was created
updated_at	timestamp	The date and time in UTC when the record was last updated

proposal [table]

proposal_id	varchar not null	Unique identifier for proposal (e.g, S21B-OT06)
group_id	varchar not null	Group ID in STARS (e.g., o21195)
pi_first_name	varchar	PI's first name
pi_last_name	varchar not null	PI's last name
pi_middle_name	varchar	PI's middle name
rank	float8(17, 17) not null	TAC score
grade	varchar not null	TAC grade (A/B/C/F and N/A)
allocated_time_total	float8(17, 17)	Total fiberhours allocated by TAC (hour)
allocated_time_lr	float8(17, 17)	Total fiberhours for the low-resolution mode allocated by TAC (hour)
allocated_time_mr	float8(17, 17)	Total fiberhours for the medium-resolution mode allocated by TAC (hour)
proposal_category_id	int4	
partner_id	int4	
is_too	bool	True when the proposal is ToO
created_at	timestamp	The date and time in UTC when the record was created
updated_at	timestamp	The date and time in UTC when the record was last updated

target [table]

target_id	bigserial not null	auto-incremented Unique identifier for each target
proposal_id	varchar	
ob_code	varchar not null	Identifer for a combination of a target, observing mode, and exposure time in a program.
obj_id	int8 not null	Object ID as specified by the observer at Phase 2 (can be same as the input_catalog_object_id)
ra	float8(17, 17) not null	RA (ICRS, degree)
"dec"	float8(17, 17) not null	Dec (ICRS, degree)
epoch	varchar	Epoch (default: J2000.0)
parallax	float8(17, 17)	Parallax (mas)
pmra	float8(17, 17)	Proper motion in right ascension direction (mas/yr)
pmdec	float8(17, 17)	Proper motion in declination direction (mas/yr)
tract	int4	same definition as HSC-SSP?; can be derived from the coordinate
patch	int4	same definition as HSC-SSP?; can be derived from the coordinate; Note that it's defined as an integer
target_type_id	int4	target type ID (default: 1 = SCIENCE)
input_catalog_id	int4 not null	Input catalog ID from the input_catalog table
fiber_mag_u	float8(17, 17)	u-band magnitude within a fiber (AB mag)
fiber_mag_v	float8(17, 17)	v-band magnitude within a fiber (AB mag)
fiber_mag_g	float8(17, 17)	g-band magnitude within a fiber (AB mag)
fiber_mag_r	float8(17, 17)	r-band magnitude within a fiber (AB mag)
fiber_mag_i	float8(17, 17)	i-band magnitude within a fiber (AB mag)
fiber_mag_z	float8(17, 17)	z-band magnitude within a fiber (AB mag)
fiber_mag_y	float8(17, 17)	y-band magnitude within a fiber (AB mag)
fiber_mag_j	float8(17, 17)	J band magnitude within a fiber (AB mag)
psf_mag_u	float8(17, 17)	u-band PSF magnitude (AB mag)
psf_mag_v	float8(17, 17)	v-band PSF magnitude (AB mag)
psf_mag_g	float8(17, 17)	g-band PSF magnitude (AB mag)
psf_mag_r	float8(17, 17)	r-band PSF magnitude (AB mag)
psf_mag_i	float8(17, 17)	i-band PSF magnitude (AB mag)
psf_mag_z	float8(17, 17)	z-band PSF magnitude (AB mag)
psf_mag_y	float8(17, 17)	y-band PSF magnitude (AB mag)
psf_mag_j	float8(17, 17)	J band PSF magnitude (AB mag)
psf_mag_error_u	float8(17, 17)	Error in u-band PSF magnitude (AB mag)
psf_mag_error_v	float8(17, 17)	Error in v-band PSF magnitude (AB mag)
psf_mag_error_g	float8(17, 17)	Error in g-band PSF magnitude (AB mag)
psf_mag_error_r	float8(17, 17)	Error in r-band PSF magnitude (AB mag)
psf_mag_error_i	float8(17, 17)	Error in i-band PSF magnitude (AB mag)
psf_mag_error_z	float8(17, 17)	Error in z-band PSF magnitude (AB mag)
psf_mag_error_y	float8(17, 17)	Error in y-band PSF magnitude (AB mag)
psf_mag_error_j	float8(17, 17)	Error in J band PSF magnitude (AB mag)
psf_flux_u	float8(17, 17)	u-band PSF flux (nJy)
psf_flux_v	float8(17, 17)	v-band PSF flux (nJy)
psf_flux_g	float8(17, 17)	g-band PSF flux (nJy)
psf_flux_r	float8(17, 17)	r-band PSF flux (nJy)
psf_flux_i	float8(17, 17)	i-band PSF flux (nJy)
psf_flux_z	float8(17, 17)	z-band PSF flux (nJy)
psf_flux_y	float8(17, 17)	y-band PSF flux (nJy)
psf_flux_j	float8(17, 17)	J band PSF flux (nJy)
psf_flux_error_u	float8(17, 17)	Error in u-band PSF flux (nJy)
psf_flux_error_v	float8(17, 17)	Error in v-band PSF flux (nJy)
psf_flux_error_g	float8(17, 17)	Error in g-band PSF flux (nJy)
psf_flux_error_r	float8(17, 17)	Error in r-band PSF flux (nJy)
psf_flux_error_i	float8(17, 17)	Error in i-band PSF flux (nJy)
psf_flux_error_z	float8(17, 17)	Error in z-band PSF flux (nJy)
psf_flux_error_y	float8(17, 17)	Error in y-band PSF flux (nJy)
psf_flux_error_j	float8(17, 17)	Error in J band PSF flux (nJy)
total_flux_u	float8(17, 17)	u-band total flux (nJy)
total_flux_v	float8(17, 17)	v-band total flux (nJy)
total_flux_g	float8(17, 17)	g-band total flux (nJy)
total_flux_r	float8(17, 17)	r-band total flux (nJy)
total_flux_i	float8(17, 17)	i-band total flux (nJy)
total_flux_z	float8(17, 17)	z-band total flux (nJy)
total_flux_y	float8(17, 17)	y-band total flux (nJy)
total_flux_j	float8(17, 17)	J band total flux (nJy)
total_flux_error_u	float8(17, 17)	Error in u-band total flux (nJy)
total_flux_error_v	float8(17, 17)	Error in v-band total flux (nJy)
total_flux_error_g	float8(17, 17)	Error in g-band total flux (nJy)
total_flux_error_r	float8(17, 17)	Error in r-band total flux (nJy)
total_flux_error_i	float8(17, 17)	Error in i-band total flux (nJy)
total_flux_error_z	float8(17, 17)	Error in z-band total flux (nJy)
total_flux_error_y	float8(17, 17)	Error in y-band total flux (nJy)
total_flux_error_j	float8(17, 17)	Error in J band total flux (nJy)
filter_u	varchar	u-band filter (u_sdss, u_cfht, u_skymapper, etc.)
filter_v	varchar	v-band filter (v_skymapper, v_splus, etc.)
filter_g	varchar	g-band filter (g_hsc, g_ps1, g_sdss, etc.)
filter_r	varchar	r-band filter (r_hsc, r_ps1, r_sdss, etc.)
filter_i	varchar	i-band filter (i_hsc, i_ps1, i_sdss, etc.)
filter_z	varchar	z-band filter (z_hsc, z_ps1, z_sdss, etc.)
filter_y	varchar	y-band filter (y_hsc, y_ps1, y_sdss, etc.)
filter_j	varchar	j-band filter (j_mko, etc.)
priority	float8(17, 17)	Priority of the target specified by the observer within the proposal
effective_exptime	float8(17, 17) not null	Requested effective exposure time (s)
single_exptime	float8(17, 17) not null	Individual exposure time (s)
is_medium_resolution	bool	True if the medium resolution mode is requested
qa_relative_throughput	float8(17, 17)	Relative throughput to the reference value requested by the observer (default: 1.0)
qa_relative_noise	float8(17, 17)	Relative noise to the reference value requested by the observer (default: 1.0)
qa_reference_lambda	float8(17, 17)	Reference wavelength to evaluate effective exposure time (angstrom or nm?)
qa_reference_arm	varchar	Reference arm to evaluate effective exposure time ('b', 'r', 'n', 'm')
is_cluster	bool	True if it is a cluster of multiple targets.
created_at	timestamp	The date and time in UTC when the record was created
updated_at	timestamp	The date and time in UTC when the record was last updated

pfs_arm [table]

name	varchar not null	Arm name (e.g., 'b', 'r', 'n', and 'm')
description	varchar	Arm description
created_at	timestamp	The date and time in UTC when the record was created
updated_at	timestamp	The date and time in UTC when the record was last updated

target_type [table]

target_type_id	int4 not null	Unique identifier for target types
target_type_name	varchar not null	Name for the target type.
target_type_description	varchar	Description of the target type
created_at	timestamp	The date and time in UTC when the record was created
updated_at	timestamp	The date and time in UTC when the record was last updated

filter_name [table]

filter_name	varchar not null	Filter name (e.g., g_ps1)
filter_name_description	varchar	Description of the filter
created_at	timestamp	The date and time in UTC when the record was created
updated_at	timestamp	The date and time in UTC when the record was last updated

input_catalog [table]

input_catalog_id	int4 not null	auto-incremented Unique identifier for input catalogs
input_catalog_name	varchar not null	Name of the input catalog (e.g., Gaia DR2, HSC-SSP PDR3, etc.)
input_catalog_description	varchar	Description of the input catalog
upload_id	varchar(16)	A 8-bit hex string (16 characters) assigned at the submission of the target list (default: empty string)
active	bool	Flag to indicate if the input catalog is active (default: True)
is_classical	bool	True if the classical mode is requested
is_user_pointing	bool	True if user-defined pointings are provided
created_at	timestamp	The date and time in UTC when the record was created
updated_at	timestamp	The date and time in UTC when the record was last updated

sky [table]

sky_id	bigserial not null	auto-incremented Unique identifier for each sky position
obj_id	int8 not null	Object ID in the sky catalog
obj_id_orig	varchar	Original object ID in the sky catalog
ra	float8(17, 17) not null	RA (ICRS, degree)
"dec"	float8(17, 17) not null	Dec (ICRS, degree)
epoch	varchar	Epoch (e.g., J2000.0, J2015.5, etc.)
tract	int4	Tract from HSC-SSP
patch	int4	Patch from HSC-SSP
target_type_id	int4	target_type_id from the target_type table (must be 2 for SKY)
input_catalog_id	int4 not null	input_catalog_id from the input_catalog table
mag_thresh	float8(17, 17)	Sky intensity threshold in mag/arcsec^2 (only for HSC-SSP).
version	varchar not null	Version string of the sky position
created_at	timestamp	The date and time in UTC when the record was created
updated_at	timestamp	The date and time in UTC when the record was last updated

cluster [table]

cluster_id	int8 not null	Unique identifier of clusters found at duplication checking
target_id	int8 not null	
n_targets	int4	Number of targets in the cluster
ra_cluster	float8(17, 17)	Mean RA of targets in the cluster (ICRS, degree)
dec_cluster	float8(17, 17)	Mean Dec of targets in the cluster (ICRS, degree)
d_ra	float8(17, 17)	RA(target) - RA(cluster) (degree)
d_dec	float8(17, 17)	Dec(target) - Dec(cluster) (degree)
input_catalog_id	int4	Input catalog ID from the input_catalog table
created_at	timestamp	UTC
updated_at	timestamp	UTC

fluxstd [table]

fluxstd_id	bigserial not null	auto-incremented Unique identifier for each flux standard star
obj_id	int8 not null	source_id (e.g., Gaia EDR3, DR3, etc.)
ra	float8(17, 17) not null	RA (ICRS, degree)
"dec"	float8(17, 17) not null	Dec (ICRS, degree)
epoch	varchar	Epoch (e.g., J2000.0, J2015.5, etc.)
parallax	float8(17, 17)	Parallax (mas)
parallax_error	float8(17, 17)	Standard error of parallax (mas)
pmra	float8(17, 17)	Proper motion in right ascension direction (mas/yr)
pmra_error	float8(17, 17)	Standard error of pmra (mas/yr)
pmdec	float8(17, 17)	Proper motion in declination direction (mas/yr)
pmdec_error	float8(17, 17)	Standard error of pmdec (mas/yr)
tract	int4	same definition as HSC-SSP?; can be derived from the coordinate
patch	int4	same definition as HSC-SSP?; can be derived from the coordinate; Note that it's defined as an integer
target_type_id	int4	target_type_id from the target_type table (must be 3 for FLUXSTD)
input_catalog_id	int4 not null	input_catalog_id from the input_catalog table
psf_mag_u	float8(17, 17)	u-band PSF magnitude (AB mag)
psf_mag_v	float8(17, 17)	v-band PSF magnitude (AB mag)
psf_mag_g	float8(17, 17)	g-band PSF magnitude (AB mag)
psf_mag_r	float8(17, 17)	r-band PSF magnitude (AB mag)
psf_mag_i	float8(17, 17)	i-band PSF magnitude (AB mag)
psf_mag_z	float8(17, 17)	z-band PSF magnitude (AB mag)
psf_mag_y	float8(17, 17)	y-band PSF magnitude (AB mag)
psf_mag_j	float8(17, 17)	J band PSF magnitude (AB mag)
psf_mag_error_u	float8(17, 17)	Error in u-band PSF magnitude (AB mag)
psf_mag_error_v	float8(17, 17)	Error in v-band PSF magnitude (AB mag)
psf_mag_error_g	float8(17, 17)	Error in g-band PSF magnitude (AB mag)
psf_mag_error_r	float8(17, 17)	Error in r-band PSF magnitude (AB mag)
psf_mag_error_i	float8(17, 17)	Error in i-band PSF magnitude (AB mag)
psf_mag_error_z	float8(17, 17)	Error in z-band PSF magnitude (AB mag)
psf_mag_error_y	float8(17, 17)	Error in y-band PSF magnitude (AB mag)
psf_mag_error_j	float8(17, 17)	Error in J band PSF magnitude (AB mag)
psf_flux_u	float8(17, 17)	u-band PSF flux (nJy)
psf_flux_v	float8(17, 17)	v-band PSF flux (nJy)
psf_flux_g	float8(17, 17)	g-band PSF flux (nJy)
psf_flux_r	float8(17, 17)	r-band PSF flux (nJy)
psf_flux_i	float8(17, 17)	i-band PSF flux (nJy)
psf_flux_z	float8(17, 17)	z-band PSF flux (nJy)
psf_flux_y	float8(17, 17)	y-band PSF flux (nJy)
psf_flux_j	float8(17, 17)	J band PSF flux (nJy)
psf_flux_error_u	float8(17, 17)	Error in u-band PSF flux (nJy)
psf_flux_error_v	float8(17, 17)	Error in v-band PSF flux (nJy)
psf_flux_error_g	float8(17, 17)	Error in g-band PSF flux (nJy)
psf_flux_error_r	float8(17, 17)	Error in r-band PSF flux (nJy)
psf_flux_error_i	float8(17, 17)	Error in i-band PSF flux (nJy)
psf_flux_error_z	float8(17, 17)	Error in z-band PSF flux (nJy)
psf_flux_error_y	float8(17, 17)	Error in y-band PSF flux (nJy)
psf_flux_error_j	float8(17, 17)	Error in J band PSF flux (nJy)
filter_u	varchar	u-band filter (u_sdss, u_cfht, u_skymapper, etc.)
filter_v	varchar	v-band filter (v_skymapper, v_splus, etc.)
filter_g	varchar	g-band filter (g_hsc, g_ps1, g_sdss, etc.)
filter_r	varchar	r-band filter (r_hsc, r_ps1, r_sdss, etc.)
filter_i	varchar	i-band filter (i_hsc, i_ps1, i_sdss, etc.)
filter_z	varchar	z-band filter (z_hsc, z_ps1, z_sdss, etc.)
filter_y	varchar	y-band filter (y_hsc, y_ps1, y_sdss, etc.)
filter_j	varchar	j-band filter (j_mko, etc.)
prob_f_star	float8(17, 17)	Probability of being an F-type star
flags_dist	bool	Distance uncertanty flag, True if parallax_error/parallax > 0.2
flags_ebv	bool	E(B-V) uncertainty flag, True if E(B-V) uncertainty is greater than 20%
teff_brutus	float8(17, 17)	Effective temperature from Brutus code [K]
teff_brutus_low	float8(17, 17)	Lower confidence level (16%) of effective temperature from Brutus code [K]
teff_brutus_high	float8(17, 17)	Upper confidence level (84%) of effective temperature from Brutus code [K]
logg_brutus	float8(17, 17)	Surface gravity from Brutus code [log cgs]
logg_brutus_low	float8(17, 17)	Lower confidence level (16%) of surface gravity from Brutus code [log cgs]
logg_brutus_high	float8(17, 17)	Upper confidence level (84%) of surface gravity from Brutus code [log cgs]
teff_gspphot	float8(17, 17)	Effective temperature inferred by GSP-phot Aeneas [K]
teff_gspphot_lower	float8(17, 17)	Lower confidence level (16%) of effective temperature inferred by GSP-phot Aeneas [K]
teff_gspphot_upper	float8(17, 17)	Upper confidence level (84%) of effective temperature inferred by GSP-phot Aeneas [K]
is_fstar_gaia	bool	Flag for F-star from Gaia (Teff=6000-7500K if True)
is_gc_neighbor	bool	Flag for globular cluster neighbor
is_dense_region	bool	Flag for dense stellar region
version	varchar not null	Version string of the F-star selection
created_at	timestamp	The date and time in UTC when the record was created
updated_at	timestamp	The date and time in UTC when the record was last updated

user_pointing [table]

user_pointing_id	bigserial not null	auto-incremented Unique identifier for each user-defined pointing (autoincremented primary key)
ppc_code	varchar not null	String identifier of the pointing set either by the uploader or user
ppc_ra	float8(17, 17) not null	RA of the pointing center (ICRS, degree)
ppc_dec	float8(17, 17) not null	Dec of the pointing center (ICRS, degree)
ppc_pa	float8(17, 17) not null	Position angle of the pointing center (degree)
ppc_resolution	resolutionmode not null	Resolution mode of the pointing ('L' or 'M')
ppc_priority	float8(17, 17) not null	Priority of the pointing calculated by the uploader
input_catalog_id	int4 not null	Input catalog ID from the input_catalog table
created_at	timestamp	The date and time in UTC when the record was created
updated_at	timestamp	The date and time in UTC when the record was last updated

PFS Target Database
generated by SchemaCrawler 16.22.2
generated on 2026-08-04 08:34:58