NAME – SUBASH G
REG NO – 192572150

COURSE NAME – Operation System
COURSE CODE – CSA0408

Lab Observations

EXPERIMENT - 12

Design a C program to simulate the concept of Dining-Philosophers problem

PROGRAM:

```
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>
#include <unistd.h>

#define NUM_PHILOSOPHERS 5

pthread_mutex_t chopsticks[NUM_PHILOSOPHERS];

void* philosopherLifeCycle(void* arg)
{
    int id = *((int*)arg);

    int left_chopstick = id;
    int right_chopstick = (id + 1) % NUM_PHILOSOPHERS;

    while (1)
    {
        // Think
        printf("Philosopher %d is thinking...\n", id);

        // Pick up chopsticks
        pthread_mutex_lock(&chopsticks[left_chopstick]);
        pthread_mutex_lock(&chopsticks[right_chopstick]);

        // Eat
```

```
        printf("Philosopher %d is eating...\n", id);
        sleep(rand() % 3 + 1);

        // Put down chopsticks
        pthread_mutex_unlock(&chopsticks[left_chopstick]);
        pthread_mutex_unlock(&chopsticks[right_chopstick]);
    }

    return NULL;
}

int main()
{
    pthread_t philosophers[NUM_PHILOSOPHERS];
    int philosopher_ids[NUM_PHILOSOPHERS];

    // Initialize mutex locks
    for (int i = 0; i < NUM_PHILOSOPHERS; i++)
    {
        pthread_mutex_init(&chopsticks[i], NULL);
    }

    // Create philosopher threads
    for (int i = 0; i < NUM_PHILOSOPHERS; i++)
    {
        philosopher_ids[i] = i;

        pthread_create(&philosophers[i], NULL,
                       philosopherLifeCycle,
                       (void*)&philosopher_ids[i]);
    }

    // Wait for threads
    for (int i = 0; i < NUM_PHILOSOPHERS; i++)
    {
        pthread_join(philosophers[i], NULL);
    }

    // Destroy mutex locks
    for (int i = 0; i < NUM_PHILOSOPHERS; i++)
    {
        pthread_mutex_destroy(&chopsticks[i]);
    }
```

```
    return 0;
}
```

OUTPUT:

