NAME – SUBASH G
REG NO – 192572150

COURSE NAME – Operation System
COURSE CODE – CSA0408

Lab Observations

EXPERIMENT - 14

Construct a C program to organise the file using a single level directory.

PROGRAM:

```
#include <stdio.h>
#include <stdlib.h>

void create()
{
    FILE *fp;

    fp = fopen("sasi.txt", "w");

    if (fp == NULL)
    {
        printf("File creation failed.\n");
        return;
    }

    fclose(fp);
    printf("File created successfully.\n");
}

void copy()
{
    FILE *source, *destination;
    char ch;

    source = fopen("sasi.txt", "r");

    if (source == NULL)
```

```
    {
        printf("Source file not found.\n");
        return;
    }

    destination = fopen("sk.txt", "w");

    if (destination == NULL)
    {
        printf("Cannot create destination file.\n");
        fclose(source);
        return;
    }

    while ((ch = fgetc(source)) != EOF)
    {
        fputc(ch, destination);
    }

    fclose(source);
    fclose(destination);

    printf("File copied successfully.\n");
}

void deleteFile()
{
    if (remove("sasi.txt") == 0)
        printf("File deleted successfully.\n");
    else
        printf("File not found or deletion failed.\n");
}

int main()
{
    int n;

    printf("\n1. Create");
    printf("\n2. Copy");
    printf("\n3. Delete");
    printf("\nEnter your choice: ");
    scanf("%d", &n);
```

```
    switch (n)
    {
        case 1:
            create();
            break;

        case 2:
            copy();
            break;

        case 3:
            deleteFile();
            break;

        default:
            printf("Invalid choice.\n");
    }

    return 0;
}
```

OUTPUT:

